

Appendix for the SAR Test Report

Dosimetric Assessment of the Trex Device Communicator from R. Stahl HMI Systems GmbH (FCC ID: 2AIM6-GC667032 / IC: 21553-20122901X)

According to the FCC Requirements SAR Distribution Plots

July 15, 2016

IMST GmbH

Carl-Friedrich-Gauß-Str. 2 - 4
47475 Kamp-Lintfort
Germany

Customer

R. Stahl HMI Systems GmbH
Adolf-Grimme-Allee 8
50829 Köln
Germany

The test results only relate to the items tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

SAR Distribution Plots

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:
[RS_529_b_wlan_b_ch6_5b5_pwl18_front_0mm.da4](#)

DUT: RS_529; Type: RStahl HMI System; Serial: 01452529
 Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.97$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.52, 7.52, 7.52); Calibrated: 18.09.2015
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 16.09.2015
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (14x19x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 1.07 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.2 V/m; Power Drift = -0.022 dB

Peak SAR (extrapolated) = 2.00 W/kg

SAR(1 g) = 0.898 mW/g; SAR(10 g) = 0.374 mW/g

Maximum value of SAR (measured) = 1.02 mW/g




Fig. 1: SAR distribution for IEEE802.11 b (5.5MBit/s), channel 6, front side of the device towards the phantom, 0mm distance

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:
[RS_529_b_wlan_b_ch6_5b5_pwl18_back_0mm.da4](#)

DUT: RS_529; Type: RStahl HMI System; Serial: 01452529
Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.97 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.52, 7.52, 7.52); Calibrated: 18.09.2015
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 16.09.2015
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (13x19x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.114 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.37 V/m ; Power Drift = 0.049 dB

Peak SAR (extrapolated) = 0.205 W/kg

SAR(1 g) = 0.106 mW/g ; SAR(10 g) = 0.054 mW/g

Maximum value of SAR (measured) = 0.115 mW/g




Fig. 2: SAR distribution for IEEE802.11 b (5.5MBit/s), channel 6, back side of the device towards the phantom, 0mm distance

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:
[RS_529_b_wlan_b_ch6_5b5_pwl18_front_0mm_mv.da4](#)

DUT: RS_529; Type: RStahl HMI System; Serial: 01452529
Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.97 \text{ mho/m}$; $\epsilon_r = 51.5$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.52, 7.52, 7.52); Calibrated: 18.09.2015
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 16.09.2015
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (14x19x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.978 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.9 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 2.06 W/kg

SAR(1 g) = 0.931 mW/g; SAR(10 g) = 0.417 mW/g

Maximum value of SAR (measured) = 1.08 mW/g




Fig. 3: SAR distribution for IEEE802.11 b (5.5MBit/s), channel 6, front side of the device towards the phantom, 0mm distance, measurement variability

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:
[RS_529_b_wlan_b_ch1_5b5_pwl18_front_0mm.da4](#)

DUT: RS_529; Type: RStahl HMI System; Serial: 01452529
Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2412 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 51.6$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.52, 7.52, 7.52); Calibrated: 18.09.2015
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 16.09.2015
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (13x10x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.801 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.4 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 0.774 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.898 mW/g




Fig. 4: SAR distribution for IEEE802.11 b (5.5MBit/s), channel 1, front side of the device towards the phantom, 0mm distance

Test Laboratory: IMST GmbH, DASY Blue (I); File Name:
[RS_529_b_wlan_b_ch11_5b5_pwl18_front_0mm.da4](#)

DUT: RS_529; Type: RStahl HMI System; Serial: 01452529
 Program Name: IEEE 802.11 b

Communication System: WLAN 2450; Frequency: 2462 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.99$ mho/m; $\epsilon_r = 51.4$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3860; ConvF(7.52, 7.52, 7.52); Calibrated: 18.09.2015
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 16.09.2015
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body Worn/Area Scan (13x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.760 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.0 V/m; Power Drift = 0.042 dB

Peak SAR (extrapolated) = 1.93 W/kg

SAR(1 g) = 0.874 mW/g; SAR(10 g) = 0.381 mW/g

Maximum value of SAR (measured) = 1.01 mW/g




Fig. 5: SAR distribution for IEEE802.11 b (5.5MBit/s), channel 11, front side of the device towards the phantom, 0mm distance