




EMC TEST REPORT



Report No.: 16071443-FCC-E

Supersede Report No: N/A

Applicant	SMT TELECOMM HK LIMITED	
Product Name	Mobile Phone	
Model No.	X455A	
Serial No.	N/A	
Test Standard	FCC Part 15 Subpart B Class B:2015, ANSI C63.4: 2014	
Test Date	Dec 15 to Dec 24, 2016	
Issue Date	Dec 24, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16071443-FCC-E
Page	3 of 29

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 AC POWER LINE CONDUCTED EMISSIONS.....	10
6.2 RADIATED EMISSIONS.....	16
ANNEX A. TEST INSTRUMENT.....	21
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	22
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	25
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	28
ANNEX E. DECLARATION OF SIMILARITY	29

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071443-FCC-E	NONE	Original	Dec 24, 2016

2. Customer information

Applicant Name	SMT TELECOMM HK LIMITED
Applicant Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL
Manufacturer	SMT TELECOMM HK LIMITED
Manufacturer Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	X455A
Serial Model:	N/A
Antenna Gain:	GSM850: 1.0dBi PCS1900: 0.8dBi UMTS-FDD Band V: 1.0dBi UMTS-FDD Band II: 1.0dBi Bluetooth/BLE/WIFI: 1.0dBi GPS: 1.0dBi
Antenna Type:	PIFA antenna
Input Power:	Adapter: Model: PCX455A Input: AC100-240V, 50/60Hz, 0.15A Output: DC 5.0V-500mA Battery: Model: BPX455A Voltage: 3.7V Battery Capacity: 1400mAh Charging limit voltage: 4.2V
Equipment Category :	JBP

Type of Modulation:	<p>GSM / GPRS: GMSK</p> <p>EGPRS: GMSK,8PSK</p> <p>UMTS-FDD: QPSK</p> <p>LTE Band: QPSK, 16QAM</p> <p>802.11b/g/n: DSSS, OFDM</p> <p>Bluetooth: GFSK, π /4DQPSK, 8DPSK</p> <p>BLE: GFSK</p> <p>GPS:BPSK</p>
RF Operating Frequency (ies):	<p>GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz</p> <p>PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz</p> <p>UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz</p> <p>UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz</p> <p>UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz</p> <p>WIFI: 802.11b/g/n(20M): 2412-2462 MHz</p> <p>WIFI: 802.11n(40M): 2422-2452 MHz</p> <p>Bluetooth& BLE: 2402-2480 MHz</p> <p>GPS: 1575.42 MHz</p>
Number of Channels:	<p>GSM 850: 124CH</p> <p>PCS1900: 299CH</p> <p>UMTS-FDD Band V: 102CH</p> <p>UMTS-FDD Band II: 277CH</p> <p>WIFI :802.11b/g/n(20M): 11CH</p> <p>WIFI :802.11n(40M): 7CH</p> <p>Bluetooth: 79CH</p> <p>BLE: 40CH</p> <p>GPS:1CH</p>
Port:	Power Port, Earphone Port, USB Port
Trade Name :	N/A
FCC ID:	2AIMEX455A
Date EUT received:	Dec 14, 2016

Test Report	16071443-FCC-E
Page	8 of 29

Test Date(s): Dec 15 to Dec 24, 2016

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty


Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-


6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	24 °C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	Dec 15, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.107	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.			
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.
-----------	--


Test Report	16071443-FCC-E
Page	11 of 29

	<p>3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.</p> <p>4. All other supporting equipment were powered separately from another main supply.</p> <p>5. The EUT was switched on and allowed to warm up to its normal operating condition.</p> <p>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</p> <p>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</p> <p>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode : USB Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1758	39.32	QP	10.03	49.35	64.68	-15.33
2	L1	0.1758	25.28	AVG	10.03	35.31	54.68	-19.37
3	L1	0.3177	46.18	QP	10.03	56.21	59.77	-3.56
4	L1	0.3177	37.82	AVG	10.03	47.85	49.77	-1.92
5	L1	0.5634	25.55	QP	10.03	35.58	56.00	-20.42
6	L1	0.5634	16.83	AVG	10.03	26.86	46.00	-19.14
7	L1	0.6765	23.88	QP	10.03	33.91	56.00	-22.09
8	L1	0.6765	13.56	AVG	10.03	23.59	46.00	-22.41
9	L1	1.0860	20.30	QP	10.03	30.33	56.00	-25.67
10	L1	1.0860	12.94	AVG	10.03	22.97	46.00	-23.03
11	L1	3.3471	26.05	QP	10.06	36.11	56.00	-19.89
12	L1	3.3471	19.93	AVG	10.06	29.99	46.00	-16.01

Test Mode : USB Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1500	41.22	QP	10.02	51.24	66.00	-14.76
2	N	0.1500	19.09	AVG	10.02	29.11	56.00	-26.89
3	N	0.3177	45.97	QP	10.02	55.99	59.77	-3.78
4	N	0.3177	37.56	AVG	10.02	47.58	49.77	-2.19
5	N	0.5829	25.07	QP	10.02	35.09	56.00	-20.91
6	N	0.5829	16.70	AVG	10.02	26.72	46.00	-19.28
7	N	1.7022	13.81	QP	10.04	23.85	56.00	-32.15
8	N	1.7022	5.73	AVG	10.04	15.77	46.00	-30.23
9	N	3.4212	20.16	QP	10.05	30.21	56.00	-25.79
10	N	3.4212	11.03	AVG	10.05	21.08	46.00	-24.92
11	N	6.9624	24.70	QP	10.10	34.80	60.00	-25.20
12	N	6.9624	18.91	AVG	10.10	29.01	50.00	-20.99

Test Mode : USB Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1930	26.29	QP	13.04	39.33	63.91	-24.58
2	L1	0.1930	21.53	AVG	13.04	34.57	53.91	-19.34
3	L1	0.3844	28.70	QP	12.33	41.03	58.18	-17.15
4	L1	0.3844	19.99	AVG	12.33	32.32	48.18	-15.86
5	L1	1.0484	24.85	QP	11.40	36.25	56.00	-19.75
6	L1	1.0484	16.37	AVG	11.40	27.77	46.00	-18.23
7	L1	2.8141	22.44	QP	11.40	33.84	56.00	-22.16
8	L1	2.8141	12.29	AVG	11.40	23.69	46.00	-22.31
9	L1	3.2969	24.65	QP	11.40	36.05	56.00	-19.95
10	L1	3.2969	12.03	AVG	11.40	23.43	46.00	-22.57
11	L1	3.7930	20.87	QP	11.40	32.27	56.00	-23.73
12	L1	3.7930	12.64	AVG	11.40	24.04	46.00	-21.96

Test Mode : USB Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1891	25.71	QP	13.05	38.76	64.08	-25.32
2	N	0.1891	19.14	AVG	13.05	32.19	54.08	-21.89
3	N	0.3805	27.39	QP	12.34	39.73	58.27	-18.54
4	N	0.3805	22.51	AVG	12.34	34.85	48.27	-13.42
5	N	1.1500	26.27	QP	11.42	37.69	56.00	-18.31
6	N	1.1500	19.10	AVG	11.42	30.52	46.00	-15.48
7	N	1.4781	22.67	QP	11.46	34.13	56.00	-21.87
8	N	1.4781	5.52	AVG	11.46	16.98	46.00	-29.02
9	N	2.8687	28.06	QP	11.63	39.69	56.00	-16.31
10	N	2.8687	19.19	AVG	11.63	30.82	46.00	-15.18
11	N	3.4688	20.31	QP	11.71	32.02	56.00	-23.98
12	N	3.4688	11.77	AVG	11.71	23.48	46.00	-22.52

6.2 Radiated Emissions

Temperature	25 °C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	Dec 20, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.109(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	<div><input checked="" type="checkbox"/></div>	
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarization (whichever gave the higher emission level
-----------	--

Test Report	16071443-FCC-E
Page	17 of 29


	<p>over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%)</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode : USB Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	71.0803	50.24	QP	-13.62	36.62	40.00	-3.38	100	92
2	H	178.1327	44.80	peak	-9.74	35.06	43.50	-8.44	100	116
3	H	218.3085	43.06	peak	-8.91	34.15	46.00	-11.85	100	54
4	H	297.2241	44.34	peak	-7.02	37.32	46.00	-8.68	100	73
5	H	348.0274	43.75	peak	-5.52	38.23	46.00	-7.77	100	81
6	H	798.9797	31.83	peak	3.20	35.03	46.00	-10.97	100	103

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	30.0000	38.07	QP	-0.26	37.81	40.00	-2.19	100	193
2	V	71.0803	49.57	QP	-13.62	35.95	40.00	-4.05	100	347
3	V	105.6415	45.76	peak	-9.79	35.97	43.50	-7.53	100	126
4	V	178.1327	43.20	peak	-9.74	33.46	43.50	-10.04	100	82
5	V	346.8092	37.35	peak	-5.56	31.79	46.00	-14.21	100	70
6	V	890.7278	37.43	QP	4.52	41.95	46.00	-4.05	100	154

Above 1GHz

Frequency (MHz)	Amplitude (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1565.75	50.33	87	155	V	-21.42	74	-23.67	PK
2075.42	50.41	63	133	V	-22.83	74	-23.59	PK
1672.45	49.57	49	150	V	-21.72	74	-24.43	PK
2176.42	50.12	72	120	H	-21.68	74	-23.88	PK
2863.15	49.63	52	110	H	-21.47	74	-24.37	PK
1882.41	50.72	83	125	H	-21.46	74	-23.28	PK

Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to $5 \times 2480 \text{ MHz} = 12,400 \text{ MHz}$.

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>

Test Report	16071443-FCC-E
Page	22 of 29

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Test Report	16071443-FCC-E
Page	23 of 29

Annex B.ii. Photograph: EUT Internal Photo


Test Report	16071443-FCC-E
Page	24 of 29

Annex B.iii. Photograph: Test Setup Photo


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. II. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	JX120051274
USB Cable	Un-shielding	No	2m	CBA3000AH0C1
RJ45 Cable	Un-shielding	No	2m	KX156327541
Router Power cable	Un-shielding	No	2m	13274630Z
Printer Power cable	Un-shielding	No	2m	127581031
Power Cable	Un-shielding	No	0.8m	GT211032

Test Report	16071443-FCC-E
Page	28 of 29

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	16071443-FCC-E
Page	29 of 29

Annex E. DECLARATION OF SIMILARITY

N/A