

FCC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Active speaker

ISSUED TO
Guangzhou Xihe Electronics Co., Ltd.

No.33 Industrial Road Dong Guang Village Huadu District,
Guangzhou



Tested by:

Cao Shaodong
(Engineer)

Date

Aug. 3, 2016

Approved by:

Liao Jianming
(Technical Director)

Date

Aug. 3, 2016

Report No.: BL-SZ1650217-601

EUT Type: Active speaker

Model Name: SBX-20810

Brand Name: N/A

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2AIMS-XIHE

Test conclusion: Pass

Test Date: Jun. 20, 2016 ~ Aug. 2, 2016

Date of Issue: Aug. 3, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Aug. 3, 2016	Initial Issue

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	6
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information	7
2.3	Factory Information	7
2.4	General Description for Equipment under Test (EUT)	7
2.5	Ancillary Equipment	7
2.6	Technical Information	8
2.7	Additional Instructions	8
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List	10
4.3	Description of Test Setup	11
4.3.1	For Antenna Port Test	11
4.3.2	For AC Power Supply Port Test	11
4.3.3	For Radiated Test (Below 30 MHz)	12
4.3.4	For Radiated Test (30 MHz-1 GHz)	12

4.3.5	For Radiated Test (Above 1 GHz).....	13
5	TEST ITEMS.....	14
5.1	Antenna Requirements	14
5.1.1	Standard Applicable	14
5.1.2	Antenna Anti-Replacement Construction	14
5.1.3	Antenna Gain	14
5.2	20 Db Bandwidth	15
5.2.1	Limit.....	15
5.2.2	Test Setups	15
5.2.3	Test Procedure.....	15
5.2.4	Test Result	15
5.3	AC Conducted Emission	16
5.3.1	Limit.....	16
5.3.2	Test Setups	16
5.3.3	Test Procedure.....	16
5.3.4	Test Result	16
5.4	Radiated Spurious Emission	17
5.4.1	Limit.....	17
5.4.2	Test Setups	17
5.4.3	Test Procedure.....	17
5.4.4	Test Result	18
5.5	Band Edge (Restricted-band band-edge)	19
5.5.1	Limit.....	19
5.5.2	Test Setups	19
5.5.3	Test Procedure.....	19
5.5.4	Test Result	19
ANNEX A	TEST RESULT	20
A.1	20Db bandwidth	20
A.2	AC Conducted Emission	22
A.3	Radiated Emission	24

A.4 Band Edge(Restricted-band band-edge)32

ANNEX B TEST SETUP PHOTOS36

ANNEX C EUT EXTERNAL PHOTOS36

ANNEX D EUT INTERNAL PHOTOS36

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v4.3.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Guangzhou Xihe Electronics Co., Ltd.
Address	No.33 Industrial Road Dongguang Village Huadu District, Guangzhou

2.2 Manufacturer Information

Manufacturer	Guangzhou Xihe Electronics Co., Ltd.
Address	No.33 Industrial Road Dongguang Village Huadu District, Guangzhou

2.3 Factory Information

Factory	Guangzhou Xihe Electronics Co., Ltd.
Address	No.33 Industrial Road Dongguang Village Huadu District, Guangzhou

2.4 General Description for Equipment under Test (EUT)

EUT Type	Active speaker
Model Name Under Test	SBX-20810
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Bluetooth 2.1 + EDR

2.5 Ancillary Equipment

Ancillary Equipment 1	Charger	
	Brand Name	N/A
	Model No.	AV-8115BT5
	Serial No.	N/A
	Rated Input	120 V /240 V~, 350 Ma, 50 Hz
	Rated Output	25 V~, 2300 Ma, 50 Hz

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:


Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Transfer Rate	1 Mbps, 2 Mbps, 3 Mbps
Product Type	Mobile and portable
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency range used is 2400 MHz to 2483.5 MHz.
Number of channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz).
Antenna Type	PCB Antenna
Antenna Gain	0 dBi (All involve the antenna gain test item, has been included in the final results)
About the Product	Only the Bluetooth 2.1 + EDR was tested in this report.

2.7 Additional Instructions

EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMU.
------	---

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-15 Edition)	Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	--	Pass	Note1
2	20 Db Bandwidth	15.215©	ANNEX A.1	Pass	Note2
3	AC Conducted Emission	15.207	ANNEX A.2	Pass	--
4	Radiated Spurious Emission	15.249(a)	ANNEX A.3	Pass	Note2
5	Band Edge(Restricted-band band-edge)	15.249(a)	ANNEX A.4	Pass	Note2

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Because of the modulation of $\pi/4$ -DQPSK same as 8-DPSK, and the test results are basically the same with them, so we chose 8-DPSK as a typical representative to appear on the report.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:


Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa — 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	120 V /240 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2016.07.13	2017.07.12
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2016.07.13	2017.07.12
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2016.07.13	2017.07.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2016.07.13	2017.07.12
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.18	2016.10.17
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2016.07.13	2017.07.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.13	2017.07.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2016.07.13	2017.07.12
Power Splitter	KMW	DCPD-LDC	1305003215	2016.07.13	2017.07.12
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2016.07.13	2017.07.12
Attenuator (20 Db)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 Db)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2016.07.13	2017.07.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2015.08.07	2016.08.06
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703	--	--


4.3 Description of Test Setup

4.3.1 For Antenna Port Test




(Diagram 1)

4.3.2 For AC Power Supply Port Test




(Diagram 2)

4.3.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.3.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.3.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-210, 5.4 (6)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in Db comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one Db for every 3 Db that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	An embedded-in antenna design is used.

Reference Documents	Item
Photo	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 20 Db Bandwidth

5.2.1 Limit

FCC §15.215©; RSS-Gen 6.6

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 Db bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.2.2 Test Setups

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 Db bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 Db bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 AC Conducted Emission

5.3.1 Limit

FCC §15.207; RSS-Gen 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (Db μ V)	
	Quai-peak	Average
0.15 — 0.50	66 to 56	56 to 46
0.50 — 5	56	46
0.50 — 30	60	50

5.3.2 Test Setups

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Radiated Spurious Emission

5.4.1 Limit

FCC §15.249(a); RSS-210 2.5

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency (MHz)	Field Strength of Fundamental (Mv/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 Db below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 — 0.490	2400/F(kHz)	300
0.490 — 1.705	24000/F(kHz)	30
1.705 — 30.0	30	30
30 — 88	100	3
88 — 216	150	3
216 — 960	200	3
Above 960	500	3

Note:

- For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 Db above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.4.2 Test Setups

See section 4.3.2-4.3.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Restricted-band band-edge)

5.5.1 Limit

FCC §15.249(a); RSS-210 A8.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.5.2 Test Setups

See section 4.3.3 to 4.3.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 Db lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.5.4 Test Result

Please refer to ANNEX A.4.

ANNEX A TEST RESULT

A.1 20Db bandwidth

Test Data

DH5 Mode:


Channel	20 Db Bandwidth (MHz)
Low	1.012
Middle	1.012
High	0.999

3DH5 Mode:

Channel	20 Db Bandwidth (MHz)
Low	1.255
Middle	1.259
High	1.259


Test plots

DH5 LOW CHANNEL




Date: 8.JUN.2016 09:06:07

DH5 MIDDLE CHANNEL




Date: 8.JUN.2016 09:08:27

DH5 HIGH CHANNEL



Date: 8.JUN.2016 09:09:19

3DH5 LOW CHANNEL




Date: 8.JUN.2016 09:11:19

3DH5 MIDDLE CHANNEL



Date: 8.JUN.2016 09:10:43

3DH5 HIGH CHANNEL




Date: 8.JUN.2016 09:10:08

A.2 AC Conducted Emission

Note 1: The EUT is working in the Normal link mode.


Note 2: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (Db)	Limit (dBuV)	Margin (Db)	Detector	Line	Verdict
1	0.21	59.2	11.00	64.4	5.20	Peak	L Line	Pass
1**	0.21	49.0	11.00	54.4	5.40	AV	L Line	Pass
2	0.27	51.6	11.00	62.5	10.90	Peak	L Line	Pass
2**	0.27	35.6	11.00	52.5	16.90	AV	L Line	Pass
3	0.51	42.0	11.00	56.0	14.00	Peak	L Line	Pass
3**	0.51	29.6	11.00	46.0	16.40	AV	L Line	Pass
4	1.47	38.9	11.00	56.0	17.10	Peak	L Line	Pass
4**	1.47	24.6	11.00	46.0	21.40	AV	L Line	Pass
5	4.53	41.3	11.00	56.0	14.70	Peak	L Line	Pass
5**	4.53	28.1	11.00	46.0	17.90	AV	L Line	Pass
6	19.76	36.2	11.00	60.0	23.80	Peak	L Line	Pass
6**	19.76	24.7	11.00	50.0	25.30	AV	L Line	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (Db)	Limit (dBuV)	Margin (Db)	Detector	Line	Verdict
1	0.21	57.4	11.00	64.4	7.00	Peak	N Line	Pass
1**	0.21	46.5	11.00	54.4	7.90	AV	N Line	Pass
2	0.27	50.5	11.00	62.5	12.00	Peak	N Line	Pass
2**	0.27	38.7	11.00	52.5	13.80	AV	N Line	Pass
3	0.50	44.1	11.00	56.0	11.90	Peak	N Line	Pass
3**	0.50	32.1	11.00	46.0	13.90	AV	N Line	Pass
4	1.46	41.8	11.00	56.0	14.20	Peak	N Line	Pass
4**	1.46	27.8	11.00	46.0	18.20	AV	N Line	Pass
5	4.42	39.8	11.00	56.0	16.20	Peak	N Line	Pass
5**	4.42	25.0	11.00	46.0	21.00	AV	N Line	Pass
6	20.17	37.6	11.00	60.0	22.40	Peak	N Line	Pass
6**	20.17	26.9	11.00	50.0	23.10	AV	N Line	Pass

A.3 Radiated Emission

Note 1: The symbol of “—” in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 Db lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz.


Test Data and Plots

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (Db)	Limit (dBuV/m)	Margin (Db)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	63.70	34.76	-20.37	40.0	5.24	Peak	20.10	100	Vertical	Pass
2	86.00	36.94	-23.11	40.0	3.06	Peak	37.00	100	Vertical	Pass
3	90.12	37.13	-21.92	43.5	6.37	Peak	57.10	100	Vertical	Pass
4	135.95	32.81	-23.50	43.5	10.69	Peak	43.60	100	Vertical	Pass
5	219.83	28.34	-20.06	46.0	17.66	Peak	206.30	100	Vertical	Pass
6	396.33	33.25	-15.33	46.0	12.75	Peak	206.30	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (Db)	Limit (dBuV/m)	Margin (Db)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	69.28	28.39	-24.08	40.0	11.61	Peak	115.50	100	Horizontal	Pass
2	130.85	30.02	-25.38	43.5	13.48	Peak	306.00	100	Horizontal	Pass
3	219.35	26.40	-22.66	46.0	19.60	Peak	125.60	100	Horizontal	Pass
4	315.35	29.26	-20.37	46.0	16.74	Peak	232.90	100	Horizontal	Pass
5	355.11	29.03	-19.50	46.0	16.97	Peak	155.60	100	Horizontal	Pass
6	750.29	30.90	-13.19	46.0	15.10	Peak	182.60	100	Horizontal	Pass

Test Data (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz is the fundamental signal.

Note 2: Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Note 3: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 Db below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Note 4: Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20 Db from the applicable limit) and considered that's already beyond the background noise floor.

Note 5: Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.

Note 6: The Peak value is less than the AV limit, so don't show in this report.

DH5 LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (Db)	Limit (dBuV/m)	Margin (Db)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.45	48.16	-0.42	74	25.84	Peak	83	150	Vertical	Pass
2	2401.65	78.03	-0.27	114.0	35.97	Peak	111.00	150	Vertical	Pass ^{Note 1}
2**	2401.65	N/A	-0.27	94.0	N/A	AV	111.00	150	Vertical	Pass ^{Note 6}
3	4803.30	54.26	13.74	74.0	19.74	Peak	36.10	150	Vertical	Pass
3**	4803.30	50.16	13.74	74.0	3.84	AV	36.10	150	Vertical	Pass
4	9436.77	45.96	17.89	74	28.04	Peak	26.7	150	Vertical	Pass
5	13498.75	46.92	20.24	74	27.08	Peak	203.6	150	Vertical	Pass
6	18989.60	45.54	12.60	74	28.46	Peak	45.6	150	Vertical	Pass

DH5 LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1724.87	54.55	-4.01	74	19.46	Peak	229.8	150	Horizontal	Pass
2	2401.65	84.87	-0.27	114.0	29.13	Peak	60.40	150	Horizontal	Pass ^{Note 1}
2**	2401.65	N/A	-0.27	94.0	N/A	AV	60.40	150	Horizontal	Pass ^{Note 6}
3	4804.80	57.22	13.77	74.0	16.78	Peak	62.30	150	Horizontal	Pass
3**	4804.80	52.34	13.77	54.0	1.66	AV	62.30	150	Horizontal	Pass
4	11065.31	43.76	15.05	74	30.24	Peak	90.9	150	Horizontal	Pass
5	14777.87	46.43	9.08	74	27.57	Peak	66.9	150	Horizontal	Pass
6	18261.65	46.08	12.82	74	27.92	Peak	282	150	Horizontal	Pass

DH5 MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.45	48.16	-0.42	74	25.84	Peak	83	150	Vertical	Pass
2	2440.64	78.61	-0.41	114.0	35.39	Peak	11.00	150	Vertical	Pass ^{Note 1}
2**	2440.64	N/A	-0.41	94.0	N/A	AV	11.00	150	Vertical	Pass ^{Note 6}
3	4882.03	54.74	13.60	74.0	19.26	Peak	251.00	150	Vertical	Pass
3**	4882.03	50.12	13.60	54.0	3.88	AV	251.00	150	Vertical	Pass
4	9436.77	45.96	17.89	74	28.04	Peak	26.7	150	Vertical	Pass
5	13498.75	46.92	20.24	74	27.08	Peak	203.6	150	Vertical	Pass
6	18989.60	45.54	12.60	74	28.46	Peak	45.6	150	Vertical	Pass

DH5 MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1991.75	49.52	-2.53	74.0	24.48	Peak	149.00	150	Horizontal	Pass
2	2441.14	85.47	-0.38	114.0	28.53	Peak	82.00	150	Horizontal	Pass ^{Note 1}
2**	2441.14	N/A	-0.38	94.0	N/A	AV	82.00	150	Horizontal	Pass ^{Note 6}
3	4882.03	58.03	13.60	74.0	15.97	Peak	175.00	150	Horizontal	Pass
3**	4882.03	50.94	13.60	54.0	3.06	AV	175.00	150	Horizontal	Pass
4	11065.31	43.76	15.05	74	30.24	Peak	90.9	150	Horizontal	Pass
5	14777.87	46.43	9.08	74	27.57	Peak	66.9	150	Horizontal	Pass
6	18261.65	46.08	12.82	74	27.92	Peak	282	150	Horizontal	Pass

DH5 HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.45	48.16	-0.42	74	25.84	Peak	83	150	Vertical	Pass
2	2480.13	76.48	-0.60	114.0	37.52	Peak	320.90	150	Vertical	Pass ^{Note 1}
2**	2480.13	N/A	-0.60	94.0	N/A	AV	320.90	150	Vertical	Pass ^{Note 6}
3	4960.01	56.21	14.22	74.0	17.79	Peak	32.80	150	Vertical	Pass
3**	4960.01	49.51	14.22	54.0	4.49	AV	32.80	150	Vertical	Pass
4	9436.77	45.96	17.89	74	28.04	Peak	26.7	150	Vertical	Pass
5	13498.75	46.92	20.24	74	27.08	Peak	203.6	150	Vertical	Pass
6	18989.60	45.54	12.60	74	28.46	Peak	45.6	150	Vertical	Pass

DH5 HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1991.75	49.52	-2.53	74.0	24.48	Peak	149.00	150	Horizontal	Pass
2	2480.13	84.82	-0.60	114.0	29.18	Peak	9.70	150	Horizontal	Pass ^{Note 1}
2**	2480.13	N/A	-0.60	94.0	N/A	AV	9.70	150	Horizontal	Pass ^{Note 6}
3	4960.01	60.24	14.22	74.0	13.76	Peak	5.30	150	Horizontal	Pass
3**	4960.01	49.54	14.22	54.0	4.06	AV	5.30	150	Horizontal	Pass
4	11065.31	43.76	15.05	74	30.24	Peak	90.9	150	Horizontal	Pass
5	14777.87	46.43	9.08	74	27.57	Peak	66.9	150	Horizontal	Pass
6	18261.65	46.08	12.82	74	27.92	Peak	282	150	Horizontal	Pass

3DH5 LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.70	47.60	-0.42	74	26.40	Peak	271.2	150	Vertical	Pass
2	2401.65	78.03	-0.27	114.0	35.97	Peak	111.00	150	Vertical	Pass ^{Note 1}
2**	2401.65	N/A	-0.27	94.0	N/A	AV	111.00	150	Vertical	Pass ^{Note 6}
3	4803.30	54.26	13.74	74.0	19.74	Peak	36.10	150	Vertical	Pass
3**	4803.30	47.29	13.74	54.0	6.71	AV	36.10	150	Vertical	Pass
4	10155.57	45.30	16.61	74	28.70	Peak	315	150	Vertical	Pass
5	16472.96	46.91	10.59	74	27.10	Peak	60.3	150	Vertical	Pass
6	18261.65	44.31	11.18	74	29.70	Peak	182	150	Vertical	Pass

3DH5 LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1722.68	52.86	-4.03	74	21.15	Peak	125.1	150	Horizontal	Pass
2	2401.65	85.09	-0.27	114.0	28.91	Peak	60.50	150	Horizontal	Pass ^{Note 1}
2**	2401.65	N/A	-0.27	94.0	N/A	AV	60.50	150	Horizontal	Pass ^{Note 6}
3	4806.30	57.04	13.77	74.0	16.96	Peak	359.20	150	Horizontal	Pass
3**	4806.30	48.63	13.77	54.0	5.37	AV	359.20	150	Horizontal	Pass
4	7785.77	44.44	19.33	74	29.56	Peak	271.1	150	Horizontal	Pass
5	15235.44	43.81	9.68	74	30.19	Peak	356.6	150	Horizontal	Pass
6	20337.77	46.55	9.52	74	27.45	Peak	52	150	Horizontal	Pass

3DH5 MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.70	47.60	-0.42	74	26.40	Peak	271.2	150	Vertical	Pass
2	2440.64	78.35	-0.41	114.0	35.65	Peak	284.00	150	Vertical	Pass ^{Note 1}
2**	2440.64	N/A	-0.41	94.0	N/A	AV	284.00	150	Vertical	Pass ^{Note 6}
3	4882.03	54.48	13.60	74.0	19.52	Peak	115.00	150	Vertical	Pass
3**	4882.03	48.48	13.60	54.0	5.52	AV	115.00	150	Vertical	Pass
4	10155.57	45.30	16.61	74	28.70	Peak	315	150	Vertical	Pass
5	16472.96	46.91	10.59	74	27.10	Peak	60.3	150	Vertical	Pass
6	18261.65	44.31	11.18	74	29.70	Peak	182	150	Vertical	Pass

3DH5 MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1722.68	52.86	-4.03	74	21.15	Peak	125.1	150	Horizontal	Pass
2	2440.64	85.29	-0.41	114.0	28.71	Peak	127.00	150	Horizontal	Pass ^{Note 1}
2**	2440.64	N/A	-0.41	94.0	N/A	AV	127.00	150	Horizontal	Pass ^{Note 6}
3	4882.03	57.70	13.60	74.0	16.30	Peak	327.00	150	Horizontal	Pass
3**	4882.03	50.23	13.60	54.0	3.77	AV	327.00	150	Horizontal	Pass
4	7785.77	44.44	19.33	74	29.56	Peak	271.1	150	Horizontal	Pass
5	15235.44	43.81	9.68	74	30.19	Peak	356.6	150	Horizontal	Pass
6	20337.77	46.55	9.52	74	27.45	Peak	52	150	Horizontal	Pass

3DH5 HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.70	47.60	-0.42	74	26.40	Peak	271.2	150	Vertical	Pass
2	2480.13	76.49	-0.60	114.0	37.51	Peak	194.00	150	Vertical	Pass ^{Note 1}
2**	2480.13	N/A	-0.60	94.0	N/A	AV	194.00	150	Vertical	Pass ^{Note 6}
3	4960.76	55.98	14.26	74.0	18.02	Peak	328.00	150	Vertical	Pass
3**	4960.76	45.54	14.26	54.0	8.46	AV	328.00	150	Vertical	Pass
4	10155.57	45.30	16.61	74	28.70	Peak	315	150	Vertical	Pass
5	16472.96	46.91	10.59	74	27.10	Peak	60.3	150	Vertical	Pass
6	18261.65	44.31	11.18	74	29.70	Peak	182	150	Vertical	Pass

3DH5 HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1722.68	52.86	-4.03	74	21.15	Peak	125.1	150	Horizontal	Pass
2	2480.13	84.75	-0.60	114.0	29.25	Peak	176.00	150	Horizontal	Pass ^{Note 1}
2**	2480.13	N/A	-0.60	94.0	N/A	AV	176.00	150	Horizontal	Pass ^{Note 6}
3	4962.26	60.07	14.23	74.0	13.93	Peak	173.00	150	Horizontal	Pass
3**	4962.26	46.68	14.23	54.0	7.32	AV	173.00	150	Horizontal	Pass
4	7785.77	44.44	19.33	74	29.56	Peak	271.1	150	Horizontal	Pass
5	15235.44	43.81	9.68	74	30.19	Peak	356.6	150	Horizontal	Pass
6	20337.77	46.55	9.52	74	27.45	Peak	52	150	Horizontal	Pass

Hopping Mode:

GFSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.45	48.16	-0.42	74	25.84	Peak	83	150	Vertical	Pass
2	2475.13	82.95	-0.50	114.0	31.05	Peak	197.20	150	Vertical	Pass ^{Note 1}
2**	2475.13	N/A	-0.50	94.0	N/A	AV	197.20	150	Vertical	Pass ^{Note 6}
3	4955.51	55.92	14.09	74.0	18.08	Peak	191.40	150	Vertical	Pass
3**	4955.51	47.92	14.09	54.0	6.08	AV	191.40	150	Vertical	Pass
4	9436.77	45.96	17.89	74	28.04	Peak	26.7	150	Vertical	Pass
5	13498.75	46.92	20.24	74	27.08	Peak	203.6	150	Vertical	Pass
6	18989.60	45.54	12.60	74	28.46	Peak	45.6	150	Vertical	Pass

GFSK MODE 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1991.75	49.52	-2.53	74.0	24.48	Peak	149.00	150	Horizontal	Pass
2	2403.15	82.32	-0.21	114.0	31.68	Peak	193.00	150	Horizontal	Pass ^{Note 1}
2**	2403.15	N/A	-0.21	94.0	N/A	AV	193.00	150	Horizontal	Pass ^{Note 6}
3	4945.76	56.58	14.11	74.0	17.42	Peak	100.00	150	Horizontal	Pass
3**	4945.76	48.68	14.11	54.0	5.32	AV	100.00	150	Horizontal	Pass
4	11065.31	43.76	15.05	74	30.24	Peak	90.9	150	Horizontal	Pass
5	14777.87	46.43	9.08	74	27.57	Peak	66.9	150	Horizontal	Pass
6	18261.65	46.08	12.82	74	27.92	Peak	282	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2292.70	47.60	-0.42	74	26.40	Peak	271.2	150	Vertical	Pass
2	2403.15	79.96	-0.21	114.0	34.04	Peak	189.70	150	Vertical	Pass ^{Note 1}
2**	2403.15	N/A	-0.21	94.0	N/A	AV	189.70	150	Vertical	Pass ^{Note 6}
3	4957.76	55.60	14.15	74.0	18.40	Peak	190.60	150	Vertical	Pass
3**	4957.76	48.99	14.15	54.0	5.01	AV	190.60	150	Vertical	Pass
4	10155.57	45.30	16.61	74	28.70	Peak	315	150	Vertical	Pass
5	16472.96	46.91	10.59	74	27.10	Peak	60.3	150	Vertical	Pass
6	18261.65	44.31	11.18	74	29.70	Peak	182	150	Vertical	Pass

8-DPSK MODE 1 GHz to 25 GHz, ANT H


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1722.68	52.86	-4.03	74	21.15	Peak	125.1	150	Horizontal	Pass
2	2401.65	82.11	-0.27	114.0	31.89	Peak	261.00	150	Horizontal	Pass ^{Note 1}
2**	2401.65	N/A	-0.27	94.0	N/A	AV	261.00	150	Horizontal	Pass ^{Note 6}
3	4818.30	54.98	13.90	74.0	19.02	Peak	239.00	150	Horizontal	Pass
3**	4818.30	49.84	13.90	54.0	4.16	AV	239.00	150	Horizontal	Pass
4	7785.77	44.44	19.33	74	29.56	Peak	271.1	150	Horizontal	Pass
5	15235.44	43.81	9.68	74	30.19	Peak	356.6	150	Horizontal	Pass
6	20337.77	46.55	9.52	74	27.45	Peak	52	150	Horizontal	Pass

A.4 Band Edge(Restricted-band band-edge)


Test Data and Test Plots

Note 1: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


DH5 LOW CHANNEL; PEAK




DH5 LOW CHANNEL; AVERAGE




DH5 HIGH CHANNEL; PEAK




DH5 HIGH CHANNEL; AVERAGE




3DH5 LOW CHANNEL; PEAK




3DH5 LOW CHANNEL; AVERAGE



3DH5 HIGH CHANNEL; PEAK




3DH5 HIGH CHANNEL; AVERAGE




Hopping Mode:


DH5 LOW CHANNEL; PEAK




DH5 LOW CHANNEL; AVERAGE




DH5 HIGH CHANNEL; PEAK




DH5 HIGH CHANNEL; AVERAGE




3DH5 LOW CHANNEL; PEAK




3DH5 LOW CHANNEL; AVERAGE



3DH5 HIGH CHANNEL; PEAK



3DH5 HIGH CHANNEL; AVERAGE



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ1650217-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ1650217-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ1650217-AI.PDF”.

--END OF REPORT--