

FCC REPORT

Applicant: JOYO TECHNOLOGY CO., LTD

Address of Applicant: 2/F, Lushi Industry Building, 28th District, Baoan, Shenzhen, 518101 China.

Manufacturer/Factory: JOYO TECHNOLOGY CO., LTD

Address of Manufacturer/Factory: 2/F, Lushi Industry Building, 28th District, Baoan, Shenzhen, 518101 China.

Equipment Under Test (EUT)

Product Name: 5.8G Digital Wireless Transmitter

Model No.: JW-02

Trade Mark: N/A

FCC ID: 2AIN7-JW-02

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: April 03, 2018

Date of Test: April 03, 2018 - May 10, 2018

Date of report issued: May 10, 2018

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	May 10, 2018	Original

Prepared By:




Date:

May 10, 2018

Project Engineer

Check By:



Date:

May 10, 2018

Reviewer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION.....	2
3	CONTENTS.....	3
4	TEST SUMMARY	4
4.1	MEASUREMENT UNCERTAINTY.....	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE	7
5.3	DESCRIPTION OF SUPPORT UNITS.....	7
5.4	TEST FACILITY.....	7
5.5	TEST LOCATION	7
5.6	ADDITIONAL INSTRUCTIONS	8
6	TEST INSTRUMENTS LIST	9
7	TEST RESULTS AND MEASUREMENT DATA	10
7.1	ANTENNA REQUIREMENT	10
7.2	CONDUCTED EMISSIONS	11
7.3	RADIATED EMISSION METHOD	14
7.3.1	Field Strength of The Fundamental Signal	16
7.3.2	Spurious emissions	17
7.3.3	Bandedge emissions.....	22
7.4	20dB OCCUPY BANDWIDTH	24
8	TEST SETUP PHOTO.....	26
9	EUT CONSTRUCTIONAL DETAILS.....	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10: 2013 and ANSI C63.4: 2014.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	5.8G Digital Wireless Transmitter
Model No.:	JW-02
Test Model No:	JW-02
Quantity of tested samples	1
Serial No.:	N/A
Test sample(s) ID:	N/A
Sample(s) Status	Engineer sample
Hardware:	N/A
Software:	N/A
Operation Frequency:	5731MHz-5819MHz
Channel numbers:	45
Channel separation:	2MHz
Modulation type:	GFSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi(declare by Applicant)
Power supply:	DC 3.7V From Battery, DC 5V From Adapter input AC 120V, 60Hz

Operation Frequency each of channel					
Channel	Frequency	Channel	Frequency	Channel	Frequency
CH1	5731 MHz	CH21	5771 MHz
CH2	5733 MHz	CH22	5773 MHz	CH43	5815 MHz
CH3	5735 MHz	CH23	5775 MHz	CH44	5817 MHz
...	...	CH24	5777 MHz	CH45	5819 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
Lowest channel	5731 MHz
Middle channel	5775 MHz
Highest channel	5819 MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

Per-test mode .

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows: X axis is worse case and reported

Axis	X	Y	Z
Field Strength(dBuV/m)	101.56	98.35	99.98

5.3 Description of Support Units

None

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

5.5 Test Location


All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.6 Additional instructions

Software (Used for test) from client

Mode	Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.		
Power level setup in software			
Test Software Name	I2C Tool		
Test Software Version	2.7		
Support Units (Software installation media)	Description	Manufacturer	Model
	LCD TV	PHILIPS	AU1A1212002906
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH1	5731	TX level is built-in set parameters and cannot be changed and selected.
	CH23	5775	
	CH45	5819	

Run Software



6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 28 2017	June 27 2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 28 2017	June 27 2018
10	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
11	Coaxial cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
12	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
16	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
17	Power Meter	Anritsu	ML2495A	GTS540	June 28 2017	June 27 2018
18	Power Sensor	Anritsu	MA2411B	GTS541	June 28 2017	June 27 2018

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
<p><i>The antenna is PCB antenna, the best case gain of the antenna is 0dBi</i></p> 	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50	* Decreases with the logarithm of the frequency.	
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
Test setup:	<div><p style="text-align: center;">Reference Plane</p><p style="text-align: center;">Test table/Insulation plane</p><p><i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i></p></div>																
Test procedure:	<div><div>1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</div></div>																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test results:	Pass																


Site LAB
Limit: FCC Part 15 B QP
EUT: Digital Wireless Transmitter&Receiver
M/N: JW-02
Mode: Charging
Note:

Phase: **L1**
Power: AC 120V/60Hz

Report No.: GTS201805000121F01

Temperature: 23.6
Humidity: 54 %

Conducted Emission Measurement



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1590	43.01	9.73	52.74	65.52	-12.78	peak	
2	*	0.1949	42.33	9.74	52.07	63.83	-11.76	peak	
3		0.3750	35.94	9.77	45.71	58.39	-12.68	peak	
4		1.3604	31.00	9.86	40.86	56.00	-15.14	peak	
5		3.7500	30.32	10.10	40.42	56.00	-15.58	peak	
6		5.3340	29.43	10.20	39.63	60.00	-20.37	peak	

*:Maximum data x:Over limit l:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Site LAB
Limit: FCC Part 15 B QP
EUT: Digital Wireless Transmitter&Receiver
M/N: JW-02
Mode: Charging
Note:

Phase: **N**
Power: AC 120V/60Hz

Report No.: GTS201805000121F01

Temperature: 23.6
Humidity: 54 %


Conducted Emission Measurement

File :JW-02 CE

Data :#4

Date: 2018-4-9

Time: 10:06:24



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1565	44.14	9.73	53.87	65.65	-11.78	peak	
2		0.1770	40.49	9.73	50.22	64.63	-14.41	peak	
3		0.3255	36.90	9.77	46.67	59.57	-12.90	peak	
4		0.5369	33.35	9.79	43.14	56.00	-12.86	peak	
5		1.5539	31.41	9.88	41.29	56.00	-14.71	peak	
6		7.4310	26.76	10.28	37.04	60.00	-22.96	peak	

*:Maximum data x:Over limit !:over margin


(Reference Only)


Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 40GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	Carrier frequency		94.00		Average Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	<div>Below 1GHz</div> <div></div> <div>Above 1GHz</div>				

	
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5731.00	78.89	31.54	13.22	30.25	93.40	114.00	-20.60	Vertical
5775.00	78.35	31.65	13.64	30.29	93.35	114.00	-20.65	Vertical
5819.00	79.34	31.72	13.96	30.34	94.68	114.00	-19.32	Vertical
5731.00	86.22	31.54	13.22	30.25	100.73	114.00	-13.27	Horizontal
5775.00	86.75	31.65	13.64	30.29	101.75	114.00	-12.25	Horizontal
5819.00	86.75	31.72	13.96	30.34	102.09	114.00	-11.91	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5731.00	69.55	31.54	13.22	30.25	84.06	94.00	-9.94	Vertical
5775.00	69.59	31.65	13.64	30.29	84.59	94.00	-9.41	Vertical
5819.00	70.02	31.72	13.96	30.34	85.36	94.00	-8.64	Vertical
5731.00	77.09	31.54	13.22	30.25	91.60	94.00	-2.40	Horizontal
5775.00	76.69	31.65	13.64	30.29	91.69	94.00	-2.31	Horizontal
5819.00	76.66	31.72	13.96	30.34	92.00	94.00	-2.00	Horizontal

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*

NOTE: RBW 5MHz VBW 5MHz Peak detector is for PK value , RMS detector is for AV value

7.3.2 Spurious emissions

■ Below 1GHz


Horizontal:

Site LAB
 Limit: FCC Part15 Class B Radiation
 EUT: 5.8G Digital Wireless Transmitter
 M/N: JW-02
 Mode:Charging
 Note:
 Engineer Signature:

Polarization: **Horizontal**
 Power: AC 120V/60Hz
 Distance: 3m

Temperature: 23.9
 Humidity: 46 %

Radiated Emission Measurement



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		34.5173	8.20	13.49	21.69	40.00	-18.31	peak		
2		58.4074	8.20	13.11	21.31	40.00	-18.69	peak		
3	*	209.3129	20.37	10.67	31.04	43.50	-12.46	peak		
4		392.0951	8.74	15.40	24.14	46.00	-21.86	peak		
5		658.8362	8.94	20.23	29.17	46.00	-16.83	peak		
6		731.9203	9.44	21.38	30.82	46.00	-15.18	peak		

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


Vertical:

Site LAB
Limit: FCC Part15 Class B Radiation
EUT: 5.8G Digital Wireless Transmitter
M/N: JW-02
Mode:Charging
Note:
Engineer Signature:

Polarization: **Vertical**
Power: AC 120V/60Hz
Distance: 3m

Temperature: 23.9
Humidity: 46 %

Radiated Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	41.2765	18.68	14.11	32.79	40.00	-7.21	peak		
2		72.0843	13.91	10.67	24.58	40.00	-15.42	peak		
3		96.4362	19.51	10.31	29.82	43.50	-13.68	peak		
4		152.1297	9.22	14.56	23.78	43.50	-19.72	peak		
5		219.8449	12.59	11.30	23.89	46.00	-22.11	peak		
6		726.8052	9.28	21.33	30.61	46.00	-15.39	peak		

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

■ Above 1GHz

Test channel:	Channel 1
---------------	-----------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11462.00	39.09	34.27	14.78	31.78	56.36	74.00	-17.64	Vertical
17193.00	35.53	36.32	15.65	32.03	55.47	74.00	-18.53	Vertical
22924.00	35.89	38.51	16.14	32.12	58.42	74.00	-15.58	Vertical
28665.00	*					74.00		Vertical
40000.00	*					74.00		Vertical
11462.00	43.79	34.27	14.78	31.78	61.06	74.00	-12.94	Horizontal
17193.00	38.87	36.32	15.65	32.03	58.81	74.00	-15.19	Horizontal
22924.00	37.57	38.51	16.14	32.12	60.10	74.00	-13.90	Horizontal
28665.00	*					74.00		Horizontal
40000.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11462.00	26.73	34.27	14.78	31.78	44.00	54.00	-10.00	Vertical
17193.00	23.74	36.32	15.65	32.03	43.68	54.00	-10.32	Vertical
22924.00	20.95	38.51	16.14	32.12	43.48	54.00	-10.52	Vertical
28665.00	*					54.00		Vertical
40000.00	*					54.00		Vertical
11462.00	30.89	34.27	14.78	31.78	48.16	54.00	-5.84	Horizontal
17193.00	26.51	36.32	15.65	32.03	46.45	54.00	-7.55	Horizontal
22924.00	23.49	38.51	16.14	32.12	46.02	54.00	-7.98	Horizontal
28665.00	*					54.00		Horizontal
40000.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Channel 23
---------------	------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11550.00	39.84	34.29	14.79	31.79	57.13	74.00	-16.87	Vertical
17325.00	35.88	36.34	15.66	32.04	55.84	74.00	-18.16	Vertical
23100.00	35.33	38.53	16.15	32.13	57.88	74.00	-16.12	Vertical
28875.00	*					74.00		Vertical
40000.00	*					74.00		Vertical
11550.00	43.56	34.29	14.79	31.79	60.85	74.00	-13.15	Horizontal
17325.00	39.21	36.34	15.66	32.04	59.17	74.00	-14.83	Horizontal
23100.00	37.95	38.53	16.15	32.13	60.50	74.00	-13.50	Horizontal
28875.00	*					74.00		Horizontal
40000.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11550.00	26.68	34.29	14.79	31.79	43.97	54.00	-10.03	Vertical
17325.00	23.63	36.34	15.66	32.04	43.59	54.00	-10.41	Vertical
23100.00	21.91	38.53	16.15	32.13	44.46	54.00	-9.54	Vertical
28875.00	*					54.00		Vertical
40000.00	*					54.00		Vertical
11550.00	31.00	34.29	14.79	31.79	48.29	54.00	-5.71	Horizontal
17325.00	27.19	36.34	15.66	32.04	47.15	54.00	-6.85	Horizontal
23100.00	23.53	38.53	16.15	32.13	46.08	54.00	-7.92	Horizontal
28875.00	*					54.00		Horizontal
40000.00	*					54.00		Horizontal

Remark:

4. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
5. *"*", means this data is the too weak instrument of signal is unable to test.*
6. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:	Channel 45
---------------	------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11638.00	39.51	34.31	14.80	31.80	56.82	74.00	-17.18	Vertical
17457.00	35.89	36.36	15.67	32.05	55.87	74.00	-18.13	Vertical
23276.00	35.13	38.55	16.16	32.14	57.70	74.00	-16.30	Vertical
29095.00	*					74.00		Vertical
40000.00	*					74.00		Vertical
11638.00	43.61	34.31	14.80	31.80	60.92	74.00	-13.08	Horizontal
17457.00	39.20	36.36	15.67	32.05	59.18	74.00	-14.82	Horizontal
23276.00	37.80	38.55	16.16	32.14	60.37	74.00	-13.63	Horizontal
29095.00	*					74.00		Horizontal
40000.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11638.00	27.06	34.31	14.80	31.80	44.37	54.00	-9.63	Vertical
17457.00	24.24	36.36	15.67	32.05	44.22	54.00	-9.78	Vertical
23276.00	21.04	38.55	16.16	32.14	43.61	54.00	-10.39	Vertical
29095.00	*					54.00		Vertical
40000.00	*					54.00		Vertical
11638.00	31.28	34.31	14.80	31.80	48.59	54.00	-5.41	Horizontal
17457.00	26.30	36.36	15.67	32.05	46.28	54.00	-7.72	Horizontal
23276.00	23.38	38.55	16.16	32.14	45.95	54.00	-8.05	Horizontal
29095.00	*					54.00		Horizontal
40000.00	*					54.00		Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- “*”, means this data is the too weak instrument of signal is unable to test.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

7.3.3 Bandedge emissions

Test channel:	channel 1
---------------	-----------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5725.00	39.38	31.54	13.22	30.25	53.89	74.00	-20.11	Vertical
5875.00	35.74	31.65	13.64	30.29	50.74	74.00	-23.26	Vertical
5725.00	40.04	31.54	13.22	30.25	54.55	74.00	-19.45	Horizontal
5875.00	38.73	31.65	13.64	30.29	53.73	74.00	-20.27	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5725.00	23.58	31.54	13.22	30.25	38.09	54.00	-15.91	Vertical
5875.00	23.55	31.65	13.64	30.29	38.55	54.00	-15.45	Vertical
5725.00	23.93	31.54	13.22	30.25	38.44	54.00	-15.56	Horizontal
5875.00	23.68	31.65	13.64	30.29	38.68	54.00	-15.32	Horizontal

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*

Test channel:	channel 45
---------------	------------

Peak value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5725.00	39.98	31.54	13.22	30.25	54.49	74.00	-19.51	Vertical
5875.00	35.82	31.65	13.64	30.29	50.82	74.00	-23.18	Vertical
5725.00	40.04	31.54	13.22	30.25	54.55	74.00	-19.45	Horizontal
5875.00	38.57	31.65	13.64	30.29	53.57	74.00	-20.43	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5725.00	23.69	31.54	13.22	30.25	38.20	54.00	-15.80	Vertical
5875.00	23.82	31.65	13.64	30.29	38.82	54.00	-15.18	Vertical
5725.00	24.60	31.54	13.22	30.25	39.11	54.00	-14.89	Horizontal
5875.00	23.86	31.65	13.64	30.29	38.86	54.00	-15.14	Horizontal

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*


7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 5725-5875 MHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
1	3.391	Pass
23	4.039	Pass
45	3.365	Pass


Test plot as follows:



CH1



CH23



CH45

8 Test Setup Photo

Radiated Emission



Conducted Emission




9 EUT Constructional Details




























-----End-----