FCC ID: 2AIOO-C8

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances $\leqslant$ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{}$ f(GHz)] $\leqslant$ 3.0 for 1-g SAR and $\leqslant$ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz；

Power and distance are rounded to the nearest mW and mm before calculation；

The result is rounded to one decimal place for comparison；

The test exclusions are applicable only when the minimum test separation distance is $\leqslant$ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculated.

Bluetooth BLE:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1g SAR
2.402	GFSK	0.45	1±1	2	0.4913	3
2.441		0.91	1±1	2	0.4952	3
2.480		0.98	1±1	2	0.4992	3

Conclusion:
For the max result : 0.4992≤ 3.0 for 1g SAR, No SAR is required.

Jason chen

Signature:　　　　　　　　　　　　　　　　　　**Date:** 2017-08-01

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street Bao'an District, Shenzhen 518126 P.R. China