

Report No.: FR8O0518D



FCC RADIO TEST REPORT

: 2AIP8-SR00300W FCC ID

Equipment : Smartphone **Brand Name** : SIRIN LABS : SR00300-W Model Name

: SIRIN LABS AG **Applicant**

Freier Platz 10, 8200 Schaffhausen, Switzerland

: SIRIN LABS AG Manufacturer

Freier Platz 10, 8200 Schaffhausen, Switzerland

Standard : FCC Part 15 Subpart C §15.225

The product was received on Oct. 05, 2018 and testing was started from Oct. 19, 2018 and completed on Oct. 29, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Joseph Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018 Report Version : 01

Report Template No.: BU5-FR15CNFC Version 2.1

Table of Contents

Report No. : FR8O0518D

History	y of this test report	3
	ary of Test Result	
	eral Description	
1.1	Product Feature of Equipment Under Test	5
1.2	Modification of EUT	5
1.3	Testing Location	5
1.4	Applicable Standards	6
2. Test	Configuration of Equipment Under Test	7
2.1	Descriptions of Test Mode	7
2.2	Connection Diagram of Test System	7
2.3	Table for Supporting Units	8
2.4	EUT Operation Test Setup	8
3. Test	Results	9
3.1	AC Power Line Conducted Emissions Measurement	9
3.2	20dB and 99% OBW Spectrum Bandwidth Measurement	11
3.3	Frequency Stability Measurement	12
3.4	Field Strength of Fundamental Emissions and Mask Measurement	13
3.5	Radiated Emissions Measurement	15
3.6	Antenna Requirements	18
4. List	of Measuring Equipment	19
5. Unce	ertainty of Evaluation	20
Append	dix A. Test Results of Conducted Emission Test	
Append	dix B. Test Results of Conducted Test Items	
B1. 7	Test Result of 20dB Spectrum Bandwidth	
B2. 1	Test Result of Frequency Stability	
Append	dix C. Test Results of Radiated Test Items	
C1. 7	Test Result of Field Strength of Fundamental Emissions	
C2. F	Results of Radiated Emissions (9 kHz~30MHz)	
C3. F	Results of Radiated Emissions (30MHz~1GHz)	
Append	dix D. Setup Photographs	

TEL: 886-3-327-3456 Page Number : 2 of 20
FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

History of this test report

Report No.: FR8O0518D

Report No.	Version	Description	Issued Date
FR8O0518D	01	Initial issue of report	Nov. 21, 2018

TEL: 886-3-327-3456 Page Number : 3 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

Summary of Test Result

Report No.: FR8O0518D

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	Under limit 3.40 dB at 13.560MHz
0.0	15.215(c)	20dB Spectrum Bandwidth	Pass	-
3.2	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 54.42 dBµV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	Under limit 9.52 dB at 30.000MHz
3.6	15.203	Antenna Requirements	Pass	-

Reviewed by: Wii Chang

Report Producer: Nancy Yang

TEL: 886-3-327-3456 Page Number : 4 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

1. General Description

1.1 Product Feature of Equipment Under Test

GSM/CDMA/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS

Report No.: FR8O0518D

Product Specification subjective to this standard			
Antenna Type	WWAN: PIFA Antenna WLAN: <ant. 1="">: PIFA Antenna <ant. 2="">: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC: Loop Antenna</ant.></ant.>		

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	Sporton Site No.			
rest Site No.	TH03-HY	CO05-HY	03CH07-HY	
Test Engineer	Louis Chung Jimmy Chang Jesse Wang, Nick and Stan Hsieh			
Temperature	22~24°C 24~26°C 22~24°C			
Relative Humidity	53~55% 51~53% 51~53%			

Note: The test site complies with ANSI C63.4 2014 requirement.

TEL: 886-3-327-3456 Page Number : 5 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Report No.: FR8O0518D

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

TEL: 886-3-327-3456 Page Number : 6 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.


Test Items		
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions	
20dB Spectrum Bandwidth	Frequency Stability	
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz	

Report No.: FR8O0518D

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

	Test Cases				
AC Conducted	Mode 1 : WCDMA Band V Idle + Bluetooth Link + WLAN (2.4GHz) Link + NFC Tx				
Emission	+ USB Type C Cable (Charging form Adapter)				

2.2 Connection Diagram of Test System



TEL: 886-3-327-3456 Page Number : 7 of 20
FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	NFC Card	N/A	N/A	N/A	N/A	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

Report No.: FR8O0518D

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.

TEL: 886-3-327-3456 Page Number : 8 of 20
FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR8O0518D

Frequency of Emission	Conducted Limit (dBµV)	
(MHz)	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments


See list of measuring equipment of this test report.

3.1.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

TEL: 886-3-327-3456 Page Number : 9 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.1.4 Test setup



Report No.: FR8O0518D

3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 10 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

Report No.: FR8O0518D


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 3. Measured the spectrum width with power higher than 20dB below carrier.
- 4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 11 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Report No.: FR8O0518D


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
- 6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 12 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.4 Field Strength of Fundamental Emissions and Mask Measurement

Report No.: FR8O0518D

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with th	Compliance with the spectrum mask is tested with RBW set to 9kHz.		
Frog of Emission (MUT)	Field Strength	Field Strength	Field Strength	Field Strength
Freq. of Emission (MHz)	(µV/m) at 30m	(dBµV/m) at 30m	(dBµV/m) at 10m	(dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

TEL: 886-3-327-3456 Page Number : 13 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.4.3 Test Procedures


 Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.

Report No.: FR8O0518D

- Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- 4. For Fundamental emissions, use the receiver to measure QP reading.
- 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- Compliance with the spectrum mask is tested with RBW set to 9kHz.
 Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

TEL: 886-3-327-3456 Page Number : 14 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Report No.: FR8O0518D

Frequencies	Field Strength	Measurement Distance	
(MHz)	(μV/m)	(meters)	
0.009~0.490	2400/F(kHz)	300	
0.490~1.705	24000/F(kHz)	30	
1.705~30.0	30	30	
30~88	100	3	
88~216	150	3	
216~960	200	3	
Above 960	500	3	

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

TEL: 886-3-327-3456 Page Number : 15 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.5.4 Test Procedures

 Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.


Report No.: FR8O0518D

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

TEL: 886-3-327-3456 Page Number : 16 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018


3.5.5 Test Setup

For radiated emissions below 30MHz



Report No.: FR8O0518D

For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

TEL: 886-3-327-3456 Page Number : 17 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: FR8O0518D

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

TEL: 886-3-327-3456 Page Number : 18 of 20
FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F10407001 1	50Hz~60Hz	Mar. 21, 2018	Oct. 27, 2018	Mar. 20, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 29, 2018	Oct. 27, 2018	Jun. 28, 2019	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Dec. 06, 2017	Oct. 27, 2018	Dec. 05, 2019	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 29, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Oct. 29, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Oct. 29, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 29, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Oct. 29, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Oct. 29, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Dec. 18, 2017	Oct. 19, 2018	Dec. 17, 2018	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	Oct. 19, 2018	Nov. 09, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	May 21, 2018	Oct. 19, 2018	May 20, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/ 4,MY2865 5/4	9KHz~30MHz	Jan. 02, 2018	Oct. 19, 2018	Jan. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/ 4, MY24971/ 4, MY15682/ 4	30MHz~1GHz	Feb. 27, 2018	Oct. 19, 2018	Feb. 26, 2019	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Oct. 19, 2018	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Oct. 19, 2018	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 16, 2018	Oct. 19, 2018	Jan. 15, 2019	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8- 24	805040046 56H	N/A	N/A	Oct. 19, 2018	N/A	Radiation (03CH07-HY)
Filter	Wainwright	WHK20/1000 C7/40SS	SN3	20M High Pass	Nov. 21, 2017	Oct. 19, 2018	Nov. 20, 2018	Radiation (03CH07-HY)

Report No. : FR8O0518D

TEL: 886-3-327-3456 Page Number : 19 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.2
of 95% (U = 2Uc(y))	2.2

Report No.: FR8O0518D

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.4
of 95% (U = 2Uc(y))	3.4

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	F 7
of 95% (U = 2Uc(y))	5.7

TEL: 886-3-327-3456 Page Number : 20 of 20 FAX: 886-3-328-4978 Issued Date : Nov. 21, 2018

Appendix A. Test Results of Conducted Emission Test

Report No. : FR8O0518D

TEL: 886-3-327-3456 Page Number : A1 of A1

EUT Information


 Report NO :
 800518

 Test Mode :
 Mode 1

 Test Voltage :
 120Vac/60Hz

Phase: Line

FullSpectrum




Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.156750		26.37	55.63	29.26	L1	OFF	19.5
0.156750	39.60	-	65.63	26.03	L1	OFF	19.5
0.235500		29.13	52.25	23.12	L1	OFF	19.5
0.235500	37.77		62.25	24.48	L1	OFF	19.5
0.541500		26.49	46.00	19.51	L1	OFF	19.5
0.541500	36.44		56.00	19.56	L1	OFF	19.5
2.141250		25.21	46.00	20.79	L1	OFF	19.4
2.141250	31.29		56.00	24.71	L1	OFF	19.4
7.005750		26.23	50.00	23.77	L1	OFF	19.8
7.005750	29.75	-	60.00	30.25	L1	OFF	19.8
13.560000		46.60	50.00	3.40	L1	OFF	20.0
13.560000	50.40		60.00	9.60	L1	OFF	20.0
24.069750		25.07	50.00	24.93	L1	OFF	20.3
24.069750	26.24		60.00	33.76	L1	OFF	20.3

EUT Information

Report NO: 800518
Test Mode: Mode 1
Test Voltage: 120Vac/60Hz
Phase: Neutral

FullSpectrum




Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.152250		29.93	55.88	25.95	N	OFF	19.5
0.152250	51.49	-	65.88	14.39	N	OFF	19.5
0.156750		28.78	55.63	26.85	N	OFF	19.5
0.156750	50.40		65.63	15.23	N	OFF	19.5
0.165750		27.88	55.17	27.29	N	OFF	19.5
0.165750	46.71		65.17	18.46	N	OFF	19.5
0.552750		24.66	46.00	21.34	N	OFF	19.5
0.552750	32.24	-	56.00	23.76	N	OFF	19.5
4.348500		26.11	46.00	19.89	N	OFF	19.7
4.348500	31.87	-	56.00	24.13	N	OFF	19.7
13.560000		46.04	50.00	3.96	N	OFF	20.1
13.560000	48.51		60.00	11.49	N	OFF	20.1
24.441000		25.21	50.00	24.79	N	OFF	20.5
24.441000	26.34	-	60.00	33.66	N	OFF	20.5

Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth



Report No.: FR8O0518D

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

TEL: 886-3-327-3456 Page Number: B1 of B3



B2. Test Result of Frequency Stability

B3. Voltage vs. F	requency Stability	Temperature vs. Frequency Stability					
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)			
120	13.560540	-20	0	13.560540			
102	13.560540		2	13.560580			
138	13.560520		5	13.560620			
			10	13.560640			
		-10	0	13.560650			
			2	13.560660			
			5	13.560660			
			10	13.560650			
		0	0	13.560660			
			2	13.560650			
			5	13.560640			
			10	13.560640			
		10	0	13.560640			
			2	13.560630			
			5	13.560530			
			10	13.560620			
		20	0	13.560530			
			2	13.560520			
			5	13.560520			
			10	13.560530			
		30	0	13.560520			
			2	13.560530			
			5	13.560520			
			10	13.560530			
		40	0	13.560500			
			2	13.560500			
			5	13.560510			
			10	13.560500			

Report No.: FR8O0518D

TEL: 886-3-327-3456 Page Number : B2 of B3


Voltage vs. Frequ	ency Stability	Temperature vs. Frequency Stability				
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃) Time		Temperature (°C)		Measurement Frequency (MHz)
		50	0	13.560480		
			2	13.560480		
			5	13.560480		
			10	13.560490		
Max.Deviation (MHz)	0.000540	Max.Deviation	on (MHz)	0.000660		
Max.Deviation (ppm)	39.8230	Max.Deviation (ppm)		48.6726		
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm		
Test Result	PASS	Test Result		PASS		

Report No.: FR8O0518D

TEL: 886-3-327-3456 Page Number : B3 of B3

Appendix C. Test Results of Radiated Test Items


C1. Test Result of Field Strength of Fundamental Emissions



Report No.: FR8O0518D

TEL: 886-3-327-3456 : C1 of C5 Page Number


C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)



Report No.: FR8O0518D

TEL: 886-3-327-3456 Page Number : C2 of C5

-8.6



Frequency	Level	Over	Limit	Read	Antenna	Cable	Ant	Table	Remark
(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB)	Loss (dB)	Pos (cm)	Pos (deg)	
0.0092	50.02	-78.31	128.33	28.96	20.63	0.43	-	-	Average
0.06498	49.97	-61.38	111.35	29.44	20.1	0.43	-	-	Average
0.09918	50.04	-57.64	107.68	29.52	20.09	0.43	-	-	QP
0.11444	50.12	-56.31	106.43	29.62	20.07	0.43	-	-	Average
0.15	50.19	-53.89	104.08	29.7	20.06	0.43	-	-	Average
0.49	50.38	-23.42	73.8	29.96	19.99	0.43	100	0	QP
11.456	37.57	-31.93	69.5	17.21	19.93	0.43	-	-	QP
13.56	50.51	-18.99	69.5	30.17	19.91	0.43	-	-	QP
22.435	39.25	-30.25	69.5	17.64	20.41	1.2	-	-	QP
29.15	39.72	-29.78	69.5	18.42	20.1	1.2	-	-	QP

12.005

Frequency (MHz)

18.004

24.002

Note:


1. 13.56 MHz is fundamental signal which can be ignored.

6.007

- 2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- 4. Limit line = specific limits $(dB\mu V)$ + distance extrapolation factor.

TEL: 886-3-327-3456 Page Number : C3 of C5


C3. Results of Radiated Spurious Emissions (30MHz~1GHz)



Report No.: FR8O0518D

TEL: 886-3-327-3456 Page Number : C4 of C5





Report No.: FR8O0518D

Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Emission level $(dB\mu V/m) = 20 \log Emission level (\mu V/m)$.
- 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor= Level.

TEL: 886-3-327-3456 Page Number : C5 of C5