


# ENGINEERING TEST REPORT



**Dual Band Wireless AC-7260**  
**Model: 7260H**  
**FCC ID: 2AIPX7260H**

*Applicant:*

**Contec DTx Inc.**  
1800 Penn St. Suite 1  
Melbourne, FL  
USA 32901

**In Accordance With**

**Federal Communications Commission (FCC) Part 15, Subpart E, Section 15.407**  
**Unlicensed National Information Infrastructure (U-NII) Device**  
**Operating in the 5.15–5.25, 5.25-5.35, 5.47–5.725 and 5.725–5.825 GHz Bands**

**UltraTech's File No.: 16CDTX003\_FCC15E407**

This Test report is Issued under the Authority of  
Tri M. Luu  
Vice President of Engineering  
UltraTech Group of Labs

Date: July 29, 2016

Report Prepared by: Dharmajit Solanki

Tested by: Hung Trinh

Issued Date: July 29, 2016

Test Dates: July 10 – 28, 2016

- *The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.*
- *This report must not be used by the client to claim product endorsement by NVLAP or any agency of the US Government.*
- *This test report shall not be reproduced, except in full, without a written approval from UltraTech*

## UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4  
Tel.: (905) 829-1570 Fax.: (905) 829-8050  
Website: [www.ultratech-labs.com](http://www.ultratech-labs.com), Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Email: [tri@ultratech-labs.com](mailto:tri@ultratech-labs.com)



91038



1309



46390-2049



NVLAP LAB  
CODE 200093-0



AT-1945



SL2-IN-E-  
1119R



Korea  
KCC-RRA

CA2049



TL363\_B



TPTDP  
DA1300

## TABLE OF CONTENTS

<b>EXHIBIT 1. INTRODUCTION .....</b>	<b>1</b>
1.1. SCOPE.....	1
1.2. RELATED SUBMITTAL(S)/GRANT(S) .....	1
1.3. NORMATIVE REFERENCES .....	1
<b>EXHIBIT 2. PERFORMANCE ASSESSMENT .....</b>	<b>2</b>
2.1. CLIENT INFORMATION.....	2
2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	2
2.3. EUT'S TECHNICAL SPECIFICATIONS .....	3
2.4. ASSOCIATED ANTENNA DESCRIPTIONS.....	3
2.5. LIST OF EUT'S PORTS.....	3
2.6. ANCILLARY EQUIPMENT .....	3
<b>EXHIBIT 3. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS.....</b>	<b>4</b>
3.1. CLIMATE TEST CONDITIONS .....	4
3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TESTS .....	4
<b>EXHIBIT 4. SUMMARY OF TEST RESULTS .....</b>	<b>5</b>
4.1. LOCATION OF TESTS.....	5
4.2. APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS .....	5
4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES .....	5
<b>EXHIBIT 5. TEST DATA.....</b>	<b>6</b>
5.1. DUTY CYCLE [§ 15.35(C)] .....	6
5.2. MAXIMUM CONDUCTED OUTPUT POWER [§ 15.407(A)] .....	12
5.3. UNDESIRABLE EMISSIONS [§ 15.407(B)] .....	20
5.4. RF EXPOSURE REQUIRMENTS [§§ 15.247(I), 1.1310 & 2.1091] .....	144
<b>EXHIBIT 6. TEST EQUIPMENT LIST .....</b>	<b>146</b>
<b>EXHIBIT 7. MEASUREMENT UNCERTAINTY.....</b>	<b>147</b>
7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY .....	147

## EXHIBIT 1. INTRODUCTION

### 1.1. SCOPE

<b>Reference:</b>	FCC Part 15, Subpart E, Section 15.407
<b>Title:</b>	Code of Federal Regulations (CFR), Title 47 – Telecommunication, Part 15 – Radio Frequency Devices
<b>Purpose of Test:</b>	Class II Permissive Change Certification Application under FCC Part 15, Subpart E to verify the compliance of modified Unlicensed National Information Infrastructure (U-NII) Device Operating in the 5.15–5.25 GHz, 5.25-5.35 GHz, 5.47–5.725 GHz and 5.725–5.825 GHz Band and for Co-location RF Exposure Evaluation of WIFI and Bluetooth Radios
<b>Test Procedures:</b>	<ul style="list-style-type: none"><li>ANSI C63.4</li><li>ANSI C63.10</li><li>FCC KDB Publication No.789033 D02 General U-NII Test Procedures New Rules v01r02</li><li>FCC, KDB Publication No.662911 D01 Multiple Transmitter Output v02r01</li></ul>
<b>Environmental Classification:</b>	<input checked="" type="checkbox"/> Commercial, industrial or business environment <input checked="" type="checkbox"/> Residential environment

### 1.2. RELATED SUBMITTAL(S)/GRANT(S)

None

### 1.3. NORMATIVE REFERENCES

Publication	Year	Title
47 CFR Parts 0-19	2016	Code of Federal Regulations (CFR), Title 47 – Telecommunication
ANSI C63.4	2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
FCC, KDB Publication No. 789033 D02 General U-NII Test Procedures New Rules v01r02	2016	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices, Part 15, Subpart E
FCC, KDB Publication No. 662911 D01 Multiple Transmitter Output v02r01	2013	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

## EXHIBIT 2. PERFORMANCE ASSESSMENT

### 2.1. CLIENT INFORMATION

APPLICANT	
<b>Name:</b>	Contec DTx Inc.
<b>Address:</b>	1800 Penn St. Suite 1 Melbourne, FL USA 32901
<b>Contact Person:</b>	Mr. Paul Parkinson Phone #: 321 728 0172 Fax #: 321 722 2216 Email Address: Paul.parkinson@dtx.com

MANUFACTURER	
<b>Name:</b>	Intel Corporation
<b>Address:</b>	2111 NE 25 <sup>th</sup> Avenue JF3-302, Hillsboro, OR USA 97124
<b>Contact Person:</b>	Mr. Steven C Hackett Email Address: steven.c.hackett@intel.com

### 2.2. EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information (with the exception of the Date of Receipt) has been supplied by the applicant.

<b>Brand Name:</b>	Contec DTx Inc.
<b>Product Name:</b>	Dual Band Wireless AC-7260
<b>Model Name or Number:</b>	7260H
<b>Serial Number:</b>	Test Sample
<b>Type of Equipment:</b>	Unlicensed National Information Infrastructure TX
<b>Input Power Supply Type:</b>	120 VAC 60 Hz AC Adaptor
<b>Primary User Functions of EUT:</b>	802.11 a/b/g/n/ac wireless LAN + BT PCIe half-mini card

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

## 2.3. EUT'S TECHNICAL SPECIFICATIONS

Transmitter	
Equipment Type:	<ul style="list-style-type: none"> <li>Mobile</li> <li>Base Station (fixed use)</li> </ul>
Intended Operating Environment:	Commercial, Industrial or Business/ Residential environments
Power Supply Requirement:	3.3 VDC
RF Output Power Rating:	<ul style="list-style-type: none"> <li>14.68 dBm (29.37 mW) (5180 – 5240 MHz)</li> <li>13.45 dBm (22.15 mW) (5190 – 5230 MHz)</li> <li>15.05 dBm (32.02 mW) (5260 – 5320 MHz)</li> <li>15.56 dBm (35.96 mW) (5500 – 5700 MHz)</li> <li>14.65 dBm (29.17 mW) (5510 – 5670 MHz)</li> <li>10.14 dBm (13.05 mW) (5530 – 5690 MHz)</li> <li>16.11 dBm (40.80 mW) (5710 – 5710 MHz)</li> <li>15.69 dBm (37.05 mW) (5720 – 5720 MHz)</li> <li>16.07 dBm (40.47 mW) (5745 – 5825 MHz)</li> <li>15.36 dBm (34.39 mW) (5755 – 5795 MHz)</li> <li>13.38 dBm (21.76 mW) (5775 – 5775 MHz)</li> </ul>
Operating Frequency Range:	5180 – 5240 MHz, 5190 – 5230 MHz 5260 – 5320 MHz 5500 – 5700 MHz, 5510 – 5670 MHz, 5530 – 5690 MHz 5710 – 5710 MHz, 5720 – 5720 MHz 5745 – 5825 MHz, 5755 – 5795 MHz, 5775 – 5775 MHz
RF Output Impedance:	50 $\Omega$
Modulation Modes:	802.11 a/n/ac
Antenna Connector Types:	U.FL to RP-SMA(M) Hinged Antenna

## 2.4. ASSOCIATED ANTENNA DESCRIPTIONS

New Antenna Type	Maximum Gain after assembly cable loss (dBi)
Dipole Antenna, GW.71.5153	2.07 dBi (2.4-2.5 GHz) & 2.91 dBi (5.0-5.8 GHz) Bands

## 2.5. LIST OF EUT'S PORTS

Port Number	EUT's Port Description	Number of Identical Ports	Connector Type	Cable Type (Shielded/Non-shielded)
1	ANT1 & ANT2	2	U.FL – RP-SMA	Cable connector U.FL- LP-066
2	Connector Interface	1	52-Pin Mini Card Edge	Direct connection (no cable)

## 2.6. ANCILLARY EQUIPMENT

The EUT was tested with special test-jig connected with the representative configuration of ancillary equipments necessary to exercise the ports during tests as shown in the test set-up diagrams.

## EXHIBIT 3. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS

### 3.1. CLIMATE TEST CONDITIONS

The climate conditions of the test environment are as follows:

Temperature:	21 to 23 °C
Humidity:	45 to 58%
Pressure:	102 kPa
Power Input Source:	3.3 V DC via HMC/NGFC test board

### 3.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TESTS

<b>Operating Modes:</b>	The transmitter was operated in a continuous transmission mode with the carrier modulated as specified in the Test Data.
<b>Special Test Software:</b>	Special software provided by the Applicant to operate the EUT at each channel frequency continuously and in the range of typical modes of operation.
<b>Special Hardware Used:</b>	N/A
<b>Transmitter Test Antenna:</b>	The EUT is tested with the antenna fitted in a manner typical of normal intended use as non-integral antenna equipment as described with the test results.

Transmitter Test Signals	
<b>Frequency Band(s):</b>	5180 – 5240 MHz, 5190 – 5230 MHz 5260 – 5320 MHz 5500 – 5700 MHz, 5510 – 5670 MHz, 5530 – 5690 MHz 5710 – 5710 MHz, 5720 – 5720 MHz 5745 – 5825 MHz, 5755 – 5795 MHz, 5775 – 5775 MHz
<b>Frequency(ies) Tested:</b>	5180, 5200, 5240, 5190, 5210, 5230 MHz 5260, 5270, 5290, 5300, 5310, 5320 MHz 5500, 5600, 5700, 5720, 5510, 5590, 5670, 5710, 5530, 5610, 5690 MHz 5745, 5755, 5775, 5785, 5795, 5825 MHz
<b>RF Power Output:</b> (measured maximum output power at antenna terminals)	<ul style="list-style-type: none"> <li>▪ 14.68 dBm (29.37 mW) (5180 – 5240 MHz)</li> <li>▪ 13.45 dBm (22.15 mW) (5190 – 5230 MHz)</li> <li>▪ 15.05 dBm (32.02 mW) (5260 – 5320 MHz)</li> <li>▪ 15.56 dBm (35.96 mW) (5500 – 5700 MHz)</li> <li>▪ 14.65 dBm (29.17 mW) (5510 – 5670 MHz)</li> <li>▪ 10.14 dBm (13.05 mW) (5530 – 5690 MHz)</li> <li>▪ 16.11 dBm (40.80 mW) (5710 – 5710 MHz)</li> <li>▪ 15.69 dBm (37.05 mW) (5720 – 5720 MHz)</li> <li>▪ 16.07 dBm (40.47 mW) (5745 – 5825 MHz)</li> <li>▪ 15.36 dBm (34.39 mW) (5755 – 5795 MHz)</li> <li>▪ 13.38 dBm (21.76 mW) (5775 – 5775 MHz)</li> </ul>
<b>Normal Test Modulation:</b>	OFDM
<b>Modulating Signal Source:</b>	Internal

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 4. SUMMARY OF TEST RESULTS

### 4.1. LOCATION OF TESTS

All of the measurements described in this report were performed at Ultratech Group of Labs located in the city of Oakville, Province of Ontario, Canada.

Radiated Emissions were performed at the Ultratech's 3-10 TDK Semi-Anechoic Chamber situated in the Town of Oakville, province of Ontario. This test site been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec. 2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville 3-10 TDK Semi-Anechoic Chamber has been filed with FCC office (FCC File No.: 91038) and Industry Canada office (Industry Canada File No.: 2049A-3). Expiry Date: 2017-04-02.

### 4.2. APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS

FCC Section(s)	Test Requirements	Compliance (Yes/No)
15.203	Antenna Requirements	Yes
15.207(a)	AC Power Line Conducted Emissions	See Note 1
15.407(a)	Output Power	Yes
15.407(a)	Power Spectral Density	See Note 1
15.407(b)	Undesirable Emission	Yes
15.407(c)	Transmission Requirements	See Note 1
15.407(e)	6 dB Bandwidth	See Note 1
15.407(f)	RF Exposure	Yes
15.407(g)	Frequency Stability	See Note 1
15.407(h)	Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).	See Note 1
15.407(i)	Device Security	As per Original filing

Note 1: Refer to the original filing UNII test report under FCC ID: PD97260H, Report Number:38067RRF.003A1.

### 4.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None

---

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

## EXHIBIT 5. TEST DATA

### 5.1. DUTY CYCLE [§ 15.35(c)]


#### 5.1.1. Requirements

§ 15.35(c) Unless otherwise specified, e.g., § 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

#### 5.1.2. Method of Measurements

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02, Section II B.2.b

#### 5.1.3. Test Arrangement






#### 5.1.4. Test Data

Operating Mode	Channel Number	Frequency (MHz)	Duty Cycle X (%)	Duty Cycle Correction Factor (dB)
802.11a	157	5785	98.1	0.0834
802.11n/ac HT20	157	5785	91.68	0.3772
802.11n/ac HT40	151	5755	87.04	0.6030
802.11ac HT80	155	5775	76.52	1.1622


Note: The configuration chosen for testing based on recommendation from Intel: "The data rates of 6Mb/s for 802.11a, HT4 (SISO)/(MIMO) for 802.11 n/ac20 & n/ac40, and VHT6 (SISO)/(MIMO) for 802.11 ac80 were selected based on preliminary testing that identified those data rates corresponding to the worst cases for output power and spurious levels at the band edges."

Refer to the following plots for details.

Plot 5.1.4.1. Duty Cycle, 802.11a, 5785 GHz, Data Rate 6 Mbps, Pulse Width = 2.0681 ms




Plot 5.1.4.2. Duty Cycle, 802.11a, 5785 GHz, Data Rate 6 Mbps, Pulse Train = 2.1082 ms




Duty Cycle Correction Factor =  $10 \cdot \log [1 / (2.0681 / 2.1082)] = 0.0834 \text{ dB}$

Plot 5.1.4.3. Duty Cycle, 802.11a HT20, 5785 GHz, Data Rate HT4, Pulse Width = 352.7054  $\mu$ s




Plot 5.1.4.4. Duty Cycle, 802.11a HT20, 5785 GHz, Data Rate HT4, Pulse Train = 384.7695  $\mu$ s




Duty Cycle Correction Factor =  $10 \cdot \log [1 / (352.7054 / 384.7695)] = 0.3772$  dB

Plot 5.1.4.5. Duty Cycle, 802.11a HT40, 5755 GHz, Data Rate HT4, Pulse Width = 188.3768  $\mu$ s



Plot 5.1.4.6. Duty Cycle, 802.11a HT40, 5755 GHz, Data Rate HT4, Pulse Train = 216.4329  $\mu$ s



Duty Cycle Correction Factor =  $10 \cdot \log [1 / (188.3768 / 216.4329)] = 0.6030$  dB

# ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407


July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.1.4.7. Duty Cycle, 802.11ac80, 5775 GHz, Data Rate VHT6, Pulse Width = 88.1764  $\mu$ s



Plot 5.1.4.8. Duty Cycle, 802.11ac80, 5775 GHz, Data Rate VHT6, Pulse Train = 115.2305  $\mu$ s



Duty Cycle Correction Factor =  $10 \cdot \log [1 / (88.1764 / 115.2305)] = 1.1622$  dB

# ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 5.2. MAXIMUM CONDUCTED OUTPUT POWER [§ 15.407(a)]

### 5.2.1. Limit(s)

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point UNII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional

---

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016


*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

applications, and multiple collocated transmitters transmitting the same information. The operator of the UNII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 5.2.2. Method of Measurements

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02, Section II.E.3.a  
FCC KDB 662911 D01 Multiple Transmitter Output v02r01, Section E.1

### 5.2.3. Test Arrangement



### 5.2.4. Test Data

Notes:

1. Assembly Gain for Dipole Antenna = 2.91dBi (Antenna Gain – Assembly Cable loss) = (5.5 – 2.59) dBi
2. Output power is adjusted by Gain Control
3. Duty Cycle is corrected using Duty Cycle Correction factors calculated as in Sec 5.1.

**(A) 5150-5250 MHz Band**

**802.11a, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate (Mbps)	Channel #	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
6	36	5180	31.5	13.21	14.10	0.08	13.29	14.18	16.20	17.09
6	40	5200	31.5	13.83	14.45	0.08	13.91	14.53	16.82	17.44
6	48	5240	31.5	14.46	14.42	0.08	14.54	14.50	17.45	17.41

**802.11n/ac, HT20, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	36	5180	31.0	13.08	11.66	0.38	13.46	12.04	16.37	14.95
HT4	40	5200	31.0	13.21	12.44	0.38	13.59	12.82	16.50	15.73
HT4	48	5240	31.0	12.87	12.77	0.38	13.25	13.15	16.16	16.06

**802.11n/ac, HT20, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	36	5180	31.0	11.96	8.30	13.51	0.38	13.89	24.50	16.80
HT4	40	5200	31.0	11.57	8.79	13.41	0.38	13.79	23.91	16.70
HT4	48	5240	31.0	12.47	9.67	14.30	0.38	14.68	29.37	17.59

**802.11n/ac, HT40, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	38	5190	27.5	10.25	11.56	0.60	10.85	12.16	13.76	15.07
HT4	46	5230	27.5	10.81	11.78	0.60	11.41	12.38	14.32	15.29

**802.11n/ac, HT40, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	38	5190	27.5	8.17	10.41	12.44	0.60	13.05	20.17	15.96
HT4	46	5230	27.5	9.16	10.43	12.85	0.60	13.45	22.15	16.36

**802.11ac80, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	42	5210	25.0	6.32	6.54	1.16	7.48	7.70	10.39	10.61

**802.11ac80, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	42	5210	25.0	4.22	4.51	7.38	1.16	8.54	7.14	11.45

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*



**(B) 5250-5350 MHz Band**

**802.11a, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate (Mbps)	Channel #	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
6	52	5260	30	13.96	14.27	0.08	14.04	14.35	16.95	17.26
6	60	5300	30	14.25	14.69	0.08	14.33	14.77	17.24	17.68
6	64	5320	30	14.07	14.08	0.08	14.15	14.16	17.06	17.07

**802.11n/ac, HT20, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	52	5260	31	14.05	14.42	0.38	14.43	14.80	17.34	17.71
HT4	60	5300	31	14.57	14.60	0.38	14.95	14.98	17.86	17.89
HT4	64	5320	31	13.50	14.06	0.38	13.88	14.44	16.79	17.35

**802.11n/ac, HT20, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	52	5260	31	10.54	12.56	14.68	0.38	15.05	32.02	17.96
HT4	60	5300	31	10.33	10.65	13.50	0.38	13.88	24.44	16.79
HT4	64	5320	31	10.54	11.98	14.33	0.38	14.71	29.56	17.62

**802.11n/ac, HT40, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	54	5270	26	9.14	9.47	0.60	9.74	10.07	12.65	12.98
HT4	62	5310	26	9.44	9.54	0.60	10.04	10.14	12.95	13.05

**802.11n/ac, HT40, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	54	5270	26	6.59	7.18	9.91	0.60	10.51	11.24	13.42
HT4	62	5310	26	6.87	7.50	10.21	0.60	10.81	12.05	13.72

**802.11ac80, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	58	5290	25	8.85	9.08	1.16	10.01	10.24	12.92	13.15

**802.11ac80, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	58	5290	25	5.19	5.32	8.27	1.16	9.43	12.34	8.77

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

**(C) 5470-5725 MHz Band**

**802.11a, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate (Mbps)	Channel #	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
6	100	5500	29	13.76	14.32	0.08	13.84	14.40	16.75	17.31
6	120	5600	29	13.58	13.53	0.08	13.66	13.61	16.57	16.52
6	140	5700	29	12.24	12.94	0.08	12.32	13.02	15.23	15.93

**802.11n/ac, HT20, Chain #1 or #2 (SISO) (no MIMO), Except channel # 144**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	100	5500	30	14.98	14.86	0.38	15.36	15.24	18.27	18.15
HT4	120	5600	30	14.09	14.43	0.38	14.47	14.81	17.38	17.72
HT4	140	5700	30	13.79	12.83	0.38	14.17	13.21	17.08	16.12

**802.11n/ac, HT20, Chain #1 & #2 (MIMO), Except channel # 144**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	100	5500	29	12.49	11.70	15.12	0.38	15.50	35.48	18.41
HT4	120	5600	29	12.21	12.13	15.18	0.38	15.56	35.96	18.47
HT4	140	5700	29	12.69	11.06	14.96	0.38	15.34	34.19	18.25

**802.11n/ac, HT40, Chain #1 or #2 (SISO), Except channel # 142**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	102	5510	27	12.34	12.13	0.60	12.94	12.73	15.85	15.64
HT4	118	5590	27	12.02	11.52	0.60	12.62	12.12	15.53	15.03
HT4	134	5670	27	10.65	10.94	0.60	11.25	11.54	14.16	14.45

**802.11n/ac, HT40, Chain #1 & #2 (MIMO), Except channel # 142**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	EIRP (dBm)	Comb. Power (mW)
HT4	102	5510	27	10.98	11.09	14.05	0.60	14.65	17.56	29.17
HT4	118	5590	27	10.27	10.93	13.62	0.60	14.23	17.14	26.46
HT4	134	5670	27	9.78	9.47	12.64	0.60	13.24	16.15	21.09

**802.11ac80, Chain #1 or #2 (SISO), Except channel # 138**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	106	5530	23	8.15	7.61	1.16	9.31	8.77	12.22	11.68
VHT6	122	5610	23	7.05	7.56	1.16	8.21	8.72	11.12	11.63

**802.11ac80, Chain #1 & #2 (MIMO), Except channel # 138**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	106	5530	23	6.64	5.18	8.98	1.16	10.14	13.05	10.34
VHT6	122	5610	23	5.58	5.28	8.44	1.16	9.61	12.52	9.13

**802.11ac20, Chain #1 or #2 (SISO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	144	5720	36	15.02	15.12	0.38	15.40	15.50	18.31	18.41

**802.11ac20, Chain #1 & #2 (MIMO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	144	5720	36	12.28	12.32	15.31	0.38	15.69	37.05	18.60

**802.11ac20, Chain #1 or #2 (SISO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	144	5720	25	8.56	8.74	0.38	8.94	9.12	11.85	12.03

**802.11ac20, Chain #1 & #2 (MIMO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	144	5720	25	5.58	5.21	8.38	0.38	8.76	7.51	11.67

**802.11ac40, Chain #1 or #2 (SISO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	142	5710	33	13.56	14.66	0.60	14.16	15.26	17.07	18.17

**802.11ac40, Chain #1 & #2 (MIMO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	142	5710	33	12.75	12.22	15.50	0.60	16.11	40.80	19.02

**802.11ac40, Chain #1 or #2 (SISO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	142	5710	19	2.02	1.90	0.60	2.62	2.50	5.53	5.41

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

**802.11ac40, Chain #1 & #2 (MIMO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	142	5710	19	0.23	-0.92	2.70	0.60	3.31	2.14	6.22

**802.11ac80, Chain #1 or #2 (SISO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	138	5690	32	12.78	12.37	0.60	13.38	12.97	16.29	15.88

**802.11ac80, Chain #1 & #2 (MIMO), U-NII-2C**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	138	5690	32	10.76	10.74	13.76	0.60	14.36	27.31	17.27

**802.11ac80, Chain #1 or #2 (SISO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	138	5690	23	-4.53	-4.72	0.60	-3.93	-4.12	-1.02	-1.21

**802.11ac80, Chain #1 & #2 (MIMO), U-NII-3**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	138	5690	23	-5.65	-4.82	-2.20	0.60	-1.60	0.69	1.31

**(D) 5725-5850 MHz Band**

**802.11a, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate (Mbps)	Channel #	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
6	149	5745	33	15.29	14.71	0.08	15.37	14.79	18.28	17.70
6	157	5785	33	15.28	13.47	0.08	15.36	13.55	18.27	16.46
6	165	5825	33	14.74	13.38	0.08	14.82	13.46	17.73	16.37

**802.11n/ac, HT20, Chain #1 or #2 (SISO) (no MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	149	5745	33	14.12	14.69	0.38	14.50	15.07	17.41	17.98
HT4	157	5785	33	13.57	13.56	0.38	13.95	13.94	16.86	16.85
HT4	165	5825	33	13.10	13.06	0.38	13.48	13.44	16.39	16.35

**802.11n/ac, HT20, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	149	5745	33	11.57	13.57	15.69	0.38	16.07	40.47	18.98
HT4	157	5785	33	11.29	12.91	15.19	0.38	15.56	36.00	18.47
HT4	165	5825	33	11.06	12.12	14.63	0.38	15.01	31.69	17.92

**802.11n/ac, HT40, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
HT4	151	5755	30	13.49	12.54	0.60	14.09	13.14	17.00	16.05
HT4	159	5795	30	12.41	11.54	0.60	13.01	12.14	15.92	15.05

**802.11n/ac, HT40, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
HT4	151	5755	30	12.34	11.07	14.76	0.60	15.36	34.39	18.27
HT4	159	5795	30	11.75	11.21	14.50	0.60	15.10	32.37	18.01

**802.11ac80, Chain #1 or #2 (SISO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Duty Cycle (dB)	Chain #1 (dBm)	Chain #2 (dBm)	EIRP#1 (dBm)	EIRP#2 (dBm)
VHT6	155	5775	28	10.11	9.93	1.16	11.27	11.09	14.18	14.00

**802.11ac80, Chain #1 & #2 (MIMO)**

Data Rate	Channel	Frequency (MHz)	Gain Control	Chain #1 (dBm)	Chain #2 (dBm)	Combined Power (dBm)	Duty Cycle (dB)	Comb. Power (dBm)	Comb. Power (mW)	EIRP (dBm)
VHT6	155	5775	28	9.53	8.85	12.21	1.16	13.38	21.76	16.29

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

### 5.3. UNDESIRABLE EMISSIONS [§ 15.407(b)]

#### 5.3.1. Limit(s)


§ 15.407(b) *Undesirable emission limits.* Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
  - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

#### 5.3.2. Method of Measurements

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02, Section II.G.

### 5.3.3. Test Arrangement



### 5.3.4. Test Data

Remark(s):

- All spurious emissions that are in excess of 20 dB below the specified limit shall be recorded.
- EUT shall be tested in three orthogonal positions.
- Exploratory tests performed to determine worst-case test configurations, the following test results are the worst-case measurements.
- Equipment transmits continuously in the selected channel so no necessity for a duty cycle correction.

### 5.3.5. 5150-5250 MHz Band Tx Spurious Radiated

#### 802.11a, 6 Mbps, Gain Control Setting 31.5, SISO

Fundamental Frequency:		5180 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10360	56.35	--	V	74.0	54.0	68.2	-11.8	Pass
10360	57.72	--	H	74.0	54.0	68.2	-10.5	Pass
20720	49.94	--	V	74.0	54.0	68.2	-4.1	Pass*
20720	49.37	--	H	74.0	54.0	68.2	-4.6	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5200 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10400	56.02	--	V	74.0	54.0	68.2	-12.2	Pass
10400	55.58	--	H	74.0	54.0	68.2	-12.6	Pass
20800	49.52	--	V	74.0	54.0	68.2	-4.5	Pass*
20800	50.32	--	H	74.0	54.0	68.2	-3.7	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5240 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10480	56.65	--	V	74.0	54.0	68.2	-11.5	Pass
10480	56.56	--	H	74.0	54.0	68.2	-11.6	Pass
20960	49.74	--	V	74.0	54.0	68.2	-4.3	Pass*
20960	49.88	--	H	74.0	54.0	68.2	-4.1	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



### 802.11n HT20, HT4, Gain Control Setting 31, SISO & MIMO

Fundamental Frequency:		5180 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10360	57.32	--	V	74.0	54.0	<b>68.2</b>	-10.9	Pass
10360	56.57	--	H	74.0	54.0	<b>68.2</b>	-11.6	Pass
20720	48.32	--	V	74.0	<b>54.0</b>	68.2	-5.7	Pass*
20720	49.35	--	H	74.0	<b>54.0</b>	68.2	-4.6	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5200 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10400	56.43	--	V	74.0	54.0	<b>68.2</b>	-11.8	Pass
10400	55.32	--	H	74.0	54.0	<b>68.2</b>	-12.9	Pass
20800	49.93	--	V	74.0	<b>54.0</b>	68.2	-4.1	Pass*
20800	50.33	--	H	74.0	<b>54.0</b>	68.2	-3.7	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5240 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10480	58.53	--	V	74.0	54.0	<b>68.2</b>	-10.7	Pass
10480	56.01	--	H	74.0	54.0	<b>68.2</b>	-12.2	Pass
20960	50.50	--	V	74.0	<b>54.0</b>	68.2	-3.5	Pass*
20960	49.99	--	H	74.0	<b>54.0</b>	68.2	-4.0	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

### 802.11n HT40, HT4, Gain Control Setting 27.5, SISO & MIMO

Fundamental Frequency:		5190 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10380	56.00	--	V	74.0	54.0	68.2	-12.2	Pass
10380	55.43	--	H	74.0	54.0	68.2	-12.8	Pass
20760	49.84	--	V	74.0	54.0	68.2	-4.2	Pass*
20760	50.69	--	H	74.0	54.0	68.2	-3.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5230 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10460	54.86	--	V	74.0	54.0	68.2	-13.3	Pass
10460	55.55	--	H	74.0	54.0	68.2	-12.6	Pass
20920	50.18	--	V	74.0	54.0	68.2	-3.8	Pass*
20920	50.30	--	H	74.0	54.0	68.2	-3.7	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### 802.11ac80, VHT6, Gain Control Setting 25, SISO & MIMO

Fundamental Frequency:		5210 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10420	55.12	--	V	74.0	54.0	68.2	-13.1	Pass
10420	54.99	--	H	74.0	54.0	68.2	-13.2	Pass
20840	49.79	--	V	74.0	54.0	68.2	-4.2	Pass*
20840	49.60	--	H	74.0	54.0	68.2	-4.4	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.


#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


**Plot 5.3.6.1.1.** Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 36, 5180 MHz, SISO, Gain Control 31.5, Horizontal, Chain # 1




Plot 5.3.6.1.3. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 36, 5180 MHz, SISO, Gain Control 31.5, Vertical, Chain # 1




Plot 5.3.6.1.4. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 36, 5180 MHz, SISO, Gain Control 31.5, Vertical, Chain # 2




Plot 5.3.6.1.5. Integration Method for Chain # 2, 802.11a, 6 Mbps, Ch 36, 5180 MHz, SISO, Gain Control 31.5, Vertical




Plot 5.3.6.1.6. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 48, 5240 MHz, SISO, Gain Control 31.5, Horizontal, Chain # 1




Plot 5.3.6.1.7. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 48, 5240 MHz, SISO, Gain Control 31.5, Horizontal, Chain # 2




Plot 5.3.6.1.8. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 48, 5240 MHz, SISO, Gain Control 31.5, Vertical, Chain # 1




Plot 5.3.6.1.9. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 48, 5240 MHz, SISO, Gain Control 31.5, Vertical, Chain # 2



Plot 5.3.6.1.10. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 36, 5180 MHz, SISO, Gain Control 31, Horiz, Chain # 1



Plot 5.3.6.1.11. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 36, 5180 MHz, SISO, Gain Control 31, Horiz, Chain # 2





Ref 130 dBuV/m Att 10 dB RBW 1 MHz VBW 3 MHz SWT 20 ms Marker 1 [T1] 107.86 dBuV/m 5.186848000 GHz

130 Offset 10 dB

1 PR VIEW

VIEW

A

LVL

TDF

6DB

-70dBm

Center 5.18 GHz 8 MHz/ Span 80 MHz

Date: 21.JUL.2016 13:21:32

Ref 130 dBuV/m \* Att 10 dB \* RBW 1 MHz \* VBW 3 MHz \* SWT 20 ms Marker 1 [T1] 108.35 dBuV/m 5.187488000 GHz

130 Offset 10 dB

1 PR VIEW

70 dB Offset

1

LVL


TDF

6DB

Center 5.18 GHz 8 MHz/ Span 80 MHz

Date: 21.JUL.2016 13:30:10

Plot 5.3.6.1.14. Integration Method for Chain # 2, 802.11n HT20, HT4, Ch 36, 5180 MHz, SISO, Gain Control 31, Vertical



[illegible]

Ref 130 dBmV/m \* Att 10 dB SWT 20 ms

\* RBW 1 MHz \* VBW 3 MHz

Marker 1 [T1] 104.56 dBmV/m 5.23700000 GHz

130 Offset 10 dB

1 PE VIEW

1

TOS\_RRIS

Center 5.24 GHz 25 MHz/ Span 250 MHz

6DB

76.5

104.56

130

120

110

100

90

80

70

60

50

40

30

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

-90

-100

-110

-120

-130

5.23700000 GHz

5.24 GHz

5.245 GHz

5.25 GHz

5.255 GHz

5.26 GHz

5.265 GHz

5.27 GHz

5.275 GHz

5.28 GHz

5.285 GHz

5.29 GHz

5.295 GHz

5.3 GHz

5.305 GHz

5.31 GHz

5.315 GHz

5.32 GHz

5.325 GHz

5.33 GHz

5.335 GHz

5.34 GHz

5.345 GHz

5.35 GHz

5.355 GHz

5.36 GHz

5.365 GHz

5.37 GHz

5.375 GHz

5.38 GHz

5.385 GHz

5.39 GHz

5.395 GHz

5.4 GHz

5.405 GHz

5.41 GHz

5.415 GHz

5.42 GHz

5.425 GHz

5.43 GHz

5.435 GHz

5.44 GHz

5.445 GHz

5.45 GHz

5.455 GHz

5.46 GHz

5.465 GHz

5.47 GHz

5.475 GHz

5.48 GHz

5.485 GHz

5.49 GHz

5.495 GHz

5.5 GHz

5.505 GHz

5.51 GHz

5.515 GHz

5.52 GHz

5.525 GHz

5.53 GHz

5.535 GHz

5.54 GHz

5.545 GHz

5.55 GHz

5.555 GHz

5.56 GHz

5.565 GHz

5.57 GHz

5.575 GHz

5.58 GHz

5.585 GHz

5.59 GHz

5.595 GHz

5.6 GHz

5.605 GHz

5.61 GHz

5.615 GHz

5.62 GHz

5.625 GHz

5.63 GHz

5.635 GHz

5.64 GHz

5.645 GHz

5.65 GHz

5.655 GHz

5.66 GHz

5.665 GHz

5.67 GHz

5.675 GHz

5.68 GHz

5.685 GHz

5.69 GHz

5.695 GHz

5.7 GHz

5.705 GHz

5.71 GHz

5.715 GHz

5.72 GHz

5.725 GHz

5.73 GHz

5.735 GHz

5.74 GHz

5.745 GHz

5.75 GHz

5.755 GHz

5.76 GHz

5.765 GHz

5.77 GHz

5.775 GHz

5.78 GHz

5.785 GHz

5.79 GHz

5.795 GHz

5.8 GHz

5.805 GHz

5.81 GHz

5.815 GHz

5.82 GHz

5.825 GHz

5.83 GHz

5.835 GHz

5.84 GHz

5.845 GHz

5.85 GHz

5.855 GHz

5.86 GHz

5.865 GHz

5.87 GHz

5.875 GHz

5.88 GHz

5.885 GHz

5.89 GHz

5.895 GHz

5.9 GHz

5.905 GHz

5.91 GHz

5.915 GHz

5.92 GHz

5.925 GHz

5.93 GHz

5.935 GHz

5.94 GHz

5.945 GHz

5.95 GHz

5.955 GHz

5.96 GHz

5.965 GHz

5.97 GHz

5.975 GHz

5.98 GHz

5.985 GHz

5.99 GHz

5.995 GHz

6 GHz

6.005 GHz

6.01 GHz

6.015 GHz

6.02 GHz

6.025 GHz

6.03 GHz

6.035 GHz

6.04 GHz

6.045 GHz

6.05 GHz

6.055 GHz

6.06 GHz

6.065 GHz

6.07 GHz

6.075 GHz

6.08 GHz

6.085 GHz

6.09 GHz

6.095 GHz

6.1 GHz

6.105 GHz

6.11 GHz

6.115 GHz

6.12 GHz

6.125 GHz

6.13 GHz

6.135 GHz

6.14 GHz

6.145 GHz

6.15 GHz

6.155 GHz

6.16 GHz

6.165 GHz

6.17 GHz

6.175 GHz

6.18 GHz

6.185 GHz

6.19 GHz

6.195 GHz

6.2 GHz

6.205 GHz

6.21 GHz

6.215 GHz

6.22 GHz

6.225 GHz

6.23 GHz

6.235 GHz

6.24 GHz

6.245 GHz

6.25 GHz

6.255 GHz

6.26 GHz

6.265 GHz

6.27 GHz

6.275 GHz

6.28 GHz

6.285 GHz

6.29 GHz

6.295 GHz

6.3 GHz

6.305 GHz

6.31 GHz

6.315 GHz

6.32 GHz

6.325 GHz

6.33 GHz

6.335 GHz

6.34 GHz

6.345 GHz

6.35 GHz

6.355 GHz

6.36 GHz

6.365 GHz

6.37 GHz

6.375 GHz

6.38 GHz

6.385 GHz

6.39 GHz

6.395 GHz

6.4 GHz

6.405 GHz

6.41 GHz

6.415 GHz

6.42 GHz

6.425 GHz

6.43 GHz

6.435 GHz

6.44 GHz

6.445 GHz

6.45 GHz

6.455 GHz

6.46 GHz

6.465 GHz

6.47 GHz

6.475 GHz

6.48 GHz

6.485 GHz

6.49 GHz

6.495 GHz

6.5 GHz

6.505 GHz

6.51 GHz

6.515 GHz

6.52 GHz

6.525 GHz

6.53 GHz

6.535 GHz

6.54 GHz

6.545 GHz

6.55 GHz

6.555 GHz

6.56 GHz

6.565 GHz

6.57 GHz

6.575 GHz

6.58 GHz

6.585 GHz

6.59 GHz

6.595 GHz

6.6 GHz

6.605 GHz

6.61 GHz

6.615 GHz

6.62 GHz

6.625 GHz

6.63 GHz

6.635 GHz

6.64 GHz

6.645 GHz

6.65 GHz

6.655 GHz

6.66 GHz

6.665 GHz

6.67 GHz

6.675 GHz

6.68 GHz

6.685 GHz

6.69 GHz

6.695 GHz

6.7 GHz

6.705 GHz

6.71 GHz

6.715 GHz

6.72 GHz

6.725 GHz

6.73 GHz

6.735 GHz

6.74 GHz

6.745 GHz


6.75 GHz

6.755 GHz


6.76 GHz

6.


Plot 5.3.6.1.17. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 48, 5240 MHz, SISO, Gain Control 31, Vertical, Chain # 1




Plot 5.3.6.1.18. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 48, 5240 MHz, SISO, Gain Control 31, Vertical, Chain # 2



Plot 5.3.6.1.19. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 36, 5180 MHz, MIMO, Gain Control 31, Horizontal  
Chain # 1 & 2



Plot 5.3.6.1.20. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 36, 5180 MHz, MIMO, Gain Control 31, Vertical,  
Chain # 1 & 2




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.3.6.1.21. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 48, 5240 MHz, MIMO, Gain Control 31, Horizontal  
Chain # 1 & 2



Ref 130 dB $\mu$ V/m \* Att 10 dB \* RBW 1 MHz \* VBW 3 MHz \* SWT 20 ms

Marker 1 [T1] 109.43 dB $\mu$ V/m 5.241400000 GHz

130 Offset 10 dB

1 PR VIEW

LVL

TDF

6DB

70E-RAB

Center 5.24 GHz 25 MHz/ Span 250 MHz



Ref 130 dBμV/m Att 10 dB RBW 1 MHz VBW 3 MHz SWT 20 ms Marker 1 [T1] 97.70 dBμV/m 5.195600000 GHz

130 Offset 10 dB

1 PR VIEW

LVL TDF

70dBm

Center 5.19 GHz 10 MHz/ Span 100 MHz

Date: 22.JUL.2016 07:21:06

Ref 130 dBuV/m \* Att 10 dB SWT 20 ms 5.197680000 GHz

\* RBW 1 MHz Marker 1 [T1] 98.53 dBuV/m

\* VBW 3 MHz

1 PE VIEW

130 Offset 10 dB

120

110

100

90

80

70

60

50

40

30

Center 5.19 GHz 10 MHz/ Span 100 MHz

70 dBm

100 dBm

1

LVL

TDF

6DB

Date: 22.JUL.2016 07:18:03

Ref 130 dBuV/m \* Att 10 dB RBW 1 MHz VBW 3 MHz SWT 20 ms

Marker 1 [T1]  
103.58 dBuV/m  
5.19768000 GHz

130 Offset 10 dB

1 PR VIEW

70 dB Ref

1


LVL  
TDF  
6DB

Center 5.19 GHz 10 MHz/ Span 100 MHz


Date: 22.JUL.2016 06:04:26

[illegible]


Plot 5.3.6.1.27. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 46, 5230 MHz, SISO, Gain Control 27.5, Horiz, Chain # 1




Plot 5.3.6.1.28. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 46, 5230 MHz, SISO, Gain Control 27.5, Horiz, Chain # 2




Plot 5.3.6.1.29. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 46, 5230 MHz, SISO, Gain Control 27.5, Vert, Chain # 1




Plot 5.3.6.1.30. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 46, 5230 MHz, SISO, Gain Control 27.5, Vert, Chain # 2



**Plot 5.3.6.1.31.** Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 38, 5190 MHz, MIMO, Gain Control 27.5, Horizontal Chain # 1 & 2



**Plot 5.3.6.1.32.** Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 38, 5190 MHz, MIMO, Gain Control 27.5, Vertical, Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

Ref 130 dBμV/m \* Att 10 dB SWT 20 ms

\* RBW 1 MHz \* VBW 3 MHz

Marker 1 [T1] 99.74 dBμV/m 5.219680000 GHz

130 Offset 10 dB

1 PK VIEW

70B\_RAE


1

6DB

Center 5.23 GHz 30 MHz/ Span 300 MHz


Date: 22.JUL.2016 06:48:57

Plot 5.3.6.1.34. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 46, 5230 MHz, MIMO, Gain Control 27.5, Vertical  
Chain # 1 & 2







Plot 5.3.6.1.35. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, SISO, Gain Control 25, Horiz, Chain # 1




Plot 5.3.6.1.36. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, SISO, Gain Control 25, Horiz, Chain # 2




Plot 5.3.6.1.37. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, SISO, Gain Control 25, Vert, Chain # 1




Plot 5.3.6.1.38. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, SISO, Gain Control 25, Vert, Chain # 2



**Plot 5.3.6.1.39.** Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, MIMO, Gain Control 25, Horizontal  
Chain # 1 & 2



Plot 5.3.6.1.40. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 42, 5210 MHz, MIMO, Gain Control 25, Vertical,  
Chain # 1 & 2



### 5.3.7. 5250-5350 MHz Band Tx Spurious Radiated

#### 802.11a, 6 Mbps, Gain Control Setting 30, SISO

Fundamental Frequency:		5260 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10520	57.21	--	V	74.0	54.0	<b>68.2</b>	-11.0	Pass
10520	57.10	--	H	74.0	54.0	<b>68.2</b>	-11.1	Pass
21040	48.17	--	V	74.0	<b>54.0</b>	68.2	-5.8	Pass*
21040	48.07	--	H	74.0	<b>54.0</b>	68.2	-5.9	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5300 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10600	56.24	--	V	74.0	54.0	<b>68.2</b>	-12.0	Pass
10600	58.45	--	H	74.0	54.0	<b>68.2</b>	-9.7	Pass
21200	49.54	--	V	74.0	<b>54.0</b>	68.2	-4.5	Pass*
21200	49.96	--	H	74.0	<b>54.0</b>	68.2	-4.0	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5320 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10640	55.85	--	V	74.0	54.0	<b>68.2</b>	-12.3	Pass
10640	58.24	--	H	74.0	54.0	<b>68.2</b>	-10.0	Pass
21280	49.37	--	V	74.0	<b>54.0</b>	68.2	-4.6	Pass*
21280	50.63	--	H	74.0	<b>54.0</b>	68.2	-3.4	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

## 802.11n HT20, HT4, Gain Control Setting 31, SISO & MIMO

Fundamental Frequency:		5260 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10520	58.04	--	V	74.0	54.0	68.2	-10.2	Pass
10520	57.42	--	H	74.0	54.0	68.2	-10.8	Pass
21040	48.48	--	V	74.0	54.0	68.2	-5.5	Pass*
21040	48.39	--	H	74.0	54.0	68.2	-5.6	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5300 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10600	57.04	--	V	74.0	54.0	68.2	-11.2	Pass
10600	58.27	--	H	74.0	54.0	68.2	-9.9	Pass
21200	49.34	--	V	74.0	54.0	68.2	-4.6	Pass*
21200	48.37	--	H	74.0	54.0	68.2	-5.6	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5320 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10640	56.65	--	V	74.0	54.0	68.2	-11.5	Pass
10640	57.90	--	H	74.0	54.0	68.2	-10.3	Pass
21280	50.01	--	V	74.0	54.0	68.2	-4.0	Pass*
21280	49.73	--	H	74.0	54.0	68.2	-4.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 802.11n HT40, HT4, Gain Control Setting 26, SISO & MIMO

Fundamental Frequency:		5270 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10540	55.39	--	V	74.0	54.0	68.2	-12.8	Pass
10540	55.14	--	H	74.0	54.0	68.2	-13.0	Pass
21080	48.00	--	V	74.0	54.0	68.2	-6.0	Pass*
21080	47.57	--	H	74.0	54.0	68.2	-6.4	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5310 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10620	55.50	--	V	74.0	54.0	68.2	-12.7	Pass
10620	55.94	--	H	74.0	54.0	68.2	-12.2	Pass
21240	49.17	--	V	74.0	54.0	68.2	-4.8	Pass*
21240	50.41	--	H	74.0	54.0	68.2	-3.6	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.


### 802.11ac80, VHT6, Gain Control Setting 25, SISO & MIMO

Fundamental Frequency:		5290 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
10580	54.19	--	V	74.0	54.0	68.2	-14.0	Pass
10580	54.90	--	H	74.0	54.0	68.2	-13.3	Pass
21160	46.81	--	V	74.0	54.0	68.2	-7.2	Pass*
21160	47.53	--	H	74.0	54.0	68.2	-6.5	Pass*


\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### 5.3.8. 5250-5350 MHz Band, Band-Edge Radiated

Plot 5.3.8.1.1. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 52, 5260 MHz, SISO, Gain Control 30, Horizontal, Chain # 1




Plot 5.3.8.1.2. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 52, 5260 MHz, SISO, Gain Control 30, Horizontal, Chain # 2







Plot 5.3.8.1.3. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 52, 5260 MHz, SISO, Gain Control 30, Vertical, Chain # 1




Plot 5.3.8.1.4. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 52, 5260 MHz, SISO, Gain Control 30, Vertical, Chain # 2




Plot 5.3.8.1.5. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 64, 5320 MHz, SISO, Gain Control 30, Horizontal, Chain # 1




Plot 5.3.8.1.6. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 64, 5320 MHz, SISO, Gain Control 30, Horizontal, Chain # 2




Plot 5.3.8.1.7. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 64, 5320 MHz, SISO, Gain Control 30, Vertical, Chain # 1




Plot 5.3.8.1.8. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 64, 5320 MHz, SISO, Gain Control 30, Vertical, Chain # 2




Plot 5.3.8.1.9. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 52, 5260 MHz, SISO, Gain Control 31, Horiz, Chain # 1




Plot 5.3.8.1.10. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 52, 5260 MHz, SISO, Gain Control 31, Horiz, Chain # 2




Plot 5.3.8.1.11. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 52, 5260 MHz, SISO, Gain Control 31, Vertical, Chain # 1




Plot 5.3.8.1.12. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 52, 5260 MHz, SISO, Gain Control 31, Vertical, Chain # 2




Plot 5.3.8.1.13. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 64, 5320 MHz, SISO, Gain Control 31, Horiz, Chain # 1




Plot 5.3.8.1.14. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 64, 5320 MHz, SISO, Gain Control 31, Horiz, Chain # 2




Plot 5.3.8.1.15. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 64, 5320 MHz, SISO, Gain Control 31, Vertical, Chain # 1



Plot 5.3.8.1.16. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 64, 5320 MHz, SISO, Gain Control 31, Vertical, Chain # 2



Plot 5.3.8.1.17. Integration Method Chain# 2, 802.11n HT20, HT4, Ch 64, 5320 MHz, SISO, Gain Control 31, Vertical





Ref 130 dBμV/m \* Att 10 dB \* RBW 1 MHz \* VBW 3 MHz \* SWT 20 ms

Marker 1 [T1 ] 105.06 dBμV/m 5.263400000 GHz

130 Offset 10 dB

1 PR VIEW

76.5 RAD

105.06

1

A

LVL


TDF

6DB

Center 5.26 GHz 25 MHz/ Span 250 MHz

Date: 22.JUL.2016 13:12:38


**Plot 5.3.8.1.19.** Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 52, 5260 MHz, MIMO, Gain Control 31, Vertical, Chain # 1 & 2




[illegible]

[illegible]


Plot 5.3.8.1.22. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, SISO, Gain Control 26, Horiz, Chain # 1




Plot 5.3.8.1.23. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, SISO, Gain Control 26, Horiz, Chain # 2




Plot 5.3.8.1.24. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, SISO, Gain Control 26, Vert, Chain # 1




Plot 5.3.8.1.25. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, SISO, Gain Control 26, Vert, Chain # 2




Plot 5.3.8.1.26. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 62, 5310 MHz, SISO, Gain Control 26, Horiz, Chain # 1




Plot 5.3.8.1.27. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 62, 5310 MHz, SISO, Gain Control 26, Horiz, Chain # 2



Plot 5.3.8.1.28. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 62, 5310 MHz, SISO, Gain Control 26, Vert, Chain # 1




Plot 5.3.8.1.29. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 62, 5310 MHz, SISO, Gain Control 26, Vert, Chain # 2





Plot 5.3.8.1.30. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, MIMO, Gain Control 26, Horizontal  
Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407


July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.3.8.1.31. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 54, 5270 MHz, MIMO, Gain Control 26, Vertical, Chain # 1 & 2



Plot 5.3.8.1.32. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 62, 5310 MHz, MIMO, Gain Control 26, Horizontal  
Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Ref 130 dBμV/m      \* Att 10 dB      \* RBW 1 MHz      Marker 1 [T1]      104.95 dBμV/m

\* VBW 3 MHz      SWT 20 ms      5.302240000 GHz

1 PR VIEW

130 Offset 10 dB

120

110

100

90

80

70

60

50

40

30


Center 5.31 GHz      10 MHz/      Span 100 MHz

LVL


TDF

6DB


Plot 5.3.8.1.34. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 58, 5290 MHz, SISO, Gain Control 25, Horiz, Chain # 1




Plot 5.3.8.1.35. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 58, 5290 MHz, SISO, Gain Control 25, Horiz, Chain # 2




Plot 5.3.8.1.36. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 58, 5290 MHz, SISO, Gain Control 25, Vert, Chain # 1



Plot 5.3.8.1.37. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 58, 5290 MHz, SISO, Gain Control 25, Vert, Chain # 2



Plot 5.3.8.1.38. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 52, 5290 MHz, MIMO, Gain Control 25, Horizontal  
Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

Plot 5.3.8.1.39. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 52, 5290 MHz, MIMO, Gain Control 25, Vertical,  
Chain # 1 & 2





### 5.3.9. 5470-5725 MHz Band Tx Spurious Radiated

#### 802.11a, 6 Mbps, Gain Control Setting 29

Fundamental Frequency:		5500 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11000	59.81	46.63	V	74.0	54.0	68.2	-7.4	Pass*
11000	60.68	48.06	H	74.0	54.0	68.2	-5.9	Pass*
22000	49.40	--	V	74.0	54.0	68.2	-4.6	Pass*
22000	47.97	--	H	74.0	54.0	68.2	-6.0	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5600 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11200	59.58	45.94	V	74.0	54.0	68.2	-8.1	Pass*
11200	58.43	47.05	H	74.0	54.0	68.2	-6.9	Pass*
22400	52.99	--	V	74.0	54.0	68.2	-1.0	Pass*
22400	49.81	--	H	74.0	54.0	68.2	-4.2	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5700 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11400	57.12	45.02	V	74.0	54.0	68.2	-9.0	Pass*
11400	59.94	45.69	H	74.0	54.0	68.2	-8.3	Pass*
22800	45.11	--	V	74.0	54.0	68.2	-8.9	Pass*
22800	46.97	--	H	74.0	54.0	68.2	-7.0	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

## 802.11n HT20, HT4, Gain Control Setting 29, SISO & MIMO

Fundamental Frequency:		5500 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11000	60.31	47.82	V	74.0	54.0	68.2	-6.2	Pass*
11000	60.72	47.63	H	74.0	54.0	68.2	-6.4	Pass*
22000	48.26	--	V	74.0	54.0	68.2	-5.7	Pass*
22000	46.66	--	H	74.0	54.0	68.2	-7.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5600 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11200	60.33	46.08	V	74.0	54.0	68.2	-7.9	Pass*
11200	59.14	46.10	H	74.0	54.0	68.2	-7.9	Pass*
22400	50.88	--	V	74.0	54.0	68.2	-3.1	Pass*
22400	50.72	--	H	74.0	54.0	68.2	-3.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5700 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBµV/m)	RF Avg Level (dBµV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBµV/m)	Avg Limit 15.209 (dBµV/m)	Limit 15.407(b) (dBµV/m)	Margin (dB)	Pass/Fail
11400	56.79	44.39	V	74.0	54.0	68.2	-9.6	Pass*
11400	56.77	45.32	H	74.0	54.0	68.2	-8.7	Pass*
22800	45.69	--	V	74.0	54.0	68.2	-8.3	Pass*
22800	47.05	--	H	74.0	54.0	68.2	-6.9	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 802.11n HT40, HT4, Gain Control Setting 27, SISO & MIMO

Fundamental Frequency:		5510 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11020	57.04	45.53	V	74.0	54.0	68.2	-8.5	Pass*
11020	57.91	45.77	H	74.0	54.0	68.2	-8.2	Pass*
22040	48.53	--	V	74.0	54.0	68.2	-5.5	Pass*
22040	50.14	--	H	74.0	54.0	68.2	-4.9	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5590 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11180	57.74	45.05	V	74.0	54.0	68.2	-8.9	Pass*
11180	57.09	46.59	H	74.0	54.0	68.2	-7.4	Pass*
22360	53.39	--	V	74.0	54.0	68.2	-0.6	Pass*
22360	50.47	--	H	74.0	54.0	68.2	-3.5	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5670 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11340	56.07	43.80	V	74.0	54.0	68.2	-10.2	Pass*
11340	55.68	44.83	H	74.0	54.0	68.2	-9.2	Pass*
22680	49.00	--	V	74.0	54.0	68.2	-5.0	Pass*
22680	49.47	--	H	74.0	54.0	68.2	-4.5	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

# 802.11ac80, VHT6, Gain Control Setting 23, SISO & MIMO

Fundamental Frequency:		5530 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11060	56.05	44.55	V	74.0	54.0	68.2	-9.4	Pass*
11060	56.68	47.60	H	74.0	54.0	68.2	-6.4	Pass*
22120	50.24	--	V	74.0	54.0	68.2	-3.8	Pass*
22120	50.26	--	H	74.0	54.0	68.2	-3.7	Pass*


\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5610 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11220	56.20	45.07	V	74.0	54.0	68.2	-8.9	Pass*
11220	56.42	45.86	H	74.0	54.0	68.2	-8.1	Pass*
22440	50.37	--	V	74.0	54.0	68.2	-3.6	Pass*
22440	49.98	--	H	74.0	54.0	68.2	-4.0	Pass*


\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### 5.3.10. 5470-5725 MHz Band, Band-Edge Radiated


Plot 5.3.10.1.1. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 100, 5500 MHz, SISO, Gain Control 29, Horiz, Chain # 1




Plot 5.3.10.1.2. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 100, 5500 MHz, SISO, Gain Control 29, Horiz, Chain # 2




Plot 5.3.10.1.3. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 100, 5500 MHz, SISO, Gain Control 29, Vertical, Chain # 1




Plot 5.3.10.1.4. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 100, 5500 MHz, SISO, Gain Control 29, Vertical, Chain # 2




Plot 5.3.10.1.5. Integration Method Chain# 2, 802.11a, 6 Mbps, Ch 100, 5500 MHz, SISO, Gain Control 29, Vertical



Plot 5.3.10.1.6. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 140, 5700 MHz, SISO, Gain Control 29, Horiz, Chain # 1




Plot 5.3.10.1.7. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 140, 5700 MHz, SISO, Gain Control 29, Horiz, Chain # 2







**Plot 5.3.10.1.8.** Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 140, 5700 MHz, SISO, Gain Control 29, Vertical, Chain # 1




**Plot 5.3.10.1.9.** Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 140, 5700 MHz, SISO, Gain Control 29, Vertical, Chain # 2




Plot 5.3.10.1.10. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 100, 5500 MHz, SISO, Gain Control 30, Horiz, Chain # 1




Plot 5.3.10.1.11. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 100, 5500 MHz, SISO, Gain Control 30, Horiz, Chain # 2




Plot 5.3.10.1.12. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 100, 5500 MHz, SISO, Gain Control 30, Vert, Chain # 1




Plot 5.3.10.1.13. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 100, 5500 MHz, SISO, Gain Control 30, Vert, Chain # 2




Plot 5.3.10.1.14. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 140, 5700 MHz, SISO, Gain Control 30, Horiz, Chain # 1




Plot 5.3.10.1.15. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 140, 5700 MHz, SISO, Gain Control 30, Horiz, Chain # 2



Plot 5.3.10.1.16. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 140, 5700 MHz, SISO, Gain Control 30, Vert, Chain # 1




Plot 5.3.10.1.17. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 140, 5700 MHz, SISO, Gain Control 30, Vert, Chain # 2




[illegible]

Plot 5.3.10.1.19. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 102, 5510 MHz, MIMO, Gain Control 27, Vertical, Chain # 1 & 2



Plot 5.3.10.1.20. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 134, 5670 MHz, MIMO, Gain Control 27, Horizontal Chain # 1 & 2



**ULTRATECH GROUP OF LABS**


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016


All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)




Plot 5.3.10.1.21. Band-Edge Rad Emissions, 802.11n HT20, HT4, HT4, Ch 134, 5670 MHz, MIMO, Gain Control 27, Vertical Chain # 1 & 2



Plot 5.3.10.1.22. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 102, 5510 MHz, SISO, Gain Control 27, Horiz, Chain # 1



Plot 5.3.10.1.23. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 102, 5510 MHz, SISO, Gain Control 27, Horiz, Chain # 2



Ref 130 dBuV/m \*Att 10 dB RBW 1 MHz VBW 3 MHz SWT 20 ms

Marker 1 [T1] 104.37 dBuV/m 5.50583333 GHz

130 Offset 10 dB

1 PK VIEW


LVL TDF 6DB

70dB Ref


Center 5.51 GHz 10 MHz/ Span 100 MHz

Date: 27.JUL.2016 16:04:00


Plot 5.3.10.1.26. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, SISO, Gain Control 27, Horiz, Chain # 1




Plot 5.3.10.1.27. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, SISO, Gain Control 27, Horiz, Chain # 2




Plot 5.3.10.1.28. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, SISO, Gain Control 27, Vert, Chain # 1



Plot 5.3.10.1.29. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, SISO, Gain Control 27, Vert, Chain # 2



Plot 5.3.10.1.30. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 102, 5510 MHz, MIMO, Gain Control 27, Horizontal Chain # 1 & 2



**ULTRATECH GROUP OF LABS**


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


[illegible]

Plot 5.3.10.1.32. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, MIMO, Gain Control 27, Horizontal Chain # 1 & 2







Plot 5.3.10.1.33. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 134, 5670 MHz, MIMO, Gain Control 27, Vertical  
Chain # 1 & 2



Plot 5.3.10.1.34. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 106, 5530 MHz, SISO, Gain Control 23, Horiz, Chain # 1



Plot 5.3.10.1.35. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 106, 5530 MHz, SISO, Gain Control 23, Horiz, Chain # 2



Ref 130 dBuV/m \* Att 10 dB SWT 20 ms

Marker 1 [T1] 97.59 dBuV/m 5.514375000 GHz

130 Offset 10 dB

1 PK VIEW


LVL

TDF

6DB

Center 5.53 GHz 15 MHz/ Span 150 MHz

Date: 28.JUL.2016 07:43:44



Ref 130 dBuV/m Att 10 dB RBW 1 MHz Marker 1 [T1] 100.51 dBuV/m  
 VSWR 3 MHz SWT 20 ms 5.538173077 GHz

130 Offset 10 dB

1 PK VIEW

1


TDF

6DB


Center 5.53 GHz 15 MHz/ Span 150 MHz

Date: 28.JUL.2016 07:40:20

Plot 5.3.10.1.38. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 122, 5610 MHz, SISO, Gain Control 23, Horiz, Chain # 1



Plot 5.3.10.1.39. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 122, 5610 MHz, SISO, Gain Control 23, Horiz, Chain # 2



[illegible]

1 PK VIEW

Ref 130 dBuV/m \* Att 10 dB RBW 1 MHz Marker 1 [T1] VBW 3 MHz 95.54 dBuV/m SWT 20 ms 5.605192308 GHz

130 Offset 10 dB

1


70 dBm

6dB

Center 5.61 GHz 25 MHz/ Span 250 MHz

Date: 28.JUL.2016 07:58:10

Plot 5.3.10.1.42. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 106, 5530 MHz, MIMO, Gain Control 23, Horizontal  
Chain # 1 & 2



Ref 130 dBuV/m \*Att 10 dB SWT 20 ms

\*RBW 1 MHz \*VBW 3 MHz

Marker 1 [T1] 100.13 dBuV/m 5.542500000 GHz

130 Offset 10 dB

1 PK VIEW


70 dBm

6dB

Center 5.53 GHz 15 MHz/ Span 150 MHz

1

Plot 5.3.10.1.44. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 122, 5610 MHz, MIMO, Gain Control 23, Horizontal  
Chain # 1 & 2





Ref 130 Offset 10 dB

\*RBW 1 MHz

\*VBW 3 MHz

\*Att 10 dB

SWT 20 ms

Marker 1 [T1]

98.01 dBuV/m

5.616810897 GHz

1 PK VIEW

120

110

100

90

80

70

60

50

40

30

Center 5.61 GHz

25 MHz/

Span 250 MHz

A

LVL

TDF

6DB

10E\_RAL

**Note:** As stated in the FCC presentation in April 2015 TCB Workshop for use of 802.11ac channels that straddle in the upper 5725 MHz, No band-edge measurements are required hence not tested.

### 5.3.11. 5725-5850 MHz Band Tx Spurious Radiated

#### 802.11a, 6 Mbps, Gain Control Setting 33, SISO

Fundamental Frequency:		5745 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11490	57.94	45.38	V	74.0	54.0	68.2	-8.6	Pass*
11490	59.74	48.25	H	74.0	54.0	68.2	-5.7	Pass*
22980	50.58	--	V	74.0	54.0	68.2	-3.4	Pass*
22980	51.79	--	H	74.0	54.0	68.2	-2.2	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5785 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11570	58.42	45.77	V	74.0	54.0	68.2	-8.2	Pass
11570	61.74	48.74	H	74.0	54.0	68.2	-5.3	Pass
23140	50.72	--	V	74.0	54.0	68.2	-17.5	Pass*
23140	53.11	--	H	74.0	54.0	68.2	-15.1	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5825 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11650	60.31	46.84	V	74.0	54.0	68.2	-7.2	Pass
11650	61.19	48.92	H	74.0	54.0	68.2	-5.1	Pass
23300	49.47	--	V	74.0	54.0	68.2	-18.7	Pass*
23300	51.37	--	H	74.0	54.0	68.2	-16.8	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 802.11n HT20, HT4, Gain Control Setting 33, SISO & MIMO

Fundamental Frequency:		5745 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11490	59.36	46.27	V	74.0	54.0	68.2	-7.7	Pass*
11490	61.47	48.21	H	74.0	54.0	68.2	-5.8	Pass*
22980	51.42	--	V	74.0	54.0	68.2	-2.6	Pass*
22980	51.74	--	H	74.0	54.0	68.2	-2.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5785 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11570	60.42	45.51	V	74.0	54.0	68.2	-8.5	Pass
11570	61.04	48.18	H	74.0	54.0	68.2	-5.3	Pass
23140	51.94	--	V	74.0	54.0	68.2	-16.3	Pass*
23140	51.97	--	H	74.0	54.0	68.2	-16.2	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5825 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11650	59.45	46.42	V	74.0	54.0	68.2	-7.6	Pass
11650	62.98	48.65	H	74.0	54.0	68.2	-5.3	Pass
23300	48.86	--	V	74.0	54.0	68.2	-19.3	Pass*
23300	51.80	--	H	74.0	54.0	68.2	-16.4	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 802.11n HT40, HT4, Gain Control Setting 30, SISO & MIMO

Fundamental Frequency:		5755 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11510	57.21	43.59	V	74.0	54.0	68.2	-10.4	Pass*
11510	56.35	43.93	H	74.0	54.0	68.2	-10.1	Pass*
23020	51.09	--	V	74.0	54.0	68.2	-2.9	Pass*
23020	52.72	--	H	74.0	54.0	68.2	-2.3	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

Fundamental Frequency:		5795 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11590	57.60	43.65	V	74.0	54.0	68.2	-8.5	Pass
11590	56.79	43.68	H	74.0	54.0	68.2	-5.3	Pass
23180	51.05	--	V	74.0	54.0	68.2	-16.3	Pass*
23180	52.16	--	H	74.0	54.0	68.2	-16.2	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

### 802.11ac80, VHT6, Gain Control Setting 28, SISO & MIMO

Fundamental Frequency:		5775 MHz						
Test Frequency Range:		30 MHz – 40 GHz						
Frequency (MHz)	RF Peak Level (dBμV/m)	RF Avg Level (dBμV/m)	Antenna Plane (H/V)	Peak Limit 15.209 (dBμV/m)	Avg Limit 15.209 (dBμV/m)	Limit 15.407(b) (dBμV/m)	Margin (dB)	Pass/Fail
11550	56.49	43.29	V	74.0	54.0	68.2	-10.7	Pass*
11550	56.80	46.59	H	74.0	54.0	68.2	-7.4	Pass*
23100	51.24	--	V	74.0	54.0	68.2	-2.8	Pass*
23100	51.88	--	H	74.0	54.0	68.2	-2.1	Pass*

\*Field strength of emissions appearing within restricted frequency bands shall not exceed the limits in § 15.209.

#### ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016


All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 5.3.12. 5725-5850 MHz Band, Band-Edge Radiated


Plot 5.3.12.1.1. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 149, 5745 MHz, SISO, Gain Control 33, Horiz, Chain # 1




Plot 5.3.12.1.2. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 149, 5745 MHz, SISO, Gain Control 33, Horiz, Chain # 2




Plot 5.3.12.1.3. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 149, 5745 MHz, SISO, Gain Control 33, Vertical, Chain # 1



Plot 5.3.12.1.4. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 149, 5745 MHz, SISO, Gain Control 33, Vertical, Chain # 2




Plot 5.3.12.1.5. Chain # 2 Integration Method, 802.11a, 6 Mbps, Ch 149, 5745 MHz, SISO, Gain Control 33, Vertical







Plot 5.3.12.1.6. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 165, 5825 MHz, SISO, Gain Control 33, Horiz, Chain # 1




Plot 5.3.12.1.7. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 165, 5825 MHz, SISO, Gain Control 33, Horiz, Chain # 2




Plot 5.3.12.1.8. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 165, 5825 MHz, SISO, Gain Control 33, Vertical, Chain # 1




Plot 5.3.12.1.9. Band-Edge Rad Emissions, 802.11a, 6 Mbps, Ch 165, 5825 MHz, SISO, Gain Control 33, Vertical, Chain # 2



Plot 5.3.12.1.10. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 149, 5745 MHz, SISO, Gain Control 33, Horiz, Chain # 1




Plot 5.3.12.1.11. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 149, 5745 MHz, SISO, Gain Control 33, Horiz, Chain # 2




Plot 5.3.12.1.12. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 149, 5745 MHz, SISO, Gain Control 33, Vert, Chain # 1




Plot 5.3.12.1.13. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 149, 5745 MHz, SISO, Gain Control 33, Vert, Chain # 2




Plot 5.3.12.1.14. Chain # 1 Integration Method, 802.11n HT20, HT4, Ch 149, 5745 MHz, SISO, Gain Control 33, Vertical




**Plot 5.3.12.1.15.** Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, SISO, Gain Control 33, Horiz, Chain # 1




**Plot 5.3.12.1.16.** Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, SISO, Gain Control 33, Horiz, Chain # 2



Plot 5.3.12.1.17. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, SISO, Gain Control 33, Vert, Chain # 1




Plot 5.3.12.1.18. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, SISO, Gain Control 33, Vert, Chain # 2



[illegible]



Plot 5.3.12.1.20. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 149, 5745 MHz, MIMO, Gain Control 33, Vertical, Chain # 1 & 2



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.3.12.1.21. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, MIMO, Gain Control 33, Horizontal Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot 5.3.12.1.22. Band-Edge Rad Emissions, 802.11n HT20, HT4, Ch 165, 5825 MHz, MIMO, Gain Control 33, Vertical Chain # 1 & 2




**Plot 5.3.12.1.23.** Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, SISO, Gain Control 30, Horiz, Chain # 1




**Plot 5.3.12.1.24.** Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, SISO, Gain Control 30, Horiz, Chain # 2




Plot 5.3.12.1.25. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, SISO, Gain Control 30, Vert, Chain # 1




Plot 5.3.12.1.26. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, SISO, Gain Control 30, Vert, Chain # 2



Plot 5.3.12.1.27. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, SISO, Gain Control 30, Horiz, Chain # 1



Plot 5.3.12.1.28. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, SISO, Gain Control 30, Horiz, Chain # 2



# ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4


Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407


July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.3.12.1.29. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, SISO, Gain Control 30, Vert, Chain # 1




Plot 5.3.12.1.30. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, SISO, Gain Control 30, Vert, Chain # 2







Plot 5.3.12.1.31. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, MIMO, Gain Control 30, Horizontal Chain # 1 & 2



Plot 5.3.12.1.32. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 151, 5755 MHz, MIMO, Gain Control 30, Vertical, Chain # 1 & 2



Plot 5.3.12.1.33. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, MIMO, Gain Control 30, Horizontal Chain # 1 & 2




**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot 5.3.12.1.34. Band-Edge Rad Emissions, 802.11n HT40, HT4, Ch 159, 5795 MHz, MIMO, Gain Control 30, Vertical  
Chain # 1 & 2



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: 16CDTX003\_FCC15E407  
July 29, 2016

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


Plot 5.3.12.1.35. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, SISO, Gain Control 28, Horiz, Chain # 1




Plot 5.3.12.1.36. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, SISO, Gain Control 28, Horiz, Chain # 2




Plot 5.3.12.1.37. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, SISO, Gain Control 28, Vert, Chain # 1



Plot 5.3.12.1.38. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, SISO, Gain Control 28, Vert, Chain # 2




Plot 5.3.12.1.39. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, MIMO, Gain Control 28, Horizontal  
Chain # 1 & 2





Plot 5.3.12.1.40. Band-Edge Rad Emissions, 802.11ac80, VHT6, Ch 155, 5775 MHz, MIMO, Gain Control 28, Vertical, Chain # 1 & 2



## 5.4. RF EXPOSURE REQUIRMENTS [§§ 15.247(i), 1.1310 & 2.1091]

### 5.4.1. Limits

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

**Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

Note 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

### 5.4.2. Method of Measurements

Calculation Method of Power Density/RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm<sup>2</sup>

G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407

July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

#### 5.4.3. RF Evaluation

Antenna Type Certified with	Antenna Location (Main/Aux)	2.4GHz Peak Gain in dBi*	2.6GHz Peak Gain in dBi*	5.2GHz Peak Gain in dBi*	5.5GHz Peak Gain in dBi*	5.7GHz Peak Gain in dBi*
PIFA Type (Original Filing)	Main/Aux	3.24	3.47	3.73	4.77	4.77
Dipole Model# GW.71 ( <b>C2PC</b> )	Main/Aux	<b>2.07</b>	<b>2.07</b>	<b>2.91</b>	<b>2.91</b>	<b>2.91</b>
*All antenna gains include cable loss.						

Since the single & combined measured conducted power at antenna ports for this C2PC and the above calculated net antenna gains after assembly loss are lower than the Original filing, the RF exposure evaluations submitted with Original filing continue to comply for this filing as well.

## EXHIBIT 6. TEST EQUIPMENT LIST

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSEK30	100077	20Hz–40 GHz	Nov 21, 2016
Attenuator	Pasternack	7024-20	6	DC–26.5 GHz	Cal on use
DC Block	Hewlett Packard	11742A	12460	0.045 – 26.5 GHz	Cal on use
Peak Power Analyzer	Hewlett Packard	8991A	3342A00657	0.5 - 40 GHz	Jul 15, 2016
Peak Power Sensor	Hewlett Packard	84814A	3205A00175	0.5 - 40 GHz	Jul 15, 2016
Spectrum Analyzer	Rohde & Schwarz	FSU26	100398	20Hz–26.5 GHz	Sep 14, 2017
RF Amplifier	Hewlett Packard	84498	3008A00769	1 – 26.5 GHz	May 5, 2017
Environmental Chamber	Envirotronics	SSH32C	11994847-S-11059	-60 to 177 °C	Jun 2, 2017
EMI Receiver	Rohde & Schwarz	ESU40	100037	20Hz–40 GHz	May 8, 2017
RF Amplifier	Com-Power	PAM-0118A	551052	0.5 – 18 GHz	Jul 12, 2017
Biconilog	Emco	3142	9601-1005	26-1000 MHz	May 12, 2017
Horn Antenna	Emco	3155	5955	1 – 18 GHz	Apr 21, 2017
Horn Antenna	Emco	3160-09	118385	18 – 26.5 GHz	Aug 4, 2016
Horn Antenna	Emco	3160-10	102686	26.5 - 40 GHz	Aug 4, 2016
High Pass Filter	K & L	11SH10-8000/T18000	3	Cut off 5800 MHz	Cal on use

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [yic@ultratech-labs.com](mailto:yic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: 16CDTX003\_FCC15E407  
July 29, 2016

*All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

## EXHIBIT 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties stated were calculated in accordance with the requirements of CISPR 16-4-2 @ IEC:2003 and JCGM 100:2008 (GUM 1995) – Guide to the Expression of Uncertainty in Measurement.

### 7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY

	Radiated Emission Measurement Uncertainty @ 3m, Horizontal (30-1000 MHz):	Measured (dB)	Limit (dB)
$u_c$	Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$	$\pm 2.39$	$\pm 2.6$
$U$	Expanded uncertainty U: $U = 2u_c(y)$	$\pm 4.79$	$\pm 5.2$

	Radiated Emission Measurement Uncertainty @ 3m, Vertical (30-1000 MHz):	Measured (dB)	Limit (dB)
$u_c$	Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$	$\pm 2.39$	$\pm 2.6$
$U$	Expanded uncertainty U: $U = 2u_c(y)$	$\pm 4.78$	$\pm 5.2$

	Radiated Emission Measurement Uncertainty @ 3 m, Horizontal & Vertical (1 – 18 GHz):	Measured (dB)	Limit (dB)
$u_c$	Combined standard uncertainty: $u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)}$	$\pm 1.87$	Under consideration
$U$	Expanded uncertainty U: $U = 2u_c(y)$	$\pm 3.75$	Under consideration