

Annex A: System Check

Tested Model: PG-103

Report Number: FCC17070748A-SAR

I. RESULTS

TYPE	BAND	<u>PARAMETERS</u>
Validation	CW835	Measurement 1: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW1900	Measurement 2: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW2450	Measurement 3: Validation Plane with Dipole device position on Middle Channel in CW mode

MEASUREMENT 1

BODY

Type: Validation measurement (Complete)

Date of measurement: 21/11/2017

Measurement duration: 11 minutes 54 seconds


A. Experimental conditions.

<u>Area Scan</u>	dx=8mm dy=8mm
<u>ZoomScan</u>	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Middle Band SAR (Channel -1):

Frequency (MHz)	835.000000
Relative permittivity (real part)	53.927799
Relative permittivity (imaginary part)	21.281300
Conductivity (S/m)	0.987216
Variation (%)	0.120000




Maximum location: X=-1.00, Y=0.00

SAR Peak: 1.44 W/kg

SAR 10g (W/Kg)	0.644746	
SAR 1g (W/Kg)	1.014583	

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.3418	0.9674	0.6426	0.4358	0.2947	0.1989	0.1326
	1.3- 1.2- 1.0- (%)/\%) 9.8- 9.6- 0.4- 0.2- 0.1-	02.55.07.5	12.5 17	.5 22.5 2 Z (mm)	27.5 32.5	40.0	



MEASUREMENT 2

BODY

Type: Validation measurement (Complete)

Date of measurement: 21/11/2017

Measurement duration: 10 minutes 57 seconds


A. Experimental conditions.

<u>Area Scan</u>	dx=8mm dy=8mm
<u>ZoomScan</u>	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
<u>Phantom</u>	<u>Validation plane</u>
Device Position	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Middle Band SAR (Channel -1):

Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.365299
Relative permittivity (imaginary part)	14.757600
Conductivity (S/m)	1.557747
Variation (%)	-0.450000




Maximum location: X=-1.00, Y=-1.00

SAR Peak: 6.26 W/kg

SAR 10g (W/Kg)	2.093533	
SAR 1g (W/Kg)	3.932904	

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	5.7034	3.7183	2.1347	1.2560	0.7338	0.4260	0.2429
	5.70- 5.00- 4.00- 3.00- 88 2.00- 1.00- 0.13-		12.5 17		27.5 32.5	40.0	
				Z (mm)			



MEASUREMENT 3

BODY

Type: Validation measurement (Complete)

Date of measurement: 22/11/2017

Measurement duration: 9 minutes 46 seconds


A. Experimental conditions.

<u>Area Scan</u>	dx=8mm dy=8mm
<u>ZoomScan</u>	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
<u>Phantom</u>	<u>Validation plane</u>
Device Position	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Middle Band SAR (Channel -1):

Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.735699
Relative permittivity (imaginary part)	14.017300
Conductivity (S/m)	1.907910
Variation (%)	0.390000



Maximum location: X=-5.00, Y=-1.00

SAR Peak: 10.96 W/kg

SAR 10g (W/Kg)	2.333453	
SAR 1g (W/Kg)	5.633343	

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	10.218 8	5.8819	2.7478	1.3151	0.6266	0.2969	0.1341
	10.22 8.00 6.00 4.00 2.00 0.06		5 12.5 1	7.5 22.5 Z (mm)	27.5 32.5	40.0	

