



TEST REPORT

FCC ID: 2AIU6SG1000

Applicant : Enblink Co., Ltd.

Address : 105-dong 212-ho, Gwanak-ro 1, Gwanak-gu, Seoul 08826, KOREA

Equipment Under Test(EUT):

Name : SG1000 home gateway

Model : SG1000

In Accordance with: FCC PART 15, SUBPART C : 2015 (Section 15.247)
ANSI C63.4:2014 ; ANSI C63.10:2013

Report No : T1860375 07

Date of Test : March 24-June 21, 2016

Date of Issue : June 22, 2016

Test Result : PASS

Test Result: **PASS**

In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

(Mark Zhu)

General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Alpha Product Testing Co., Ltd. Or test done by Shenzhen Alpha Product Testing Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Alpha Product Testing Co., Ltd. Approvals in writing.

TABLE OF CONTENT

Description

Page

1 General Information	4
1.1 Description of Device (EUT)	4
1.2 Description of Test Facility	5
2 EMC Equipment List	5
3 Test Procedure	6
4 Summary of Measurement	7
4.1 Summary of test result	7
4.2 Test connection	8
4.3 Assistant equipment used for test	8
4.4 Test mode	8
4.5 Channel list	9
4.6 Test Conditions	9
4.7 Measurement Uncertainty (95% confidence levels, k=2)	9
5 Spurious Emission	10
5.1 Radiation Emission	10
5.1.1 Radiation Emission Limits(15.209)	10
5.1.2 Test Setup	10
5.1.3 Test Procedure	12
5.1.4 Test Equipment Setting For emission test Result	12
5.1.5 Test Condition	13
5.1.6 Test Result	13
6 POWER LINE CONDUCTED EMISSION	36
6.1 Conducted Emission Limits(15.207)	36
6.2 Test Setup	36
6.3 Test Procedure	37
6.4 Test Results	38
7 Conducted Maximum Output Power	42
7.1 Test limit	42
7.2 Test Procedure	42
7.3 Test Setup	42
7.4 Test Results	42
8 PEAK POWER SPECTRAL DENSITY	44
8.1 Test limit	44
8.2 Method of measurement	44
8.3 Test Setup	44
8.4 Test Results	45
Ant0	46
Ant1	52
9 Bandwidth	58
9.1 Test limit	58
9.2 Method of measurement	58

9.3	Test Setup -----	58
9.4	Test Results -----	58
10	Band Edge Check-----	66
10.1	Test limit-----	66
10.2	Test Procedure -----	66
10.3	Test Setup -----	66
10.4	Test Result-----	66
11	Antenna Requirement -----	83
11.1	Standard Requirement -----	83
11.2	Antenna Connected Construction -----	83
11.3	Result -----	83
12	Test setup photo -----	84
13	Photos of EUT -----	86

1 General Information

1.1 Description of Device (EUT)

Trade Name : **enblink**

EUT : SG1000 home gateway

Model No. SG1000

DIFF : N/A

Antenna Type : Integrated Antenna*2, Maximum Gain is 0dBi

Operation IEEE 802.11b/g: 2412MHz-2462MHz (SISO mode)
Frequency : IEEE 802.11n HT20: 2412MHz-2462MHz (MIMO mode)
IEEE 802.11n HT40: 2422MHz-2452MHz (MIMO mode)
IEEE 802.11b/g: 11Channels

Channel number : IEEE 802.11n HT20: 11 Channels
IEEE 802.11n HT40: 7Channels

Modulation type : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11n :OFDM(64QAM, 16QAM, QPSK, BPSK)

Power Supply : DC 5V from USB port

Applicant : Enblink Co., Ltd.

Address : 105-dong 212-ho, Gwanak-ro 1, Gwanak-gu, Seoul 08826, KOREA

Manufacturer : Shenzhen HouTian Network Communication Technology Co., Ltd

Address : Room 420-421,Area 3,Block B,Mingyou Industrial product purchasing center,Baoyuan Road,Bao'an District, Shenzhen City Guangdong Province

1.2 Description of Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building B, East Area of Nanchang Second, Industrial Zone, Gushu 2nd Road,
Bao'an, Shenzhen, China

March 25, 2015 File on Federal Communication Commission
Registration Number: 203110

July 18, 2014 Certificated by IC
Registration Number: 12135A

2 EMC Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal. Due to	Cal Interval
3m Semi-Anechoic	CHENYU	N/A	N/A	2018.01.18	2Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2017.01.16	1 Year
Receiver	R&S	ESPI	101873	2017.01.16	1 Year
Receiver	R&S	ESCI	101165	2017.01.16	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2017.01.18	1 Year
L.I.S.N.#2	ROHDE&SCHW ARZ	ENV216	101043	2017.01.18	1 Year
Bilog Antenna	SCHWARZBECK	VULB 9168	VULB9168-438	2018.01.18	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2017.01.20	2Year
Cable	Resenberger	N/A	No.1	2017.01.16	1 Year
Cable	SCHWARZBECK	N/A	No.2	2017.01.16	1 Year
Cable	SCHWARZBECK	N/A	No.3	2017.01.16	1 Year
Pre-amplifier	HP	HP8347A	2834A00455	2017.01.18	1 Year
Pre-amplifier	Agilent	8449B	3008A02664	2017.01.18	1 Year
vector Signal Generator	Agilent	N5182A	MY49060042	2016.11.16	1 Year

vector Signal Generator	Agilent	E4438C	US44271917	2016.11.16	1 Year
X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY54080020	2016.11.16	1 Year
X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY54110001	2016.11.16	1 Year
Signal Analyzer	Agilent	N9020A	MY48030494	2016.11.16	1 Year

3 Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The test procedure used was ANSI Standard ANSI C63.10:2013 using a 50 u H LISN. Both Lines were observed. The bandwidth of the receiver was 10kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25°C with a humidity of 58%.

RADIATION INTERFERENCE: The test procedure used was ANSI Standard ANSI C63.10:2013 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3MHz above 1 GHz. The ambient temperature of the EUT was 25°C with a humidity of 58%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS

33.20 dBuV + 10.36 dB + 0.9 dB= 44.46 dBuV/m @ 3m

ANSI STANDARD ANSI C63.10:2013 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard ANSI C63.10:2013 with the EUT 40 cm from the vertical ground wall.

4 Summary of Measurement

4.1 Summary of test result

Test Item	Test Requirement	Standards Paragraph	Result
Spurious Emission	FCC PART 15:2015	Section 15.247&15.209	Compliance
Conduction Emission	FCC PART 15:2015	Section 15.207	Compliance
Bandwidth Test	FCC PART 15:2015	Section 15.247	Compliance
Peak Power	FCC PART 15:2015	Section 15.247	Compliance
Power Density	FCC PART 15:2015	Section 15.247	Compliance
Band Edge	FCC PART 15:2015	Section 15.247	Compliance
Antenna Requirement	FCC PART 15:2015	Section 15.203	Compliance

Note: The EUT has been tested as an independent unit. And Continual Transmitting in maximum power, Test had been referenced to the kdb 558074 D01 DTS Meas Guidance v03r04 .

4.2 Test connection



4.3 Assistant equipment used for test

Description : N/A
Manufacturer : N/A
Model No. : N/A
Input : N/A
Output : N/A

4.4 Test mode

Dutycycle :100% Keeping TX			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20 with 2.4G	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11 n/HT40 with 2.4G	13.5	Low :CH3	2422
	13.5	Middle:CH6	2437
	13.5	High:CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate. so those data rate were used for all test.			

4.5 Channel list

For IEEE 802.11b/g and IEEE 802.11n/HT20 with 2.4G					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		

For IEEE 802.11n/HT40 with 2.4G					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	/	CH5	2432	CH9	2452
CH2	/	CH6	2437	/	/
CH3	2422	CH7	2442	/	/
CH4	2427	CH8	2447	/	/

4.6 Test Conditions

Temperature range	21-25℃
Humidity range	40-75%
Pressure range	86-106kPa

4.7 Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.71dB	
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.90 dB	Polarize: V
	3.92dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.26 dB	Polarize: H
	4.28 dB	Polarize: V
Uncertainty for conducted RF Power	0.16dB	

5 Spurious Emission

5.1 Radiation Emission

5.1.1 Radiation Emission Limits(15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

NOTE:


- a) The tighter limit applies at the band edges.
- b) Emission Level(dB uV/m)=20log Emission Level(uv/m)

5.1.2 Test Setup


See the next page



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

5.1.3 Test Procedure

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Quasi Peak Detector mode premeasured
- If Peak value comply with QP limit Below 1GHz. The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.
- For the actual test configuration, please see the test setup photo.

5.1.4 Test Equipment Setting For emission test Result

9KHz~150KHz	RBW 200Hz	VBW 1KHz
150KHz~30MHz	RBW 9KHz	VBW 30KHz
30MHz~1GHz	RBW 120KHz	VBW 300KHz
Above 1GHz	RBW 1MHz	VBW 3MHz

5.1.5 Test Condition

Continual Transmitting in maximum power.

5.1.6 Test Result

TX MODE

All modes have been tested , and only worse case of 802.11 b mode is reported only.


We have scanned the 9KHz from 25GHz to the EUT.

Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Ant1
H:



V:




Ant2



Data: 6

File: F:\REPORT\A PU TEIRAZ X6.EM6 (6)

Date: 2016-06-18 Time: 15:05:06



Condition : FCC PART 15 B POL: VERTICAL
 EUT :
 Model No :
 Test Mode :
 Power :
 Test Engineer :
 Remark :
 Temp : 24.2 °C
 Hum : 54 %

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	44.43	36.78	13.79	29.96	0.03	20.64	40.00	-19.36	Peak
2	68.63	40.18	10.82	30.26	0.30	21.04	40.00	-18.96	Peak
3	107.13	45.84	10.93	29.96	0.44	27.25	43.50	-16.25	Peak
4	151.07	40.93	14.16	29.41	0.42	26.10	43.50	-17.40	Peak
5	270.37	45.60	12.09	28.13	0.69	30.25	46.00	-15.75	Peak
6	665.80	36.79	19.28	25.66	0.85	31.26	46.00	-14.74	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

Ant0:

From 1G-25GHz

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

IEEE 802.11b

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remarks
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	45.93	---	-11.24	34.69	---	74	54	39.31	Peak
4824	V	38.31	---	0.64	38.95	---	74	54	35.05	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	45.45	---	-11.24	34.21	---	74	54	39.79	Peak
4824	H	38.04	---	0.64	38.68	---	74	54	35.32	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	44.9	---	-11.24	33.66	---	74	54	40.34	Peak
4874	V	40.64	---	0.76	41.4	---	74	54	32.6	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	45.06	---	-11.24	33.82	---	74	54	40.18	Peak
4874	H	41.64	---	0.76	42.4	---	74	54	31.6	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	44.85	---	-11.24	33.61	---	74	54	40.39	Peak
4924	V	36.27	---	0.87	37.14	---	74	54	36.86	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	45.26	---	-11.24	34.02	---	74	54	39.98	Peak
4924	H	35.11	---	0.87	35.98	---	74	54	38.02	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11 g:

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1145	V	45.73	---	-11.24	34.49	---	74	54	39.51	Peak
2586	V	47.8	---	-7.13	40.67	---	74	54	33.33	Peak
3062	V	45.86	---	-5.74	40.12	---	74	54	33.88	Peak
4824	V	45.46	---	0.64	46.1	---	74	54	27.9	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1294	H	45.07	---	-10.96	34.11	---	74	54	39.89	Peak
2038	H	45.26	---	-8.58	36.68	---	74	54	37.32	Peak
3483	H	44.16	---	-4.95	39.21	---	74	54	34.79	Peak
4824	H	42.96	---	0.64	43.6	---	74	54	30.4	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1374	V	45.26	---	-10.43	34.83	---	74	54	39.17	Peak
2589	V	45.85	---	-7.13	38.72	---	74	54	35.28	Peak
3365	V	45.23	---	-5.18	40.05	---	74	54	33.95	Peak
4874	V	44.45	---	0.76	45.21	---	74	54	28.79	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1321	H	45.26	---	-10.84	34.42	---	74	54	39.58	Peak
2314	H	45.96	---	-7.46	38.5	---	74	54	35.5	Peak
3577	H	44.25	---	-4.76	39.49	---	74	54	34.51	Peak
4874	H	41.96	---	0.76	42.72	---	74	54	31.28	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1302	V	45.26	---	-10.84	34.42	---	74	54	39.58	Peak
2982	V	45.8	---	-5.86	39.94	---	74	54	34.06	Peak
3831	V	44.86	---	-3.96	40.9	---	74	54	33.1	Peak
4924	V	43.26	---	0.87	44.13	---	74	54	29.87	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1446	H	45.44	---	-10.29	35.15	---	74	54	38.85	Peak
2198	H	44.26	---	-8.24	36.02	---	74	54	37.98	Peak
3905	H	45.36	---	-3.68	41.68	---	74	54	32.32	Peak
4924	H	42.84	---	0.87	43.71	---	74	54	30.29	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

Ant1:
From 1G-25GHz

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

IEEE 802.11b

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remarks
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	45.82	---	-11.24	34.58	---	74	54	39.42	Peak
4824	V	38.2	---	0.64	38.84	---	74	54	35.16	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	45.34	---	-11.24	34.1	---	74	54	39.9	Peak
4824	H	37.93	---	0.64	38.57	---	74	54	35.43	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	44.79	---	-11.24	33.55	---	74	54	40.45	Peak
4874	V	40.53	---	0.76	41.29	---	74	54	32.71	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	44.95	---	-11.24	33.71	---	74	54	40.29	Peak
4874	H	41.53	---	0.76	42.29	---	74	54	31.71	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	44.74	---	-11.24	33.5	---	74	54	40.5	Peak
4924	V	36.16	---	0.87	37.03	---	74	54	36.97	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	45.15	---	-11.24	33.91	---	74	54	40.09	Peak
4924	H	34.82	---	0.87	35.69	---	74	54	38.31	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11 g:

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1145	V	45.62	---	-11.24	34.38	---	74	54	39.62	Peak
2586	V	47.51	---	-7.13	40.38	---	74	54	33.62	Peak
3062	V	45.75	---	-5.74	40.01	---	74	54	33.99	Peak
4824	V	45.17	---	0.64	45.81	---	74	54	28.19	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1294	H	45.07	---	-10.96	34.11	---	74	54	39.89	Peak
2038	H	45.26	---	-8.58	36.68	---	74	54	37.32	Peak
3483	H	44.16	---	-4.95	39.21	---	74	54	34.79	Peak
4824	H	42.96	---	0.64	43.6	---	74	54	30.4	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1374	V	45.15	---	-10.43	34.72	---	74	54	39.28	Peak
2589	V	45.56	---	-7.13	38.43	---	74	54	35.57	Peak
3365	V	45.12	---	-5.18	39.94	---	74	54	34.06	Peak
4874	V	44.16	---	0.76	44.92	---	74	54	29.08	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1321	H	45.15	---	-10.84	34.31	---	74	54	39.69	Peak
2314	H	45.67	---	-7.46	38.21	---	74	54	35.79	Peak
3577	H	44.14	---	-4.76	39.38	---	74	54	34.62	Peak
4874	H	41.67	---	0.76	42.43	---	74	54	31.57	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1302	V	45.15	---	-10.84	34.31	---	74	54	39.69	Peak
2982	V	45.51	---	-5.86	39.65	---	74	54	34.35	Peak
3831	V	44.75	---	-3.96	40.79	---	74	54	33.21	Peak
4924	V	42.97	---	0.87	43.84	---	74	54	30.16	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1446	H	45.33	---	-10.29	35.04	---	74	54	38.96	Peak
2198	H	43.97	---	-8.24	35.73	---	74	54	38.27	Peak
3905	H	45.25	---	-3.68	41.57	---	74	54	32.43	Peak
4924	H	42.55	---	0.87	43.42	---	74	54	30.58	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11n/HT20 with 2.4G

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1492	V	45.44	---	-10.27	35.17	---	74	54	38.83	Peak
2671	V	45.03	---	-6.94	38.09	---	74	54	35.91	Peak
3948	V	45.22	---	-3.68	41.54	---	74	54	32.46	Peak
4824	V	43.97	---	0.64	44.61	---	74	54	29.39	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1451	H	45.47	---	-10.27	35.2	---	74	54	38.8	Peak
2839	H	45.74	---	-6.17	39.57	---	74	54	34.43	Peak
3607	H	45.31	---	-4.52	40.79	---	74	54	33.21	Peak
4824	H	44.23	---	0.64	44.87	---	74	54	29.13	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1262	V	45.16	---	-10.96	34.2	---	74	54	39.8	Peak
2013	V	45.6	---	-8.58	37.02	---	74	54	36.98	Peak
3798	V	44.84	---	-4.07	40.77	---	74	54	33.23	Peak
4874	V	43.96	---	0.76	44.72	---	74	54	29.28	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1511	H	45.06	---	-10.14	34.92	---	74	54	39.08	Peak
2353	H	45.22	---	-7.59	37.63	---	74	54	36.37	Peak
3266	H	45.49	---	-5.39	40.1	---	74	54	33.9	Peak
4874	H	44.23	---	0.76	44.99	---	74	54	29.01	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1477	V	46.49	---	-10.27	36.22	---	74	54	37.78	Peak
2703	V	45.37	---	-6.43	38.94	---	74	54	35.06	Peak
3561	V	45.26	---	-4.76	40.5	---	74	54	33.5	Peak
4924	V	44.09	---	0.87	44.96	---	74	54	29.04	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1503	H	45.04	---	-10.14	34.9	---	74	54	39.1	Peak
3588	H	45.34	---	-4.96	40.38	---	74	54	33.62	Peak
4153	H	45.15	---	-2.48	42.67	---	74	54	31.33	Peak
4924	H	43.2	---	0.87	44.07	---	74	54	29.93	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11n/HT40 with 2.4G

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1551	V	45.5	---	-10.07	35.43	---	74	54	38.57	Peak
2695	V	45.37	---	-6.94	38.43	---	74	54	35.57	Peak
3463	V	44.66	---	-4.95	39.71	---	74	54	34.29	Peak
4844	V	43.25	---	0.64	43.89	---	74	54	30.11	Peak
N/A										

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1542	H	45.27	---	-10.14	35.13	---	74	54	38.87	Peak
2358	H	45.13	---	-7.59	37.54	---	74	54	36.46	Peak
3096	H	45.54	---	-5.74	39.8	---	74	54	34.2	Peak
4844	H	43.94	---	0.64	44.58	---	74	54	29.42	Peak
N/A										

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1628	V	45.83	---	-9.84	35.99	---	74	54	38.01	Peak
2593	V	45.25	---	-7.13	38.12	---	74	54	35.88	Peak
3301	V	45.39	---	-5.31	40.08	---	74	54	33.92	Peak
4874	V	44.24	---	0.76	45	---	74	54	29	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1564	H	45.46	---	-10.07	35.39	---	74	54	38.61	Peak
2248	H	45.8	---	-8.13	37.67	---	74	54	36.33	Peak
3159	H	44.76	---	-5.52	39.24	---	74	54	34.76	Peak
4874	H	44.01	---	0.76	44.77	---	74	54	29.23	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.
Emissions attenuated more than 20 dB below the permissible value are not reported.

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1645	V	45.89	---	-9.84	36.05	---	74	54	37.95	Peak
2590	V	45.42	---	-7.13	38.29	---	74	54	35.71	Peak
3851	V	44.84	---	-3.84	41	---	74	54	33	Peak
4904	V	43.19	---	0.87	44.06	---	74	54	29.94	Peak

EUT	SG1000 home gateway	Model Name	SG1000
Temperature	26°C	Relative Humidity	56%
Pressure	960hPa	Test voltage	DC 5V from USB Port
Test Mode	MIMO TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1792	H	45.56	---	-9.27	36.29	---	74	54	37.71	Peak
2804	H	45.74	---	-6.17	39.57	---	74	54	34.43	Peak
3743	H	46.1	---	-4.24	41.86	---	74	54	32.14	Peak
4904	H	44.53	---	0.87	45.4	---	74	54	28.6	Peak

Notes: AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

6 POWER LINE CONDUCTED EMISSION

6.1 Conducted Emission Limits(15.207)


Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

6.2 Test Setup



6.3 Test Procedure


TX MODE

All modes have been tested, and only worse case of 802.11 b (ANT 1) mode is reported only.

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCI) is set at 9 kHz.

6.4 Test Results

Ant1



Condition : FCC PART 15 B QP POL: LINE Temp: 25.7 °C Hum: 51 %
 EUT :
 Model No :
 Test Mode :
 Power :
 Test Engineer :
 Remark :


Item	Freq MHz	Read Level dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.164	39.71	0.03	-9.52	0.10	49.36	65.25	-15.89	Peak
2	0.310	38.91	0.03	-9.56	0.10	48.60	59.97	-11.37	Peak
3	0.381	37.13	0.03	-9.57	0.10	46.83	58.25	-11.42	Peak
4	0.735	34.74	0.04	-9.59	0.10	44.47	56.00	-11.53	Peak
5	1.744	28.24	0.05	-9.70	0.10	38.09	56.00	-17.91	Peak
6	2.527	26.32	0.06	-9.75	0.11	36.24	56.00	-19.76	Peak

Remark: Level = Read Level + LISN Factor - Preamp Factor + Cable Loss

Data: 15

File: E:\Conduction 0.15-30.EM6 (46)

Date: 2016-06-20 Time: 14:08:16



Condition : FCC PART 15 B QP POL: NEUTRAL Temp: 25.7 °C Hum: 51 %
 EUT :
 Model No :
 Test Mode :
 Power :
 Test Engineer :
 Remark :

Item	Freq MHz	Read Level dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.170	37.41	0.03	-9.52	0.10	47.06	64.94	-17.88	Peak
2	0.381	36.04	0.03	-9.57	0.10	45.74	58.25	-12.51	Peak
3	0.743	32.96	0.04	-9.59	0.10	42.69	56.00	-13.31	Peak
4	1.184	27.64	0.04	-9.65	0.10	37.43	56.00	-18.57	Peak
5	2.707	21.38	0.07	-9.77	0.11	31.33	56.00	-24.67	Peak
6	9.451	18.29	0.17	-9.94	0.19	28.59	60.00	-31.41	Peak

Remark: Level = Read Level + LISN Factor - Preamp Factor + Cable Loss

7 Conducted Maximum Output Power

7.1 Test limit

Please refer section 15.247.

7.2 Test Procedure

Details see the KDB558074 Meas Guidance V03


7.2.1 Place the EUT on the table and set it in transmitting mode.

7.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

Details see the KDB558074 DTS Meas Guidance V03

7.3 Test Setup



7.4 Test Results

PASS

Detailed information please see the following page.

Mode	Frequency (MHz)	Ant Port	PK Output power(dBm)		Limit (dBm)	Result
IEEE 802.11 b	CH1: 2412	0	9.23	9.23	30	PASS
		1	9.27	9.27	30	PASS
	CH6: 2437	0	9.17	9.17	30	PASS
		1	9.19	9.19	30	PASS
	CH11: 2462	0	9.22	9.22	30	PASS
		1	9.11	9.11	30	PASS
IEEE 802.11 g	CH1: 2412	0	8.81	8.81	30	PASS
		1	8.90	8.90	30	PASS
	CH6: 2437	0	8.82	8.82	30	PASS
		1	8.35	8.35	30	PASS
	CH11: 2462	0	8.70	8.70	30	PASS
		1	8.90	8.90	30	PASS
IEEE 802.11 n/HT20 with 2.4G	CH1: 2412	0	5.22	8.22	30	PASS
		1	5.19			
	CH6: 2437	0	5.19	8.19	30	PASS
		1	5.16			
	CH11: 2462	0	5.16	8.14	30	PASS
		1	5.09			
IEEE 802.11 n/HT40 with 2.4G	CH3: 2422	0	4.23	7.26	30	PASS
		1	4.26			
	CH6: 2437	0	4.24	7.18	30	PASS
		1	4.10			
	CH9: 2452	0	4.25	7.23	30	PASS
		1	4.19			
Conclusion: PASS						

8 PEAK POWER SPECTRAL DENSITY

8.1 Test limit

8.1.1 Please refer section 15.247.

8.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

8.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

8.2 Method of measurement

Details see the KDB558074 DTS Meas Guidance V03

8.2.1 Place the EUT on the table and set it in transmitting mode.

8.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

8.2.3 Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, span=5-30%EBW, detail see the test plot.

8.2.4 Record the max reading.

8.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

8.3 Test Setup



8.4 Test Results

PASS.

Detailed information please see the following page.

Mode	Frequency (MHz)	Ant Port	PK Output power(dBm)		Limit (dBm)	Result
IEEE 802.11 b	CH1: 2412	0	-8.215	-8.215	8	PASS
		1	-8.212	-8.212	8	PASS
	CH6: 2437	0	-7.434	-7.434	8	PASS
		1	-7.443	-7.443	8	PASS
	CH11: 2462	0	-7.163	-7.163	8	PASS
		1	-7.146	-7.146	8	PASS
IEEE 802.11 g	CH1: 2412	0	-8.422	-8.422	8	PASS
		1	-8.413	-8.413	8	PASS
	CH6: 2437	0	-12.035	-12.035	8	PASS
		1	-12.007	-12.007	8	PASS
	CH11: 2462	0	-12.322	-12.322	8	PASS
		1	-12.361	-12.361	8	PASS
IEEE 802.11 n/HT20 with 2.4G	CH1: 2412	0	-12.488	-9.46	8	PASS
		1	-12.457			
	CH6: 2437	0	-11.733	-8.73	8	PASS
		1	-11.739			
	CH11: 2462	0	-12.325	-9.32	8	PASS
		1	-12.327			
IEEE 802.11 n/HT40 with 2.4G	CH3: 2422	0	-18.357	-15.33	8	PASS
		1	-18.329			
	CH6: 2437	0	-16.549	-13.52	8	PASS
		1	-16.509			
	CH9: 2452	0	-18.100	-15.09	8	PASS
		1	-18.106			
Conclusion: PASS						


Ant0
IEEE 802.11b :
CH Low :



CH Mid:




CH Hig:




IEEE 802.11g :
CH Low



CH Mid:




CH Hig:




IEEE 802.11n HT20 :
CH Low :



CH Mid:




CH Hig:




IEEE 802.11n HT40 :


CH Low :



CH Mid:



CH Hig:



Ant1
IEEE 802.11b :
CH Low :



CH Mid:

