



# FCC RF Test Report

**APPLICANT** : INFINIX MOBILITY LIMITED  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Infinix  
**MODEL NAME** : X5515  
**FCC ID** : 2AIZN-X5515  
**STANDARD** : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 11, 2018 and completely tested on Jun. 30, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.26-2015 and the testing has shown the tested sample to be in compliance with the applicable technical standards. The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

**Sportun International (Shenzhen) Inc.**  
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City  
Guangdong Province 518055 China



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	7
1.7 Testing Location .....	9
1.8 Applicable Standards.....	9
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>10</b>
2.1 Test Mode .....	10
2.2 Connection Diagram of Test System.....	12
2.3 Support Unit used in test configuration and system .....	13
2.4 Measurement Results Explanation Example.....	13
2.5 Frequency List of Low/Middle/High Channels .....	14
<b>3 CONDUCTED TEST ITEMS .....</b>	<b>16</b>
3.1 Measuring Instruments .....	16
3.2 Test Setup .....	16
3.3 Test Result of Conducted Test.....	16
3.4 Conducted Output Power and ERP/EIRP .....	17
3.5 Peak-to-Average Ratio .....	18
3.6 Occupied Bandwidth.....	19
3.7 Conducted Band Edge .....	20
3.8 Conducted Spurious Emission .....	22
3.9 Frequency Stability .....	23
<b>4 RADIATED TEST ITEMS .....</b>	<b>24</b>
4.1 Measuring Instruments .....	24
4.2 Test Setup .....	24
4.3 Test Result of Radiated Test .....	24
4.4 Radiated Spurious Emission .....	25
<b>5 LIST OF MEASURING EQUIPMENT .....</b>	<b>26</b>
<b>6 UNCERTAINTY OF EVALUATION.....</b>	<b>27</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>	
<b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>	
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (Band 5)	ERP < 7 Watt		
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2) (Band 7)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5)	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	§27.53(m)(4)		
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5)	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5)	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 16.46 dB at 7585.02 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])		



## 1 General Description

### 1.1 Applicant

**INFINIX MOBILITY LIMITED**

RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST  
KLN HONG KONG

### 1.2 Manufacturer

**SHENZHEN TECNO TECHNOLOGY CO.,LTD.**

1/4/TH FLOOR,7TH FLOOR, 3RD BUILDING, PACIFIC INDUSTRIAL PARK, NO.2088, SHENYAN  
ROAD, YANTIAN DISTRICT, SHENZHEN, GUANGDONG, CHINA

### 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Phone
<b>Brand Name</b>	Infinix
<b>Model Name</b>	X5515
<b>FCC ID</b>	2AIZN-X5515
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR / EDR / LE
<b>IMEI Code</b>	Conducted: 357546090074163/357546090074171 Radiation: 357546090074163/357546090074171
<b>HW Version</b>	V1.0
<b>SW Version</b>	X5515-H398DEG-GO-180430V48
<b>EUT Stage</b>	Identical Prototype



## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz
<b>Rx Frequency</b>	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz
<b>Bandwidth</b>	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 7 : 5MHz / 10MHz / 15MHz / 20MHz
<b>Maximum Output Power to Antenna</b>	LTE Band 2 : 22.87 dBm LTE Band 4 : 22.79 dBm LTE Band 5 : 23.16 dBm LTE Band 7 : 23.36 dBm
<b>Antenna Gain</b>	LTE Band 2 : -0.80 dBi LTE Band 4 : -0.80 dBi LTE Band 5 : -2.30 dBi LTE Band 7 : -0.60 dBi
<b>Type of Modulation</b>	QPSK / 16QAM / 64QAM

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 2		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1909.3	1M10G7D	-	0.1607	1M09W7D	-	0.1315
3	1851.5 ~ 1908.5	2M72G7D	-	0.1574	2M72W7D	-	0.1318
5	1852.5 ~ 1907.5	4M50G7D	-	0.1607	4M51W7D	-	0.1309
10	1855.0 ~ 1905.0	9M09G7D	0.0071	0.1596	9M07W7D	-	0.1315
15	1857.5 ~ 1902.5	13M5G7D	-	0.1607	13M5W7D	-	0.1315
20	1860.0 ~ 1900.0	18M5G7D	-	0.1611	18M5W7D	-	0.1315
LTE Band 2		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
1.4	1850.7 ~ 1909.3	1M09W7D		-		0.0991	
3	1851.5 ~ 1908.5	2M71W7D		-		0.0984	
5	1852.5 ~ 1907.5	4M52W7D		-		0.1021	
10	1855.0 ~ 1905.0	9M07W7D		-		0.1002	
15	1857.5 ~ 1902.5	13M5W7D		-		0.1026	
20	1860.0 ~ 1900.0	18M5W7D		-		0.1030	
LTE Band 4		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1754.3	1M09G7D	-	0.1535	1M10W7D	-	0.1282
3	1711.5 ~ 1753.5	2M72G7D	-	0.1528	2M72W7D	-	0.1288
5	1712.5 ~ 1752.5	4M50G7D	-	0.1560	4M51W7D	-	0.1315
10	1715.0 ~ 1750.0	9M07G7D	0.0117	0.1542	9M07W7D	-	0.1306
15	1717.5 ~ 1747.5	13M5G7D	-	0.1560	13M5W7D	-	0.1312
20	1720.0 ~ 1745.0	18M4G7D	-	0.1581	18M4W7D	-	0.1309
LTE Band 4		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
1.4	1710.7 ~ 1754.3	1M10W7D		-		0.0959	
3	1711.5 ~ 1753.5	2M73W7D		-		0.0953	



5	1712.5 ~ 1752.5	4M50W7D			-	0.0977	
10	1715.0 ~ 1750.0	9M09W7D			-	0.0964	
15	1717.5 ~ 1747.5	13M5W7D			-	0.0979	
20	1720.0 ~ 1745.0	18M5W7D			-	0.0973	
LTE Band 5		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERF(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERF(W)
1.4	824.7 ~ 848.3	1M09G7D	-	0.0721	1M09W7D	-	0.0601
3	825.5 ~ 847.5	2M73G7D	-	0.0658	2M72W7D	-	0.0551
5	826.5 ~ 846.5	4M51G7D	-	0.0733	4M51W7D	-	0.0611
10	829.0 ~ 844.0	9M07G7D	0.0188	0.0743	9M05W7D	-	0.0605
LTE Band 5		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum ERF(W)	
1.4	824.7 ~ 848.3	1M09W7D		-		0.0442	
3	825.5 ~ 847.5	2M73W7D		-		0.0439	
5	826.5 ~ 846.5	4M51W7D		-		0.0454	
10	829.0 ~ 844.0	9M11W7D		-		0.0443	
LTE Band 7		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M53G7D	-	0.1884	4M51W7D	-	0.1545
10	2505.0 ~ 2565.0	9M05G7D	0.0159	0.1884	9M05W7D	-	0.1545
15	2507.5 ~ 2562.5	13M5G7D	-	0.1866	13M5W7D	-	0.1531
20	2510.0 ~ 2560.0	18M5G7D	-	0.1888	18M5W7D	-	0.1549
LTE Band 7		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)		Frequency Tolerance (ppm)		Maximum EIRP(W)	
5	2502.5 ~ 2567.5	4M49W7D		-		0.1140	
10	2505.0 ~ 2565.0	9M03W7D		-		0.1114	
15	2507.5 ~ 2562.5	13M5W7D		-		0.1159	
20	2510.0 ~ 2560.0	18M5W7D		-		0.1140	



## 1.7 Testing Location

Sportun International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

<b>Test Site</b>	Sportun International (Shenzhen) Inc.	
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sportun Site No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	251365
<b>Test Site</b>	Sportun International (Shenzhen) Inc.	
<b>Test Site Location</b>	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
<b>Test Site No.</b>	<b>Sportun Site No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH01-SZ	577730

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	2						v	v	v	v	v		v	v	v	v
	4						v	v	v	v	v		v	v	v	v
	5				v	-	-	v	v	v	v		v	v	v	v
	7	-	-				v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v	v			v	v	v	v
	4	v	v	v	v	v	v	v	v	v			v	v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v		v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v		v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v		v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v	v		v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v		v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v		v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v		v	v	v	v
Frequency Stability	2				v			v					v		v	
	4				v			v					v		v	
	5				v	-	-	v					v		v	
	7	-	-	v	v	v	v	v					v		v	



Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v				v	v	v
	4	v	v	v	v	v	v	v	v	v				v	v	v
	5	v	v	v	v	-	-	v	v	v				v	v	v
	7	-	-	v	v	v	v	v	v	v				v	v	v
Radiated Spurious Emission	2	v	v	v	v	v	v	v			v				v	
	4	v	v	v	v	v	v	v			v				v	
	5	v	v	v	v	-	-	v			v				v	
	7	-	-	v	v	v	v	v			v				v	
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.															

## 2.2 Connection Diagram of Test System





## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

$$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}$$

$$= 4.5 + 10 = 14.5 \text{ (dB)}$$



## 2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



#### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 7.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



## 3.6 Occupied Bandwidth

### 3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is  $43 + 10\log_{10}(P[\text{Watts}])$  dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emissi

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is  $43 + 10\log_{10}(P[\text{Watts}])$  dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is  $43 + 10\log_{10}(P[\text{Watts}])$  dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.



### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$\begin{aligned} &= P(W) - [43 + 10\log(P)] \text{ (dB)} \\ &= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13 \text{ dBm}. \end{aligned}$$

9. For LTE Band 7, the other 40 dB, and 55 dB have additionally applied same calculation above.



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

For Band 7:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $55 + 10 \log(P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.

#### 11. For Band 7

The limit line is derived from  $55 + 10\log(P)$  dB below the transmitter power P(Watts)

$$\begin{aligned} &= P(W) - [55 + 10\log(P)] \text{ (dB)} \\ &= [30 + 10\log(P)] \text{ (dBm)} - [55 + 10\log(P)] \text{ (dB)} \\ &= -25 \text{ dBm.} \end{aligned}$$



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^\circ\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^\circ\text{C}$  step up to  $50^\circ\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20 \pm 5^\circ\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.



## 4.4 Radiated Spurious Emission

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $55 + 10 \log(P)$  dB.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10.  $EIRP (\text{dBm}) = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP (\text{dBm}) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(\text{W}) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13 \text{ dBm}$ .

13. For Band 7:

The limit line is derived from  $55 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $EIRP (\text{dBm}) = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$   
 $ERP (\text{dBm}) = EIRP - 2.15$



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 19, 2018	Jun. 27, 2018~Jun. 30, 2018	Apr. 18, 2019	Conducted (TH01-SZ)
DC Power Supply	GWINSTEK	AnritsuGPS-3030D	EM882636	Max 30V	Apr. 19, 2018	Jun. 27, 2018~Jun. 30, 2018	Apr. 18, 2019	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 20, 2017	Jun. 27, 2018~Jun. 30, 2018	Jul. 19, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 19, 2018	May 19, 2018	Apr.18, 2019	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5Ghz	Oct.19, 2017	May 19, 2018	Oct 18, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Apr. 19, 2018	May 19, 2018	Apr. 18, 2019	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	119436	1GHz~18GHz	Jul. 28, 2017	May 19, 2018	Jul. 27, 2018	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Mar. 30, 2018	May 19, 2018	Mar. 29, 2019	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 19, 2018	May 19, 2018	Apr. 18, 2019	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 OP-R	1707137	1GHz~18GHz	Oct. 19, 2017	May 19, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2017	May 19, 2018	Jul. 17, 2018	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	May 19, 2018	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	May 19, 2018	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	May 19, 2018	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	2.5dB
--	-------

### Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	3.5dB
--	-------

### Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	4.0dB
--	-------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.41	22.48	22.56
	1	49		22.75	22.76	22.87
	1	99		22.25	22.33	22.48
	50	0		21.83	21.86	21.97
	50	24		21.66	21.70	21.80
	50	50		21.45	21.63	21.78
	100	0		21.71	21.65	21.90
	1	0		21.52	21.68	21.52
20	1	49	16-QAM	21.99	21.99	21.97
	1	99		21.57	21.43	21.69
	50	0		20.86	20.57	20.97
	50	24		20.76	20.72	20.82
	50	50		20.57	20.84	20.80
	100	0		20.71	20.67	20.89
	1	0		20.59	20.47	20.20
	1	49		20.93	20.72	20.58
20	1	99	64-QAM	20.38	20.13	20.08
	50	0		19.80	19.34	19.63
	50	24		19.67	19.46	19.38
	50	50		19.57	19.36	19.34
	100	0		19.68	19.38	19.45
	1	0		22.55	22.55	22.56
	1	37		22.84	22.83	22.86
	1	74		22.42	22.45	22.64
15	36	0	QPSK	21.75	21.62	21.82
	36	20		21.68	21.71	21.80
	36	39		21.58	21.74	21.86
	75	0		21.72	21.71	21.86



15	1	0	16-QAM	21.64	21.84	21.70
15	1	37		21.95	21.95	21.99
15	1	74		21.71	21.65	21.84
15	36	0		20.78	20.66	20.90
15	36	20		20.73	20.74	20.83
15	36	39		20.63	20.77	20.89
15	75	0		20.70	20.73	20.86
15	1	0		20.73	20.63	20.46
15	1	37	64-QAM	20.91	20.76	20.60
15	1	74		20.63	20.38	20.23
15	36	0		19.75	19.44	19.46
15	36	20		19.71	19.48	19.33
15	36	39		19.61	19.40	19.36
15	75	0		19.67	19.39	19.35



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.63	22.63	22.70
10	1	25		22.70	22.74	22.83
10	1	49		22.57	22.58	22.72
10	25	0		21.80	21.62	21.91
10	25	12		21.71	21.69	21.83
10	25	25		21.63	21.82	21.97
10	50	0		21.73	21.72	21.93
10	1	0		21.71	21.93	21.89
10	1	25	16-QAM	21.84	21.99	21.97
10	1	49		21.80	21.75	21.96
10	25	0		20.77	20.66	20.91
10	25	12		20.70	20.71	20.83
10	25	25		20.62	20.82	20.98
10	50	0		20.73	20.74	20.95
10	1	0		20.72	20.65	20.41
10	1	25		20.81	20.67	20.52
10	1	49	64-QAM	20.72	20.48	20.34
10	25	0		19.72	19.39	19.28
10	25	12		19.67	19.47	19.27
10	25	25		19.59	19.47	19.39
10	50	0		19.68	19.46	19.35
5	1	0	QPSK	22.51	22.55	22.65
5	1	12		22.79	22.81	22.86
5	1	24		22.46	22.49	22.64
5	12	0		21.65	21.62	21.71
5	12	7		21.66	21.69	21.83
5	12	13		21.57	21.68	21.84
5	25	0		21.65	21.66	21.85
5	1	0		21.60	21.79	21.88
5	1	12	16-QAM	21.89	21.92	21.97
5	1	24		21.63	21.77	21.84
5	12	0		20.65	20.68	20.78
5	12	7		20.70	20.79	20.93
5	12	13		20.60	20.75	20.91



5	25	0	64-QAM	20.64	20.69	20.87
5	1	0		20.68	20.53	20.31
5	1	12		20.89	20.70	20.55
5	1	24		20.61	20.38	20.24
5	12	0		19.68	19.60	19.71
5	12	7		19.68	19.63	19.59
5	12	13		19.59	19.62	19.56
5	25	0		19.59	19.39	19.20



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.62	22.65	22.75
3	1	8		22.62	22.65	22.77
3	1	14		22.59	22.62	22.76
3	8	0		21.63	21.65	21.78
3	8	4		21.65	21.70	21.84
3	8	7		21.63	21.63	21.82
3	15	0		21.65	21.65	21.80
3	1	0		21.65	21.90	22.00
3	1	8	16-QAM	21.71	21.84	21.98
3	1	14		21.73	21.87	21.92
3	8	0		20.67	20.75	20.89
3	8	4		20.69	20.80	20.91
3	8	7		20.67	20.77	20.88
3	15	0		20.64	20.71	20.85
3	1	0		20.73	20.58	20.39
3	1	8		20.73	20.54	20.37
3	1	14	64-QAM	20.69	20.57	20.33
3	8	0		19.65	19.46	19.25
3	8	4		19.64	19.46	19.30
3	8	7		19.62	19.42	19.23
3	15	0		19.58	19.37	19.20
1.4	1	0	QPSK	22.57	22.57	22.74
1.4	1	3		22.69	22.70	22.86
1.4	1	5		22.56	22.59	22.71
1.4	3	0		22.66	22.68	22.80
1.4	3	1		22.74	22.75	22.86
1.4	3	3		22.66	22.68	22.80
1.4	6	0		21.70	21.69	21.82
1.4	1	0		21.64	21.86	21.95
1.4	1	3	16-QAM	21.78	21.96	21.99
1.4	1	5		21.69	21.82	21.90
1.4	3	0		21.55	21.70	21.82
1.4	3	1		21.61	21.73	21.84
1.4	3	3		21.56	21.70	21.76



1.4	6	0	64-QAM	20.74	20.80	20.92
1.4	1	0		20.65	20.55	20.30
1.4	1	3		20.73	20.60	20.33
1.4	1	5		20.67	20.47	20.24
1.4	3	0		20.70	20.52	20.33
1.4	3	1		20.76	20.57	20.38
1.4	3	3		20.70	20.51	20.32
1.4	6	0		19.59	19.36	19.17



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.18	22.23	22.36
	1	49		22.51	22.67	22.79
	1	99		22.15	22.20	22.24
	50	0		21.48	21.61	21.70
	50	24		21.43	21.54	21.67
	50	50		21.39	21.48	21.58
	100	0		21.43	21.56	21.60
20	1	0	16-QAM	21.43	21.52	21.62
	1	49		21.80	21.97	21.95
	1	99		21.44	21.53	21.47
	50	0		20.52	20.63	20.73
	50	24		20.56	20.65	20.69
	50	50		20.50	20.57	20.60
	100	0		20.47	20.56	20.61
20	1	0	64QAM	20.37	20.40	20.29
	1	49		20.68	20.65	20.45
	1	99		20.17	20.05	19.99
	50	0		19.39	19.45	19.27
	50	24		19.37	19.35	19.20
	50	50		19.31	19.31	19.12
	100	0		19.32	19.35	19.18
15	1	0	QPSK	22.35	22.47	22.53
	1	37		22.57	22.73	22.71
	1	74		22.31	22.43	22.45
	36	0		21.50	21.61	21.62
	36	20		21.51	21.60	21.66
	36	39		21.49	21.61	21.59
	75	0		21.50	21.59	21.63
15	1	0	16-QAM	21.58	21.71	21.80
	1	37		21.87	21.98	21.97
	1	74		21.59	21.70	21.66
	36	0		20.55	20.66	20.70
	36	20		20.57	20.67	20.72



15	36	39	64QAM	20.54	20.63	20.65
15	75	0		20.54	20.62	20.66
15	1	0		20.54	20.51	20.39
15	1	37		20.71	20.67	20.52
15	1	74		20.40	20.32	20.20
15	36	0		19.47	19.45	19.25
15	36	20		19.41	19.39	19.22
15	36	39		19.35	19.36	19.21
15	75	0		19.38	19.36	19.19



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.42	22.53	22.59
	1	25		22.58	22.67	22.68
	1	49		22.38	22.53	22.57
	25	0		21.49	21.62	21.68
	25	12		21.52	21.61	21.68
	25	25		21.52	21.61	21.68
	50	0		21.54	21.63	21.70
10	1	0	16-QAM	21.66	21.82	21.84
	1	25		21.81	21.93	21.96
	1	49		21.66	21.78	21.79
	25	0		20.50	20.66	20.72
	25	12		20.56	20.65	20.71
	25	25		20.55	20.64	20.70
	50	0		20.55	20.65	20.70
10	1	0	64QAM	20.57	20.52	20.37
	1	25		20.64	20.64	20.49
	1	49		20.41	20.39	20.33
	25	0		19.44	19.41	19.25
	25	12		19.41	19.38	19.24
	25	25		19.39	19.31	19.21
	50	0		19.43	19.37	19.23
5	1	0	QPSK	22.32	22.45	22.55
	1	12		22.61	22.69	22.73
	1	24		22.33	22.46	22.51
	12	0		21.42	21.54	21.64
	12	7		21.47	21.62	21.67
	12	13		21.44	21.55	21.63
	25	0		21.46	21.56	21.65
5	1	0	16-QAM	21.54	21.73	21.78
	1	12		21.80	21.99	21.92
	1	24		21.57	21.70	21.74
	12	0		20.50	20.63	20.73
	12	7		20.55	20.71	20.77



5	12	13	64QAM	20.51	20.65	20.69
5	25	0		20.50	20.62	20.72
5	1	0		20.50	20.44	20.29
5	1	12		20.70	20.67	20.52
5	1	24		20.42	20.38	20.20
5	12	0		19.44	19.39	19.24
5	12	7		19.51	19.44	19.29
5	12	13		19.44	19.35	19.21
5	25	0		19.39	19.32	19.19



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.42	22.57	22.64
	1	8		22.45	22.57	22.61
	1	14		22.44	22.56	22.61
	8	0		21.44	21.59	21.66
	8	4		21.47	21.65	21.69
	8	7		21.44	21.59	21.66
	15	0		21.47	21.60	21.66
3	1	0	16-QAM	21.64	21.86	21.90
	1	8		21.70	21.87	21.87
	1	14		21.68	21.79	21.84
	8	0		20.56	20.72	20.77
	8	4		20.57	20.73	20.77
	8	7		20.57	20.69	20.73
	15	0		20.52	20.66	20.69
3	1	0	64QAM	20.55	20.50	20.35
	1	8		20.59	20.50	20.33
	1	14		20.56	20.48	20.32
	8	0		19.46	19.37	19.24
	8	4		19.50	19.36	19.25
	8	7		19.47	19.35	19.21
	15	0		19.37	19.30	19.15
1.4	1	0	QPSK	22.35	22.49	22.56
	1	3		22.46	22.62	22.66
	1	5		22.35	22.49	22.57
	3	0		22.42	22.57	22.63
	3	1		22.46	22.64	22.65
	3	3		22.43	22.59	22.62
	6	0		21.43	21.58	21.66
1.4	1	0	16-QAM	21.60	21.76	21.76
	1	3		21.64	21.88	21.88
	1	5		21.59	21.72	21.77
	3	0		21.41	21.57	21.63
	3	1		21.44	21.63	21.68



1.4	3	3	64QAM	21.45	21.59	21.57
1.4	6	0		20.54	20.71	20.75
1.4	1	0		20.54	20.49	20.33
1.4	1	3		20.62	20.54	20.45
1.4	1	5		20.52	20.42	20.31
1.4	3	0		20.56	20.50	20.34
1.4	3	1		20.60	20.59	20.37
1.4	3	3		20.58	20.49	20.34
1.4	6	0		19.44	19.32	19.19



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.95	22.92	22.80
10	1	25		23.16	22.99	22.96
10	1	49		22.87	22.84	22.77
10	25	0		22.06	22.03	21.92
10	25	12		22.00	21.96	21.87
10	25	25		21.95	21.93	21.92
10	50	0		22.02	22.01	21.93
10	1	0		22.19	22.19	22.06
10	1	25	16-QAM	22.27	22.23	22.18
10	1	49		22.13	22.06	22.04
10	25	0		21.00	21.06	20.86
10	25	12		21.03	20.99	20.91
10	25	25		21.06	20.96	20.87
10	50	0		21.01	21.01	20.87
10	1	0	64QAM	20.73	20.74	20.69
10	1	25		20.91	20.86	20.86
10	1	49		20.78	20.71	20.68
10	25	0		19.67	19.69	19.64
10	25	12		19.68	19.69	19.69
10	25	25		19.69	19.60	19.60
10	50	0		19.68	19.66	19.63
5	1	0	QPSK	22.83	22.81	22.76
5	1	12		23.10	23.03	22.97
5	1	24		22.85	22.72	22.68
5	12	0		21.87	21.89	21.86
5	12	7		21.96	21.92	21.88
5	12	13		21.97	21.88	21.80
5	25	0		21.94	21.92	21.88
5	1	0	16-QAM	22.05	22.05	21.99
5	1	12		22.31	22.25	22.25
5	1	24		22.09	21.99	21.97
5	12	0		20.96	20.99	20.87
5	12	7		21.07	20.99	20.88
5	12	13		21.04	20.94	20.81



5	25	0	64QAM	20.98	20.94	20.82
5	1	0		20.69	20.72	20.64
5	1	12		21.02	20.95	20.98
5	1	24		20.76	20.63	20.60
5	12	0		19.63	19.69	19.66
5	12	7		19.73	19.75	19.71
5	12	13		19.70	19.65	19.66
5	25	0		19.62	19.64	19.59



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.44	22.55	22.61
	1	8		22.44	22.56	22.61
	1	14		22.43	22.56	22.63
	8	0		21.43	21.59	21.63
	8	4		21.46	21.61	21.66
	8	7		21.46	21.58	21.64
	15	0		21.45	21.59	21.64
3	1	0	16-QAM	21.65	21.79	21.82
	1	8		21.65	21.83	21.83
	1	14		21.71	21.85	21.86
	8	0		20.54	20.68	20.73
	8	4		20.56	20.71	20.76
	8	7		20.54	20.68	20.74
	15	0		20.49	20.63	20.69
3	1	0	64QAM	20.79	20.79	20.74
	1	8		20.87	20.76	20.73
	1	14		20.86	20.73	20.69
	8	0		19.70	19.71	19.65
	8	4		19.75	19.72	19.71
	8	7		19.72	19.71	19.65
	15	0		19.62	19.63	19.60
1.4	1	0	QPSK	22.89	22.84	22.77
	1	3		23.02	22.94	22.89
	1	5		22.89	22.82	22.76
	3	0		22.97	22.89	22.86
	3	1		23.03	22.98	22.87
	3	3		22.96	22.93	22.86
	6	0		21.99	21.93	21.88
1.4	1	0	16-QAM	22.16	22.04	22.03
	1	3		22.24	22.20	22.13
	1	5		22.16	22.09	21.99
	3	0		21.98	21.94	21.85
	3	1		22.05	21.98	21.90



1.4	3	3	64QAM	21.95	21.91	21.86
1.4	6	0		21.10	21.04	20.92
1.4	1	0		20.77	20.77	20.64
1.4	1	3		20.90	20.87	20.82
1.4	1	5		20.78	20.70	20.62
1.4	3	0		20.83	20.79	20.74
1.4	3	1		20.88	20.87	20.80
1.4	3	3		20.82	20.79	20.74
1.4	6	0		19.68	19.63	19.61



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.95	22.77	22.71
20	1	49		23.36	23.23	23.13
20	1	99		22.92	22.85	22.76
20	50	0		22.45	22.35	22.29
20	50	24		22.44	22.30	22.10
20	50	50		22.35	22.24	22.08
20	100	0		22.42	22.21	22.09
20	1	0		22.10	22.03	22.00
20	1	49	16-QAM	22.42	22.31	22.50
20	1	99		22.17	21.98	22.11
20	50	0		21.37	21.11	21.06
20	50	24		21.42	21.14	21.27
20	50	50		21.41	20.99	21.27
20	100	0		21.36	21.02	21.16
20	1	0		20.45	20.59	20.63
20	1	49		20.98	20.97	21.17
20	1	99	64QAM	20.65	20.66	20.81
20	50	0		19.80	19.70	19.73
20	50	24		19.79	19.78	19.95
20	50	50		19.92	19.64	20.00
20	100	0		19.85	19.65	19.89
15	1	0	QPSK	23.18	22.92	22.96
15	1	37		23.31	23.12	23.27
15	1	74		23.15	22.91	23.12
15	36	0		22.41	22.14	22.20
15	36	20		22.44	22.16	22.30
15	36	39		22.43	22.11	22.32
15	75	0		22.48	22.15	22.28
15	1	0		22.35	22.17	22.22
15	1	37	16-QAM	22.44	22.30	22.45
15	1	74		22.40	22.10	22.29
15	36	0		21.38	21.13	21.16
15	36	20		21.41	21.14	21.28
15	36	39		21.41	21.07	21.28



15	75	0	64QAM	21.42	21.09	21.21
15	1	0		20.64	20.74	20.85
15	1	37		20.98	20.97	21.24
15	1	74		20.81	20.82	20.94
15	36	0		19.84	19.77	19.84
15	36	20		19.81	19.81	19.99
15	36	39		19.82	19.75	20.02
15	75	0		19.80	19.72	19.93



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.26	22.98	23.10
	1	25		23.35	23.11	23.26
	1	49		23.27	22.99	23.21
	25	0		22.41	22.19	22.27
	25	12		22.44	22.19	22.31
	25	25		22.48	22.13	22.33
	50	0		22.50	22.19	22.34
10	1	0	16-QAM	22.41	22.22	22.33
	1	25		22.42	22.31	22.43
	1	49		22.49	22.18	22.36
	25	0		21.41	21.16	21.20
	25	12		21.37	21.10	21.25
	25	25		21.41	21.07	21.25
	50	0		21.41	21.14	21.26
10	1	0	64QAM	20.73	20.76	20.95
	1	25		20.89	20.86	21.07
	1	49		20.84	20.84	21.04
	25	0		19.81	19.76	19.89
	25	12		19.76	19.76	19.96
	25	25		19.75	19.70	19.95
	50	0		19.76	19.74	19.93
5	1	0	QPSK	23.15	22.88	22.99
	1	12		23.30	23.13	23.35
	1	24		23.16	22.89	23.12
	12	0		22.36	22.05	22.25
	12	7		22.41	22.11	22.32
	12	13		22.31	22.05	22.26
	25	0		22.40	22.11	22.31
5	1	0	16-QAM	22.32	22.11	22.22
	1	12		22.44	22.32	22.49
	1	24		22.28	22.09	22.23
	12	0		21.32	21.05	21.20
	12	7		21.36	21.09	21.27



5	12	13	64QAM	21.26	21.03	21.21
5	25	0		21.32	21.05	21.24
5	1	0		20.62	20.69	20.91
5	1	12		20.94	21.03	21.17
5	1	24		20.67	20.70	20.91
5	12	0		19.72	19.77	19.95
5	12	7		19.77	19.80	20.02
5	12	13		19.65	19.71	19.90
5	25	0		19.68	19.71	19.94

**ERP/EIRP**

LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	22.69	22.70	22.86	22.62	22.65	22.77	22.79	22.81	22.86
Conducted Power (Watts)	0.1858	0.1862	0.1932	0.1828	0.1841	0.1892	0.1901	0.1910	0.1932
EIRP(dBm)	21.89	21.90	22.06	21.82	21.85	21.97	21.99	22.01	22.06
EIRP(Watts)	0.1545	0.1549	0.1607	0.1521	0.1531	0.1574	0.1581	0.1589	0.1607

LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) QPSK									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	22.70	22.74	22.83	22.84	22.83	22.86	22.75	22.76	22.87
Conducted Power (Watts)	0.1862	0.1879	0.1919	0.1923	0.1919	0.1932	0.1884	0.1888	0.1936
EIRP(dBm)	21.90	21.94	22.03	22.04	22.03	22.06	21.95	21.96	22.07
EIRP(Watts)	0.1549	0.1563	0.1596	0.1600	0.1596	0.1607	0.1567	0.1570	0.1611



LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
	Conducted Power (dBm)	21.78	21.96	21.99	21.65	21.90	22.00	21.89	21.92
Conducted Power (Watts)	0.1507	0.1570	0.1581	0.1462	0.1549	0.1585	0.1545	0.1556	0.1574
EIRP(dBm)	20.98	21.16	21.19	20.85	21.10	21.20	21.09	21.12	21.17
EIRP(Watts)	0.1253	0.1306	0.1315	0.1216	0.1288	0.1318	0.1285	0.1294	0.1309

LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) 16QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
	Conducted Power (dBm)	21.84	21.99	21.97	21.95	21.95	21.99	21.99	21.97
Conducted Power (Watts)	0.1528	0.1581	0.1574	0.1567	0.1567	0.1581	0.1581	0.1581	0.1574
EIRP(dBm)	21.04	21.19	21.17	21.15	21.15	21.19	21.19	21.19	21.17
EIRP(Watts)	0.1271	0.1315	0.1309	0.1303	0.1303	0.1315	0.1315	0.1315	0.1309



LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	20.76	20.57	20.38	20.73	20.58	20.39	20.89	20.70	20.55
Conducted Power (Watts)	0.1191	0.1140	0.1091	0.1183	0.1143	0.1094	0.1227	0.1175	0.1135
EIRP(dBm)	19.96	19.77	19.58	19.93	19.78	19.59	20.09	19.90	19.75
EIRP(Watts)	0.0991	0.0948	0.0908	0.0984	0.0951	0.0910	0.1021	0.0977	0.0944

LTE Band 2 ( $G_T - L_C = -0.80 \text{ dB}$ ) 64QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	20.81	20.67	20.52	20.91	20.76	20.60	20.93	20.72	20.58
Conducted Power (Watts)	0.1205	0.1167	0.1127	0.1233	0.1191	0.1148	0.1239	0.1180	0.1143
EIRP(dBm)	20.01	19.87	19.72	20.11	19.96	19.80	20.13	19.92	19.78
EIRP(Watts)	0.1002	0.0971	0.0938	0.1026	0.0991	0.0955	0.1030	0.0982	0.0951



LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	22.46	22.62	22.66	22.42	22.57	22.64	22.61	22.69	22.73
Conducted Power (Watts)	0.1762	0.1828	0.1845	0.1746	0.1807	0.1837	0.1824	0.1858	0.1875
EIRP(dBm)	21.66	21.82	21.86	21.62	21.77	21.84	21.81	21.89	21.93
EIRP(Watts)	0.1466	0.1521	0.1535	0.1452	0.1503	0.1528	0.1517	0.1545	0.1560

LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) QPSK									
Bandwidth	10M			15M			20M		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	22.58	22.67	22.68	22.57	22.73	22.71	22.51	22.67	22.79
Conducted Power (Watts)	0.1811	0.1849	0.1854	0.1807	0.1875	0.1866	0.1782	0.1849	0.1901
EIRP(dBm)	21.78	21.87	21.88	21.77	21.93	21.91	21.71	21.87	21.99
EIRP(Watts)	0.1507	0.1538	0.1542	0.1503	0.1560	0.1552	0.1483	0.1538	0.1581



LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	21.64	21.88	21.88	21.64	21.86	21.90	21.80	21.99	21.92
Conducted Power (Watts)	0.1459	0.1542	0.1542	0.1459	0.1535	0.1549	0.1514	0.1581	0.1556
EIRP(dBm)	20.84	21.08	21.08	20.84	21.06	21.10	21.00	21.19	21.12
EIRP(Watts)	0.1213	0.1282	0.1282	0.1213	0.1276	0.1288	0.1259	0.1315	0.1294

LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	21.81	21.93	21.96	21.87	21.98	21.97	21.80	21.97	21.95
Conducted Power (Watts)	0.1517	0.1560	0.1570	0.1538	0.1578	0.1574	0.1514	0.1574	0.1567
EIRP(dBm)	21.01	21.13	21.16	21.07	21.18	21.17	21.00	21.17	21.15
EIRP(Watts)	0.1262	0.1297	0.1306	0.1279	0.1312	0.1309	0.1259	0.1309	0.1303



LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	20.62	20.54	20.45	20.59	20.50	20.33	20.70	20.67	20.52
Conducted Power (Watts)	0.1153	0.1132	0.1109	0.1146	0.1122	0.1079	0.1175	0.1167	0.1127
EIRP(dBm)	19.82	19.74	19.65	19.79	19.70	19.53	19.90	19.87	19.72
EIRP(Watts)	0.0959	0.0942	0.0923	0.0953	0.0933	0.0897	0.0977	0.0971	0.0938

LTE Band 4 ( $G_T - L_C = -0.80 \text{ dB}$ ) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	20.64	20.64	20.49	20.71	20.67	20.52	20.68	20.65	20.45
Conducted Power (Watts)	0.1159	0.1159	0.1119	0.1178	0.1167	0.1127	0.1169	0.1161	0.1109
EIRP(dBm)	19.84	19.84	19.69	19.91	19.87	19.72	19.88	19.85	19.65
EIRP(Watts)	0.0964	0.0964	0.0931	0.0979	0.0971	0.0938	0.0973	0.0966	0.0923



LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	23.03	22.98	22.87	22.43	22.56	22.63	23.10	23.03	22.97
Conducted Power (Watts)	0.2009	0.1986	0.1936	0.1750	0.1803	0.1832	0.2042	0.2009	0.1982
ERP(dBm)	18.58	18.53	18.42	17.98	18.11	18.18	18.65	18.58	18.52
ERP(Watts)	0.0721	0.0713	0.0695	0.0628	0.0647	0.0658	0.0733	0.0721	0.0711

LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) QPSK			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	23.16	22.99	22.96
Conducted Power (Watts)	0.2070	0.1991	0.1977
ERP(dBm)	18.71	18.54	18.51
ERP(Watts)	0.0743	0.0714	0.0710



LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	22.24	22.20	22.13	21.71	21.85	21.86	22.31	22.25	22.25
Conducted Power (Watts)	0.1675	0.1660	0.1633	0.1483	0.1531	0.1535	0.1702	0.1679	0.1679
ERP(dBm)	17.79	17.75	17.68	17.26	17.40	17.41	17.86	17.80	17.80
ERP(Watts)	0.0601	0.0596	0.0586	0.0532	0.0550	0.0551	0.0611	0.0603	0.0603

LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) 16QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	22.27	22.23	22.18
Conducted Power (Watts)	0.1687	0.1671	0.1652
ERP(dBm)	17.82	17.78	17.73
ERP(Watts)	0.0605	0.0600	0.0593



LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	20.90	20.87	20.82	20.87	20.76	20.73	21.02	20.95	20.98
Conducted Power (Watts)	0.1230	0.1222	0.1208	0.1222	0.1191	0.1183	0.1265	0.1245	0.1253
ERP(dBm)	16.45	16.42	16.37	16.42	16.31	16.28	16.57	16.50	16.53
ERP(Watts)	0.0442	0.0439	0.0434	0.0439	0.0428	0.0425	0.0454	0.0447	0.0450

LTE Band 5 ( $G_T - L_C = -2.30 \text{ dB}$ ) 64QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	20.91	20.86	20.86
Conducted Power (Watts)	0.1233	0.1219	0.1219
ERP(dBm)	16.46	16.41	16.41
ERP(Watts)	0.0443	0.0438	0.0438



LTE Band 7 ( $G_T - L_C = -0.60\text{dB}$ ) QPSK				
Bandwidth	5M			
Channel	20775 (Low)	21100 (Mid)	21425 (High)	
	2502.5	2535	2567.5	
Conducted Power (dBm)	23.30	23.13	23.35	
Conducted Power (Watts)	0.2138	0.2056	0.2163	
EIRP(dBm)	22.70	22.53	22.75	
EIRP(Watts)	0.1862	0.1791	0.1884	

LTE Band 7 ( $G_T - L_C = -0.60 \text{ dB}$ ) QPSK									
Bandwidth	10M			15M			20M		
Channel	20800 (Low)	21100 (Mid)	21400 (High)	20825 (Low)	21100 (Mid)	21375 (High)	20850 (Low)	21100 (Mid)	21350 (Mid)
	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Frequency (MHz)	23.35	23.11	23.26	23.31	23.12	23.27	23.36	23.23	23.13
Conducted Power (dBm)	23.35	23.11	23.26	23.31	23.12	23.27	23.36	23.23	23.13
Conducted Power (Watts)	0.2163	0.2046	0.2118	0.2143	0.2051	0.2123	0.2168	0.2104	0.2056
EIRP(dBm)	22.75	22.51	22.66	22.71	22.52	22.67	22.76	22.63	22.53
EIRP(Watts)	0.1884	0.1782	0.1845	0.1866	0.1786	0.1849	0.1888	0.1832	0.1791



LTE Band 7 ( $G_T - L_C = -0.60\text{dB}$ ) 16QAM			
Bandwidth	5M		
Channel	20775 (Low)	21100 (Mid)	21425 (High)
	2502.5	2535	2567.5
Frequency (MHz)	22.44	22.32	22.49
Conducted Power (dBm)	0.1754	0.1706	0.1774
EIRP(dBm)	21.84	21.72	21.89
EIRP(Watts)	0.1528	0.1486	0.1545

LTE Band 7 ( $G_T - L_C = -0.60\text{dB}$ ) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20800 (Low)	21100 (Mid)	21400 (High)	20825 (Low)	21100 (Mid)	21375 (High)	20850 (Low)	21100 (Mid)	21350 (Mid)
	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Frequency (MHz)	22.49	22.18	22.36	22.44	22.30	22.45	22.42	22.31	22.50
Conducted Power (dBm)	0.1774	0.1652	0.1722	0.1754	0.1698	0.1758	0.1746	0.1702	0.1778
EIRP(dBm)	21.89	21.58	21.76	21.84	21.70	21.85	21.82	21.71	21.90
EIRP(Watts)	0.1545	0.1439	0.1500	0.1528	0.1479	0.1531	0.1521	0.1483	0.1549



LTE Band 7 ( $G_T - L_C = -0.60 \text{ dB}$ ) 64QAM					
Bandwidth	5M				
Channel	20775		21100		21425
	(Low)		(Mid)		(High)
Frequency (MHz)	2502.5		2535		2567.5
	20.94		21.03		21.17
Conducted Power (dBm)	0.1242		0.1268		0.1309
EIRP(dBm)	20.34		20.43		20.57
EIRP(Watts)	0.1081		0.1104		0.1140

LTE Band 7 ( $G_T - L_C = -0.60 \text{ dB}$ ) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
	20.89	20.86	21.07	20.98	20.97	21.24	20.98	20.97	21.17
Conducted Power (dBm)	0.1227	0.1219	0.1279	0.1253	0.1250	0.1330	0.1253	0.1250	0.1309
EIRP(dBm)	20.29	20.26	20.47	20.38	20.37	20.64	20.38	20.37	20.57
EIRP(Watts)	0.1069	0.1062	0.1114	0.1091	0.1089	0.1159	0.1091	0.1089	0.1140



## Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz					
Mod.	QPSK		16QAM		Limit: 13dB	
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	3.25	4.78	4.41	5.83	PASS	
Middle CH	5.36	5.01	6.26	5.97		
Highest CH	3.83	4.99	4.72	5.88		
Mod.	64QAM		Limit: 13dB			
RB Size	1RB	Full RB	Result			
Lowest CH	4.12	5.74	PASS			
Middle CH	5.51	5.97				
Highest CH	4.75	5.88				

Mode	LTE Band 4 / 20MHz					
Mod.	QPSK		16QAM		Limit: 13dB	
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	4.46	5.16	5.80	6.00	PASS	
Middle CH	4.84	5.22	5.68	6.12		
Highest CH	5.04	5.13	5.91	6.06		
Mod.	64QAM		Limit: 13dB			
RB Size	1RB	Full RB	Result			
Lowest CH	5.39	6.03	PASS			
Middle CH	5.39	6.17				
Highest CH	6.58	6.17				




Mode	LTE Band 5 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.93	5.19	5.77	6.03	PASS
Middle CH	4.87	5.1	5.74	5.97	
Highest CH	4.26	4.99	5.1	5.88	
Mod.	64QAM		Limit: 13dB		PASS
RB Size	1RB	Full RB	Result		
Lowest CH	5.62	6.23	PASS		
Middle CH	6.17	6.09			
Highest CH	5.28	6.03			

Mode	LTE Band 7 / 20MHz					
Mod.	QPSK		16QAM		Limit: 13dB	
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	3.8	4.96	4.78	5.88	PASS	
Middle CH	4.64	4.87	5.65	5.74		
Highest CH	4.84	4.96	5.94	5.86		
Mod.	64QAM		Limit: 13dB		PASS	
RB Size	1RB	Full RB	Result			
Lowest CH	4.41	5.88	PASS			
Middle CH	5.42	5.77				
Highest CH	5.22	5.91				



## LTE Band 2 / 20MHz / QPSK


## Lowest Channel / 1RB




## Lowest Channel / Full RB



## Middle Channel / 1RB




## Middle Channel / Full RB





## Highest Channel / 1RB





## Highest Channel / Full RB


































## 26dB Bandwidth

Mode	LTE Band 2 : 26dB BW(MHz)													
	BW		1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.267	1.267	2.949	2.949	5.185	4.945	9.85	10.13	14.416	14.565	20.3	20.3		
Middle CH	1.278	1.278	2.937	2.961	5.125	4.945	9.89	9.75	14.386	14.655	20.22	20.22		
Highest CH	1.278	1.273	2.949	2.943	5.065	5.015	10.01	9.87	14.685	14.535	20.34	20.38		
BW	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz								
Mod.	64QAM	64QAM	64QAM	64QAM	64QAM	64QAM								
Lowest CH	1.306	2.919	5.015	9.77	14.146	20.22								
Middle CH	1.250	2.967	5.065	10.03	14.326	20.22								
Highest CH	1.312	2.931	4.955	10.11	14.715	20.38								

Mode	LTE Band 4 : 26dB BW(MHz)													
	BW		1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.284	1.295	2.943	2.961	5.055	4.905	9.83	9.67	14.625	14.625	20.3	20.38		
Middle CH	1.248	1.25	2.949	2.937	5.105	4.935	10.09	10.01	14.176	14.416	20.38	20.3		
Highest CH	1.273	1.273	2.961	2.973	5.065	5.065	9.73	9.75	14.685	14.386	20.34	20.3		
BW	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz								
Mod.	64QAM	64QAM	64QAM	64QAM	64QAM	64QAM								
Lowest CH	1.29	2.967	4.965	10.01	14.625	20.1								
Middle CH	1.281	2.967	5.005	9.67	14.505	20.18								
Highest CH	1.315	2.949	5.035	10.11	15.015	20.38								



Mode	LTE Band 5 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.242	1.278	2.949	2.967	5.095	5.005	10.11	10.03	-	-	-	-
Middle CH	1.267	1.245	2.913	2.961	4.915	5.015	10.03	9.91	-	-	-	-
Highest CH	1.262	1.256	2.955	2.925	5.105	5.085	9.81	9.91	-	-	-	-
BW	1.4MHz	3MHz	5MHz	10MHz								
Mod.	64QAM	64QAM	64QAM	64QAM								
Lowest CH	1.264	2.967	5.055	9.75								
Middle CH	1.262	2.949	5.025	9.91								
Highest CH	1.264	2.979	4.995	9.99								

Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.025	5.015	10.03	10.33	15.015	14.625	20.34	20.26
Middle CH	-	-	-	-	5.075	5.015	9.83	9.99	14.326	14.865	20.1	20.06
Highest CH	-	-	-	-	5.065	5.005	10.13	9.67	14.805	14.505	20.18	20.1
Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	<th>64QAM</th> <td><th>64QAM</th><td><th>64QAM</th><td><th>64QAM</th><td><th>64QAM</th><td></td></td></td></td></td>	64QAM	<th>64QAM</th> <td><th>64QAM</th><td><th>64QAM</th><td><th>64QAM</th><td></td></td></td></td>	64QAM	<th>64QAM</th> <td><th>64QAM</th><td><th>64QAM</th><td></td></td></td>	64QAM	<th>64QAM</th> <td><th>64QAM</th><td></td></td>	64QAM	<th>64QAM</th> <td></td>	64QAM	
Lowest CH	-		-		5.105		9.67		14.745		20.26	
Middle CH	-		-		4.955		9.89		14.595		20.02	
Highest CH	-		-		4.945		9.93		14.595		20.38	

