



FCC PART 15.247

TEST REPORT

For

Eurosun International Limited

3F, Bldg F1, F518 Idea Land, Baoyuan Road ,Xixiang Avenue,Bao An District, ShenZhen,
China

FCC ID: 2AJ33-5B309BT1

Report Type: Original Report	Product Name: Bluetooth speaker
Test Engineer: <u>Tom Tang</u>	<i>Tom Tang</i>
Report Number: <u>RDG170426801</u>	
Report Date: <u>2017-05-10</u>	
Reviewed By: <u>Henry Ding</u> EMC Leader	<i>Henry Ding</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER SETUP	11
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS	12
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	21
APPLICABLE STANDARD	21
TEST EQUIPMENT LIST AND DETAILS	21
TEST PROCEDURE	21
TEST DATA	21
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS	27
TEST DATA	27

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS	33
TEST DATA	33
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS	37
TEST DATA	37
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS	53
TEST DATA	53
FCC §15.247(d) - BAND EDGES TESTING	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS	59
TEST DATA	60

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Eurosun International Limited**'s product, model number: **5B309BT1** (**FCC ID: 2AJ33-5B309BT1**) (the "EUT") in this report was a **Bluetooth speaker**, which was measured approximately: 5.5 cm (L) x 5.5 cm (W) x 5.9 cm (H), rated input voltage: DC3.7V from lithium battery or DC5V from USB port.

**All measurement and test data in this report was gathered from final production sample, serial number: 170426801 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-04-26, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Eurosun International Limited** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s)/grant(s).

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The Bay Area Compliance Laboratories Corp. Chengdu's measurement Uncertainties (calculated for a k=2 Coverage Factor corresponding to approximately 95% Coverage) were as follows:

- For all of the AC Line Conducted Emissions Tests reported herein: ± 3.17 dB.
- For of all of the Direct Antenna Conducted Emissions Tests reported herein: ± 0.56 dB.
- For of all of the direct Radiated Emissions Tests reported herein are:
 - 30 MHz to 200 MHz: ± 4.7 dB;
 - 200 MHz to 1 GHz: ± 6.0 dB;
 - 1 GHz to 6 GHz: ± 5.13 dB; and,
 - 6 GHz to 40 GHz: ± 5.47 dB.

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The software "RDA ToolKit 8.03.02" was used during testing, which was provided by the manufacturer. The software configured maximum output power as below setting:

Test Software Version	RDA ToolKit 8.03.02		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	2	2	2
$\pi/4$ -DQPSK	2	2	2
8PSK	2	2	2

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HuaJin	AC Adapter	HJ-0501000E1	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	0.8	USB Port of Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum tune-up power including tolerance is 2.0 dBm (1.58mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.58/5 \cdot (\sqrt{2.480}) = 0.5 < 3.0$

So the SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for buletooth and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the Main LISN with AC 120 V/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
Unknown	Conducted Cable	Unknown	NO.5	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data


Environmental Conditions

Temperature:	21.5 °C
Relative Humidity:	59 %
ATM Pressure:	96.2 kPa

The testing was performed by Tom Tang on 2017-05-05.

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.387896	38.0	9.000	L1	19.6	20.1	58.1	Compliance
0.415134	31.2	9.000	L1	19.6	26.3	57.5	Compliance
0.435505	32.1	9.000	L1	19.6	25.0	57.1	Compliance
0.720179	34.1	9.000	L1	19.6	21.9	56.0	Compliance
0.821586	34.4	9.000	L1	19.6	21.6	56.0	Compliance
1.832861	34.7	9.000	L1	19.7	21.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.432041	33.6	9.000	L1	19.6	13.6	47.2	Compliance
0.831485	31.8	9.000	L1	19.6	14.2	46.0	Compliance
0.851641	31.0	9.000	L1	19.6	15.0	46.0	Compliance
0.875775	33.2	9.000	L1	19.6	12.8	46.0	Compliance
0.897005	30.5	9.000	L1	19.6	15.5	46.0	Compliance
2.563075	22.2	9.000	L1	19.7	23.8	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.349654	34.2	9.000	N	19.7	24.7	59.0	Compliance
0.428606	40.6	9.000	N	19.7	16.7	57.3	Compliance
0.433770	32.2	9.000	N	19.7	25.0	57.2	Compliance
0.737637	29.0	9.000	N	19.7	27.0	56.0	Compliance
1.369520	30.9	9.000	N	19.7	25.1	56.0	Compliance
1.698983	25.0	9.000	N	19.7	31.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.428606	27.9	9.000	N	19.7	19.4	47.3	Compliance
0.433770	28.6	9.000	N	19.7	18.6	47.2	Compliance
0.815053	21.6	9.000	N	19.7	24.4	46.0	Compliance
0.858468	22.7	9.000	N	19.7	23.3	46.0	Compliance
0.879278	27.8	9.000	N	19.7	18.2	46.0	Compliance
0.900593	25.9	9.000	N	19.7	20.1	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2016-11-10	2017-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2016-11-10	2017-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2016-11-10	2017-11-09

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	54 %
ATM Pressure:	96.8 kPa

** The testing was performed by Tom Tang on 2017-05-06.*

Test Mode: Transmitting

30MHz to 25 GHz:

BDR Mode (GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	65.33	PK	H	23.53	3.00	0.00	91.86	N/A	N/A
2402	54.07	AV	H	23.53	3.00	0.00	80.60	N/A	N/A
2402	62.34	PK	V	23.53	3.00	0.00	88.87	N/A	N/A
2402	53.39	AV	V	23.53	3.00	0.00	79.92	N/A	N/A
2390	37.72	PK	H	23.57	3.00	0.00	64.29	74.00	9.71
2390	23.8	AV	H	23.57	3.00	0.00	50.37	54.00	3.63
4804	49.41	PK	H	30.77	5.12	26.87	58.43	74.00	15.57
4804	31.7	AV	H	30.77	5.12	26.87	40.72	54.00	13.28
7206	39.15	PK	H	34.71	6.16	26.35	53.67	74.00	20.33
7206	21.67	AV	H	34.71	6.16	26.35	36.19	54.00	17.81
1410	43.77	PK	H	23.87	2.55	26.42	43.77	74.00	30.23
1410	28.92	AV	H	23.87	2.55	26.42	28.92	54.00	25.08
105.53	49.4	QP	H	12.36	0.62	28.22	34.16	43.50	9.34
106.14	50.1	QP	H	12.52	0.61	28.21	35.02	43.50	8.48
Middle Channel: 2441 MHz									
2441	67.26	PK	H	23.40	3.00	0.00	93.66	N/A	N/A
2441	59.3	AV	H	23.40	3.00	0.00	85.70	N/A	N/A
2441	62.89	PK	V	23.40	3.00	0.00	89.29	N/A	N/A
2441	53.92	AV	V	23.40	3.00	0.00	80.32	N/A	N/A
4882	44.29	PK	V	31.02	5.09	26.87	53.53	74.00	20.47
4882	29.55	AV	V	31.02	5.09	26.87	38.79	54.00	15.21
7323	39	PK	V	34.95	6.22	26.40	53.77	74.00	20.23
7323	23.68	AV	V	34.95	6.22	26.40	38.45	54.00	15.55
1400	45.23	PK	V	23.84	2.53	26.43	45.17	74.00	28.83
1400	27.69	AV	V	23.84	2.53	26.43	27.63	54.00	26.37
1591	39.44	PK	V	24.25	2.74	26.42	40.01	74.00	33.99
1591	28.92	AV	V	24.25	2.74	26.42	29.49	54.00	24.51
105.53	49.67	QP	H	12.36	0.62	28.22	34.43	43.50	9.07
106.14	50.24	QP	H	12.52	0.61	28.21	35.16	43.50	8.34
High Channel: 2480 MHz									
2480	67.32	PK	H	23.27	2.99	0.00	93.58	N/A	N/A
2480	59.95	AV	H	23.27	2.99	0.00	86.21	N/A	N/A
2480	65.2	PK	V	23.27	2.99	0.00	91.46	N/A	N/A
2480	56.73	AV	V	23.27	2.99	0.00	82.99	N/A	N/A
2483.5	36.37	PK	H	23.26	2.99	0.00	62.62	74.00	11.38
2483.5	23.68	AV	H	23.26	2.99	0.00	49.93	54.00	4.07
4960	55.7	PK	H	31.27	5.05	26.88	65.14	74.00	8.86
4960	32.82	AV	H	31.27	5.05	26.88	42.26	54.00	11.74
7440	43.03	PK	H	35.18	6.27	26.45	58.03	74.00	15.97
7440	21.28	AV	H	35.18	6.27	26.45	36.28	54.00	17.72
1410	40.41	PK	H	23.87	2.55	26.42	40.41	74.00	33.59
1410	24.26	AV	H	23.87	2.55	26.42	24.26	54.00	29.74
105.53	50.51	QP	H	12.36	0.62	28.22	35.27	43.50	8.23
106.14	50.66	QP	H	12.52	0.61	28.21	35.58	43.50	7.92

EDR Mode ($\pi/4$ -DQPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	64.33	PK	H	23.53	3.00	0.00	90.86	N/A	N/A
2402	53.42	AV	H	23.53	3.00	0.00	79.95	N/A	N/A
2402	61.45	PK	V	23.53	3.00	0.00	87.98	N/A	N/A
2402	52.5	AV	V	23.53	3.00	0.00	79.03	N/A	N/A
2390	33.8	PK	H	23.57	3.00	0.00	60.37	74.00	13.63
2390	22.73	AV	H	23.57	3.00	0.00	49.30	54.00	4.70
4804	47.75	PK	H	30.77	5.12	26.87	56.77	74.00	17.23
4804	31.94	AV	H	30.77	5.12	26.87	40.96	54.00	13.04
7206	37.96	PK	H	34.71	6.16	26.35	52.48	74.00	21.52
7206	23.06	AV	H	34.71	6.16	26.35	37.58	54.00	16.42
1410	39.3	PK	H	23.87	2.55	26.42	39.30	74.00	34.70
1410	24.26	AV	H	23.87	2.55	26.42	24.26	54.00	29.74
105.53	50.04	QP	H	12.36	0.62	28.22	34.80	43.50	8.70
106.14	51.1	QP	H	12.52	0.61	28.21	36.02	43.50	7.48
Middle Channel: 2441 MHz									
2441	65.42	PK	H	23.40	3.00	0.00	91.82	N/A	N/A
2441	56.44	AV	H	23.40	3.00	0.00	82.84	N/A	N/A
2441	61.14	PK	V	23.40	3.00	0.00	87.54	N/A	N/A
2441	52.51	AV	V	23.40	3.00	0.00	78.91	N/A	N/A
4882	41.71	PK	H	31.02	5.09	26.87	50.95	74.00	23.05
4882	22.39	AV	H	31.02	5.09	26.87	31.63	54.00	22.37
7323	33.9	PK	H	34.95	6.22	26.40	48.67	74.00	25.33
7323	19.04	AV	H	34.95	6.22	26.40	33.81	54.00	20.19
1540	44.18	PK	H	24.16	2.70	26.37	44.67	74.00	29.33
1540	24.26	AV	H	24.16	2.70	26.37	24.75	54.00	29.25
1880	42.63	PK	H	24.71	2.96	26.70	43.60	74.00	30.40
1880	26.48	AV	H	24.71	2.96	26.70	27.45	54.00	26.55
105.53	49.57	QP	H	12.36	0.62	28.22	34.33	43.50	9.17
106.14	51.54	QP	H	12.52	0.61	28.21	36.46	43.50	7.04
High Channel: 2480 MHz									
2480	65.89	PK	H	23.27	2.99	0.00	92.15	N/A	N/A
2480	56.91	AV	H	23.27	2.99	0.00	83.17	N/A	N/A
2480	63.38	PK	V	23.27	2.99	0.00	89.64	N/A	N/A
2480	54.43	AV	V	23.27	2.99	0.00	80.69	N/A	N/A
2483.5	33.71	PK	H	23.26	2.99	0.00	59.96	74.00	14.04
2483.5	22.73	AV	H	23.26	2.99	0.00	48.98	54.00	5.02
4960	43.68	PK	H	31.27	5.05	26.88	53.12	74.00	20.88
4960	23.38	AV	H	31.27	5.05	26.88	32.82	54.00	21.18
7440	32.6	PK	H	35.18	6.27	26.45	47.60	74.00	26.40
7440	18.52	AV	H	35.18	6.27	26.45	33.52	54.00	20.48
1410	39.48	PK	H	23.87	2.55	26.42	39.48	74.00	34.52
1410	23.98	AV	H	23.87	2.55	26.42	23.98	54.00	30.02
105.53	48.77	QP	H	12.36	0.62	28.22	33.53	43.50	9.97
106.14	51.03	QP	H	12.52	0.61	28.21	35.95	43.50	7.55

EDR Mode (8-DPSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	63.1	PK	H	23.53	3.00	0.00	89.63	N/A	N/A
2402	53.59	AV	H	23.53	3.00	0.00	80.12	N/A	N/A
2402	60.87	PK	V	23.53	3.00	0.00	87.40	N/A	N/A
2402	50.41	AV	V	23.53	3.00	0.00	76.94	N/A	N/A
2390	34.69	PK	V	23.57	3.00	0.00	61.26	74.00	12.74
2390	23.38	AV	V	23.57	3.00	0.00	49.95	54.00	4.05
4804	41.67	PK	V	30.77	5.12	26.87	50.69	74.00	23.31
4804	24.8	AV	V	30.77	5.12	26.87	33.82	54.00	20.18
7206	34.78	PK	V	34.71	6.16	26.35	49.30	74.00	24.70
7206	19.04	AV	V	34.71	6.16	26.35	33.56	54.00	20.44
1396	41.16	PK	V	23.83	2.53	26.43	41.09	74.00	32.91
1396	23.98	AV	V	23.83	2.53	26.43	23.91	54.00	30.09
105.53	49.88	QP	H	12.36	0.62	28.22	34.64	43.50	8.86
106.14	51.59	QP	H	12.52	0.61	28.21	36.51	43.50	6.99
Middle Channel: 2441 MHz									
2441	65.76	PK	H	23.40	3.00	0.00	92.16	N/A	N/A
2441	56.33	AV	H	23.40	3.00	0.00	82.73	N/A	N/A
2441	60.32	PK	V	23.40	3.00	0.00	86.72	N/A	N/A
2441	50.68	AV	V	23.40	3.00	0.00	77.08	N/A	N/A
4882	41.48	PK	V	31.02	5.09	26.87	50.72	74.00	23.28
4882	23.06	AV	V	31.02	5.09	26.87	32.30	54.00	21.70
7323	24.17	PK	V	34.95	6.22	26.40	38.94	74.00	35.06
7323	20.01	AV	V	34.95	6.22	26.40	34.78	54.00	19.22
1410	40.84	PK	V	23.87	2.55	26.42	40.84	74.00	33.16
1410	24.26	AV	V	23.87	2.55	26.42	24.26	54.00	29.74
1650	38.68	PK	V	24.34	2.78	26.48	39.32	74.00	34.68
1650	23.98	AV	V	24.34	2.78	26.48	24.62	54.00	29.38
105.53	49.41	QP	H	12.36	0.62	28.22	34.17	43.50	9.33
106.14	52.03	QP	H	12.52	0.61	28.21	36.95	43.50	6.55
High Channel: 2480 MHz									
2480	66.34	PK	H	23.27	2.99	0.00	92.60	N/A	N/A
2480	56.91	AV	H	23.27	2.99	0.00	83.17	N/A	N/A
2480	63.06	PK	V	23.27	2.99	0.00	89.32	N/A	N/A
2480	53.56	AV	V	23.27	2.99	0.00	79.82	N/A	N/A
2483.5	34.52	PK	V	23.26	2.99	0.00	60.77	74.00	13.23
2483.5	22.39	AV	V	23.26	2.99	0.00	48.64	54.00	5.36
4960	42.9	PK	V	31.27	5.05	26.88	52.34	74.00	21.66
4960	23.98	AV	V	31.27	5.05	26.88	33.42	54.00	20.58
7440	33.12	PK	V	35.18	6.27	26.45	48.12	74.00	25.88
7440	18.52	AV	V	35.18	6.27	26.45	33.52	54.00	20.48
1400	38.99	PK	V	23.84	2.53	26.43	38.93	74.00	35.07
1400	24.26	AV	V	23.84	2.53	26.43	24.20	54.00	29.80
105.53	48.94	QP	H	12.36	0.62	28.22	33.70	43.50	9.80
106.14	52.47	QP	H	12.52	0.61	28.21	37.39	43.50	6.11

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/
Unkown	10dB Attenuator	10dB	10dB-1	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa

* The testing was performed by Tom Tang on 2017-05-04.


Test Result: Compliance.

Please refer to following tables and plots

Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/
Unkown	10dB Attenuator	10dB	10dB-1	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa

* The testing was performed by Tom Tang on 2017-05-04.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.83
	Middle	2441	0.84
	High	2480	0.84
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.18
	Middle	2441	1.18
	High	2480	1.19
EDR Mode (8-DPSK)	Low	2402	1.21
	Middle	2441	1.21
	High	2480	1.21


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):

Low Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/
Unkown	10dB Attenuator	10dB	10dB-1	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa

* The testing was performed by Tom Tang on 2017-05-04.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa

* The testing was performed by Tom Tang on 2017-05-09.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.388	0.124	0.4	Compliance
	Middle	0.388	0.124	0.4	Compliance
	High	0.39	0.125	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Low	1.656	0.265	0.4	Compliance
	Middle	1.68	0.269	0.4	Compliance
	High	1.668	0.267	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Low	2.93	0.313	0.4	Compliance
	Middle	2.93	0.313	0.4	Compliance
	High	2.92	0.311	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Low Channel




Date: 9.MAY.2017 08:55:23

DH1: Middle Channel




Date: 9.MAY.2017 08:55:53

DH1: High Channel




Date: 9.MAY.2017 08:56:34

DH3: Low Channel




Date: 9.MAY.2017 08:58:43

DH3: Middle Channel




Date: 9.MAY.2017 08:59:20

DH3: High Channel




Date: 9.MAY.2017 09:00:27

DH5: Low Channel




Date: 9.MAY.2017 09:03:31

DH5: Middle Channel



Date: 9.MAY.2017 09:04:28

DH5: High Channel




Date: 9.MAY.2017 09:04:58

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.394	0.126	0.4	Compliance
	Middle	0.396	0.127	0.4	Compliance
	High	0.398	0.127	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
2DH3	Low	1.674	0.268	0.4	Compliance
	Middle	1.656	0.265	0.4	Compliance
	High	1.674	0.268	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
2DH5	Low	2.93	0.313	0.4	Compliance
	Middle	2.93	0.313	0.4	Compliance
	High	2.94	0.314	0.4	Compliance
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

2DH1: Low Channel




Date: 9.MAY.2017 09:06:54

2DH1: Middle Channel




Date: 9.MAY.2017 09:07:52

2DH1: High Channel




Date: 9.MAY.2017 09:08:33

2DH3: Low Channel




Date: 9.MAY.2017 09:27:40

2DH3: Middle Channel




Date: 9.MAY.2017 09:28:26

2DH3: High Channel



Date: 9.MAY.2017 09:29:08

2DH5: Low Channel




Date: 9.MAY.2017 09:33:59

EDR Mode (8-DPSK):



Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.398	0.127	0.4	Compliance
	Middle	0.396	0.127	0.4	Compliance
	High	0.396	0.127	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
3DH3	Low	1.662	0.266	0.4	Compliance
	Middle	1.668	0.267	0.4	Compliance
	High	1.668	0.267	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
3DH5	Low	2.93	0.313	0.4	Compliance
	Middle	2.94	0.314	0.4	Compliance
	High	2.92	0.311	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

3DH1: Low Channel




Date: 9.MAY.2017 09:36:40

Page 50 of 63




3DH3: High Channel




Date: 9.MAY.2017 09:46:07

3DH5: Low Channel




Date: 9.MAY.2017 09:47:21

3DH5: Middle Channel



Date: 9.MAY.2017 09:48:26

3DH5: High Channel



Date: 9.MAY.2017 09:48:34

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/
Unkown	10dB Attenuator	10dB	10dB-1	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa

* The testing was performed by Tom Tang on 2017-05-04.


Test Result: Compliance.

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	0.34	30
	Middle	2441	-0.29	30
	High	2480	-0.03	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	0.98	30
	Middle	2441	0.47	30
	High	2480	0.6	30
EDR Mode (8-DPSK)	Low	2402	1.49	30
	Middle	2441	0.98	30
	High	2480	1.1	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):



Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):


Output Power, Low Channel



Output Power, Middle Channel




Output Power, High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/VBW=100/300kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Unkown	RF Cable	Unkown	C-2	Each Time	/
Unkown	10dB Attenuator	10dB	10dB-1	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data


Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	56 %
ATM Pressure:	95.9 kPa


* The testing was performed by Tom Tang on 2017-05-04.

Test Result: Compliance

BDR Mode (GFSK):




Band Edge, Right Side




EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side




Band Edge, Right Side




EDR Mode (8-DPSK):

Band Edge, Left Side



Band Edge, Right Side



*****END OF REPORT*****