## 4 FCC §1.1310, § 2.1091- Maximum Permissible Exposure (MPE)

## 4.1 Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: RLK1801002-00C

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### **Calculated Formulary:**

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$ 

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

FCC Part 22H+24E Page 10 of 49

# **4.2** RF Exposure Evaluation Result

### **MPE** evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		T. 1. (1		
		(dBi)	(numeric)	(dBm)	(mW)	Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm²)
GSM 850	824-849	4.07	2.553	22.5	177.8	20	0.0903	0.55
PCS 1900	1850-1910	5.44	3.499	20	100.0	20	0.0696	1
WCDMA Band V	824-849	4.07	2.553	23	199.5	20	0.1013	0.55
WCDMA Band II	1850-1910	5.44	3.499	23	199.5	20	0.1389	1
BLE	2402-2480	0.5	1.122	-1	0.794	20	0.0002	1

Report No.: RLK1801002-00C

The BLE and WCDMA Band V can transmit simultaneously:

 $=S_{BLE}/S_{limit-BLE} + S_{WCDMA\ BAND\ V}/S_{limit-WCDMA\ BAND\ V} = 0.0002/1 + 0.1013/0.55 = 0.1844 < 1.0$ 

**Result:** MPE evaluation meet 20 cm the requirement of standard.

FCC Part 22H+24E Page 11 of 49

<sup>\*</sup>Due to GSM not have GPRS and EDGE, so only one Averaging Time and the power calculate as below GSM 850: 31.5 - 9 = 22.5 (dBm) and PCS 1900 = 29 - 9 = 20 (dBm)