



**Intertek Testing Services Shenzhen Ltd.  
Guangzhou Branch**

Job No.: 160921039GZU

Page: 1 of 1

FCC ID: 2AJV9-Topmost668

## RF Exposure Compliance Requirement

The product belongs to **standalone portable device** base the FCC rule part 2.1091&2.1093. The transmission frequencies of the device are between 100 MHz and 6 GHz. The worst case test separation distance is **5mm**.

The Max Conducted Output Power and SAR Test Exclusion Threshold (mW) are listed below:

Transmit frequency (GHz)	Max Conducted Output Power (mW)	SAR Test Exclusion Threshold (mW)
2.402	1.40	9.7
2.441	1.09	9.6
2.480	0.86	9.5

The SAR Test Exclusion Threshold is calculated from:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

According to SAR Exclusion Threshold in KDB 447498 (D01) General RF Exposure Guidance v05, the SAR report is not required.