

8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm ²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

1. Manufacturer declared that the maximum antenna gain is 16.0dBi(Max.) for 5180~5240 & 5745~5825MHz.
2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
3. Only record worst case data.

8.2 Test Results

Standalone MPE

5G wifi:

Test	Mode	Channel	ANT Power (dBm)	ANT Max. Tune Up Power (dBm)	ANT Max. Tune Up Power (mW)	ANT MPE (mW/cm2)	Limit (mW/cm2)
IEEE 802.11a	Chain 0	36	15.13	15.0±1.0	39.8107	0.3154	1.0
		44	15.22	15.0±1.0	39.8107	0.3154	1.0
		48	15.47	15.0±1.0	39.8107	0.3154	1.0
		149	14.68	15.0±1.0	39.8107	0.3154	1.0
		157	14.53	15.0±1.0	39.8107	0.3154	1.0
		165	14.89	15.0±1.0	39.8107	0.3154	1.0
	Chain 1	36	15.37	15.0±1.0	39.8107	0.3154	1.0
		44	15.23	15.0±1.0	39.8107	0.3154	1.0
		48	15.77	15.0±1.0	39.8107	0.3154	1.0
		149	15.03	15.0±1.0	39.8107	0.3154	1.0
		157	15.26	15.0±1.0	39.8107	0.3154	1.0
		165	15.41	15.0±1.0	39.8107	0.3154	1.0
IEEE 802.11n-HT20	Chain 0	36	14.49	14.0±1.0	31.6228	0.2506	1.0
		44	14.75	14.0±1.0	31.6228	0.2506	1.0
		48	14.63	14.0±1.0	31.6228	0.2506	1.0
		149	14.73	14.0±1.0	31.6228	0.2506	1.0
		157	14.55	14.0±1.0	31.6228	0.2506	1.0
		165	14.36	14.0±1.0	31.6228	0.2506	1.0
	Chain 1	36	14.79	14.0±1.0	31.6228	0.2506	1.0
		44	14.56	14.0±1.0	31.6228	0.2506	1.0
		48	14.69	14.0±1.0	31.6228	0.2506	1.0
		149	14.13	14.0±1.0	31.6228	0.2506	1.0
		157	14.25	14.0±1.0	31.6228	0.2506	1.0
		165	14.09	14.0±1.0	31.6228	0.2506	1.0
IEEE 802.11n-HT40	Chain 0	38	13.62	14.0±1.0	31.6228	0.2506	1.0
		46	14.03	14.0±1.0	31.6228	0.2506	1.0
		151	13.48	13.0±1.0	25.1189	0.1990	1.0
		159	12.27	13.0±1.0	25.1189	0.1990	1.0
	Chain 1	38	13.45	14.0±1.0	31.6228	0.2506	1.0
		46	14.55	14.0±1.0	31.6228	0.2506	1.0
		151	13.78	13.0±1.0	25.1189	0.1990	1.0
		159	12.38	13.0±1.0	25.1189	0.1990	1.0

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

Mode	Channel No.	Frequency (MHz)	Σ MPE ratios	Limit	Results
Chain 0+Chain 1					
IEEE 802.11a	36	5180	N/A	1.000	Pass
	44	5220	N/A	1.000	Pass
	48	5240	N/A	1.000	Pass
	149	5745	N/A	1.000	Pass
	157	5785	N/A	1.000	Pass
	165	5825	N/A	1.000	Pass
IEEE 802.11n-HT20	36	5180	0.5021	1.000	Pass
	44	5220	0.5021	1.000	Pass
	48	5240	0.5021	1.000	Pass
	149	5745	0.5021	1.000	Pass
	157	5785	0.5021	1.000	Pass
	165	5825	0.5021	1.000	Pass
IEEE 802.11n-HT40	38	5190	0.5021	1.000	Pass
	46	5230	0.5021	1.000	Pass
	151	5755	0.3980	1.000	Pass
	159	5795	0.3980	1.000	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.