FCC ID: 2AJ7E-HLD503-Z

Maximum Permissible Exposure (MPE)
According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f^2	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f^2	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30*P*G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30*P*G}{377*D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

MAX OUTPUT POWER

ZIGBEE:

Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict
1Mbps					
00	2405	Default	-3.38	30	PASS
08	2440	Default	-4.09	30	PASS
16	2480	Default	-5.51	30	PASS

Measurement Result

Operation Frequency: Zigbee: 2402MHz~2480MHz
Power density limited: 1mW/ cm^2
Antenna Type: PCB Antenna
Antenna gain: 3dBi,
R=20cm
Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Antenna Gain (dBi)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density (mW/cm2)
2405	GFSK	-3.38	-4±1	-3	0.501	3.00	2.00	0.00020	1
2440	GFSK	-4.09	-4±1	-3	0.501	3.00	2.00	0.00020	1
2480		-5.51	-5±1	-4	0.398	3.00	2.00	0.00016	1

Conclusion:
For the max result : 0.00020≤ 1.0 for Max Power Density, No SAR is required.

Signature:

Date: 2016-12-13

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.