

<b>Prüfbericht-Nr.:</b> Test Report No.:	<b>50073671 001</b>	<b>Auftrags-Nr.:</b> Order No.:	<b>114058593</b>	<b>Seite 1 von 58</b> Page 1 of 58
<b>Kunden-Referenz-Nr.:</b> Client Reference No.:	<b>N/A</b>	<b>Auftragsdatum:</b> Order date:	<b>17-Nov-2016</b>	
<b>Auftraggeber:</b> Client:	<b>Molekule, Inc., 2507 Bryant St, San Francisco, CA 94110</b>			
<b>Prüfgegenstand:</b> Test item:	<b>Molekule Home One Air Purifier</b>			
<b>Bezeichnung / Typ-Nr.:</b> Identification / Type No.:	<b>MH1-AAA</b>			
<b>Auftrags-Inhalt:</b> Order content:	<b>FCC Part 15C / IC RSS-247 Test report (WiFi 2.4GHz)</b>			
<b>Prüfgrundlage:</b> Test specification:	<b>FCC 47CFR Part 15: Subpart C Section 15.247 RSS-247 issue 2 Feb. 2017</b>			
<b>Wareneingangsdatum:</b> Date of receipt:	<b>7-Feb-2017</b>			
<b>Prüfmuster-Nr.:</b> Test sample No.:	<b>A000493326-005 A000493326-001</b>			
<b>Prüfzeitraum:</b> Testing period:	<b>10-Feb-2017 – 06-Mar-2017</b>			
<b>Ort der Prüfung:</b> Place of testing:	<b>EMC Laboratory Taipei</b>			
<b>Prüflaboratorium:</b> Testing laboratory:	<b>TUV Rheinland Taiwan Ltd.</b>			
<b>Prüfergebnis*:</b> Test result*:	<b>Pass</b>			
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>		
<b>2017-03-06</b> <b>Amy S.R.Hsu /Engineer</b> <b>Datum</b> <b>Name / Stellung</b> <b>Date</b> <b>Name / Position</b>		<b>2017-03-06</b> <b>Rene Charton/Senior Project Manager</b> <b>Datum</b> <b>Name / Stellung</b> <b>Date</b> <b>Name / Position</b>		
 <b>Unterschrift</b> <b>Signature</b>		 <b>Unterschrift</b> <b>Signature</b>		
<b>Sonstiges / Other:</b>				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> Condition of the test item at delivery:		<b>Prüfmuster vollständig und unbeschädigt</b> Test item complete and undamaged		
* Legende:   1 = sehr gut   2 = gut   3 = befriedigend   4 = ausreichend   5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n)   F(ail) = entspricht nicht o.g. Prüfgrundlage(n)   N/A = nicht anwendbar   N/T = nicht getestet Legend:   1 = very good   2 = good   3 = satisfactory   4 = sufficient   5 = poor P(ass) = passed a.m. test specification(s)   F(ail) = failed a.m. test specification(s)   N/A = not applicable   N/T = not tested				
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <b>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</b>				

## TEST SUMMARY

### **5.1.1 ANTENNA REQUIREMENT**

*RESULT: Passed*

### **5.1.2 PEAK OUTPUT POWER**

*RESULT: Passed*

### **5.1.3 6dB BANDWIDTH AND 99% BANDWIDTH**

*RESULT: Passed*

### **5.1.4 POWER DENSITY**

*RESULT: Passed*

### **5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100kHz BANDWIDTH**

*RESULT: Passed*

### **5.1.6 SPURIOUS EMISSION**

*RESULT: Passed*

### **5.2.1 MAINS CONDUCTED EMISSIONS**

*RESULT: Passed*

### **6.1.1 ELECTROMAGNETIC FIELDS**

*RESULT: Passed*

## Contents

<b>1.</b>	<b>GENERAL REMARKS .....</b>	<b>5</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS.....</b>	<b>5</b>
<b>2.</b>	<b>TEST SITES .....</b>	<b>6</b>
<b>2.1</b>	<b>TEST LABORATORY .....</b>	<b>6</b>
<b>2.2</b>	<b>TEST FACILITIES .....</b>	<b>6</b>
<b>2.3</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>7</b>
<b>2.4</b>	<b>TRACEABILITY .....</b>	<b>8</b>
<b>2.5</b>	<b>CALIBRATION .....</b>	<b>8</b>
<b>2.6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>3.</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>9</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE .....</b>	<b>9</b>
<b>3.2</b>	<b>SYSTEM DETAILS AND RATINGS.....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES.....</b>	<b>10</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>10</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>10</b>
<b>4.</b>	<b>TEST SET-UP AND OPERATION MODES.....</b>	<b>11</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>11</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>11</b>
<b>4.3</b>	<b>CIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>12</b>
<b>5.</b>	<b>TEST RESULTS .....</b>	<b>15</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>15</b>
5.1.1	<i>Antenna Requirement .....</i>	<i>15</i>
5.1.2	<i>Peak Output Power .....</i>	<i>16</i>
5.1.3	<i>6dB Bandwidth and 99% Bandwidth.....</i>	<i>18</i>
5.1.4	<i>Power Density .....</i>	<i>33</i>
5.1.5	<i>Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....</i>	<i>41</i>
5.1.6	<i>Spurious Emission .....</i>	<i>51</i>
<b>5.2</b>	<b>MAINS EMISSIONS.....</b>	<b>52</b>
5.2.1	<i>Mains Conducted Emissions.....</i>	<i>52</i>
<b>6.</b>	<b>SAFETY HUMAN EXPOSURE .....</b>	<b>53</b>

**Prüfbericht - Nr.: 50073671 001**  
*Test Report No.***Seite 4 von 58**  
*Page 4 of 58*

<b>6.1</b>	<b>RADIO FREQUENCY EXPOSURE COMPLIANCE .....</b>	<b>53</b>
6.1.1	<i>Electromagnetic Fields.....</i>	<i>53</i>
<b>7.</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>54</b>
<b>8.</b>	<b>LIST OF TABLES .....</b>	<b>58</b>
<b>9.</b>	<b>LIST OF PHOTOGRAPHS.....</b>	<b>58</b>

## 1. General Remarks

### 1.1 Complementary Materials

The following attachments are integral parts of this test report:

**Appendix P: Photo Documentation**  
(File Name: 50073671APPENDIX P)

**Appendix D: Test Result of Radiated Emissions**  
(File Name: 50073671APPENDIX D)

Test Specifications

The following standards were applied (in bold: product standards, otherwise: basic standards).

**Table 1: Applied Standard and Test Levels**

<b>Radio</b>
FCC CFR47 Part 15: Subpart C Section 15.247 RSS-247 issue 2 Feb. 2017 RSS-Gen, Issue 4, November 2014 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r05

## 2. Test Sites

### 2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.  
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,  
Taichung City 428  
Taiwan (R.O.C.)

### 2.2 Test Facilities

TUV Rheinland Taiwan Ltd.  
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

FCC RegistrationNo.: 365730  
IC Canada Registration No.: 9465A-1  
TAF Accredited NCC Test Lab. No.:0759  
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



**Testing Laboratory**  
**0759**

## 2.3 List of Test and Measurement Instruments

**Table 2: List of Test and Measurement Equipment**

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR7	101062	2016/09/12	2017/09/12
Spectrum Analyzer	R&S	FSV 40	100921	2016/04/21	2017/04/21
Spectrum Analyzer	Agilent	N9010A	MY53470241	2016/04/25	2017/04/24
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2016/07/29	2017/07/29
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2016/12/01	2017/12/01
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	060558	2016/11/17	2017/11/17
Bilog Antenna	TESEQ	CBL6111D	29804	2016/06/23	2017/06/23
Horn Antenna	ETS-Lindgren	3117	138160	2016/05/03	2017/05/03
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101029	2016/10/11	2017/10/11
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2016/05/11	2017/05/11
Spectrum Analyzer	R&S	FSL3	101943	2015/09/07	2017/09/07
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	2015/07/13	2017/07/12
LISN (1 phase)	R&S	ENV216	101243	2016/06/02	2017/06/02
LISN	R&S	ENV216	101262	2016/06/16	2017/06/16
Test Software	Audix	e3	Ver. 9	N/A	N/A

## 2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.5 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are  $\pm 3\text{dB}$ .

**Table 3: Emission Measurement Uncertainty**

Parameter	Uncertainty
RF power, conducted	$\pm 1.5 \text{ dB}$
Adjacent channel power	$\pm 3 \text{ dB}$
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6 \text{ dB}$
Radiated emission of receiver, valid up to 26 GHz	$\pm 6 \text{ dB}$
Temperature	$\pm 2 \text{ }^{\circ}\text{C}$
Humidity	$\pm 10 \text{ } \%$



## 3. General Product Information

### 3.1 Product Function and Intended Use

The EUT is a Air Purifier. It contains a Bluetooth/ WLAN 802.11b/g/n compatible module enabling the user to communicate data through a Wireless interface.  
For details refer to the User Guide, Data Sheet and Circuit Diagram.

### 3.2 System Details and Ratings

**Table 4: Basic Information of EUT**

Item	EUT information
Kind of Equipment	Molekule Home One Air Purifier
Type Designation	MH1-AAA
FCC ID	2AJ7M-MH1

**Table 5: Technical Specification of EUT**

Technical Specification	Value
Operating Frequencies	2412 MHz ~ 2462 MHz
Channel Spacing	5 MHz
Channel number	802.11b/g/n :11 (2412 MHz ~ 2462 MHz)
Operation Voltage	AC 120V
Modulation	802.11b: DSSS ; 802.11g/n: OFDM
Antenna gain	5.8 dBi

### 3.3 Independent Operation Modes

Basic operation modes are:

- A. Transmitting
  - 1. Low channel
  - 2. Middle channel
  - 3. High channel
- B. Receiving
- C. Standby
- D. Off

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

### 3.5 Submitted Documents

- |                         |                      |
|-------------------------|----------------------|
| - Bill of Material      | - Circuit Diagram    |
| - PCB Layout            | - Instruction Manual |
| - Photo Document        | - Rating Label       |
| - Technical Description |                      |

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:

Conducted: **A000493326-001**

Radiation: **A000493326-005**

Full test was applied on all test modes, but only worst case was shown

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

### 4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

### 4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.


### 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test




Note: Measurements above 1 GHz are done with a table height of 1.5m.


### Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



### Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



**Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement (Power meter)**



## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Passed**

Test standard	:	LP0002(2016): 3.10.1,(4) FCC Part 15.247(b)(4), Part 15.203 and RSS- Gen 8.3
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 5.8 dBi .The antenna is a Monopole Antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

**Prüfbericht - Nr.: 50073671 001**

Test Report No.

**Seite 16 von 58**

Page 16 of 58

### 5.1.2 Peak Output Power

**RESULT:****Passed**

Test standard	:	LP0002(2016): 3.10.1,(6.2.A) FCC Part 15.247(b)(3), RSS-247 5.4(4)
Basic standard	:	ANSI C63.10:2009, KDB558074
Limit	:	1 Watt
Kind of test site	:	Shielded room

**Test setup**

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa



**Table 6: Test result of Peak Output Power (802.11b)**

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	13.14	0.02061	1
Middle Channel	2437	13.95	0.02483	1
High Channel	2462	13.06	0.02023	1

**Table 7: Test result of Peak Output Power (802.11g)**

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	12.39	0.01734	1
Middle Channel	2437	11.71	0.01483	1
High Channel	2462	12.32	0.01706	1

**Table 8: Test result of Peak Output Power (802.11n HT20)**

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	12.39	0.01734	1
Middle Channel	2437	11.37	0.01371	1
High Channel	2462	12.31	0.01702	1

### 5.1.3 6dB Bandwidth and 99% Bandwidth

**RESULT:****Passed**

Test standard	:	FCC Part 15.247(a)(2), RSS-247 5.2(1)
Basic standard	:	ANSI C63.10:2009, KDB558074
Kind of test site	:	Shielded room

**Test setup**

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

**Table 9: Test result of 6dB Bandwidth (802.11b)**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	8.596	0.5	Pass
Mid Channel	2437	9.040	0.5	Pass
High Channel	2462	9.060	0.5	Pass

**Table 10: Test result of 6dB Bandwidth (802.11g)**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	15.41	0.5	Pass
Mid Channel	2437	15.71	0.5	Pass
High Channel	2462	15.47	0.5	Pass

**Table 11: Test result of 6dB Bandwidth (802.11n HT20)**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	15.41	0.5	Pass
Mid Channel	2437	16.37	0.5	Pass
High Channel	2462	15.70	0.5	Pass

**Table 12: Test result of 99% Bandwidth (802.11b)**

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	14.053
Mid Channel	2437	14.064
High Channel	2462	13.993

**Table 13: Test result of 99% Bandwidth (802.11g)**


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	16.422
Mid Channel	2437	16.408
High Channel	2462	16.439

**Table 14: Test result of 99% Bandwidth (802.11n HT20)**


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	17.555
Mid Channel	2437	17.557
High Channel	2462	17.568


## Test Plot of 6dB Bandwidth (802.11b)

### Low Channel




### Middle Channel




**High Channel**



## Test Plot of 6dB Bandwidth (802.11g)

### Low Channel



### Middle Channel




**High Channel**






## Test Plot of 6dB Bandwidth (802.11n HT20)

### Low Channel




### Middle Channel




**High Channel**



## Test Plot of 99% Bandwidth (802.11b)

### Low Channel




### Middle Channel




**High Channel**



## Test Plot of 99% Bandwidth (802.11g)

### Low Channel




### Middle Channel




**High Channel**



## Test Plot of 99% Bandwidth (802.11n HT20)

### Low Channel



### Middle Channel



**High Channel**




### 5.1.4 Power Density

**RESULT:****Passed**

Test standard : LP0002(2016): 3.10.1,(6.2.B)  
FCC Part 15.247(e) , RSS-247 5.2(2)  
Basic standard : ANSI C63.10:2009, KDB558074  
Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
Operation Mode : A  
Ambient temperature : 22-26°C  
Relative humidity : 50-65%  
Atmospheric pressure : 100-103 kPa

**Table 15: Test result of Power Density (802.11b)**

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	2.85	8
Middle Channel	2437	2.36	8
High Channel	2462	2.79	8

**Table 16: Test result of Power Density (802.11g)**


Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-7.81	8
Middle Channel	2437	-8.72	8
High Channel	2462	-7.56	8

**Table 17: Test result of Power Density (802.11n HT20)**


Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-9.58	8
Middle Channel	2437	-8.71	8
High Channel	2462	-7.72	8


## Test Plot of Power Density (802.11b)

### Low Channel




### Middle Channel




**High Channel**



## Test Plot of Power Density (802.11g)

### Low Channel




### Middle Channel




**High Channel**


## Test Plot of Power Density (802.11n HT20)


### Low Channel



### Middle Channel



## High Channel





### 5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

**RESULT:****Passed**

Test standard	:	LP0002(2016): 3.10.1, (5) FCC part 15.247(d), RSS-247 5.5
Basic standard	:	ANSI C63.10:2009, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

**Test setup**


Test Channel	:	Low/ High
Operation mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.


Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.


## Test Plot 100kHz Conducted Emissions (802.11b)

### Low Channel




### Middle Channel







## Test Plot 100kHz Conducted Emissions (802.11g)

### Low Channel




### Middle Channel







## Test Plot 100kHz Conducted Emissions (802.11n HT20)

### Low Channel




### Middle Channel






## Test Plot 100kHz RBW of Band Edge (802.11b)

### Low Channel




### High Channel






## Test Plot 100kHz RBW of Band Edge (802.11g)

### Low Channel




### High Channel




## Test Plot 100kHz RBW of Band Edge (802.11n HT20)

### Low Channel



### High Channel



## 5.1.6 Spurious Emission

**RESULT:****Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2016): 3.10.1, (5)
Basic standard	:	ANSI C63.10: 2009
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2016): 2.7 , must comply with the radiated emission limits specified in LP0002(2016): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2016): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

**Test setup**

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The X Axis orientation is the worst-case and recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

## 5.2 Mains Emissions

### 5.2.1 Mains Conducted Emissions

**RESULT:****Passed**

Test standard	:	FCC Part 15.207 FCC Part 15.107 RSS-Gen 8.8 LP0002(2016): 2.3
Limits	:	Mains Conducted emissions as defined in above standards
Kind of test site	:	Shielded Room

**Test setup**

Test Channel	:	Middle
Operation mode	:	A

Remark: For details refer to Appendix D.

## 6. Safety Human exposure

### 6.1 Radio Frequency Exposure Compliance

#### 6.1.1 Electromagnetic Fields

**RESULT:**
**Passed**

Test standard : FCC KDB Publication 447498 D01 v06  
 RSS--102

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied

**Maximum Exposure:**

Power to Antenna (mW)	24.83 mW
Power to Antenna (dBm)	13.9 dBm
Antenna Gain	5.8 dBi
Power+Ant Gain	94.4 mW
Distance	20 cm
S=	0.019 mW/cm <sup>2</sup>

**Limit FCC:**


0.3-1.34 MHz (100) mW/cm<sup>2</sup>  
 1.34-30 MHz (180/f<sup>2</sup>) mW/cm<sup>2</sup>  
 30-300 MHz 0.2 mW/cm<sup>2</sup>  
 300-1500 MHz f/1500 mW/cm<sup>2</sup>  
**1500-100,000 MHz 1.0 mW/cm<sup>2</sup>**

**Limit Canada:**  $0.02619f^{0.6834}$


---End---

## 7. Photographs of the Test Set-Up


**Photograph 1: Set-up for Spurious Emissions (Front View)**



**Photograph 2: Set-up for Spurious Emissions (Back View 1)**




**Photograph 3: Set-up for Spurious Emissions (Back View 2)**






**Photograph 4: Set-up for Spurious Emissions (Back View 3) 9k-30M**




**Photograph 5: Set-up for Conducted testing**






**Photograph 6: Set-up for for Mains Conducted testing Back**



**Photograph 7: Set-up for for Mains Conducted testing Front**



## 8. List of Tables

Table 1: Applied Standard and Test Levels .....	5
Table 2: List of Test and Measurement Equipment .....	7
Table 3: Emission Measurement Uncertainty.....	8
Table 4: Basic Information of EUT .....	9
Table 5: Technical Specification of EUT .....	9
Table 6: Test result of Peak Output Power (802.11b) .....	17
Table 7: Test result of Peak Output Power (802.11g) .....	17
Table 8: Test result of Peak Output Power (802.11n HT20) .....	17
Table 9: Test result of 6dB Bandwidth (802.11b) .....	19
Table 10: Test result of 6dB Bandwidth (802.11g) .....	19
Table 11: Test result of 6dB Bandwidth (802.11n HT20) .....	19
Table 12: Test result of 99% Bandwidth (802.11b) .....	20
Table 13: Test result of 99% Bandwidth (802.11g) .....	20
Table 14: Test result of 99% Bandwidth (802.11n HT20) .....	20
Table 15: Test result of Power Density (802.11b) .....	34
Table 16: Test result of Power Density (802.11g) .....	34
Table 17: Test result of Power Density (802.11n HT20) .....	34

## 9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....	54
Photograph 2: Set-up for Spurious Emissions (Back View 1) .....	55
Photograph 3: Set-up for Spurious Emissions (Back View 2) .....	55
Photograph 4: Set-up for Spurious Emissions (Back View 3) 9k-30M .....	56
Photograph 5: Set-up for Conducted testing .....	56
Photograph 6: Set-up for for Mains Conducted testing Back .....	57
Photograph 7: Set-up for for Mains Conducted testing Front.....	57