# **TEST REPORT**

**Reference No.** : WTS16S0960733E

FCC ID...... : 2AJ7VMWCS-T

Applicant .....: MYE Entertainment, Inc.

Address ...... : 28460 Westinghouse Pl. Valencia, California, USA, 91355

Manufacturer ...... SHENZEN TONGDA COMMUNICATION EQUIPMENT CO., LTD.

Address ...... NO,1 BLDG.,NAN LING LONG SHA INDUSTRIAL

AREA, BUJI, SHENZHEN, CHINA

Product Name ...... CableSAT

Model No. ..... : MWCS-T

**Standards** : FCC CFR47 Part 15 Section 15.249: 2015

Date of Receipt sample.... : Sep. 14, 2016

**Date of Test**.....: Sep. 14 – Oct. 14, 2016

Date of Issue ..... : Oct. 15, 2016

Test Result ..... : Pass

#### Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

#### Prepared By:

#### Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel:+86-755-83551033 Fax:+86-755-83552400

Compiled by:

Approved by:

Philo Zhong / Manager

the zhout

Zero Zhou / Test Engineer

# 2 Contents

4	COVE	ER PAGE	Page	
1 2		FENTS		
3		GENERAL INFORMATION		
J	3.1 3.2 3.3 3.4 3.5	GENERAL DESCRIPTION OF E.U.T		
4		PMENT USED DURING TEST		
	4.1 4.2 4.3	EQUIPMENTS LIST	6	
5	TEST	SUMMARY	7	
6	CONE	DUCTED EMISSION	8	
	6.1 6.2 6.3 6.4	E.U.T. OPERATION EUT SETUP MEASUREMENT DESCRIPTION TEST RESULT	8 8	
7	RADI	ATION EMISSION TEST	11	
	7.1 7.2 7.3 7.4 7.5 7.6	EUT OPERATION TEST SETUP SPECTRUM ANALYZER SETUP TEST PROCEDURE FREQUENCY RANGE OF RADIATED MEASUREMENTS TEST RESULT		
8	PERIO	ODIC OPERATION	18	
9	BAND	D EDGE	19	
	9.1 9.2	TEST PROCEDURE TEST RESULT		
10	20 DE	BANDWIDTH MEASUREMENT	20	
	10.1 10.2	TEST PROCEDURE TEST RESULT		
11	ANTE	NNA REQUIREMENT	21	
12	PHOT	TOGRAPHS- MODEL MWCS-T TEST SETUP PHOTOS	22	
	12.1 12.2	PHOTOGRAPH – RADIATION EMISSIONPHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#		
13	PHOT	TOGRAPHS - CONSTRUCTIONAL DETAILS	26	
	13.1 13.2	MODEL MWCS-T - EXTERNAL PHOTOS		

Reference No.: WTS16S0960733E Page 3 of 40

# 3 General Information

### 3.1 General Description of E.U.T

Product Name:	CableSAT
Model No.:	MWCS-T
Model Difference:	N/A
	Note: A: for US version
Type of Modulation:	FSK
Frequency Range:	915MHz
The Lowest Oscillator:	16MHz
Antenna installation:	Integrated Antenna
Antenna Gain:	0dBi

#### 3.2 Details of E.U.T.

Technical Data: Input: 100-240VAC 50/60Hz 0.2A Max

Output: 9VDC 0.2A

Reference No.: WTS16S0960733E Page 4 of 40

#### 3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC CFR47 Part 15 Section 15.249: 2015

Telecommunication-RADIO FREQUENCY DEVICES-Intentional Radiators-Operation within the bands 902-928 MHz, 2400-2483.5

MHz, 5725-5875 MHZ, and 24.0-24.25 GHz.

#### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### IC – Registration No.:7760A-1

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A-1, Octorber 15, 2015.

#### • FCC Test Site 1#- Registration No.: 880581

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

#### • FCC Test Site 2#- Registration No.: 328995

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014

#### 3.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests.

And according to FCC 47 CFR Section 15.203(m):

Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle.
1 to 10 MHz	2	1 near top and 1 near bottom.
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Test mode	Lower channel	Middle channel	Upper channel
Transmitting	1	915MHz	1

# 4 Equipment Used during Test

### 4.1 Equipments List

_	4.1 Equipments List									
Condu	Conducted Emissions Test Site 1#									
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date				
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.14,2016	Sep.13,2017				
2.	LISN	R&S	ENV216	101215	Sep.14,2016	Sep.13,2017				
3.	Cable	Тор	TYPE16(3.5M)	-	Sep.14,2016	Sep.13,2017				
3m Sei	mi-anechoic Chamber	for Radiation Emis	sions Test site	1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date				
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.14,2016	Sep.13,2017				
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.14,2016	Sep.13,2017				
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2016	Apr.18,2017				
4	Coaxial Cable (below 1GHz)	Тор	TYPE16(13M)	-	Sep.14,2016	Sep.13,2017				
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2016	Apr.18,2017				
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.19,2016	Apr.18,2017				
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2016	Mar.16,2017				
8	Coaxial Cable (above 1GHz)	Тор	1GHz-25GHz	EW02014-7	Apr.10,2016	Apr.09,2017				
3m Sei	mi-anechoic Chamber	for Radiation Emis	sions Test site	2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date				
1	Test Receiver	R&S	ESCI	101296	Sep.14,2016	Sep.13,2017				
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Sep.14,2016	Sep.13,2017				
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Sep.14,2016	Sep.13,2017				
4	Cable	HUBER+SUHNER	CBL2	525178	Sep.14,2016	Sep.13,2017				
RF Coi	RF Conducted Testing									
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date				
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.14,2016	Sep.13,2017				

Reference No.: WTS16S0960733E Page 6 of 40

2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.14,2016	Sep.13,2017
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.14,2016	Sep.13,2017

### 4.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	± 1 x 10 <sup>-6</sup>
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
·	± 5.03 dB
Radiated Spurious	(Bilog antenna 30M~1000MHz)
Emissions test	± 5.47 dB
	(Horn antenna 1000M~25000MHz)

### 4.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

Reference No.: WTS16S0960733E Page 7 of 40

# 5 Test Summary

Test Items	Test Requirement	Result		
Conducted Emissions	15.207	С		
	15.249(a)	С		
Radiated Emission	15.209			
	15.205(a)			
Periodic Operation	15.35(c)	С		
	15.249	С		
Band Edge	15.205			
	15.209			
20dB Bandwidth	15:215(c)	С		
Antenna Requirement	15.203	С		
Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.				

Reference No.: WTS16S0960733E Page 8 of 40

#### 6 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207
Test Method: ANSI C63.10:2013;ANSI C63.4:2014

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit: 66-56 dB<sub>µ</sub>V between 0.15MHz & 0.5MHz

 $56~dB\mu V$  between 0.5MHz~&~5MHz  $60~dB\mu V$  between 5MHz~&~30MHz

Detector:

Peak for pre-scan (9kHz Resolution Bandwidth)

Test Result:

Pass

not applicable (Remark)

#### 6.1 E.U.T. Operation

Operating Environment:


Temperature: 25.5 °C Humidity: 51 % RH Atmospheric Pressure: 101.2kPa

**EUT Operation:** 

The test was performed in transmitting mode, the test data were shown in the report.

#### 6.2 EUT Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013




#### 6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

#### 6.4 Test Result



#### Neutral line:



Reference No.: WTS16S0960733E Page 11 of 40

### 7 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249&15.209&15.205

Test Method: ANSI 63.10: 2013;ANSI C63.4:2014

Measurement Distance: 3m

Test Result:

15.249(a)Limit:

Fundamental frequency	Field strength	of fundamental	Field strength of harmonics		
	mV/m	dBuV/m	uV/m	dBuV/m	
902-928 MHz	50	94	500	54	
2400-2483.5 MHz	50	94	500	54	
5725-5875 MHz	50	94	500	54	
24.0-24.25 GHz	250	108	2500	68	

#### 15.209 Limit:

F	Field Strei	ngth	Field Strength Limit at	3m Measurement Dist
Frequency (MHz)	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log <sup>(2400/F(kHz))</sup> + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log <sup>(24000/F(kHz))</sup> + 40
1.705 ~ 30	30	30	100 * 30	20log <sup>(30)</sup> + 40(29.54+40)
30 ~ 88	100	3	100	20log <sup>(100)</sup> =(40)
88 ~ 216	150	3	150	20log <sup>(150)</sup> =(43.5)
216 ~ 960	200	3	200	20log <sup>(200)</sup> =(46)
Above 960	500	3	500	20log <sup>(500)</sup> =(54)

**Note**: RF Voltage(dBuV)=20 log<sub>10</sub> RF Voltage(uV)

#### 7.1 EUT Operation

Operating Environment:

Temperature: 23.5 °C
Humidity: 51.1 % RH
Atmospheric Pressure: 101.2kPa


**EUT Operation:** 

The test was performed in transmitting mode, the test data were shown in the report.


#### 7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



Anechoic 3m Chamber

Antenna Elevation Varies From 1 to 4 m
Turn Table From 0° to 360°

Turn Table

Absorbers

Spectrum

Analyzer

Combining

Network

**AMP** 

The test setup for emission measurement above 1 GHz.

System

### 7.3 Spectrum Analyzer Setup

Below 30MHz		
	Sweep Speed	.Auto
	IF Bandwidth	.10kHz
	Video Bandwidth	.10kHz
	Resolution Bandwidth	.10kHz
30MHz ~ 1GHz	z	
	Sweep Speed	. Auto
	Detector	.PK
	Resolution Bandwidth	.100kHz
	Video Bandwidth	.300kHz
Above 1GHz		
	Sweep Speed	. Auto
	Detector	.PK
	Resolution Bandwidth	.1MHz
	Video Bandwidth	.3MHz
	Detector	.Ave.
	Resolution Bandwidth	.1MHz
	Video Bandwidth	.10Hz
	Video Bandwidth	.10Hz

Reference No.: WTS16S0960733E Page 14 of 40

#### 7.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above1GHz, the EUT is 1.5m above ground plane.

- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

Reference No.: WTS16S0960733E Page 15 of 40

#### 7.5 Frequency range of radiated measurements.

According to FCC 47 CFR Section 15.33:

- (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:
- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1) through (a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

Result: So the Frequency range of radiated form: 16MHz to 10GHz.

### 7.6 Test Result

Test Frequency :9kHz ~ 30MHz

	Measurement	Detector	Correct	Extrapolation	recilite		Part 209/205
Frequency (MHz)	results	20100101	factor	factor	(calculated)	Limit	Margin
(1711.12)	dBµV/m@3m	PK/QP	dB/m	dB	dBµV/m @30m	dBµV/m @30m	dB
15.730	25.36	QP	21.35	40.00	6.71	29.54	-22.83
25.680	25.18	QP	20.67	40.00	5.85	29.54	-23.69

Test Frequency: 30MHz ~ 10GHz

Frequenc y	Receive r Reading	Detector	Turn table Angle	RX Antenna		Correcte	Carra ata d	FCC Part 15.249/209/205	
				Height	Pola r	d Factor	Corrected Amplitude	Limit	Margi n
(MHz)	(dBµV)	(PK/QP)	Degre e	(m)	(H/V )	(dB/m)	(dBµV/m)	(dBµV/m)	(dB)
35.25	46.41	QP	266	1.6	V	-14.25	32.16	40.00	-7.84
915.00	89.63	PK	140	1.3	Н	1.25	90.88	114.00	-23.12
915.00	89.52	PK	226	1.8	V	1.25	90.77	114.00	-23.23
1830.00	60.42	PK	158	1.0	Н	-13.21	47.21	74.00	-26.79
1830.00	61.53	PK	277	1.8	V	-13.21	48.32	74.00	-25.68
2745.00	55.49	PK	152	1.0	Н	-12.35	43.14	74.00	-30.86
2745.00	54.38	PK	292	1.5	V	-12.35	42.03	74.00	-31.97
3660.00	47.65	PK	359	2.0	Н	-8.95	38.70	74.00	-35.30
3660.00	48.29	PK	357	1.2	V	-8.95	39.34	74.00	-34.66

AV = Peak +20Log10(duty cycle) =PK+(-9.32) [refer to section 9 for more detail]

		RX	•		FCC Part 15.249/209/205	
Frequency	PK	Antenna Polar	Duty cycle Factor	AV	Limit	Margin
(MHz)	(dBµV/m)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
915.00	90.88	Н	-2.71	88.17	94.00	-5.83
915.00	90.77	V	-2.71	88.06	94.00	-5.94
1830.00	47.21	Н	-2.71	44.50	54.00	-9.50
1830.00	48.32	V	-2.71	45.61	54.00	-8.39
2745.00	43.14	Н	-2.71	40.43	54.00	-13.57
2745.00	42.03	V	-2.71	39.32	54.00	-14.68
3660.00	38.70	Н	-2.71	35.99	54.00	-18.01
3660.00	39.34	V	-2.71	36.63	54.00	-17.37

### 8 Periodic Operation


The duty cycle was determined by the following equation:

To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train \* % Duty Cycle Correction Factor(dB)=20 \* Log<sub>10</sub>(Duty Cycle)

Total transmission time(ms)	73.2
Length of a complete transmission period(ms)	100
Duty Cycle(%)	73.2
Duty Cycle Correction Factor(dB)	-2.71

Refer to the duty cycle plot (as below)



Reference No.: WTS16S0960733E Page 19 of 40

### 9 Band Edge

Test Requirement: 15.249(d):Emissions radiated outside of the specified frequency

bands, except for harmonics, shall be attenuated by at least 50 dB

below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Method: ANSI C63.10:2013


Test Mode: Transmitting

#### 9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
 Detector function = peak, Trace = max hold

#### 9.2 Test Result



Reference No.: WTS16S0960733E Page 20 of 40

### 10 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.215(c)

Test Method: ANSI C63.10:2013

Test Mode: Transmitting


#### 10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

#### 10.2 Test Result

Frequency (MHz)	Bandwidth Emission (kHz)		
915	580.8		



Reference No.: WTS16S0960733E Page 21 of 40


### 11 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### Result:


The EUT has one Integrated Antenna, the gain is -3dBi. meets the requirements of FCC 15.203.




# 12 Photographs- Model MWCS-T Test Setup Photos


### 12.1 Photograph – Radiation Emission


Test frequency 9kHz to 30MHz at test site 2#





Test frequency from 30MHz to 1GHz at test site 2#





Test frequency from 1GHz to 10GHz at test site 1#





Reference No.: WTS16S0960733E Page 25 of 40

### 12.2 Photograph – Conducted Emission Test Setup at Test Site 1#



# 13 Photographs - Constructional Details

### 13.1 Model MWCS-T - External Photos





Reference No.: WTS16S0960733E Page 27 of 40





Reference No.: WTS16S0960733E Page 28 of 40





Reference No.: WTS16S0960733E Page 29 of 40






Reference No.: WTS16S0960733E Page 30 of 40





Reference No.: WTS16S0960733E Page 31 of 40





Reference No.: WTS16S0960733E Page 32 of 40






Reference No.: WTS16S0960733E Page 33 of 40


### 13.2 Model MWCS-T - Internal Photos







Reference No.: WTS16S0960733E Page 34 of 40






Reference No.: WTS16S0960733E Page 35 of 40







Reference No.: WTS16S0960733E Page 36 of 40







Reference No.: WTS16S0960733E Page 37 of 40







Reference No.: WTS16S0960733E Page 38 of 40






Reference No.: WTS16S0960733E Page 39 of 40





Reference No.: WTS16S0960733E Page 40 of 40



=====End of Report=====