BLAUPUNKT

Rear of Unit



PIN	DEFINITION A PART	PIN	DEFINITION B PART
.1	NC.	.1	Rear right+
2	NC	2	Rear right-
3	NC	3	Front right+
4	ACC	4	Front right-
5	NC	-5	Front left+
6	ILLUMI	6	Front left-
7	BATT +	7	Rear left+
8	GND	8	Rear left-

	DEFINITI	ON C PAR	RT
PIN	C1 PART	PIN	C1 PART
1	AUX IN CVBS	8	AGND
2	GND	9	REAR R
3	AUX IN R	10	REAR L
4	AUX IN L	11	AGND
5	AGND	12	FRONT R
6	NC	13	FRONT L
7	SUB.W	14	AGND
-		-	
-	***	-	***
PIN	C2 PART	PIN	C3 PART
15	GND	25	DP2
16	CAMERA CVBS	26	DM2
17	NC	27	GND
18	P.ANT*	28	+5V
19	PARKING	29	GND
20	REVERSE	30	VEDIO OUT
21	ILLUMI	31	NC
22	KAY GND	32	MIC-
23	KAY A	33	MIC+
24	KAVB	3.4	NC

Model: Osaka 960

Warnings: Warranty void if this unit is damaged due to misuse or

unauthorized service attempting.

Before making any electical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Operating Instructions.

Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.

Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged,

This product was produced using lead free technology. Help keep the world clean! Dispose properly!

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and

(2) This device must accept any interference received, including interference that may cause undesired operation.





FCC ID: 2AJ8A-OSAKA960

QDID: D033651

Remarks: (*) Total max, 150 mA / Fuse: 15 Ampere

12V ⊝ GROUND === 15A max

Front USB: SV === 51A (max 2A)
Rear USB: \$V === 500mA
Blaupunkt Technology Americas S.A.
Zona America Ruta 8 km
Costa Park Montevideo, Uruguay

PN: 127072002632

