

www.fulham.com

**120V
-
277V**

Ph: (323) 599-5801
MADE IN CHINA

8 470980 3822 1

Tc, 90°C Max.

FULHAM®

WORKHORSE LED™

PROGRAMMABLE CONSTANT CURRENT DRIVER

MODEL: T1R1UNV210P-60C

SUITABLE FOR LEDS USE ONLY

SUITABLE FOR DRY OR DAMP LOCATIONS

100% - 1%, 0%

RoHS COMPLIANT

Dimmer

UL US
LISTED
E342838

IP65

L BLK
N WHT

ANT

ORG
YEL
RED
BLUE

RED
BLUE

INPUT VOLTAGE 120-277VAC, 50/60Hz

INPUT CURRENT 0.6A Max.

INPUT POWER 72W

POWER FACTOR >0.95@Full Load

OUTPUT CURRENT 500-2100mA

OUTPUT VOLTAGE 10-57VDC

OUTPUT POWER 60W Max.

U-OUT 60V

ta -40°C To 60°C

OUTPUT CHANNELS 1

DIMMING WIRELESS

THD <20%

EFFICIENCY 85% Typical@Full Load

RFI/EMI FCC PART 15B

OUTPUT TYPE Class 2

SOUND RATING A

Class P

This device complies with Part 15 of the FCC Rules.

FCC ID: 2AJ9LT1R1UNV210P60W

See www.fulham.com for installation, operation and maintenance instructions.

LED DRIVER

INPUT 120-277VAC

BLK(L)
WHT(N)

ANT

ORG
YEL
RED
BLUE

R-SET NTC

OUTPUT

ANT

ORG
YEL
RED
BLUE

RED
BLUE

TVILIGHT

WARNING: Install In Accordance With The National And Local Electrical Code. Disconnect Power Before Servicing. Driver Must Be Grounded.

ATTENTION: L'installation doit être conforme aux normes du Code National Électrique. Débranchez l'alimentation avant l'entretien. Pilote doivent être mis à la terre.

R-SET / 500mA

