

FCC Part 15B

Measurement and Test Report

For

Honeywell Integrated Technology(China) Co.,LTD

430 Li Bing Road, Shanghai ,P.R. China

FCC ID: 2AJAWVCU-X2YYYYEN

FCC Rule(s): FCC Part 15 Subpart B

Product Description: Tema-Voyager TM Compact

Tested Model: VCU-X2YYYYEN1N01

Report No.: STR16078148I-2

Tested Date: 2016-12-25 to 2017-01-11

Issued Date: 2017-01-12

Tested By: Jason Su / Engineer

Jason Su

Reviewed By: Silin Chen / EMC Manager

Silin Chen

Approved & Authorized By: Jandy So / PSQ Manager

Jandy So

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND OPERATION MODE	5
1.6 MEASUREMENT UNCERTAINTY	5
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. CONDUCTED EMISSIONS	8
3.1 TEST PROCEDURE.....	8
3.2 BASIC TEST SETUP BLOCK DIAGRAM.....	8
3.3 ENVIRONMENTAL CONDITIONS	8
3.4 SUMMARY OF TEST RESULTS/PLOTS	8
3.5 CONDUCTED EMISSIONS TEST DATA.....	9
4. RADIATED EMISSION	11
4.1 TEST PROCEDURE.....	11
4.2 TEST RECEIVER SETUP	11
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
4.4 ENVIRONMENTAL CONDITIONS	12
4.5 SUMMARY OF TEST RESULTS/PLOTS	12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Honeywell Integrated Technology(China) Co.,LTD
Address of applicant: 430 Li Bing Road, Shanghai ,P.R. China

Manufacturer: Honeywell S.r.l.
Address of manufacturer: Via PHILIPS 12, 20052, MONZA- ITALY

General Description of EUT	
Product Name:	Tema-Voyager TM Compact
Trade Name:	Honeywell
Model No.:	VCU-X2YYYYEN1N01
Adding Model(s):	/
Rated Voltage:	DC12V From Power Supply
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. VCU-X2YYYYEN1N01, X=0,A,B,C size of the cardholder Capacity; YYYY=color of the enclosure and may be any color of the RAL table</i>	

Technical Characteristics of EUT	
Rated Voltage:	DC12V From Power Supply
Power Adapter Model:	RTU Q03 I/P: AC 120V/60Hz; O/P: DC 12V
Rated Power:	/
Lowest Internal Frequency:	32.768kHz
Highest Internal Frequency:	26MHz
Classification of ITE:	CLASS B

1.2 Test Standards

The following report is prepared on behalf of the Honeywell Integrated Technology(China) Co.,LTD in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Operating	Connect to Notebook

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Special Cable List and Details

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
RJ45 Cable*2	3.0	Shielded	Without Ferrite
AC Cable	1.3	Unshielded	Without Ferrite
Signal Cable	1.8	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E23	/
Power Supply	Honeywell	RTU Q03	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant


N/A: not applicable

3. Conducted Emissions

3.1 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.2 Basic Test Setup Block Diagram



3.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.4 Summary of Test Results/Plots

According to the data in section 3.5, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:


-7.12 dB at 20.2500 MHz in the Line, Average detector, 0.15-30MHz

3.5 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Tema-Voyager TM Compact
 Tested Model: VCU-X2YYYYEN1N01
 Operating Condition: TM1
 Comment: AC 120V/60Hz; Power Supply DC 12V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	6.2058	33.08	10.27	43.35	60.00	-16.65	QP
2	6.2058	31.41	10.27	41.68	50.00	-8.32	AVG
3	7.0058	32.22	10.29	42.51	50.00	-7.49	AVG
4	7.2579	37.36	10.29	47.65	60.00	-12.35	QP
5	13.5579	60.58	10.40	70.98	/	/	Fundamental
6	13.5579	60.48	10.40	70.88	/	/	
7	23.1299	33.16	10.50	43.66	60.00	-16.34	QP
8	23.1299	26.99	10.50	37.49	50.00	-12.51	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	6.9978	35.76	10.29	46.05	60.00	-13.95	QP
2	6.9978	32.03	10.29	42.32	50.00	-7.68	AVG
3X	13.5579	60.71	10.40	71.11	/	/	Fundamental
4*	13.5579	61.15	10.40	71.55	/	/	
5	20.1260	34.13	10.46	44.59	60.00	-15.41	QP
6	20.2500	32.42	10.46	42.88	50.00	-7.12	AVG


4. RADIATED EMISSION

4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.2 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.4 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

4.5 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

-2.79 dB at 501.1789 MHz in the Horizontal polarization, 30 MHz to 1 GHz, 3Meters

Plot of Radiated Emissions Test Data


EUT: Tema-Voyager TM Compact
 Tested Model: VCU-X2YYYYEN1N01
 Operating Condition: TM1
 Comment: AC 120V/60Hz; Power Supply DC 12V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	250.3011	32.94	9.32	42.26	46.00	-3.74	53	100	QP
2	375.9384	30.07	11.81	41.88	46.00	-4.12	138	100	QP
3	501.1789	29.84	13.37	43.21	46.00	-2.79	78	100	QP
4	625.0779	24.61	17.55	42.16	46.00	-3.84	134	100	QP
5	1000.0000	22.71	19.11	41.82	54.00	-12.18	142	100	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	119.8555	33.28	4.82	38.10	43.50	-5.40	63	100	QP
2	250.3011	32.43	9.32	41.75	46.00	-4.25	176	100	QP
3	375.9384	30.10	11.81	41.91	46.00	-4.09	67	100	QP
4	501.1789	28.49	13.37	41.86	46.00	-4.14	105	100	QP
5	625.0779	24.68	17.55	42.23	46.00	-3.77	253	100	QP

***** END OF REPORT *****