# FCC ID: 2AJDH-500300

### 1. RF EXPOSURE

## 1.1. The Requirement

System operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See Section 15.247(b)(4) and Section 1.1307(b)(1)

# 1.2.Limit For Maximum Permissible Exposure (MPE)

Limits for General Population/ Uncontrolled Exposure

Frequency Range	Electric Field Strength (E)	Magnetic Field Power Density (S)		Averaging Time $ E ^2$ , $ H ^2$ or S	
(MHz)	(V/m)	(A/m)	(mW/cm <sup>2</sup> )	(minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

F = frequency in MHz, \* Plane-wave equivalent power density

#### 1.3.MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$ 

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the antenna is 2 dBi, the RF power density can be obtained.

### 1.4.TEST RESULTS

Maximum measured transmitter power

FSK mode

Test	Minimum	Outnut	Outnut	Target	Antonno	Power	Power	
Frequency	Separation	Output Power	Output Power	power	Antenna Gain	Density	Density	Test
(MHz)	Distance		(mW)	(dBm)		Limit	At 20 cm	Results
(WILLS)	(cm)	(dBm)	(IIIW)		(Numeric)	$(mW/cm^2)$	$(mW/cm^2)$	
902.5	20.00	12.85	0.0193	12 ±1	1.585	f/1500	0.0063	Pass
914.75	20.00	12.27	0.0169	12 ±1	1.585	f/1500	0.0063	Pass
927.5	20.00	11.48	0.0141	12 ±1	1.585	f/1500	0.0063	Pass

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.

# 1.5.FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, Human proximity to the antenna shall not be less than 20cm(8 inches) during normal operation. Proposed RF exposure safety information to include in User's Manual.