



FCC PART 15.247 TEST REPORT

For

G-TOUCH LLC.

1750 NW 107TH AVENUE, STE P-411, MIAMI, FLORIDA, UNITED STATES

FCC ID: 2AJDZSTELLAOMEGA

Report Type: Product Name:

Original Report Smart phone

Report Number: RDG191108020-00B

Report Date: 2019-11-19

Reviewed By: Jerry Zhang
EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)

Jerry Zhang

Test Laboratory: No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888

Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
DECLARATIONS	
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT Exercise Software	6
EQUIPMENT MODIFICATIONS	
SUPPORT CABLE LIST AND DETAILS	
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	8
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST DATA	
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	22
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
TEST DATA	22
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	28
APPLICABLE STANDARD	
TEST PROCEDURE	28

TEST EQUIPMENT LIST AND DETAILS.	28
Test Data	
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	37
APPLICABLE STANDARD	37
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	37
Test Data	37
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	43
APPLICABLE STANDARD	43
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	43
TEST DATA	43
FCC §15.247(d) - BAND EDGES TESTING	45
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
Test Data	46

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

	EUT Name:	Smart phone
EUT Model:		Stella Omega
Operation Frequency:		2402-2480MHz
Maximum Peak Output Power (Conducted):		3.93 dBm
	Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
]	Rated Input Voltage:	3.7Vdc from Battery or 5Vdc from adapter
	Model:	Stella Omega
Adapter Information	Input:	100-240V 50/60Hz 0.15A
inioi mation	Output:	5V 1A
	External Dimension:	144mm(L)*73mm(W)*11mm(H)
Serial Number:		RDG191108020-RF-S1
	EUT Received Date:	2019/11/11
E	UT Received Status:	Good

Objective

This report is prepared on behalf of *G-TOUCH LLC*. in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H, 24E PCE submissions with FCC ID: 2AJDZSTELLAOMEGA FCC Part 15B JBP submissions with FCC ID: 2AJDZSTELLAOMEGA FCC Part 15C DTS submissions with FCC ID: 2AJDZSTELLAOMEGA

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty	
Occupied Channel Bandwidth	±5 %	
RF output power, conducted	±0.61dB	
Power Spectral Density, conducted	±0.61 dB	
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB,200M~1GHz: 5.92 dB,1G~6GHz: 4.98 dB 6G~18GHz: 5.89 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB	
Unwanted Emissions, conducted	±1.5 dB	
Temperature	±1 °C	
Humidity	±5%	
DC and low frequency voltages	±0.4%	
Duty Cycle	1%	
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)	

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 897218, the FCC Designation No.: CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol "\(^{\text{\sigma}}\)". Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk " \star ".

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The Engineering Mode configured the maximum power level as default setting.


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	No	No	0.8	Adapter	EUT
Earphone Cable	No	No	1.2	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & \$1.1310 & \$2.1093	RF Exposure	Compliance
FCC §15.203	Antenna requirement	Compliance
FCC §15.207(a)	AC line conducted emissions	Compliance
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(1)	Channel separation	Compliance
FCC §15.247(a)(1)	20 dB bandwidth	Compliance
FCC §15.247(a)(1)(iii)	Quantity of hopping channel test	Compliance
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliance
FCC §15.247(b)(1)	Peak output power measurement	Compliance
FCC §15.247(d)	Band edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 4.0 dBm (2.51 mW). [(max. power of channel, mW)/(min. test separation distance, mm)][$\sqrt{f(GHz)}$] = 2.51/5*($\sqrt{2.480}$) = 0.8< 3.0

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type input impedance (Ohm)		Antenna Gain /Frequency Range		
FPC	50	2.78 dBi/2.4~2.5GHz		


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2019-09-12	2020-09-12
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	26.4℃	
Relative Humidity:	54%	
ATM Pressure:	100.9kPa	
Test by:	Sem Xiang	
Test Date:	2019-11-13	

Test Result: Compliance

Test Mode: Transmitting


AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.495058	40.2	9.000	L1	9.9	15.9	56.1
0.520311	41.1	9.000	L1	9.9	14.9	56.0
0.993465	40.7	9.000	L1	9.8	15.3	56.0
1.935016	36.1	9.000	L1	9.7	19.9	56.0
2.997955	34.3	9.000	L1	9.8	21.7	56.0
20.457389	38.2	9.000	L1	10.1	21.8	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.485304	29.7	9.000	L1	9.9	16.5	46.2
0.520311	28.8	9.000	L1	9.9	17.2	46.0
0.759409	29.7	9.000	L1	9.8	16.3	46.0
1.248947	26.7	9.000	L1	9.8	19.3	46.0
2.137462	25.9	9.000	L1	9.7	20.1	46.0
21.933090	31.8	9.000	L1	10.1	18.2	50.0

AC120V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.471031	41.2	9.000	N	9.9	15.3	56.5
0.530770	45.1	9.000	N	9.9	10.9	56.0
0.899371	36.9	9.000	N	9.8	19.1	56.0
1.097403	36.6	9.000	N	9.8	19.4	56.0
1.523953	34.8	9.000	N	9.8	21.2	56.0
25.718273	42.1	9.000	N	10.1	17.9	60.0

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.443733	29.4	9.000	N	9.9	17.6	47.0
0.480499	26.9	9.000	N	9.9	19.4	46.3
0.525514	35.3	9.000	N	9.9	10.7	46.0
0.759409	30.0	9.000	N	9.8	16.0	46.0
1.248947	27.3	9.000	N	9.8	18.7	46.0
22.597684	33.4	9.000	N	10.0	16.6	50.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 CHr	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
Radiation Below 1GHz								
R&S	EMI Test Receiver	ESR3	102453	2019-09-12	2020-09-12			
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A			
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10			
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05			
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05			
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06			
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05			
	Radiation Above 1GHz							
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09			
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A			
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12			
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18			
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05			
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2019-06-27	2020-06-27			
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2019-09-05	2020-09-05			
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27			
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2019-06-16	2020-06-16			
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16			

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data


Environmental Conditions

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	26.2 °C	25.4 °C
Relative Humidity:	42%	45%
ATM Pressure:	101.2 kPa	101.2kPa
Tester:	Tyler Pan	Lucy Lu
Test Date:	2019-11-14	2019-11-14

Test Mode: Transmitting


1) 30MHz-1GHz (BDR Low channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBµV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
30.9700	25.58	peak	0.91	26.49	40.00	13.51
162.8900	31.41	peak	-6.12	25.29	43.50	18.21
250.1900	44.44	peak	-6.03	38.41	46.00	7.59
267.6500	42.75	peak	-4.44	38.31	46.00	7.69
361.7400	29.81	peak	-2.80	27.01	46.00	18.99
930.1600	32.88	peak	0.58	33.46	46.00	12.54

Vertical:



Frequency (MHz)	Receiver Reading (dBµV)	Remark	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	27.50	peak	1.72	29.22	40.00	10.78
258.9200	35.61	peak	-5.43	30.18	46.00	15.82
270.5600	35.22	peak	-4.28	30.94	46.00	15.06
361.7400	28.89	peak	-2.80	26.09	46.00	19.91
712.8800	27.84	peak	3.19	31.03	46.00	14.97
937.9200	32.54	peak	0.74	33.28	46.00	12.72


2)1GHz-25GHz:


BDR(GFSK) Mode was the worst:


F	Reco	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	T : *4	M	
Frequency (MHz)	Reading (dBµV)	Remark	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)	
Low Channel: 2402 MHz										
2402.00	65.13	PK	Н	28.10	1.80	0.00	95.03	N/A	N/A	
2402.00	56.25	AV	Н	28.10	1.80	0.00	86.15	N/A	N/A	
2402.00	63.48	PK	V	28.10	1.80	0.00	93.38	N/A	N/A	
2402.00	54.40	AV	V	28.10	1.80	0.00	84.30	N/A	N/A	
2390.00	26.76	PK	Н	28.08	1.80	0.00	56.64	74.00	17.36	
2390.00	13.27	AV	Н	28.08	1.80	0.00	43.15	54.00	10.85	
4804.00	36.24	PK	Н	32.91	3.17	25.60	46.72	74.00	27.28	
4804.00	23.21	AV	Н	32.91	3.17	25.60	33.69	54.00	20.31	
7206.00	35.08	PK	Н	35.74	4.82	25.60	50.04	74.00	23.96	
7206.00	22.36	AV	Н	35.74	4.82	25.60	37.32	54.00	16.68	
3603.00	42.77	PK	Н	31.53	2.40	25.95	50.75	74.00	23.25	
3603.00	31.19	AV	Н	31.53	2.40	25.95	39.17	54.00	14.83	
			N	Middle Cha	nnel: 244	1 MHz		•		
2441.00	65.12	PK	Н	28.18	1.82	0.00	95.12	N/A	N/A	
2441.00	56.45	AV	Н	28.18	1.82	0.00	86.45	N/A	N/A	
2441.00	63.45	PK	V	28.18	1.82	0.00	93.45	N/A	N/A	
2441.00	56.74	AV	V	28.18	1.82	0.00	86.74	N/A	N/A	
4882.00	36.78	PK	Н	33.06	3.27	25.66	47.45	74.00	26.55	
4882.00	23.87	AV	Н	33.06	3.27	25.66	34.54	54.00	19.46	
7323.00	35.12	PK	Н	36.04	4.62	25.73	50.05	74.00	23.95	
7323.00	22.78	AV	Н	36.04	4.62	25.73	37.71	54.00	16.29	
3658.00	41.87	PK	Н	31.65	2.50	25.93	50.09	74.00	23.91	
3658.00	30.54	AV	Н	31.65	2.50	25.93	38.76	54.00	15.24	
				High Chan	nel: 2480	MHz				
2480.00	65.53	PK	Н	28.26	1.84	0.00	95.63	N/A	N/A	
2480.00	56.30	AV	Н	28.26	1.84	0.00	86.40	N/A	N/A	
2480.00	62.36	PK	V	28.26	1.84	0.00	92.46	N/A	N/A	
2480.00	53.87	AV	V	28.26	1.84	0.00	83.97	N/A	N/A	
2483.50	27.54	PK	Н	28.27	1.84	0.00	57.65	74.00	16.35	
2483.50	14.82	AV	Н	28.27	1.84	0.00	44.93	54.00	9.07	
4960.00	35.54	PK	Н	33.22	3.23	25.63	46.36	74.00	27.64	
4960.00	23.45	AV	Н	33.22	3.23	25.63	34.27	54.00	19.73	
7440.00	35.12	PK	Н	36.34	4.41	25.85	50.02	74.00	23.98	
7440.00	22.45	AV	Н	36.34	4.41	25.85	37.35	54.00	16.65	
3718.00	40.25	PK	Н	31.78	2.56	25.89	48.70	74.00	25.30	
3718.00	30.14	AV	Н	31.78	2.56	25.89	38.59	54.00	15.41	

Worst plots (GFSK low channel was the worst) **Horizontal**












Vertical

Fundamental Test with Band Rejection Filter







FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25.8°C
Relative Humidity:	51%
ATM Pressure:	101.7kPa
Test by:	Elena Lei
Test Date:	2019-11-12

Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
nnn	Low	2402	0.996	0.59
BDR (GFSK)	Middle	2441	1.002	0.58
(OPSK)	High	2480	1.002	0.58
EDD	Low	2402	1.008	0.81
EDR (π/4-DQPSK)	Middle	2441	1.002	0.81
(1//4-DQF3K)	High	2480	1.002	0.81
EDD	Low	2402	0.996	0.81
EDR (8DPSK)	Middle	2441	1.002	0.81
(obr sk)	High	2480	0.996	0.81

Note: Limit= $(2/3) \times 20dB$ bandwidth


BDR Mode (GFSK):

Low Channel




Date: 12.NOV.2019 13:35:32

Middle Channel



Date: 12.NOV.2019 13:36:23


High Channel



Date: 12.NOV.2019 13:37:20


EDR Mode ($\pi/4$ -DQPSK):






Date: 12.NOV.2019 13:33:40

Middle Channel



Date: 12.NOV.2019 13:34:11


High Channel



Date: 12.NOV.2019 13:34:41


EDR Mode (8DPSK):

Low Channel




Date: 12.NOV.2019 13:31:39

Middle Channel



Date: 12.NOV.2019 13:32:16

High Channel



Date: 12.NOV.2019 13:32:49

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8°C	
Relative Humidity:	51%	
ATM Pressure:	ure: 101.7kPa	
Test by:	Elena Lei	
Test Date:	2019-11-12	

Test Result: Compliance.

Please refer to following tables and plots


Report No.: RDG191108020-00B

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.880
	Middle	2441	0.876
	High	2480	0.876
EDR Mode (π/4-DQPSK)	Low	2402	1.212
	Middle	2441	1.212
	High	2480	1.212
EDR Mode (8DPSK)	Low	2402	1.208
	Middle	2441	1.212
	High	2480	1.208


BDR Mode (GFSK):

Low Channel




Date: 12.NOV.2019 13:22:35

Middle Channel



Date: 12.NOV.2019 13:23:33


High Channel



Date: 12.NOV.2019 13:24:15


EDR Mode ($\pi/4$ -DQPSK):






Date: 12.NOV.2019 13:27:11

Middle Channel



Date: 12.NOV.2019 13:26:24


High Channel



Date: 12.NOV.2019 13:25:23


EDR Mode (8DPSK):

Low Channel




Date: 12.NOV.2019 13:28:07

Middle Channel



Date: 12.NOV.2019 13:29:08

High Channel



Date: 12.NOV.2019 13:29:59

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8°C	
Relative Humidity:	51%	
ATM Pressure:	101.7kPa	
Test by:	Elena Lei	
Test Date:	2019-11-12	


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Test mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	≥15
π/4-DQPSK	2400-2483.5	79	≥15
8DPSK	2400-2483.5	79	≥15


BDR Mode (GFSK)



Date: 12.NOV.2019 13:44:27


EDR Mode (π/4-DQPSK)

Report No.: RDG191108020-00B



Date: 12.NOV.2019 13:47:16

EDR Mode (8DPSK)



Date: 12.NOV.2019 13:51:36

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8°C
Relative Humidity:	44%
ATM Pressure:	100.5kPa
Test by:	Elena Lei
Test Date:	2019-11-19

Test Result: Compliance.

Please refer to following tables and plots

Page 37 of 52

Test Mode: Transmitting

Mode	Packet type	Channel	Frequency (MHz)	Puse width (ms)	Result (s)	Limit (s)
	DH1	Middle	2441	0.392	0.125	
GFSK	DH3	Middle	2441	1.656	0.265	
	DH5	Middle	2441	2.910	0.310	
-/4	2DH1	Middle	2441	0.398	0.127	
π/4-	2DH3	Middle	2441	1.662	0.266	≤0.4
DQPSK	2DH5	Middle	2441	2.920	0.311	
	3DH1	Middle	2441	0.400	0.128	
8DPSK	3DH3	Middle	2441	1.656	0.265	
	3DH5	Middle	2441	2.920	0.311	

Note:


DH1:Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s

DH3:Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s

DH5:Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s


BDR Mode (GFSK):

DH1: Middle Channel




Date: 19.NOV.2019 13:30:58

DH3: Middle Channel



Date: 19.NOV.2019 13:31:35


DH5: Middle Channel



Date: 19.NOV.2019 13:31:58


EDR Mode ($\pi/4$ -DQPSK):

2DH1: Middle Channel



Date: 19.NOV.2019 13:32:18


2DH3: Middle Channel



Date: 19.NOV.2019 13:32:34

2DH5: Middle Channel


Report No.: RDG191108020-00B



Date: 19.NOV.2019 13:32:51

EDR Mode 8DPSK):


3DH1: Middle Channel



Date: 19.NOV.2019 13:33:13


3DH3: Middle Channel

Report No.: RDG191108020-00B



Date: 19.NOV.2019 13:33:27

3DH5: Middle Channel



Date: 19.NOV.2019 13:33:42

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8°C
Relative Humidity:	51%
ATM Pressure:	101.7kPa
Test by:	Elena Lei
Test Date:	2019-11-12

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
	2402	2.92	21
BDR Mode (GFSK)	2441	3.48	21
(GFSK)	2480	3.93	21
	2402	2.68	21
EDR Mode (π/4-DQPSK)	2441	3.26	21
(M4-DQF3K)	2480	3.69	21
EDR Mode (8DPSK)	2402	2.75	21
	2441	3.34	21
	2480	3.78	21

Note: The data above was tested in conducted mode.

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.8°C
Relative Humidity:	51%
ATM Pressure:	101.7kPa
Test by:	Elena Lei
Test Date:	2019-11-12

Test Result: Compliance

Single Channel Mode, BDR Mode (GFSK):


Band Edge, Left Side



Date: 12.NOV.2019 13:23:15

Band Edge, Right Side


Report No.: RDG191108020-00B



Date: 12.NOV.2019 13:24:51

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side



Date: 12.NOV.2019 13:27:51

Band Edge, Right Side


Report No.: RDG191108020-00B



Date: 12.NOV.2019 13:26:05


EDR Mode (8DPSK):

Band Edge, Left Side



Date: 12.NOV.2019 13:28:46


Band Edge, Right Side



Date: 12.NOV.2019 13:30:35


Hopping Mode, BDR Mode (GFSK):

Band Edge, Left Side



Date: 12.NOV.2019 14:01:30


Band Edge, Right Side



Date: 12.NOV.2019 14:05:45

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side



Date: 12.NOV.2019 13:59:57

Band Edge, Right Side


Report No.: RDG191108020-00B



Date: 12.NOV.2019 13:58:06


EDR Mode (8DPSK):

Band Edge, Left Side



Date: 12.NOV.2019 13:53:42





Date: 12.NOV.2019 13:55:34

***** END OF REPORT *****