



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247 TEST REPORT

For

G-TOUCH LLC.

1750 NW 107TH AVENUE, STE P-411, MIAMI, FLORIDA, UNITED STATES

FCC ID: 2AJDZSTELLAOMEGA

Report Type: Original Report	Product Name: Smart phone
Report Number: RDG191108020-00A	
Report Date: 2019-11-19	
Jerry Zhang	
Reviewed By:	EMC Manager
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	10
SUPPORT CABLE LIST AND DETAILS	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	13
APPLICABLE STANDARD	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA	21
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	31
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41

TEST DATA	41
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	44
FCC §15.247(e) - POWER SPECTRAL DENSITY	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST EQUIPMENT LIST AND DETAILS.....	50
TEST DATA	50

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Smart phone
EUT Model:		Stella Omega
Operation Frequency:		2412-2462 MHz(802.11b/g/n ht20), 2422-2452 MHz(802.11n ht40) 2402-2480MHz(BLE)
Maximum Peak Output Power (Conducted):		20.69 dBm(802.11b/g/n) 4.14 dBm(BLE)
Modulation Type:		DSSS, OFDM(802.11b/g/n) GFSK(BLE)
Rated Input Voltage:		3.7Vdc from Battery or 5Vdc from adapter
Adapter Information	Model:	Stella Omega
	Input:	100-240V 50/60Hz 0.15A
	Output:	5V 1A
External Dimension:		144mm(L)*73mm(W)*11mm(H)
Serial Number:		RDG191108020-RF-S1
EUT Received Date:		2019/11/11
EUT Received Status:		Good

Objective

This report is prepared on behalf of **G-TOUCH LLC.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H, 24E PCE submissions with FCC ID: 2AJDZSTELLAOMEGA
FCC Part 15B JBP submissions with FCC ID: 2AJDZSTELLAOMEGA
FCC Part 15C DSS submissions with FCC ID: 2AJDZSTELLAOMEGA

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1, 6, 11. For 802.11n ht40 modes were test with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

EUT Exercise Software

The software “Engineering Mode” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:


Mode	Frequency (MHz)	Data rate (Mbps)	Power level Setting
802.11 b	2412	1	21
	2437	1	21
	2462	1	19.5
802.11 g	2412	6	20
	2437	6	20
	2457	6	20
	2462	6	17
802.11n ht20	2412	MCS0	20
	2437	MCS0	20
	2457	MCS0	18.5
	2462	MCS0	16.5
802.11n ht40	2422	MCS0	16
	2437	MCS0	18.5
	2447	MCS0	15
	2452	MCS0	14.5

Bluetooth LE mode was configured by the system default setting

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	100	100	100
802.11n ht20	100	100	100
802.11n ht40	100	100	100
BLE	0.409	0.633	64.61

802.11b




Date: 12.NOV.2019 14:56:23

802.11g




Date: 12.NOV.2019 14:55:44

802.11n ht20




Date: 12.NOV.2019 14:55:16

802.11n ht40



Date: 12.NOV.2019 14:57:04



Date: 12.NOV.2019 14:18:28


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
USB Cable	No	No	0.8	Adapter	EUT
Earphone Cable	No	No	1.2	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result**For BLE:**

The max conducted power including tune-up tolerance is 5.0 dBm (3.16 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 3.16/5 \cdot (\sqrt{2.480}) = 1.0 < 3.0$

So the stand-alone SAR evaluation is not necessary.

For 802.11b/g/n:

Please refer to the SAR report: RDG191108020-20.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	2.78 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2019-09-12	2020-09-12
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	26.4℃
Relative Humidity:	54%
ATM Pressure:	100.9kPa
Tester:	Sem Xiang
Test Date:	2019-11-13


Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.495058	40.8	9.000	L1	9.9	15.3	56.1
0.520311	42.2	9.000	L1	9.9	13.8	56.0
1.033804	40.3	9.000	L1	9.8	15.7	56.0
1.993649	36.8	9.000	L1	9.7	19.2	56.0
3.027934	34.4	9.000	L1	9.8	21.6	56.0
20.054297	39.0	9.000	L1	10.1	21.0	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.490157	29.0	9.000	L1	9.9	17.2	46.2
0.525514	28.3	9.000	L1	9.9	17.7	46.0
0.759409	29.5	9.000	L1	9.8	16.5	46.0
1.248947	27.1	9.000	L1	9.8	18.9	46.0
2.180425	25.7	9.000	L1	9.7	20.3	46.0
22.373945	31.8	9.000	L1	10.1	18.2	50.0

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.475741	42.7	9.000	N	9.9	13.7	56.4
0.536077	45.0	9.000	N	9.9	11.0	56.0
1.023568	38.5	9.000	N	9.8	17.5	56.0
1.075780	37.9	9.000	N	9.8	18.1	56.0
1.164916	35.6	9.000	N	9.8	20.4	56.0
1.570131	35.1	9.000	N	9.8	20.9	56.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.443733	29.3	9.000	N	9.9	17.7	47.0
0.480499	27.1	9.000	N	9.9	19.2	46.3
0.525514	35.3	9.000	N	9.9	10.7	46.0
0.759409	30.2	9.000	N	9.8	15.8	46.0
1.248947	27.3	9.000	N	9.8	18.7	46.0
22.373945	33.3	9.000	N	10.0	16.7	50.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESR3	102453	2019-09-12	2020-09-12
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05
Radiation Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2019-06-27	2020-06-27
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	26.2 °C	25.4 °C
Relative Humidity:	42%	45%
ATM Pressure:	101.2 kPa	101.2kPa
Tester:	Tyler Pan	Lucy Lu
Test Date:	2019-11-14	2019-11-14

Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting

1) 30MHz-1GHz(802.11b_High channel was the worst)**Horizontal:**

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	25.40	peak	1.72	27.12	40.00	12.88
165.8000	38.18	peak	-6.21	31.97	43.50	11.53
245.3400	43.13	peak	-5.97	37.16	46.00	8.84
276.3800	40.96	peak	-4.14	36.82	46.00	9.18
891.3600	33.37	peak	-0.16	33.21	46.00	12.79
919.4900	33.47	peak	0.34	33.81	46.00	12.19

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	29.83	peak	1.72	31.55	40.00	8.45
45.5200	37.53	peak	-9.44	28.09	40.00	11.91
180.3500	37.33	peak	-7.17	30.16	43.50	13.34
273.4700	33.14	peak	-4.12	29.02	46.00	16.98
772.0500	26.97	peak	4.33	31.30	46.00	14.70
899.1200	32.90	peak	0.10	33.00	46.00	13.00

**2) 1-25GHz:
802.11b Mode:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	70.28	PK	H	28.12	1.81	0.00	100.21	N/A	N/A
2412.00	66.69	AV	H	28.12	1.81	0.00	96.62	N/A	N/A
2412.00	68.78	PK	V	28.12	1.81	0.00	98.71	N/A	N/A
2412.00	64.92	AV	V	28.12	1.81	0.00	94.85	N/A	N/A
2390.00	26.22	PK	H	28.08	1.80	0.00	56.10	74.00	17.90
2390.00	13.86	AV	H	28.08	1.80	0.00	43.74	54.00	10.26
4824.00	38.40	PK	H	32.95	3.19	25.62	48.92	74.00	25.08
4824.00	29.23	AV	H	32.95	3.19	25.62	39.75	54.00	14.25
7236.00	39.28	PK	H	35.81	4.77	25.64	54.22	74.00	19.78
7236.00	30.62	AV	H	35.81	4.77	25.64	45.56	54.00	8.44
3618.00	48.40	PK	H	31.56	2.42	25.94	56.44	74.00	17.56
3618.00	41.78	AV	H	31.56	2.42	25.94	49.82	54.00	4.18
Middle Channel: 2437 MHz									
2437.00	70.81	PK	H	28.17	1.82	0.00	100.80	N/A	N/A
2437.00	66.93	AV	H	28.17	1.82	0.00	96.92	N/A	N/A
2437.00	69.15	PK	V	28.17	1.82	0.00	99.14	N/A	N/A
2437.00	65.57	AV	V	28.17	1.82	0.00	95.56	N/A	N/A
4874.00	41.62	PK	H	33.05	3.26	25.65	52.28	74.00	21.72
4874.00	32.78	AV	H	33.05	3.26	25.65	43.44	54.00	10.56
7311.00	39.52	PK	H	36.01	4.64	25.71	54.46	74.00	19.54
7311.00	30.97	AV	H	36.01	4.64	25.71	45.91	54.00	8.09
3655.36	48.44	PK	H	31.64	2.50	25.93	56.65	74.00	17.35
3655.36	41.94	AV	H	31.64	2.50	25.93	50.15	54.00	3.85
High Channel: 2462 MHz									
2462.00	70.58	PK	H	28.22	1.83	0.00	100.63	N/A	N/A
2462.00	67.62	AV	H	28.22	1.83	0.00	97.67	N/A	N/A
2462.00	68.70	PK	V	28.22	1.83	0.00	98.75	N/A	N/A
2462.00	64.53	AV	V	28.22	1.83	0.00	94.58	N/A	N/A
2483.50	29.01	PK	H	28.27	1.84	0.00	59.12	74.00	14.88
2483.50	20.62	AV	H	28.27	1.84	0.00	50.73	54.00	3.27
4924.00	41.25	PK	H	33.15	3.27	25.65	52.02	74.00	21.98
4924.00	37.21	AV	H	33.15	3.27	25.65	47.98	54.00	6.02
7386.00	38.13	PK	H	36.20	4.51	25.79	53.05	74.00	20.96
7386.00	29.87	AV	H	36.20	4.51	25.79	44.79	54.00	9.21
3693.00	47.38	PK	H	31.72	2.57	25.91	55.76	74.00	18.24
3693.00	40.38	AV	H	31.72	2.57	25.91	48.76	54.00	5.24

802.11g Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	69.69	PK	H	28.12	1.81	0.00	99.62	N/A	N/A
2412.00	59.75	AV	H	28.12	1.81	0.00	89.68	N/A	N/A
2412.00	67.15	PK	V	28.12	1.81	0.00	97.08	N/A	N/A
2412.00	63.39	AV	V	28.12	1.81	0.00	93.32	N/A	N/A
2390.00	32.06	PK	H	28.08	1.80	0.00	61.94	74.00	12.06
2390.00	15.24	AV	H	28.08	1.80	0.00	45.12	54.00	8.88
4824.00	39.11	PK	H	32.95	3.19	25.62	49.63	74.00	24.37
4824.00	24.98	AV	H	32.95	3.19	25.62	35.50	54.00	18.50
7236.00	36.57	PK	H	35.81	4.77	25.64	51.51	74.00	22.49
7236.00	24.79	AV	H	35.81	4.77	25.64	39.73	54.00	14.27
3619.00	46.39	PK	H	31.56	2.43	25.94	54.44	74.00	19.56
3619.00	37.16	AV	H	31.56	2.43	25.94	45.21	54.00	8.79
Middle Channel: 2437 MHz									
2437.00	70.29	PK	H	28.17	1.82	0.00	100.28	N/A	N/A
2437.00	60.37	AV	H	28.17	1.82	0.00	90.36	N/A	N/A
2437.00	68.34	PK	V	28.17	1.82	0.00	98.33	N/A	N/A
2437.00	58.51	AV	V	28.17	1.82	0.00	88.50	N/A	N/A
4874.00	39.50	PK	H	33.05	3.26	25.65	50.16	74.00	23.84
4874.00	26.31	AV	H	33.05	3.26	25.65	36.97	54.00	17.03
7311.00	36.97	PK	H	36.01	4.64	25.71	51.91	74.00	22.09
7311.00	25.14	AV	H	36.01	4.64	25.71	40.08	54.00	13.92
3655.00	46.25	PK	H	31.64	2.49	25.93	54.45	74.00	19.55
3655.00	37.46	AV	H	31.64	2.49	25.93	45.66	54.00	8.34
High Channel: 2457 MHz									
2457.00	75.26	PK	H	28.21	1.83	0.00	105.30	N/A	N/A
2457.00	65.27	AV	H	28.21	1.83	0.00	95.31	N/A	N/A
2457.00	72.55	PK	V	28.21	1.83	0.00	102.59	N/A	N/A
2457.00	62.78	AV	V	28.21	1.83	0.00	92.82	N/A	N/A
2483.50	36.43	PK	H	28.27	1.84	0.00	66.54	74.00	7.46
2483.50	22.29	AV	H	28.27	1.84	0.00	52.40	54.00	1.60
High Channel: 2462 MHz									
2462.00	71.83	PK	H	28.22	1.83	0.00	101.88	N/A	N/A
2462.00	61.95	AV	H	28.22	1.83	0.00	92.00	N/A	N/A
2462.00	69.57	PK	V	28.22	1.83	0.00	99.62	N/A	N/A
2462.00	59.72	AV	V	28.22	1.83	0.00	89.77	N/A	N/A
2483.50	42.15	PK	H	28.27	1.84	0.00	72.26	74.00	1.74
2483.50	22.49	AV	H	28.27	1.84	0.00	52.60	54.00	1.40
4924.00	39.61	PK	H	33.15	3.27	25.65	50.38	74.00	23.62
4924.00	26.25	AV	H	33.15	3.27	25.65	37.02	54.00	16.98
7386.00	37.21	PK	H	36.20	4.51	25.79	52.13	74.00	21.87
7386.00	25.31	AV	H	36.20	4.51	25.79	40.23	54.00	13.77
3693.00	46.45	PK	H	31.72	2.57	25.91	54.83	74.00	19.17
3693.00	38.02	AV	H	31.72	2.57	25.91	46.40	54.00	7.60

802.11n ht20 Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	68.94	PK	H	28.12	1.81	0.00	98.87	N/A	N/A
2412.00	59.55	AV	H	28.12	1.81	0.00	89.48	N/A	N/A
2412.00	65.78	PK	V	28.12	1.81	0.00	95.71	N/A	N/A
2412.00	56.47	AV	V	28.12	1.81	0.00	86.40	N/A	N/A
2390.00	34.55	PK	H	28.08	1.80	0.00	64.43	74.00	9.57
2390.00	15.99	AV	H	28.08	1.80	0.00	45.87	54.00	8.13
4824.00	36.85	PK	H	32.95	3.19	25.62	47.37	74.00	26.63
4824.00	23.87	AV	H	32.95	3.19	25.62	34.39	54.00	19.61
7236.00	35.25	PK	H	35.81	4.77	25.64	50.19	74.00	23.81
7236.00	22.47	AV	H	35.81	4.77	25.64	37.41	54.00	16.59
3618.00	46.85	PK	H	31.56	2.42	25.94	54.89	74.00	19.11
3618.00	36.72	AV	H	31.56	2.42	25.94	44.76	54.00	9.24
Middle Channel: 2437 MHz									
2437.00	69.54	PK	H	28.17	1.82	0.00	99.53	N/A	N/A
2437.00	60.12	AV	H	28.17	1.82	0.00	90.11	N/A	N/A
2437.00	66.57	PK	V	28.17	1.82	0.00	96.56	N/A	N/A
2437.00	57.31	AV	V	28.17	1.82	0.00	87.30	N/A	N/A
4874.00	37.38	PK	H	33.05	3.26	25.65	48.04	74.00	25.96
4874.00	24.61	AV	H	33.05	3.26	25.65	35.27	54.00	18.73
7311.00	35.94	PK	H	36.01	4.64	25.71	50.88	74.00	23.12
7311.00	22.71	AV	H	36.01	4.64	25.71	37.65	54.00	16.35
3655.00	47.20	PK	H	31.64	2.49	25.93	55.40	74.00	18.60
3655.00	37.08	AV	H	31.64	2.49	25.93	45.28	54.00	8.72
High Channel: 2457 MHz									
2457.00	74.80	PK	H	28.21	1.83	0.00	104.84	N/A	N/A
2457.00	64.78	AV	H	28.21	1.83	0.00	94.82	N/A	N/A
2457.00	71.15	PK	V	28.21	1.83	0.00	101.19	N/A	N/A
2457.00	61.42	AV	V	28.21	1.83	0.00	91.46	N/A	N/A
2483.50	39.21	PK	H	28.27	1.84	0.00	69.32	74.00	4.68
2483.50	21.87	AV	H	28.27	1.84	0.00	51.98	54.00	2.02
High Channel: 2462 MHz									
2462.00	71.33	PK	H	28.22	1.83	0.00	101.38	N/A	N/A
2462.00	62.14	AV	H	28.22	1.83	0.00	92.19	N/A	N/A
2462.00	68.34	PK	V	28.22	1.83	0.00	98.39	N/A	N/A
2462.00	59.28	AV	V	28.22	1.83	0.00	89.33	N/A	N/A
2483.50	42.70	PK	H	28.27	1.84	0.00	72.81	74.00	1.19
2483.50	22.61	AV	H	28.27	1.84	0.00	52.72	54.00	1.28
4924.00	38.12	PK	H	33.15	3.27	25.65	48.89	74.00	25.11
4924.00	25.46	AV	H	33.15	3.27	25.65	36.23	54.00	17.77
7386.00	36.05	PK	H	36.20	4.51	25.79	50.97	74.00	23.03
7386.00	23.67	AV	H	36.20	4.51	25.79	38.59	54.00	15.41
3692.00	47.55	PK	H	31.72	2.56	25.91	55.92	74.00	18.08
3692.00	37.30	AV	H	31.72	2.56	25.91	45.67	54.00	8.33

802.11n ht40 Mode:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	66.76	PK	H	28.14	1.81	0.00	96.71	N/A	N/A
2422.00	56.82	AV	H	28.14	1.81	0.00	86.77	N/A	N/A
2422.00	63.12	PK	V	28.14	1.81	0.00	93.07	N/A	N/A
2422.00	53.27	AV	V	28.14	1.81	0.00	83.22	N/A	N/A
2390.00	39.69	PK	H	28.08	1.80	0.00	69.57	74.00	4.43
2390.00	21.17	AV	H	28.08	1.80	0.00	51.05	54.00	2.95
4844.00	34.87	PK	H	32.99	3.22	25.63	45.45	74.00	28.55
4844.00	22.45	AV	H	32.99	3.22	25.63	33.03	54.00	20.97
7266.00	33.15	PK	H	35.89	4.72	25.67	48.09	74.00	25.91
7266.00	21.26	AV	H	35.89	4.72	25.67	36.20	54.00	17.80
3619.00	43.25	PK	H	31.56	2.43	25.94	51.30	74.00	22.70
3619.00	30.15	AV	H	31.56	2.43	25.94	38.20	54.00	15.80
Middle Channel: 2437 MHz									
2437.00	69.78	PK	H	28.17	1.82	0.00	99.77	N/A	N/A
2437.00	59.99	AV	H	28.17	1.82	0.00	89.98	N/A	N/A
2437.00	66.72	PK	V	28.17	1.82	0.00	96.71	N/A	N/A
2437.00	56.87	AV	V	28.17	1.82	0.00	86.86	N/A	N/A
4874.00	36.45	PK	H	33.05	3.26	25.65	47.11	74.00	26.89
4874.00	24.78	AV	H	33.05	3.26	25.65	35.44	54.00	18.56
7311.00	35.15	PK	H	36.01	4.64	25.71	50.09	74.00	23.91
7311.00	23.41	AV	H	36.01	4.64	25.71	38.35	54.00	15.65
3655.00	46.58	PK	H	31.64	2.49	25.93	54.78	74.00	19.22
3655.00	33.36	AV	H	31.64	2.49	25.93	41.56	54.00	12.44
High Channel: 2447 MHz									
2447.00	66.91	PK	H	28.19	1.82	0.00	96.92	N/A	N/A
2447.00	56.72	AV	H	28.19	1.82	0.00	86.73	N/A	N/A
2447.00	63.45	PK	V	28.19	1.82	0.00	93.46	N/A	N/A
2447.00	53.28	AV	V	28.19	1.82	0.00	83.29	N/A	N/A
2483.50	36.82	PK	H	28.27	1.84	0.00	66.93	74.00	7.07
2483.50	20.26	AV	H	28.27	1.84	0.00	50.37	54.00	3.63
High Channel: 2452 MHz									
2452.00	67.28	PK	H	28.20	1.83	0.00	97.31	N/A	N/A
2452.00	57.54	AV	H	28.20	1.83	0.00	87.57	N/A	N/A
2452.00	64.34	PK	V	28.20	1.83	0.00	94.37	N/A	N/A
2452.00	54.28	AV	V	28.20	1.83	0.00	84.31	N/A	N/A
2483.50	41.01	PK	H	28.27	1.84	0.00	71.12	74.00	2.88
2483.50	22.63	AV	H	28.27	1.84	0.00	52.74	54.00	1.26
4904.00	35.12	PK	H	33.11	3.30	25.67	45.86	74.00	28.14
4904.00	22.89	AV	H	33.11	3.30	25.67	33.63	54.00	20.37
7356.00	34.24	PK	H	36.13	4.56	25.76	49.17	74.00	24.83
7356.00	22.07	AV	H	36.13	4.56	25.76	37.00	54.00	17.00
3693.00	45.82	PK	H	31.72	2.57	25.91	54.20	74.00	19.80
3693.00	32.64	AV	H	31.72	2.57	25.91	41.02	54.00	12.98

BLE Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	64.74	PK	H	28.10	1.80	0.00	94.64	N/A	N/A
2402.00	63.86	AV	H	28.10	1.80	0.00	93.76	N/A	N/A
2402.00	63.34	PK	V	28.10	1.80	0.00	93.24	N/A	N/A
2402.00	62.47	AV	V	28.10	1.80	0.00	92.37	N/A	N/A
2390.00	24.90	PK	H	28.08	1.80	0.00	54.78	74.00	19.22
2390.00	14.64	AV	H	28.08	1.80	0.00	44.52	54.00	9.48
4804.00	35.46	PK	H	32.91	3.17	25.60	45.94	74.00	28.06
4804.00	24.78	AV	H	32.91	3.17	25.60	35.26	54.00	18.74
7206.00	34.58	PK	H	35.74	4.82	25.60	49.54	74.00	24.46
7206.00	23.64	AV	H	35.74	4.82	25.60	38.60	54.00	15.40
3602.90	42.08	PK	H	31.53	2.40	25.95	50.06	74.00	23.94
3602.90	36.92	AV	H	31.53	2.40	25.95	44.90	54.00	9.10
Middle Channel: 2440 MHz									
2440.00	64.12	PK	H	28.18	1.82	0.00	94.12	N/A	N/A
2440.00	63.27	AV	H	28.18	1.82	0.00	93.27	N/A	N/A
2440.00	62.80	PK	V	28.18	1.82	0.00	92.80	N/A	N/A
2440.00	62.08	AV	V	28.18	1.82	0.00	92.08	N/A	N/A
4880.00	35.65	PK	H	33.06	3.27	25.66	46.32	74.00	27.68
4880.00	24.69	AV	H	33.06	3.27	25.66	35.36	54.00	18.64
7320.00	34.44	PK	H	36.03	4.62	25.72	49.37	74.00	24.63
7320.00	23.55	AV	H	36.03	4.62	25.72	38.48	54.00	15.52
3660.00	41.57	PK	H	31.65	2.50	25.93	49.79	74.00	24.21
3660.00	35.51	AV	H	31.65	2.50	25.93	43.73	54.00	10.27
High Channel: 2480 MHz									
2480.00	63.86	PK	H	28.26	1.84	0.00	93.96	N/A	N/A
2480.00	63.15	AV	H	28.26	1.84	0.00	93.25	N/A	N/A
2480.00	63.06	PK	V	28.26	1.84	0.00	93.16	N/A	N/A
2480.00	62.45	AV	V	28.26	1.84	0.00	92.55	N/A	N/A
2483.50	24.87	PK	H	28.27	1.84	0.00	54.98	74.00	19.02
2483.50	14.32	AV	H	28.27	1.84	0.00	44.43	54.00	9.57
4960.00	35.12	PK	H	33.22	3.23	25.63	45.94	74.00	28.06
4960.00	24.35	AV	H	33.22	3.23	25.63	35.17	54.00	18.83
7440.00	32.64	PK	H	36.34	4.41	25.85	47.54	74.00	26.46
7440.00	23.57	AV	H	36.34	4.41	25.85	38.47	54.00	15.53
3720.00	41.15	PK	H	31.78	2.56	25.89	49.60	74.00	24.40
3720.00	34.61	AV	H	31.78	2.56	25.89	43.06	54.00	10.94




Test plots(802.11b middle channel was the worst)
Horizontal:

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25.8~26.5°C
Relative Humidity:	51~60%
ATM Pressure:	100.3~101.7kPa
Tester:	Elena Lei
Test Date:	2019-11-12 & 2019-11-18

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.440	≥ 0.5
	Middle	2437	9.440	≥ 0.5
	High	2462	9.440	≥ 0.5
802.11g	Low	2412	16.480	≥ 0.5
	Middle	2437	16.480	≥ 0.5
	High	2462	16.480	≥ 0.5
802.11n ht20	Low	2412	17.760	≥ 0.5
	Middle	2437	17.440	≥ 0.5
	High	2462	17.520	≥ 0.5
802.11n ht40	Low	2422	36.480	≥ 0.5
	Middle	2437	36.320	≥ 0.5
	High	2452	36.480	≥ 0.5
BLE	Low	2402	0.708	≥ 0.5
	Middle	2440	0.700	≥ 0.5
	High	2480	0.708	≥ 0.5

802.11b Low Channel




Date: 12.NOV.2019 14:48:44

802.11b Middle Channel




Date: 12.NOV.2019 14:50:02

802.11b High Channel




Date: 18.NOV.2019 17:52:56


802.11g Low Channel



Date: 12.NOV.2019 14:43:55


802.11g Middle Channel

Date: 12.NOV.2019 14:45:26

802.11g High Channel


Date: 18.NOV.2019 17:54:27

802.11n ht20 Low Channel




Date: 12.NOV.2019 14:38:55

802.11n ht20 Middle Channel




Date: 12.NOV.2019 14:53:19

802.11n ht20 High Channel




Date: 18.NOV.2019 17:57:59

802.11n ht40 Low Channel




Date: 18.NOV.2019 18:03:17

802.11n ht40 Middle Channel




Date: 12.NOV.2019 14:31:27

802.11n ht40 High Channel




Date: 18.NOV.2019 18:01:09

BLE Low Channel




Date: 12.NOV.2019 14:13:08

BLE Middle Channel



Date: 12.NOV.2019 14:17:17

BLE High Channel



Date: 12.NOV.2019 14:15:39


FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8~26.5°C
Relative Humidity:	51~60%
ATM Pressure:	100.3~101.7kPa
Tester:	Elena Lei
Test Date:	2019-11-12 & 2019-11-18

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Test mode	Frequency (MHz)	Conducted Peak Output Power (dBm)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	18.66	16.26	30
	2437	18.48	16.08	30
	2462	17.56	15.04	30
802.11g	2412	20.69	15.00	30
	2437	20.19	15.15	30
	2457	18.15	13.93	30
	2462	16.52	12.19	30
802.11n ht20	2412	20.57	14.89	30
	2437	20.27	15.11	30
	2457	17.59	13.77	30
	2462	16.68	12.18	30
802.11n ht40	2422	17.65	11.87	30
	2437	20.50	14.26	30
	2442	18.04	12.68	30
	2447	16.54	10.88	30
	2452	15.64	9.94	30
BLE	2402	2.92	/	30
	2440	3.66	/	30
	2480	4.14	/	30

Note: The data above was tested in conducted mode.

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Environmental Conditions

Temperature:	25.8~26.5°C
Relative Humidity:	51~60%
ATM Pressure:	100.3~101.7kPa
Tester:	Elena Lei
Test Date:	2019-11-12~2019-11-18


Test Result: Compliance. Please refer to following plots.

[illegible]


Date: 12.NOV.2019 14:49:26

802.11b: Band Edge, Right Side


Date: 18.NOV.2019 17:53:29

802.11g: Band Edge, Left Side

Date: 12.NOV.2019 14:44:58


802.11g: Band Edge, Right Side

Date: 18.NOV.2019 17:55:16

802.11n ht20 Band Edge, Left Side


Date: 12.NOV.2019 14:39:53

802.11n ht20 Band Edge, Right Side




Date: 18.NOV.2019 17:56:50

802.11n ht40 Band Edge, Left Side




Date: 18.NOV.2019 18:00:35

802.11n ht40 Band Edge, Right Side




Date: 18.NOV.2019 18:02:41

BLE Band Edge, Left Side



Date: 12.NOV.2019 14:14:48

BLE Band Edge, Right Side



Date: 12.NOV.2019 14:16:26

FCC §15.247(e) - POWER SPECTRAL DENSITY**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	N/A


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.8~26.5°C
Relative Humidity:	51~60%
ATM Pressure:	100.3~101.7kPa
Tester:	Elena Lei
Test Date:	2019-11-12~2019-11-18


Test Result: Compliance*Test Mode: Transmitting**Test Result: Compliant. Please refer to the following table and plots*

Test mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-12.72	≤8
	2437	-12.95	≤8
	2462	-14.28	≤8
802.11g	2412	-12.42	≤8
	2437	-12.28	≤8
	2462	-15.56	≤8
802.11n ht20	2412	-12.58	≤8
	2437	-12.77	≤8
	2462	-15.44	≤8
802.11n ht40	2422	-17.14	≤8
	2437	-13.59	≤8
	2452	-18.88	≤8
BLE	2402	-12.58	≤8
	2440	-11.82	≤8
	2480	-11.30	≤8

Power Spectral Density, 802.11b Low Channel


Date: 12.NOV.2019 14:49:05

Power Spectral Density, 802.11b Middle Channel




Date: 12.NOV.2019 14:50:23

Power Spectral Density, 802.11b High Channel




Date: 18.NOV.2019 17:53:16

Power Spectral Density, 802.11g Low Channel




Date: 12.NOV.2019 14:44:45

Power Spectral Density, 802.11g Middle Channel




Date: 12.NOV.2019 14:46:07

Power Spectral Density, 802.11g High Channel




Date: 18.NOV.2019 17:55:04


Power Spectral Density, 802.11n ht20 Low Channel



Date: 12.NOV.2019 14:39:40


Power Spectral Density, 802.11n ht20 Middle Channel

Date: 12.NOV.2019 14:41:32

Power Spectral Density, 802.11n ht20 High Channel


Date: 18.NOV.2019 17:58:36

Power Spectral Density, 802.11n ht40 Low Channel




Date: 18.NOV.2019 18:04:40

Power Spectral Density, 802.11n ht40 Middle Channel




Date: 12.NOV.2019 14:32:47

Power Spectral Density, 802.11n ht40 High Channel




Date: 18.NOV.2019 18:02:28

Power Spectral Density, BLE Low Channel




Date: 12.NOV.2019 14:13:41

Power Spectral Density, BLE Middle Channel



Date: 12.NOV.2019 14:17:49

Power Spectral Density, BLE High Channel



Date: 12.NOV.2019 14:16:11

***** END OF REPORT *****