8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range	Power Density (S)	
(MHz)	(mW/cm2)	
0.3–1.34	*(100)	
1.34-30	*(180/f ²)	
30–300	0.2	
300-1500	f/1500	
1500–100,000	1.0	

F = frequency in MHz

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

 $S = PG/4\pi R^2$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

- 1. Manufacturer declared that the maximum antenna gain is 2.0dBi(Max.).
- 2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
- 3. Only record worst case data.

Conducted Power Results

^{* =} Plane-wave equivalent power density

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm, Peak)	Tolerance ±(dB)
802.11b	1	2412	17.88	17.0 ± 1.0
	6	2437	17.85	17.0 ± 1.0
	11	2462	18.02	18.0 ± 1.0
802.11g	1	2412	19.17	19.0 ± 1.0
	6	2437	18.94	18.0 ± 1.0
	11	2462	19.50	19.0 ± 1.0
802.11n HT20	1	2412	18.42	18.0 ± 1.0
	6	2437	18.16	18.0 ± 1.0
	11	2462	18.47	18.0 ± 1.0
802.11n HT40	3	2422	18.28	18.0 ± 1.0
	6	2437	17.54	17.0 ± 1.0
	9	2452	17.14	17.0 ± 1.0

Test Mode	Channel	Max. Tune Up Power (dBm)	Max. Tune Up Power (mW)	MPE (mW/cm²)	Limit (mW/cm²)
802.11b	Low	18.0	63.10	0.0198	1.0
	Middle	18.0	63.10	0.0198	1.0
	High	19.0	79.43	0.0250	1.0
802.11g	Low	20.0	100.00	0.0314	1.0
	Middle	19.0	79.43	0.0250	1.0
	High	20.0	100.00	0.0314	1.0
802.11n HT20	Low	19.0	79.43	0.0250	1.0
	Middle	19.0	79.43	0.0250	1.0
	High	19.0	79.43	0.0250	1.0
802.11n HT40	Low	19.0	79.43	0.0250	1.0
	Middle	18.0	63.10	0.0198	1.0
	High	18.0	63.10	0.0198	1.0

Antenna Gain (typical): 2.0dBi, 1.58(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.