
Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng




Page Number : 55 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310

Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	24~26 ℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng




Page Number : 56 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310


Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	24~26℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng



Page Number : 57 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No. : FR691310

Number of TX :	2	Ant. :	2
Test Mode:	802.11g	Temperature :	24~26 ℃
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng




Page Number : 58 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310

Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng




Page Number : 59 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310


Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	24~26℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng



Page Number : 60 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310


Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	24~26℃
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng



Page Number : 61 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310


Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	24~26 ℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	03	Test Engineer :	Sam Zheng



Page Number : 62 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	24~26 ℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng




Page Number : 63 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310

Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	24~26 ℃
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Sam Zheng



Page Number : 64 of 71

Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

Report No.: FR691310

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 65 of 71
Report Issued Date : Oct. 28, 2016

Report No. : FR691310

Report Version : Rev. 01

3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- 7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-8637-9589

FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 66 of 71
Report Issued Date : Oct. 28, 2016

Report No. : FR691310


Report Version : Rev. 01
Report Template No.: BU5-FR15CWL MA Version 1.3

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




Spectrum Analyzer / Receiver

Report No.: FR691310

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 67 of 71
Report Issued Date : Oct. 28, 2016

Report Version : Rev. 01

For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 68 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used

3.6.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1) dB$.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \le 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i). For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 Multiple Transmitter

Output v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	3.80	3.80	3.80	6.81	0.00	0.81

Power Limit Reduction = DG(Power) - 6dBi, (min = 0)

 $PSD \ Limit \ Reduction = DG(PSD) - 6dBi, (min = 0)$

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 69 of 71
Report Issued Date : Oct. 28, 2016

Report No.: FR691310

Report Version : Rev. 01
Report Template No.: BU5-FR15CWL MA Version 1.3

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 07, 2016	Sep. 23, 2016~ Sep. 27, 2016	May 06, 2017	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 12, 2016	Sep. 23, 2016~ Sep. 27, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 12, 2016	Sep. 23, 2016~ Sep. 27, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY544500 83	20Hz~8.4GHz	May 07, 2016	Oct. 13, 2016	May 06, 2017	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz; Max 30dBm	Oct. 11, 2016	Oct. 13, 2016	Oct. 10, 2017	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Oct. 13, 2016	May 06, 2017	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	May 21, 2016	Oct. 13, 2016	May 20, 2017	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-128 5	1GHz~18GHz	Jan. 11, 2016	Oct. 13, 2016	Jan. 10, 2017	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Oct. 13, 2016	Aug. 09, 2017	Radiation (03CH02-SZ)
Amplifier	HP	8447F	3113A046 22	9kHz~1300MHz / 30 dB	Jul. 16, 2016	Oct. 13, 2016	Jul. 15, 2017	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY532701 04	0.5GHz~26.5G Hz	Oct. 11, 2016	Oct. 13, 2016	Oct. 10, 2017	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P- R	1707137	1GHz~18GHz	Oct. 11, 2016	Oct. 13, 2016	Oct. 10, 2017	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz	Jul. 16, 2016	Oct. 13, 2016	Jul. 15, 2017	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002 470	N/A	NCR	Oct. 13, 2016	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Oct. 13, 2016	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Oct. 13, 2016	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 70 of 71
Report Issued Date : Oct. 28, 2016

Report No.: FR691310

Report Version : Rev. 01

5 Uncertainty of Evaluation

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.0dB
of 95% (U = 2Uc(y))	3.0GB

<u>Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)</u>

Measuring Uncertainty for a Level of Confidence	5.1dB
of 95% (U = 2Uc(y))	

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

	<u> </u>
Measuring Uncertainty for a Level of Confidence	5.1dB
of 95% $(U = 2Uc(y))$	უ. IUD

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : 71 of 71
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No. : FR691310

Appendix A. Conducted Test Results

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : A1 of A1
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CWL MA Version 1.3

Report No.: FR691310

Test Engineer:	Sam Zheng	Temperature:	24~26	ŷ
Test Date:	2016/9/23~2016/9/27	Relative Humidity:	50~53	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

					:	2.4GHz Band	i			
Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	99% Occ (MI	upied BW Hz)		BW Hz)	6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	12.29	12.29	10.03	10.01	0.50	Pass
11b	1Mbps	1	6	2437	12.29	12.29	9.51	10.03	0.50	Pass
11b	1Mbps	1	11	2462	12.29	12.29	10.03	10.03	0.50	Pass
11g	6Mbps	1	1	2412	17.83	17.83	16.30	16.30	0.50	Pass
11g	6Mbps	1	6	2437	17.83	17.88	16.30	16.30	0.50	Pass
11g	6Mbps	1	11	2462	17.88	17.88	16.30	16.30	0.50	Pass
HT20	MCS0	1	1	2412	18.43	18.43	17.04	17.06	0.50	Pass
HT20	MCS0	1	6	2437	18.43	18.43	17.08	17.28	0.50	Pass
HT20	MCS0	1	11	2462	18.43	18.43	17.06	17.28	0.50	Pass
HT40	MCS0	1	3	2422	36.86	36.66	36.28	36.28	0.50	Pass
HT40	MCS0	1	6	2437	36.76	36.76	36.00	36.00	0.50	Pass
HT40	MCS0	1	9	2452	36.76	36.76	36.28	36.04	0.50	Pass
11b	1Mbps	2	1	2412	12.34	12.99	9.97	9.51	0.50	Pass
11b	1Mbps	2	6	2437	12.34	13.04	10.07	10.07	0.50	Pass
11b	1Mbps	2	11	2462	12.29	13.04	10.03	10.03	0.50	Pass
11g	6Mbps	2	1	2412	17.93	17.93	16.30	16.30	0.50	Pass
11g	6Mbps	2	6	2437	17.93	17.83	16.30	16.30	0.50	Pass
11g	6Mbps	2	11	2462	17.93	17.88	16.30	16.30	0.50	Pass
HT20	MCS0	2	1	2412	18.48	18.43	17.08	17.16	0.50	Pass
HT20	MCS0	2	6	2437	18.43	18.43	17.06	17.30	0.50	Pass
HT20	MCS0	2	11	2462	18.43	18.43	17.04	17.28	0.50	Pass
HT40	MCS0	2	3	2422	36.76	36.76	35.96	36.28	0.50	Pass
HT40	MCS0	2	6	2437	36.86	36.76	36.24	36.28	0.50	Pass
HT40	MCS0	2	9	2452	36.86	36.86	36.04	36.04	0.50	Pass

TEST RESULTS DATA Peak Output Power

								2.4GHz l	Band							
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	C	Peak Conducte Power (dBm)	d	Po	ucted wer nit Bm)	_	G Bi)	Po	RP wer Bm)		wer mit	Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	15.28	13.74		30.00	30.00	3.80	3.80	19.08	17.54	36.00	36.00	Pass
11b	1Mbps	1	6	2437	15.59	13.66		30.00	30.00	3.80	3.80	19.39	17.46	36.00	36.00	Pass
11b	1Mbps	1	11	2462	16.68	13.48		30.00	30.00	3.80	3.80	20.48	17.28	36.00	36.00	Pass
11g	6Mbps	1	1	2412	21.27	19.84		30.00	30.00	3.80	3.80	25.07	23.64	36.00	36.00	Pass
11g	6Mbps	1	6	2437	21.31	19.58		30.00	30.00	3.80	3.80	25.11	23.38	36.00	36.00	Pass
11g	6Mbps	1	11	2462	21.24	19.29		30.00	30.00	3.80	3.80	25.04	23.09	36.00	36.00	Pass
HT20	MCS0	1	1	2412	21.13	19.57		30.00	30.00	3.80	3.80	24.93	23.37	36.00	36.00	Pass
HT20	MCS0	1	6	2437	21.22	19.35		30.00	30.00	3.80	3.80	25.02	23.15	36.00	36.00	Pass
HT20	MCS0	1	11	2462	21.06	18.91		30.00	30.00	3.80	3.80	24.86	22.71	36.00	36.00	Pass
HT40	MCS0	1	3	2422	18.54	16.76		30.00	30.00	3.80	3.80	22.34	20.56	36.00	36.00	Pass
HT40	MCS0	1	6	2437	18.46	16.38		30.00	30.00	3.80	3.80	22.26	20.18	36.00	36.00	Pass
HT40	MCS0	1	9	2452	18.37	16.24		30.00	30.00	3.80	3.80	22.17	20.04	36.00	36.00	Pass
11b	1Mbps	2	1	2412	15.22	14.16	17.73	30	.00	3.	80	21	.53	36	.00	Pass
11b	1Mbps	2	6	2437	15.46	14.02	17.81	30	.00	3.	80	21	.61	36	.00	Pass
11b	1Mbps	2	11	2462	15.61	13.81	17.81	30	.00	3.	80	21	.61	36	.00	Pass
11g	6Mbps	2	1	2412	20.89	19.57	23.29	30	.00	3.	80	27	.09	36	.00	Pass
11g	6Mbps	2	6	2437	20.77	19.34	23.12	30	.00	3.	80	26	.92	36	.00	Pass
11g	6Mbps	2	11	2462	20.63	19.10	22.94	30	.00	3.	80	26	.74	36	.00	Pass
HT20	MCS0	2	1	2412	20.56	19.44	23.05	30	.00	3.	80	26	.85	36	.00	Pass
HT20	MCS0	2	6	2437	20.65	19.29	23.03	30	30.00		80	26	.83	36	.00	Pass
HT20	MCS0	2	11	2462	20.59	18.91	22.84	30.00		3.	80	26	.64	36	.00	Pass
HT40	MCS0	2	3	2422	18.25	16.74	20.57	30.00		3.	80	24.37		36.00		Pass
HT40	MCS0	2	6	2437	18.06	16.40	20.32	30.00		3.80		24.12		36.00		Pass
HT40	MCS0	2	9	2452	17.95	16.11	20.14	30	.00	3.	80	23	.94	36	.00	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA Average Output Power

				2.4G	Hz Band	t			
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Fac	uty ctor B)		Average Conducte Power (dBm)	
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.10	0.13	11.79	10.28	
11b	1Mbps	1	6	2437	0.10	0.13	12.02	10.21	
11b	1Mbps	1	11	2462	0.10	0.13	12.20	10.05	
11g	6Mbps	1	1	2412	0.56	0.56	12.11	10.62	
11g	6Mbps	1	6	2437	0.56	0.56	12.18	10.37	
11g	6Mbps	1	11	2462	0.56	0.56	12.14	10.03	
HT20	MCS0	1	1	2412	0.60	0.60	11.58	9.99	
HT20	MCS0	1	6	2437	0.60	0.60	11.61	9.76	
HT20	MCS0	1	11	2462	0.60	0.60	11.55	9.55	
HT40	MCS0	1	3	2422	1.13	1.10	8.89	7.14	
HT40	MCS0	1	6	2437	1.13	1.10	8.81	6.88	
HT40	MCS0	1	9	2452	1.13	1.10	8.69	6.58	
11b	1Mbps	2	1	2412	0.11	0.10	11.70	10.65	14.21
11b	1Mbps	2	6	2437	0.11	0.10	11.94	10.52	14.30
11b	1Mbps	2	11	2462	0.11	0.10	12.06	10.32	14.28
11g	6Mbps	2	1	2412	0.61	0.56	11.81	10.32	14.14
11g	6Mbps	2	6	2437	0.61	0.56	11.66	10.15	13.98
11g	6Mbps	2	11	2462	0.61	0.56	11.58	9.90	13.83
HT20	MCS0	2	1	2412	0.65	0.60	11.07	9.94	13.55
HT20	MCS0	2	6	2437	0.65	0.60	11.13	9.77	13.51
HT20	MCS0	2	11	2462	0.65	0.60	11.01	9.46	13.31
HT40	MCS0	2	3	2422	1.16	1.15	8.70	7.20	11.03
HT40	MCS0	2	6	2437	1.16	1.15	8.61	6.93	10.86
HT40	MCS0	2	9	2452	1.16	1.15	8.43	6.69	10.66

Note: Measured power (dBm) has offset with cable loss.

<u>TEST RESULTS DATA</u> <u>Peak Power Spectral Density</u>

							2.4GHz Band	<u> </u>				
Mod.	Data Rate	Ntx	CH.	Freq.		Peak PSD (dBm/3kHz)		D (dl	~	Lii	PSD mit (3kHz)	Pass/Fail
	Rate			(IVITZ)	Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-14.96	-17.52	-	3.80	3.80	8.00	8.00	Pass
11b	1Mbps	1	6	2437	-16.62	-17.86		3.80	3.80	8.00	8.00	Pass
11b	1Mbps	1	11	2462	-16.05	-17.80		3.80	3.80	8.00	8.00	Pass
11g	6Mbps	1	1	2412	-16.07	-16.69		3.80	3.80	8.00	8.00	Pass
11g	6Mbps	1	6	2437	-14.90	-17.44		3.80	3.80	8.00	8.00	Pass
11g	6Mbps	1	11	2462	-14.29	-17.80		3.80	3.80	8.00	8.00	Pass
HT20	MCS0	1	1	2412	-15.87	-17.21		3.80	3.80	8.00	8.00	Pass
HT20	MCS0	1	6	2437	-15.88	-18.50		3.80	3.80	8.00	8.00	Pass
HT20	MCS0	1	11	2462	-15.37	-18.47		3.80	3.80	8.00	8.00	Pass
HT40	MCS0	1	3	2422	-18.55	-19.90		3.80	3.80	8.00	8.00	Pass
HT40	MCS0	1	6	2437	-18.80	-19.61		3.80	3.80	8.00	8.00	Pass
HT40	MCS0	1	9	2452	-19.05	-20.54		3.80	3.80	8.00	8.00	Pass
11b	1Mbps	2	1	2412	-15.70	-17.38	-12.69	6.8	31	7.	19	Pass
11b	1Mbps	2	6	2437	-15.20	-17.38	-12.19	6.8	31	7.	19	Pass
11b	1Mbps	2	11	2462	-15.46	-18.54	-12.45	6.8	31	7.	19	Pass
11g	6Mbps	2	1	2412	-15.28	-17.11	-12.27	6.8	31	7.	19	Pass
11g	6Mbps	2	6	2437	-16.35	-18.43	-13.34	6.8	31	7.	19	Pass
11g	6Mbps	2	11	2462	-15.84	-18.28	-12.83	6.8	31	7.	19	Pass
HT20	MCS0	2	1	2412	-16.80	-17.81	-13.79	6.8	31	7.	19	Pass
HT20	MCS0	2	6	2437	-15.69	-18.37	-12.68	6.8	31	7.	19	Pass
HT20	MCS0	2	11	2462	-15.80	-17.49 -12.79		6.8	31	7.	19	Pass
HT40	MCS0	2	3	2422	-19.16	-20.86	-16.15	6.8	31	7.	19	Pass
HT40	MCS0	2	6	2437	-17.67	-21.44	-14.66	6.81		7.19		Pass
HT40	MCS0	2	9	2452	-19.01	-20.73	-16.00	6.8	31	7.	19	Pass

Measured power density (dBm) has offset with cable loss.

Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2362.5	48.49	-25.51	74	42.69	32.56	6.48	33.24	151	261	Р	Н
		2364.18	35.89	-18.11	54	30.09	32.56	6.48	33.24	151	261	Α	Н
000 441	*	2412	96.34	-	-	90.37	32.61	6.55	33.19	151	261	Р	Н
802.11b CH 01	*	2412	94.39	-	-	88.42	32.61	6.55	33.19	151	261	Α	Н
2412MHz		2389.59	66.31	-7.69	74	60.41	32.6	6.51	33.21	160	352	Р	V
241210112		2390	44.64	-9.36	54	38.7	32.6	6.55	33.21	160	352	Α	V
	*	2412	107.45	-	-	101.48	32.61	6.55	33.19	160	352	Р	V
	*	2412	105.64	-	-	99.67	32.61	6.55	33.19	160	352	Α	V
		2359.42	48.13	-25.87	74	42.33	32.56	6.48	33.24	172	271	Р	Н
		2359.98	36.32	-17.68	54	30.52	32.56	6.48	33.24	172	271	Α	Н
	*	2437	98.83	-	-	92.74	32.65	6.59	33.15	172	271	Р	Н
	*	2437	96.73	-	-	90.64	32.65	6.59	33.15	172	271	Α	Н
		2488.59	46.87	-27.13	74	40.61	32.7	6.66	33.1	172	271	Р	Н
802.11b CH 06		2484.39	36.55	-17.45	54	30.33	32.68	6.66	33.12	172	271	Α	Н
2437MHz		2389.1	59.67	-14.33	74	53.77	32.6	6.51	33.21	151	319	Р	V
2437141112		2389.52	40.58	-13.42	54	34.68	32.6	6.51	33.21	151	319	Α	٧
	*	2437	108.63	-	-	102.54	32.65	6.59	33.15	151	319	Р	V
	*	2437	106.67	-	-	100.58	32.65	6.59	33.15	151	319	Α	V
		2494.33	58.79	-15.21	74	52.49	32.7	6.7	33.1	151	319	Р	V
		2494.05	41.7	-12.3	54	35.4	32.7	6.7	33.1	151	319	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B1 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310



	*	2462	97.15	-	-	90.99	32.67	6.63	33.14	152	316	Р	Н
	*	2462	95.6	-	-	89.44	32.67	6.63	33.14	152	316	Α	Н
200 441		2486.48	52.7	-21.3	74	46.48	32.68	6.66	33.12	152	316	Р	Н
802.11b CH 11		2484.12	36.46	-17.54	54	30.24	32.68	6.66	33.12	152	316	Α	Н
2462MHz	*	2462	107.85	-	1	101.69	32.67	6.63	33.14	151	301	Р	V
2402141112	*	2462	106.03	-	-	99.87	32.67	6.63	33.14	151	301	Α	V
		2486.48	64.6	-9.4	74	58.38	32.68	6.66	33.12	151	301	Р	V
		2483.52	43.29	-10.71	54	37.07	32.68	6.66	33.12	151	301	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7

: B2 of B15 Page Number Report Issued Date : Oct. 28, 2016 : Rev. 01 Report Version

Report No.: FR691310

No other spurious found.

Remark 2. All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		4824	49.87	-24.13	74	62.57	34.4	9.5	56.6	150	360	Р	Н
CH 01		4824	49.66	-24.34	74	62.36	34.4	9.5	56.6	150	360	Р	V
2412MHz													
000 445		4874	47.56	-26.44	74	60.48	34.43	9.56	56.91	150	360	Р	Н
802.11b CH 06		7311	47.34	-26.66	74	57.46	36.22	11.66	58	174	100	Р	Н
2437MHz		4874	50.87	-23.13	74	63.79	34.43	9.56	56.91	150	360	Р	V
2437101112		7311	48.06	-25.94	74	58.18	36.22	11.66	58	174	100	Р	V
000 441		4924	47.46	-26.54	74	59.47	34.46	9.61	56.08	150	347	Р	Н
802.11b CH 11		7386	47.96	-26.04	74	58.03	36.26	11.68	58.01	150	274	Р	Н
2462MHz		4924	49.53	-24.47	74	61.54	34.46	9.61	56.08	150	347	Р	V
2402111112		7386	47.98	-26.02	74	58.05	36.26	11.68	58.01	150	274	Р	V

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B3 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2389.38	49.45	-24.55	74	43.55	32.6	6.51	33.21	226	270	Р	Н
		2389.905	38.68	-15.32	54	32.74	32.6	6.55	33.21	226	270	Α	Н
000.44	*	2412	99.08	1	-	93.11	32.61	6.55	33.19	226	270	Р	Н
802.11g CH 01	*	2412	93.28	-	-	87.31	32.61	6.55	33.19	226	270	Α	Н
2412MHz		2389.8	62.48	-11.52	74	56.54	32.6	6.55	33.21	150	297	Р	٧
2412101112		2389.8	49.86	-4.14	54	43.92	32.6	6.55	33.21	150	297	Α	V
	*	2412	108.42	-	-	102.45	32.61	6.55	33.19	150	297	Р	V
	*	2412	102.58	-	-	96.61	32.61	6.55	33.19	150	297	Α	V
		2351.3	46.67	-27.33	74	40.91	32.54	6.48	33.26	150	270	Р	Н
		2384.76	37.16	-16.84	54	31.3	32.58	6.51	33.23	150	270	Α	Н
	*	2437	99.54	-	-	93.45	32.65	6.59	33.15	150	270	Р	Н
	*	2437	93.06	-	-	86.97	32.65	6.59	33.15	150	270	Α	Н
		2486.49	45.74	-28.26	74	39.52	32.68	6.66	33.12	150	270	Р	Н
802.11g		2485.51	36.56	-17.44	54	30.34	32.68	6.66	33.12	150	270	Α	Н
CH 06 2437MHz		2364.6	51.81	-22.19	74	46.01	32.56	6.48	33.24	176	318	Р	V
2437 WITZ		2384.76	42.8	-11.2	54	36.94	32.58	6.51	33.23	176	318	Α	V
	*	2437	109.64	-	-	103.55	32.65	6.59	33.15	176	318	Р	٧
	*	2437	103.29	-	-	97.2	32.65	6.59	33.15	176	318	Α	V
		2492.16	51.04	-22.96	74	44.74	32.7	6.7	33.1	176	318	Р	V
		2489.36	41.97	-12.03	54	35.71	32.7	6.66	33.1	176	318	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B4 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310



	*	2462	99.05	-	-	92.89	32.67	6.63	33.14	151	316	Р	Н
	*	2462	91.81	-	-	85.65	32.67	6.63	33.14	151	316	Α	Н
		2484.4	53.83	-20.17	74	47.61	32.68	6.66	33.12	151	316	Р	Н
802.11g		2483.56	40.77	-13.23	54	34.55	32.68	6.66	33.12	151	316	Α	Н
CH 11 2462MHz	*	2462	108.62	-	1	102.46	32.67	6.63	33.14	151	302	Р	V
2402141112	*	2462	101.88	-	1	95.72	32.67	6.63	33.14	151	302	Α	V
		2484.8	62.23	-11.77	74	56.01	32.68	6.66	33.12	151	302	Р	V
		2483.52	49.27	-4.73	54	43.05	32.68	6.66	33.12	151	302	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7

: B5 of B15 Page Number Report Issued Date : Oct. 28, 2016 : Rev. 01 Report Version

Report No.: FR691310

^{1.} No other spurious found.

Remark 2. All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol
Ant.	11010	Troquency	20101	Limit	Line	Level	Factor	Loss	Factor	Pos		Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)		(H/V)
802.11g		4824	47.04	-26.96	74	59.74	34.4	9.5	56.6	150	360	Р	Н
CH 01		4824	55.45	-18.55	74	68.15	34.4	9.5	56.6	150	360	Р	V
2412MHz		4824	49.63	-4.37	54	62.33	34.4	9.5	56.6	150	360	Α	٧
		4874	46.43	-27.57	74	59.35	34.43	9.56	56.91	150	360	Р	Н
802.11g		7311	48.86	-25.14	74	58.98	36.22	11.66	58	174	100	Р	Н
CH 06		4874	56.6	-17.4	74	69.52	34.43	9.56	56.91	150	360	Р	٧
2437MHz		4874	49.29	-4.71	54	62.21	34.43	9.56	56.91	150	360	Α	٧
		7311	50.56	-23.44	74	60.68	36.22	11.66	58	150	360	Р	V
		4924	46.66	-27.34	74	58.67	34.46	9.61	56.08	150	347	Р	Н
802.11g		7386	47.25	-26.75	74	57.32	36.26	11.68	58.01	150	274	Р	Н
CH 11		4924	57.7	-16.3	74	69.71	34.46	9.61	56.08	150	360	Р	٧
2462MHz		4924	49.84	-4.16	54	61.85	34.46	9.61	56.08	150	360	Α	٧
		7386	50.71	-23.29	74	60.78	36.26	11.68	58.01	150	350	Р	V

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B6 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol
	NOTE	Frequency	Level								Pos		POI.
Ant. 1+2		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)		Avg. (P/A)	(H/V)
112		2388.645	51.29	-22.71	74	45.39	32.6	6.51	33.21	227	271	P	Η
		2390	39.98	-14.02	54	34.04	32.6	6.55	33.21	227	271	Α	Н
802.11n	*	2412	99.26	-	-	93.29	32.61	6.55	33.19	227	271	Р	Н
HT20	*	2412	92.77	-	-	86.8	32.61	6.55	33.19	227	271	Α	Н
CH 01		2388.33	61.76	-12.24	74	55.86	32.6	6.51	33.21	150	307	Р	٧
2412MHz		2389.8	49.31	-4.69	54	43.37	32.6	6.55	33.21	150	307	Α	٧
	*	2412	107.55	-	-	101.58	32.61	6.55	33.19	150	307	Р	٧
	*	2412	101.08	-	-	95.11	32.61	6.55	33.19	150	307	Α	V
		2346.54	46.68	-27.32	74	40.92	32.54	6.48	33.26	215	272	Р	Н
		2384.9	37.16	-16.84	54	31.3	32.58	6.51	33.23	215	272	Α	Н
	*	2437	99.05	-	-	92.96	32.65	6.59	33.15	215	272	Р	Н
	*	2437	91.58	-	-	85.49	32.65	6.59	33.15	215	272	Α	Н
802.11n		2491.18	46.67	-27.33	74	40.37	32.7	6.7	33.1	215	272	Р	Н
HT20		2489.01	36.78	-17.22	54	30.52	32.7	6.66	33.1	215	272	Α	Н
CH 06		2383.08	51.57	-22.43	74	45.71	32.58	6.51	33.23	170	318	Р	V
2437MHz		2385.46	42.95	-11.05	54	37.09	32.58	6.51	33.23	170	318	Α	V
	*	2437	108.86	-	-	102.77	32.65	6.59	33.15	170	318	Р	٧
	*	2437	102.82	-	-	96.73	32.65	6.59	33.15	170	318	Α	V
		2492.09	51.21	-22.79	74	44.91	32.7	6.7	33.1	170	318	Р	V
		2488.87	41.87	-12.13	54	35.61	32.7	6.66	33.1	170	318	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B7 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310



	*	2462	98.9	-	-	92.74	32.67	6.63	33.14	199	298	Р	Н
	*	2462	92.68	-	-	86.52	32.67	6.63	33.14	199	298	Α	Н
802.11n		2484.72	60.16	-13.84	74	53.94	32.68	6.66	33.12	199	298	Р	Н
HT20		2483.52	43.01	-10.99	54	36.79	32.68	6.66	33.12	199	298	Α	Н
CH 11	*	2462	107.09	-	1	100.93	32.67	6.63	33.14	156	308	Р	٧
2462MHz	*	2462	101.13	-	1	94.97	32.67	6.63	33.14	156	308	Α	٧
		2484.56	61	-13	74	54.78	32.68	6.66	33.12	156	308	Р	٧
	•	2483.56	49.44	-4.56	54	43.22	32.68	6.66	33.12	156	308	Α	V

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B8 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4824	45.64	-28.36	74	58.34	34.4	9.5	56.6	150	360	P	Н
HT20		4024	45.04	-20.30	/4	36.34	34.4	9.5	50.0	130	300	Г	
CH 01		1001	40.00	07.04	7.4	50.00	0.4.4	0.5	50.0	450	000	1	,,
2412MHz		4824	46.36	-27.64	74	59.06	34.4	9.5	56.6	150	360	Р	V
802.11n		4874	45.98	-28.02	74	58.9	34.43	9.56	56.91	150	360	Р	Н
HT20		7311	48.57	-25.43	74	58.69	36.22	11.66	58	174	100	Р	Н
CH 06		4874	49.21	-24.79	74	62.13	34.43	9.56	56.91	150	360	Р	٧
2437MHz		7311	47.65	-26.35	74	57.77	36.22	11.66	58	174	100	Р	٧
802.11n		4924	46.45	-27.55	74	58.46	34.46	9.61	56.08	150	347	Р	Н
HT20		7386	47.85	-26.15	74	57.92	36.26	11.68	58.01	150	274	Р	Н
CH 11		4924	49.1	-24.9	74	61.11	34.46	9.61	56.08	150	347	Р	V
2462MHz		7386	47.51	-26.49	74	57.58	36.26	11.68	58.01	150	274	Р	V
			•		•	•							

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7

Page Number : B9 of B15 Report Issued Date : Oct. 28, 2016 Report Version : Rev. 01

Report No.: FR691310

Remark 1. No other spurious found.
2. All results are PASS again

All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)		(P/A)	(H/V)
		2387.42	48.32	-25.68	74	42.42	32.6	6.51	33.21	250	314	Р	Н
		2385.6	38.45	-15.55	54	32.55	32.6	6.51	33.21	250	314	Α	Н
	*	2422	90.56	-	-	84.51	32.63	6.59	33.17	250	314	Р	Н
	*	2422	84.62	-	-	78.57	32.63	6.59	33.17	250	314	Α	Н
802.11n		2489.43	46.71	-27.29	74	40.45	32.7	6.66	33.1	250	314	Р	Н
HT40		2484.6	37.73	-16.27	54	31.51	32.68	6.66	33.12	250	314	Α	Н
CH 03		2387	58.56	-15.44	74	52.66	32.6	6.51	33.21	150	325	Р	٧
2422MHz		2389.52	49.06	-4.94	54	43.16	32.6	6.51	33.21	150	325	Α	V
	*	2422	102.11	-	-	96.06	32.63	6.59	33.17	150	325	Р	٧
	*	2422	96.42	1	-	90.37	32.63	6.59	33.17	150	325	Α	V
		2497.69	50.28	-23.72	74	43.98	32.7	6.7	33.1	150	325	Р	٧
		2484.39	41.24	-12.76	54	35.02	32.68	6.66	33.12	150	325	Α	٧
		2331.98	46.56	-27.44	74	40.87	32.53	6.44	33.28	247	312	Р	Н
		2358.86	37.36	-16.64	54	31.56	32.56	6.48	33.24	247	312	Α	Н
	*	2437	90.01	-	-	83.92	32.65	6.59	33.15	247	312	Р	Н
	*	2437	84.38	-	-	78.29	32.65	6.59	33.15	247	312	Α	Н
802.11n		2487.05	46.43	-27.57	74	40.21	32.68	6.66	33.12	247	312	Р	Н
HT40		2484.81	37.87	-16.13	54	31.65	32.68	6.66	33.12	247	312	Α	Н
CH 06		2389.52	52.36	-21.64	74	46.46	32.6	6.51	33.21	216	307	Р	V
2437MHz		2389.38	42.91	-11.09	54	37.01	32.6	6.51	33.21	216	307	Α	V
	*	2437	102.14	-	-	96.05	32.65	6.59	33.15	216	307	Р	V
	*	2437	96.41	-	-	90.32	32.65	6.59	33.15	216	307	Α	V
		2483.55	53.91	-20.09	74	47.69	32.68	6.66	33.12	216	307	Р	V
		2484.25	43.74	-10.26	54	37.52	32.68	6.66	33.12	216	307	Α	V

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B10 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310



FCC RF Test Report No.: FR691310

	2363.62	47.16	-26.84	74	41.36	32.56	6.48	33.24	245	313	Р	Н
	2366.56	37.66	-16.34	54	31.83	32.56	6.51	33.24	245	313	Α	Н
*	2452	91.39	-	-	85.26	32.65	6.63	33.15	245	313	Р	Н
*	2452	85.15	-	-	79.02	32.65	6.63	33.15	245	313	Α	Н
	2484.04	50.7	-23.3	74	44.48	32.68	6.66	33.12	245	313	Р	Н
	2483.62	39.21	-14.79	54	32.99	32.68	6.66	33.12	245	313	Α	Н
	2386.72	50.17	-23.83	74	44.27	32.6	6.51	33.21	158	327	Р	٧
	2385.74	41.07	-12.93	54	35.17	32.6	6.51	33.21	158	327	Α	٧
*	2452	101.58	-	-	95.45	32.65	6.63	33.15	158	327	Р	٧
*	2452	95.23	-	-	89.1	32.65	6.63	33.15	158	327	Α	٧
	2484.39	63.1	-10.9	74	56.88	32.68	6.66	33.12	158	327	Р	V
	2484.81	50.3	-3.7	54	44.08	32.68	6.66	33.12	158	327	Α	V
	*	2366.56 * 2452 * 2452 2484.04 2483.62 2386.72 2385.74 * 2452 * 2452 2484.39	2366.56 37.66 * 2452 91.39 * 2452 85.15 2484.04 50.7 2483.62 39.21 2386.72 50.17 2385.74 41.07 * 2452 101.58 * 2452 95.23 2484.39 63.1	2366.56 37.66 -16.34 * 2452 91.39 - * 2452 85.15 - 2484.04 50.7 -23.3 2483.62 39.21 -14.79 2386.72 50.17 -23.83 2385.74 41.07 -12.93 * 2452 101.58 - * 2452 95.23 - 2484.39 63.1 -10.9	2366.56 37.66 -16.34 54 * 2452 91.39 - - * 2452 85.15 - - 2484.04 50.7 -23.3 74 2483.62 39.21 -14.79 54 2386.72 50.17 -23.83 74 2385.74 41.07 -12.93 54 * 2452 101.58 - - * 2452 95.23 - - 2484.39 63.1 -10.9 74	2366.56 37.66 -16.34 54 31.83 * 2452 91.39 - - 85.26 * 2452 85.15 - - 79.02 2484.04 50.7 -23.3 74 44.48 2483.62 39.21 -14.79 54 32.99 2386.72 50.17 -23.83 74 44.27 2385.74 41.07 -12.93 54 35.17 * 2452 101.58 - - 95.45 * 2452 95.23 - - 89.1 2484.39 63.1 -10.9 74 56.88	2366.56 37.66 -16.34 54 31.83 32.56 * 2452 91.39 - - 85.26 32.65 * 2452 85.15 - - 79.02 32.65 2484.04 50.7 -23.3 74 44.48 32.68 2483.62 39.21 -14.79 54 32.99 32.68 2386.72 50.17 -23.83 74 44.27 32.6 2385.74 41.07 -12.93 54 35.17 32.6 * 2452 101.58 - - 95.45 32.65 * 2452 95.23 - - 89.1 32.65 2484.39 63.1 -10.9 74 56.88 32.68	2366.56 37.66 -16.34 54 31.83 32.56 6.51 * 2452 91.39 - - 85.26 32.65 6.63 * 2452 85.15 - - 79.02 32.65 6.63 2484.04 50.7 -23.3 74 44.48 32.68 6.66 2483.62 39.21 -14.79 54 32.99 32.68 6.66 2386.72 50.17 -23.83 74 44.27 32.6 6.51 2385.74 41.07 -12.93 54 35.17 32.6 6.51 * 2452 101.58 - - 95.45 32.65 6.63 * 2452 95.23 - - 89.1 32.65 6.63 2484.39 63.1 -10.9 74 56.88 32.68 6.66	2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 * 2452 91.39 - - 85.26 32.65 6.63 33.15 * 2452 85.15 - - 79.02 32.65 6.63 33.15 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 * 2452 101.58 - - 95.45 32.65 6.63 33.15 * 2452 95.23 - - 89.1 32.65 6.63 33.12 2484.39 63.1 -10.9 74 56.88 32.68 6.66 33.12	2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 245 * 2452 91.39 - - 85.26 32.65 6.63 33.15 245 * 2452 85.15 - - 79.02 32.65 6.63 33.15 245 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 245 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 245 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 158 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 158 * 2452 101.58 - - 95.45 32.65 6.63 33.15 158 * 2452 95.23 - - 89.1 32.65 6.66 33.12 158 2484.39 63.1 -10.9 74 56.88 32.68 6.66 <t< th=""><th>2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 245 313 * 2452 91.39 - - 85.26 32.65 6.63 33.15 245 313 * 2452 85.15 - - 79.02 32.65 6.63 33.15 245 313 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 245 313 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 245 313 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 158 327 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 158 327 * 2452 101.58 - - 95.45 32.65 6.63 33.15 158 327 * 2452 95.23 - - 89.1 32.65 6.66 33.12 158 327</th><th>2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 245 313 A * 2452 91.39 - - 85.26 32.65 6.63 33.15 245 313 P * 2452 85.15 - - 79.02 32.65 6.63 33.15 245 313 A 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 245 313 P 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 245 313 A 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 158 327 P 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 158 327 A * 2452 101.58 - - 95.45 32.65 6.63 33.15 158 327 A * 2452 95.23 -</th></t<>	2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 245 313 * 2452 91.39 - - 85.26 32.65 6.63 33.15 245 313 * 2452 85.15 - - 79.02 32.65 6.63 33.15 245 313 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 245 313 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 245 313 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 158 327 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 158 327 * 2452 101.58 - - 95.45 32.65 6.63 33.15 158 327 * 2452 95.23 - - 89.1 32.65 6.66 33.12 158 327	2366.56 37.66 -16.34 54 31.83 32.56 6.51 33.24 245 313 A * 2452 91.39 - - 85.26 32.65 6.63 33.15 245 313 P * 2452 85.15 - - 79.02 32.65 6.63 33.15 245 313 A 2484.04 50.7 -23.3 74 44.48 32.68 6.66 33.12 245 313 P 2483.62 39.21 -14.79 54 32.99 32.68 6.66 33.12 245 313 A 2386.72 50.17 -23.83 74 44.27 32.6 6.51 33.21 158 327 P 2385.74 41.07 -12.93 54 35.17 32.6 6.51 33.21 158 327 A * 2452 101.58 - - 95.45 32.65 6.63 33.15 158 327 A * 2452 95.23 -

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B11 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C 2.4GHz 2400~2483.5MHz WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4844	46.01	-27.99	74	58.65	34.41	9.53	56.58	150	360	Р	Н
HT40		7266	48.3	-25.7	74	58.71	36.21	11.65	58.27	200	360	Р	Н
CH 03		4844	50.6	-23.4	74	63.24	34.41	9.53	56.58	150	360	Р	V
2422MHz		7266	48.57	-25.43	74	58.98	36.21	11.65	58.27	200	360	Р	V
802.11n		4874	45.53	-28.47	74	58.45	34.43	9.56	56.91	150	163	Р	Н
HT40		7311	48.41	-25.59	74	58.53	36.22	11.66	58	150	360	Р	Н
CH 06		4874	49.68	-24.32	74	62.6	34.43	9.56	56.91	150	163	Р	V
2437MHz		7311	48.09	-25.91	74	58.21	36.22	11.66	58	150	360	Р	V
802.11n		4904	45.57	-28.43	74	57.88	34.45	9.59	56.35	150	360	Р	Н
HT40		7356	49.38	-24.62	74	59.44	36.24	11.66	57.96	150	320	Р	Н
CH 09		4904	50.93	-23.07	74	63.24	34.45	9.59	56.35	150	360	Р	V
2452MHz		7356	48.35	-25.65	74	58.41	36.24	11.66	57.96	150	320	Р	V

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B12 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		30	26.63	-13.37	40	30.51	26.6	1.22	31.7	-	-	Р	Н
		527.61	30.56	-15.44	46	35.4	23.42	3.14	31.4	1	1	Р	Н
		579.99	30.69	-15.31	46	34.56	24.34	3.25	31.46	1	1	Р	Н
		676.99	31.69	-14.31	46	33.75	25.95	3.49	31.5	1	1	Р	Н
2.4GHz		725.49	32.28	-13.72	46	33.43	26.75	3.6	31.5	1	1	Р	Н
802.11n		773.02	35.12	-10.88	46	35.71	27.18	3.73	31.5	100	0	Р	Н
HT40		31.94	26.7	-13.3	40	31.29	25.84	1.22	31.65	-	-	Р	V
LF		214.3	29.74	-13.76	43.5	43.08	15.65	2.18	31.17	-	-	Р	V
		593.57	32.48	-13.52	46	36.23	24.45	3.29	31.49	-	-	Р	V
		676.99	33.57	-12.43	46	35.63	25.95	3.49	31.5	100	0	Р	V
		773.02	32.39	-13.61	46	32.98	27.18	3.73	31.5	1	1	Р	V
		984.48	32.35	-21.65	54	30.45	29.25	4.15	31.5	-	-	Р	V

Remark

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B13 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

^{1.} No other spurious found.

^{2.} All results are PASS against limit line.

Note symbol

	Fundamental Frequency which can be ignored. However, the level of any
*	unwanted emissions shall not exceed the level of the fundamental frequency per
	15.209(c).
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : B14 of B15
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No.: FR691310

A calculation example for radiated spurious emission is shown as below:

Report No.: FR691310

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level($dB\mu V/m$)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dB μ V) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

 SPORTON INTERNATIONAL (SHENZHEN) INC.
 Page Number
 : B15 of B15

 TEL: 86-755-8637-9589
 Report Issued Date
 : Oct. 28, 2016

 FAX: 86-755-8637-9595
 Report Version
 : Rev. 01


FCC ID: 2AJF3-E228-7 Report Template No.: BU5-FR15CWL MA Version 1.3



Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
1+2	802.11b	97.57	8.69	0.12	300Hz
1+2	802.11g	86.94	1.44	0.70	1kHz
1+2	802.11n HT20	86.19	1.35	0.74	1kHz
1+2	802.11n HT40	76.54	0.67	1.49	3kHz

802.11b Antenna 1+2



SPORTON INTERNATIONAL (SHENZHEN) INC.


TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : C1 of C3
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report Template No. : BU5-FR15CWL MA Version 1.3


Report No.: FR691310

Report No. : FR691310

802.11g Antenna 1+2




802.11n HT20 Antenna 1+2



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : C2 of C3
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01

Report No. : FR691310

802.11n HT40 Antenna 1+2



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2AJF3-E228-7 Page Number : C3 of C3
Report Issued Date : Oct. 28, 2016
Report Version : Rev. 01