

Appendix F:Frequency Stability Test & Temperature for VHF Band

Operation	Modulatio n Type	Test Conditions		Frequ	iency error (Limit	Dooult	
Mode		Voltage	Temperat ure	CH _L	CH _M	СНн	(ppm)	Result
TX-DNH	4FSK	V_N	-30	0.100	0.107	<u>0.117</u>	±5.0	PASS
TX-DNH	4FSK	Vn	-20	0.088	0.094	0.100	±5.0	PASS
TX-DNH	4FSK	Vn	-10	0.079	0.089	0.091	±5.0	PASS
TX-DNH	4FSK	Vn	0	0.075	0.079	0.085	±5.0	PASS
TX-DNH	4FSK	Vn	10	0.055	0.056	0.069	±5.0	PASS
TX-DNH	4FSK	Vn	20	0.034	0.037	0.039	±5.0	PASS
TX-DNH	4FSK	Vn	30	0.035	0.039	0.040	±5.0	PASS
TX-DNH	4FSK	Vn	40	0.053	0.059	0.061	±5.0	PASS
TX-DNH	4FSK	Vn	55	0.070	0.077	0.082	±5.0	PASS
TX-DNL	4FSK	Vn	-30	0.061	0.038	-0.090	±5.0	PASS
TX-DNL	4FSK	Vn	-20	0.055	0.031	-0.070	±5.0	PASS
TX-DNL	4FSK	Vn	-10	0.046	0.027	-0.073	±5.0	PASS
TX-DNL	4FSK	Vn	0	0.025	0.016	-0.064	±5.0	PASS
TX-DNL	4FSK	Vn	10	0.022	0.014	-0.052	±5.0	PASS
TX-DNL	4FSK	V_N	20	0.013	0.008	-0.032	±5.0	PASS
TX-DNL	4FSK	V_N	30	0.022	0.014	-0.055	±5.0	PASS
TX-DNL	4FSK	V_N	40	0.047	0.028	-0.072	±5.0	PASS
TX-DNL	4FSK	Vn	55	0.060	0.034	-0.085	±5.0	PASS



Appendix F:Frequency Stability Test & Temperature for UHF Band

Operation Mode	Modulation Type	Test Conditions		Frequency error (ppm)						Decult
		Voltage	Temperature	CH _{L1}	CH _{M1}	CH _{M2}	CH _{M3}	CH _{H1}	(ppm)	Result
TX-DNH	4FSK	Vn	-30	0.138	0.115	0.171	0.222	0.108	±5.0	PASS
TX-DNH	4FSK	Vn	-20	0.112	0.102	0.145	0.184	0.090	±5.0	PASS
TX-DNH	4FSK	Vn	-10	0.109	0.094	0.135	0.174	0.084	±5.0	PASS
TX-DNH	4FSK	Vn	0	0.091	0.081	0.116	0.149	0.072	±5.0	PASS
TX-DNH	4FSK	Vn	10	0.082	0.073	0.104	0.134	0.064	±5.0	PASS
TX-DNH	4FSK	Vn	20	0.078	0.069	0.099	0.127	0.061	±5.0	PASS
TX-DNH	4FSK	Vn	30	0.080	0.072	0.109	0.130	0.061	±5.0	PASS
TX-DNH	4FSK	Vn	40	0.144	0.135	0.197	0.152	0.107	±5.0	PASS
TX-DNH	4FSK	Vn	55	0.147	0.126	0.170	0.239	0.106	±5.0	PASS
TX-DNL	4FSK	Vn	-30	0.079	0.332	0.234	0.264	0.194	±5.0	PASS
TX-DNL	4FSK	Vn	-20	0.072	0.303	0.207	0.237	0.180	±5.0	PASS
TX-DNL	4FSK	Vn	-10	0.049	0.204	0.139	0.162	0.114	±5.0	PASS
TX-DNL	4FSK	Vn	0	0.042	0.163	0.116	0.140	0.099	±5.0	PASS
TX-DNL	4FSK	Vn	10	0.030	0.133	0.091	0.096	0.074	±5.0	PASS
TX-DNL	4FSK	Vn	20	0.018	0.074	0.051	0.059	0.043	±5.0	PASS
TX-DNL	4FSK	Vn	30	0.022	0.132	0.088	0.103	0.047	±5.0	PASS
TX-DNL	4FSK	Vn	40	0.047	0.204	0.139	0.162	0.118	±5.0	PASS
TX-DNL	4FSK	Vn	55	0.068	0.271	0.174	0.216	0.152	±5.0	PASS



Appendix G:Frequency Stability Test & Voltage for VHF Band

Operation Mode	Modulatio n Type	Test Conditions		Frequ	iency error	Limit	Daniell	
		Voltage	Temperat ure	CH _L	СНм	СНн	(ppm)	Result
TX-DNH	4FSK	Vn	Tn	0.034	0.037	0.039	±5.0	PASS
TX-DNH	4FSK	V_L	Tn	0.050	0.053	<u>0.062</u>	±5.0	PASS
TX-DNH	4FSK	Vн	Tn	0.052	0.038	0.040	±5.0	PASS
TX-DNL	4FSK	Vn	Tn	0.013	0.008	-0.032	±5.0	PASS
TX-DNL	4FSK	V_L	Tn	<u>0.022</u>	0.014	-0.055	±5.0	PASS
TX-DNL	4FSK	Vн	Tn	0.021	0.012	-0.048	±5.0	PASS




Appendix G:Frequency Stability Test & Voltage for UHF Band

Operation Mode	Modulation	Test Conditions		Frequency error (ppm)					Limit	Result
	Type	Voltage	Temperature	CH _{L1}	CH _{M1}	CH _{M2}	CH _{M3}	CH _{H1}	(ppm)	Result
TX-DNH	4FSK	Vn	Tn	0.078	0.069	0.099	0.127	0.061	±5.0	PASS
TX-DNH	4FSK	VL	Tn	0.095	0.086	0.125	<u>0.156</u>	0.075	±5.0	PASS
TX-DNH	4FSK	Vн	Tn	0.098	0.073	0.102	0.129	0.063	±5.0	PASS
TX-DNL	4FSK	Vn	Tn	0.018	0.074	0.051	0.059	0.043	±5.0	PASS
TX-DNL	4FSK	VL	Tn	0.024	0.099	0.069	0.081	0.060	±5.0	PASS
TX-DNL	4FSK	Vн	Tn	0.023	0.097	0.067	0.075	0.056	±5.0	PASS



Appendix H:Transmitter Frequency Behavior for VHF Band






Appendix H:Transmitter Frequency Behavior for UHF Band













----End of Report----



















----End of Report----