

FCC Radio Test Report

FCC ID: 2AJGR-K60PW13

Original Grant

Report No. : TB-FCC149368
Applicant : Innertainment Delivery Systems LLC
Equipment Under Test (EUT)
EUT Name : MID
Model No. : K60PW13
Series No. : N/A
Brand Name : IDS
Receipt Date : 2016-08-10
Test Date : 2016-08-11 to 2016-08-22
Issue Date : 2016-08-23
Standards : FCC Part 15, Subpart C (15.247:2015)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements

Test/Witness Engineer :

IWAN SU

**Approved &
Authorized**

:

Ray Su



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.7 Test Facility.....	8
2. TEST SUMMARY	9
3. TEST EQUIPMENT	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	19
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	45
6.1 Test Standard and Limit.....	45
6.2 Test Setup.....	45
6.3 Test Procedure.....	45
6.4 EUT Operating Condition	46
6.5 Test Data.....	46
7. BANDWIDTH TEST	62
7.1 Test Standard and Limit.....	62
7.2 Test Setup.....	62
7.3 Test Procedure.....	62
7.4 EUT Operating Condition	62
7.5 Test Data.....	63
8. PEAK OUTPUT POWER TEST.....	69
8.1 Test Standard and Limit.....	69

8.2 Test Setup.....	69
8.3 Test Procedure.....	69
8.4 EUT Operating Condition	69
8.5 Test Data.....	70
9. POWER SPECTRAL DENSITY TEST	72
9.1 Test Standard and Limit.....	72
9.2 Test Setup.....	72
9.3 Test Procedure.....	72
9.4 EUT Operating Condition	72
9.5 Test Data.....	73
10. ANTENNA REQUIREMENT.....	79
10.1 Standard Requirement.....	79
10.2 Antenna Connected Construction.....	79

1. General Information about EUT

1.1 Client Information

Applicant : Innertainment Delivery Systems LLC
Address : 162 Rosa L. Parks Blvd. Suite 1, Nashville TN 37203, USA
Manufacturer : IRL Tech Industrial Group Co.,Ltd
Address : 3/F, Building C, No. 52 Huangpu Road, Shangliao Community, Shajing Street, Boan District, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	MID
Models No.	:	K60PW13
Model Difference	:	N/A
Product Description		Operation Frequency: 802.11b/g/n(HT20): 2412MHz~2462MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels see note(3)
	RF Output Power:	802.11b: 9.27 dBm 802.11g: 9.14 dBm 802.11n (HT20): 9.12 dBm
	Antenna Gain:	1.26 dBi FPC Antenna
	Modulation Type:	802.11b: CCK, QPSK, BPSK 802.11g: OFDM 802.11n: OFDM
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Supply	:	DC Voltage supplied from Adapter. DC power by Li-ion Battery.
Power Rating	:	AC/DC Adapter: Input: 100~240V, 50/60Hz, 0.4A Output: 5.0V, 2A DC 3.7V by Li-ion Battery.
Connecting I/O Port(S)	:	Please refer to the User's Manual

Note:

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r05.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or

the User's Manual.


(3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

The EUT has been test as an independent unit

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 3	TX Mode B Mode Channel 01/06/11
Mode 4	TX Mode G Mode Channel 01/06/11
Mode 5	TX Mode N(HT20) Mode Channel 01/06/11

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK (1 Mbps)
802.11g Mode: OFDM (6 Mbps)
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	Ampak RF Test Tool VER:5.3		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.7 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: “/” for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 20, 2016	Mar. 19, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 20, 2016	Mar. 19, 2017
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 19, 2016	Mar. 18, 2017
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 19, 2016	Mar. 18, 2017
Pre-amplifier	Sonoma	310N	185903	Mar. 20, 2016	Mar. 19, 2017
Pre-amplifier	HP	8447B	3008A00849	Mar. 26, 2016	Mar. 25, 2017
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 26, 2016	Mar. 25, 2017
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please see the next page.

EUT:	MID	Model Name :	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	45.07	9.92	54.99	65.99	-11.00	QP
2		0.1500	26.60	9.92	36.52	55.99	-19.47	AVG
3		0.1900	39.66	10.00	49.66	64.03	-14.37	QP
4		0.1900	21.06	10.00	31.06	54.03	-22.97	AVG
5		0.2420	37.43	10.02	47.45	62.02	-14.57	QP
6		0.2420	19.92	10.02	29.94	52.02	-22.08	AVG
7		0.3020	29.15	10.02	39.17	60.19	-21.02	QP
8		0.3020	12.80	10.02	22.82	50.19	-27.37	AVG
9		0.3339	30.56	10.02	40.58	59.35	-18.77	QP
10		0.3339	13.90	10.02	23.92	49.35	-25.43	AVG
11		0.3980	27.77	10.02	37.79	57.89	-20.10	QP
12		0.3980	12.22	10.02	22.24	47.89	-25.65	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model Name :	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	49.36	10.12	59.48	65.99	-6.51	QP
2		0.1500	30.70	10.12	40.82	55.99	-15.17	AVG
3		0.1940	44.39	10.12	54.51	63.86	-9.35	QP
4		0.1940	25.84	10.12	35.96	53.86	-17.90	AVG
5		0.2460	41.07	10.10	51.17	61.89	-10.72	QP
6		0.2460	22.10	10.10	32.20	51.89	-19.69	AVG
7		0.2900	36.31	10.09	46.40	60.52	-14.12	QP
8		0.2900	18.56	10.09	28.65	50.52	-21.87	AVG
9		0.3339	33.80	10.08	43.88	59.35	-15.47	QP
10		0.3339	14.57	10.08	24.65	49.35	-24.70	AVG
11		0.3899	30.32	10.06	40.38	58.06	-17.68	QP
12		0.3899	12.98	10.06	23.04	48.06	-25.02	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model Name :	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Line		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	35.47	10.12	45.59	65.99	-20.40	QP
2		0.1500	19.75	10.12	29.87	55.99	-26.12	AVG
3		0.1940	32.04	10.12	42.16	63.86	-21.70	QP
4		0.1940	21.18	10.12	31.30	53.86	-22.56	AVG
5		0.2380	28.35	10.11	38.46	62.16	-23.70	QP
6		0.2380	15.02	10.11	25.13	52.16	-27.03	AVG
7	*	0.4220	27.24	10.05	37.29	57.41	-20.12	QP
8		0.4220	16.06	10.05	26.11	47.41	-21.30	AVG
9		1.4020	23.47	10.12	33.59	56.00	-22.41	QP
10		1.4020	12.07	10.12	22.19	46.00	-23.81	AVG
11		7.4260	22.73	10.07	32.80	60.00	-27.20	QP
12		7.4260	12.54	10.07	22.61	50.00	-27.39	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model Name :	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Neutral		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	35.90	10.12	46.02	65.99	-19.97	QP
2		0.1500	17.94	10.12	28.06	55.99	-27.93	AVG
3		0.1900	32.79	10.12	42.91	64.03	-21.12	QP
4		0.1900	16.55	10.12	26.67	54.03	-27.36	AVG
5		0.2380	28.43	10.11	38.54	62.16	-23.62	QP
6		0.2380	12.74	10.11	22.85	52.16	-29.31	AVG
7		1.0820	19.06	10.15	29.21	56.00	-26.79	QP
8		1.0820	8.77	10.15	18.92	46.00	-27.08	AVG
9		3.4540	23.06	10.06	33.12	56.00	-22.88	QP
10		3.4540	10.73	10.06	20.79	46.00	-25.21	AVG
11		6.7060	23.59	10.06	33.65	60.00	-26.35	QP
12		6.7060	11.39	10.06	21.45	50.00	-28.55	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class A (dBUV/m)(at 3 M)		Class B (dBUV/m)(at 3 M)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBUV/m)=20log Emission Level(uV/m)

5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		87.7248	47.38	-22.87	24.51	40.00	-15.49	peak
2		133.6188	50.59	-21.99	28.60	43.50	-14.90	peak
3		191.7450	49.66	-20.45	29.21	43.50	-14.29	peak
4		239.9874	49.29	-18.18	31.11	46.00	-14.89	peak
5		463.9696	38.76	-11.48	27.28	46.00	-18.72	peak
6	*	721.7259	48.62	-6.00	42.62	46.00	-3.38	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	46.6664	60.07	-23.10	36.97	40.00	-3.03	peak
2	!	57.3922	59.49	-24.58	34.91	40.00	-5.09	peak
3		87.7248	50.38	-22.87	27.51	40.00	-12.49	peak
4		197.8925	51.83	-20.10	31.73	43.50	-11.77	peak
5		239.9874	52.29	-18.18	34.11	46.00	-11.89	peak
6	!	721.7259	48.12	-6.00	42.12	46.00	-3.88	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		78.1389	57.36	-23.40	33.96	40.00	-6.04	peak
2		195.1365	54.95	-20.26	34.69	43.50	-8.81	peak
3		239.9874	52.57	-18.18	34.39	46.00	-11.61	peak
4		281.0074	56.26	-17.02	39.24	46.00	-6.76	peak
5		446.4141	47.22	-12.05	35.17	46.00	-10.83	peak
6	*	721.7259	48.01	-6.00	42.01	46.00	-3.99	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	!	48.5016	59.56	-23.87	35.69	40.00	-4.31	peak
2	*	77.0502	59.16	-23.44	35.72	40.00	-4.28	peak
3		169.5988	55.90	-20.88	35.02	43.50	-8.48	peak
4		280.0237	51.99	-17.05	34.94	46.00	-11.06	peak
5		483.9094	45.31	-11.14	34.17	46.00	-11.83	peak
6	!	721.7259	47.73	-6.07	41.66	46.00	-4.34	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		83.8156	47.37	-23.11	24.26	40.00	-15.74	peak
2		189.7384	51.34	-20.54	30.80	43.50	-12.70	peak
3		203.5226	48.59	-19.84	28.75	43.50	-14.75	peak
4		239.9874	47.81	-18.18	29.63	46.00	-16.37	peak
5		463.9696	49.19	-11.48	37.71	46.00	-8.29	peak
6	*	721.7259	45.30	-6.00	39.30	46.00	-6.70	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		43.9658	53.72	-21.97	31.75	40.00	-8.25	peak
2		54.0711	53.61	-24.54	29.07	40.00	-10.93	peak
3		66.9668	56.45	-23.97	32.48	40.00	-7.52	peak
4		78.9651	53.81	-23.38	30.43	40.00	-9.57	peak
5		463.9696	46.22	-11.48	34.74	46.00	-11.26	peak
6	*	721.7259	47.03	-6.07	40.96	46.00	-5.04	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4824.435	31.52	13.50	45.02	54.00	-8.98	AVG
2		4824.507	43.58	13.50	57.08	74.00	-16.92	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.010	31.87	13.50	45.37	54.00	-8.63	AVG
2		4824.528	43.29	13.50	56.79	74.00	-17.21	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.454	32.33	13.86	46.19	54.00	-7.81	AVG
2		4873.688	43.64	13.86	57.50	74.00	-16.50	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.072	43.08	13.86	56.94	74.00	-17.06	peak
2	*	4875.047	31.55	13.87	45.42	54.00	-8.58	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.526	32.00	14.15	46.15	54.00	-7.85	AVG
2		4924.732	43.86	14.15	58.01	74.00	-15.99	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.081	43.64	14.15	57.79	74.00	-16.21	peak
2	*	4924.240	32.04	14.15	46.19	54.00	-7.81	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4824.387	31.61	13.56	45.17	54.00	-8.83	AVG
2		4825.194	42.96	13.57	56.53	74.00	-17.47	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4825.176	42.71	13.57	56.28	74.00	-17.72	peak
2	*	4825.353	31.27	13.57	44.84	54.00	-9.16	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.318	43.31	13.86	57.17	74.00	-16.83	peak
2	*	4875.029	32.20	13.87	46.07	54.00	-7.93	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4872.539	43.36	13.85	57.21	74.00	-16.79	peak
2	*	4874.942	31.88	13.86	45.74	54.00	-8.26	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.667	43.95	14.15	58.10	74.00	-15.90	peak
2	*	4925.494	32.06	14.16	46.22	54.00	-7.78	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.274	43.92	14.15	58.07	74.00	-15.93	peak
2	*	4923.892	32.26	14.15	46.41	54.00	-7.59	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4824.342	31.33	13.56	44.89	54.00	-9.11	AVG
2		4824.588	42.77	13.56	56.33	74.00	-17.67	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.016	31.31	13.56	44.87	54.00	-9.13	AVG
2		4824.027	42.55	13.56	56.11	74.00	-17.89	peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.726	43.63	13.86	57.49	74.00	-16.51	peak
2	*	4874.882	31.89	13.86	45.75	54.00	-8.25	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4872.503	43.84	13.85	57.69	74.00	-16.31	peak
2	*	4872.503	30.85	13.85	44.70	54.00	-9.30	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4922.905	43.93	14.14	58.07	74.00	-15.93	peak
2	*	4924.201	31.91	14.15	46.06	54.00	-7.94	AVG

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4922.746	32.29	14.14	46.43	54.00	-7.57	AVG
2		4923.274	44.46	14.15	58.61	74.00	-15.39	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit


6.1.1 Test Standard

FCC Part 15.209 FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3 M)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	44.25	0.77	45.02	74.00	-28.98	peak
2		2390.000	31.88	0.77	32.65	54.00	-21.35	AVG
3	*	2412.900	87.79	0.86	88.65	Fundamental Frequency		AVG
4	X	2413.100	92.37	0.86	93.23	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.88	0.77	43.65	74.00	-30.35	peak
2		2390.000	31.24	0.77	32.01	54.00	-21.99	AVG
3	X	2411.100	86.14	0.86	87.00	Fundamental Frequency		peak
4	*	2411.400	81.57	0.86	82.43	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2462.700	82.49	1.08	83.57	Fundamental Frequency		AVG
2	X	2463.000	87.25	1.08	88.33	Fundamental Frequency		peak
3		2483.500	44.10	1.17	45.27	74.00	-28.73	peak
4		2483.500	31.04	1.17	32.21	54.00	-21.79	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2461.300	88.31	1.07	89.38	Fundamental Frequency		AVG
2	X	2463.000	92.80	1.08	93.88	Fundamental Frequency		peak
3		2483.500	44.69	1.17	45.86	74.00	-28.14	peak
4		2483.500	31.85	1.17	33.02	54.00	-20.98	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.66	0.77	44.43	74.00	-29.57	peak
2		2390.000	32.36	0.77	33.13	54.00	-20.87	AVG
3	*	2411.200	76.61	0.86	77.47	Fundamental Frequency		AVG
4	X	2418.100	84.95	0.89	85.84	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.66	0.77	44.43	74.00	-29.57	peak
2		2390.000	32.36	0.77	33.13	54.00	-20.87	AVG
3	*	2411.200	73.11	0.86	73.97	Fundamental Frequency		AVG
4	X	2418.100	84.95	0.89	85.84	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1	X	2455.900	85.70	1.05	86.75	Fundamental Frequency	peak
2	*	2468.400	78.47	1.11	79.58	Fundamental Frequency	AVG
3		2483.500	53.58	1.17	54.75	74.00	-19.25 peak
4		2483.500	38.73	1.17	39.90	54.00	-14.10 AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2456.100	88.09	1.05	89.14	Fundamental Frequency		peak
2	*	2468.200	76.23	1.11	77.34	Fundamental Frequency		AVG
3		2483.500	53.41	1.17	54.58	74.00	-19.42	peak
4		2483.500	34.09	1.17	35.26	54.00	-18.74	AVG

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	47.71	0.77	48.48	74.00	-25.52	peak
2		2390.000	35.17	0.77	35.94	54.00	-18.06	AVG
3	*	2412.800	80.85	0.86	81.71	Fundamental Frequency		AVG
4	X	2413.300	91.00	0.86	91.86	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	44.00	0.77	44.77	74.00	-29.23	peak
2		2390.000	32.35	0.77	33.12	54.00	-20.88	AVG
3	*	2411.000	76.57	0.86	77.43	Fundamental Frequency		AVG
4	X	2411.300	84.98	0.86	85.84	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2455.800	78.13	1.05	79.18	Fundamental Frequency		AVG
2	X	2461.700	84.84	1.07	85.91	Fundamental Frequency		peak
3		2483.500	60.06	1.17	61.23	74.00	-12.77	peak
4		2483.500	38.30	1.17	39.47	54.00	-14.53	AVG

Emission Level= Read Level+ Correct Factor

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2461.100	76.62	1.06	77.68	Fundamental Frequency		peak
2	*	2461.700	86.59	1.07	87.66	Fundamental Frequency		peak
3		2483.500	46.74	1.17	47.91	74.00	-26.09	peak
4		2483.500	33.74	1.17	34.91	54.00	-19.09	AVG



Emission Level= Read Level+ Correct Factor

(2) Conducted Test



EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programmed in continuously transmitting mode		



7. Bandwidth Test

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup



7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

7.5 Test Data

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11B Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	9.282	13.7679	>=0.5
2437	9.379	13.7546	
2462	8.763	13.7605	

802.11B Mode

2412 MHz

Agilent10:52:32 Aug 22, 2016

Ref 15 dBm

Atten 25 dB

#Peak

Log

10

dB/

Offst

1

dB

Center

2.412000000 GHz

Center 2.412 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 20 MHz

Sweep 4 ms (401 pts)

Occupied Bandwidth

13.7679 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Transmit Freq Error


68.613 kHz

x dB Bandwidth

9.282 MHz


802.11B Mode

2437 MHz




802.11B Mode

2462 MHz




802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.541	17.6615	>=0.5
2437	17.560	17.6697	
2462	17.317	17.6542	

802.11N(HT20) Mode

2412 MHz

Agilent10:58:18 Aug 22, 2016

Ref 15 dBm

#Atten 25 dB

#Peak

Log

10

dB/

Offst


1

dB

→

Ref Level

15.00 dBm



Center 2.412 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 20 MHz

Sweep 4 ms (401 pts)

Occupied Bandwidth

17.6615 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Transmit Freq Error


54.078 kHz

x dB Bandwidth

17.541 MHz


802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



8. Peak Output Power Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v03r05.

The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data


EUT:	MID	Model Name :	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	9.23	30
	2437	9.27	
	2462	9.21	
802.11g	2412	9.09	
	2437	9.12	
	2462	9.14	
802.11n (HT20)	2412	9.11	
	2437	9.09	
	2462	9.12	
Result: PASS			

Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
Please see below plots		


802.11 B Mode 2412 MHz



802.11 G Mode 2412 MHz



802.11 N(HT20) Mode 2412 MHz



9. Power Spectral Density Test

9.1 Test Standard and Limit

9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v03r05.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

9.5 Test Data

EUT:	MID	Model:	K60PW13
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Test Mode:	TX 802.11B Mode		
Channel Frequency (MHz)		Power Density (3 kHz/dBm)	Limit (dBm)
2412		-13.44	8
2437		-11.90	
2462		-13.19	
802.11B Mode			
2412 MHz			

Agilent11:11:38 Aug 22, 2016

Ref 15 dBm

#Atten 25 dB

Mkr1 2.4129000 GHz
-13.44 dBm

Peak

Log

10

dB/

Offst

1

dB

Marker

2.412900000 GHz

-13.44 dBm

M1 S2

S3 FC

AA



Center 2.412 GHz


#Res BW 3 kHz

#VBW 10 kHz

Sweep 1.715 s (401 pts)


Span 15 MHz






802.11G Mode


2437 MHz



802.11G Mode


2462 MHz






802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 1.26 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a FPC Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna