

# Test Report of FCC CFR 47 Part 15 Subpart B

## On Behalf of

### SHENZHEN HAOHUITONG TECHNOLOGY LTD.

6F Jianda Building, 10# Keyuan Road, Nanshan High-Tech Park, Nanshan,  
Shenzhen, 518053, China

Product Name:	<b>MVOICE SPEAKERPHONE</b>
Model/Type No.:	<b>MVOICE 5000</b>
Trade Mark:	<b>MVOICE</b>
FCC ID:	<b>2AJJA-MVE5000</b>
Prepared By:	<b>Shenzhen Hongcai Testing Technology Co., Ltd.</b> 1st-3rd Floor, Building C, Shuanghuan Xin Yi Dai Hi-Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen, Guangdong, China Tel: +86-755-86337020 Fax: +86-755-86337028
Report Number:	HCT16GR184E
Tested Date:	August 3~31, 2016
Issued Date:	August 31, 2016
Tested By:	Jerry Zhao/ <i>Jerry Zhao</i>

Reviewed By:

*Owen Yang*

Approved By:

*Tony Wu*

Owen.Yang


EMC Technical Supervisor

Tony Wu

EMC Technical Manager

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
1.2 TEST STANDARDS.....	4
1.3 TEST FACILITY.....	4
<b>2. SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
2.1 EUT CONFIGURATION .....	5
2.2 SUPPORT EQUIPMENTS .....	5
2.3 GENERAL TEST PROCEDURES.....	5
2.4 MEASUREMENT UNCERTAINTY .....	5
2.5 LIST OF MEASURING EQUIPMENTS USED .....	6
<b>3. SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>4. TEST OF AC POWER LINE CONDUCTED EMISSION .....</b>	<b>7</b>
4.1 LIMIT OF AC POWER LINE CONDUCTED EMISSION .....	7
4.2 EUT SETUP .....	7
4.3 INSTRUMENT SETUP.....	8
4.4 TEST PROCEDURE .....	8
4.5 TEST RESULT .....	8
<b>5 - RADIATED DISTURBANCES .....</b>	<b>11</b>
5.1 LIMIT OF RADIATED DISTURBANCES .....	11
5.2 EUT SETUP .....	11
5.3 TEST RECEIVER SETUP .....	12
5.4 TEST PROCEDURE .....	12
5.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	12
5.6 RADIATED EMISSIONS TEST RESULT .....	12



## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant:	SHENZHEN HAOHUITONG TECHNOLOGY LTD.
Address of Applicant:	6F Jianda Building,10# Keyuan Road, Nanshan High-Tech Park, Nanshan, Shenzhen, 518053, China
Manufacturer :	SHENZHEN HAOHUITONG TECHNOLOGY LTD.
Address of manufacturer:	6F Jianda Building,10# Keyuan Road, Nanshan High-Tech Park, Nanshan, Shenzhen, 518053, China

#### General Description of E.U.T

Items	Description
EUT Description:	MVOICE SPEAKERPHONE
Model No.:	MVOICE 5000
Trade Mark:	MVOICE
Rated Voltage:	Input: DC 5V/1A from micro USB

Remark: \* The test data gathered are from the production sample provided by the manufacturer.

## 1.2 Test Standards

The report of EUT is prepared in accordance with FCC Rules and Regulations Part 15 Subpart B ,  
The objective of the manufacturer is to demonstrate compliance with the described above standards.


## 1.3 Test Facility

All measurement required was performed at laboratory of Shenzhen CTL Testing Technology Co., Ltd. at Floor 1-A,Baisha Technology Park,No.3011,Shahexi Road, Nanshan District, Shenzhen, China 518055.

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC – Registration No.: 970318**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December, 2013.



## 2. SYSTEM TEST CONFIGURATION

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 Support Equipments

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

Support equipments or special accessories in test configuration:

AUX Description:	Manufacturer	Model No.	Certificate	CABLE
Laptop	DELL	INSPIRON 3420	CE,FCC	1.5m Unshielded Power Cord with core

### 2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

### 2.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

## 2.5 List of Measuring Equipments Used

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Last Calculator	Due Calculator
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2016-7-25	2017-8-24
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2015-11-1	2016-10-31
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2016-7-25	2017-8-24
4	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2016-7-25	2017-8-24
5	BCT-EMC021	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2015-11-1	2016-10-31
6	BCT-EMC026	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2016-7-25	2017-8-24
7	BCT-EMC029	6DB Attenuator	FRANKONIA	N/A	1001698	2016-7-25	2017-8-24
8	BCT-EMC032	10dB attenuator	ELECTRO-METRICS	EM-7600	836	2016-7-25	2017-8-24
9	BCT-EMC036	Spectrum Analyzer	R&S	FSP	100397	2015-11-1	2016-10-31
10	BCT-EMC037	Broadband preamplifier	SCHWARZBECK	BBV9718	9718-182	2016-7-25	2017-8-24
11	BCT-EMC039	Horn Antenna	SCHWARZBECK	BBHA 9120D	0437	2016-7-25	2017-8-24
12	BCT-EMC038	Horn Antenna	SCHWARZBECK	BBHA9170	0483	2016-7-25	2017-8-24

## 3. SUMMARY OF TEST RESULTS

Standard	Test Items	Result
FCC Part 15 Subpart B	Conduction Emission 0.15MHz to 30MHz	Pass
FCC Part 15 Subpart B	Radiation Emission 30MHz to 1000MHz	Pass

## 4. TEST OF AC POWER LINE CONDUCTED EMISSION

### 4.1 Limit of AC Power Line Conducted Emission

Frequency Range (MHz)	Limits ( dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

### 4.2 EUT Setup


The setup of EUT is according with ANSI C63.4-2009 measurement procedure. The specification used was the FCC Rules and Regulations Part 15 Subpart B limits.

The EUT was placed center and the back edge of the test table.

The AV cables were draped along the test table and bundled to 30-40cm in the middle.

The spacing between the peripherals was 10 cm.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.



Remark: The EUT was connected to a 120VAC/ 60Hz power source.

### 4.3 Instrument Setup

The test receiver was set with the following configurations:

Test Receiver Setting:

Frequency Range.....150 KHz to 30 MHz  
Detector.....Peak & Quasi-Peak & Average  
Sweep Speed.....Auto  
IF Band Width.....9 KHz

### 4.4 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first Artificial Mains.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.

All data was recorded in the peak detection mode. Quasi-peak and Average readings were only performed when an emission was found to be marginal (within -10 dB $\mu$ V of specification limits). Quasi-peak readings are distinguished with a "QP". Average readings are distinguished with a "AV".

### 4.5 Test Result

Temperature ( °C ) : 22~23	EUT: MVOICE SPEAKERPHONE
Humidity (%RH ) : 50~54	M/N: MVOICE 5000
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Normal operation

**PASS**




## Conducted Emission:

EUT: MVOICE SPEAKERPHONE  
M/N: MVOICE 5000  
Operating Condition: Normal operation  
Test Site: Shielded Room  
Operator: LV  
Test Specification: DC 5V/1A from micro USB  
Comment: L Line

### SCAN TABLE: "Voltage (150K-30M) FIN"

Short Description: 150K-30M Voltage



### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
3.340000	38.20	12.7	56	17.8	QP	L1	GND
4.050000	39.50	13.3	56	16.5	QP	L1	GND
4.190000	39.80	13.3	56	16.2	QP	L1	GND
4.550000	39.40	13.4	56	16.6	QP	L1	GND
4.565000	39.40	13.4	56	16.6	QP	L1	GND
4.675000	39.60	13.4	56	16.4	QP	L1	GND

### MEASUREMENT RESULT:


Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.390000	31.10	11.0	48	17.0	AV	L1	GND
1.170000	31.10	11.1	46	14.9	AV	L1	GND
1.950000	31.80	13.2	46	14.2	AV	L1	GND
2.565000	29.90	12.7	46	16.1	AV	L1	GND
4.680000	32.90	13.4	46	13.1	AV	L1	GND
6.930000	31.80	13.4	50	18.2	AV	L1	GND

## Conducted Emission:

EUT: MVOICE SPEAKERPHONE  
M/N: MVOICE 5000  
Operating Condition: Normal operation  
Test Site: Shielded Room  
Operator: LV  
Test Specification: DC 5V/1A from micro USB  
Comment: N Line

### SCAN TABLE: "Voltage (150K-30M) FIN"

Short Description: 150K-30M Voltage



### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
3.340000	37.70	12.7	56	18.3	QP	N	GND
3.660000	38.20	13.0	56	17.8	QP	N	GND
4.010000	39.30	13.3	56	16.7	QP	N	GND
4.745000	38.40	13.4	56	17.6	QP	N	GND
4.865000	39.10	13.5	56	16.9	QP	N	GND
4.975000	37.10	13.5	56	18.9	QP	N	GND

### MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
1.170000	29.30	11.1	46	16.7	AV	N	GND
1.950000	30.80	13.2	46	15.2	AV	N	GND
2.120000	27.80	13.1	46	18.2	AV	N	GND
2.565000	29.30	12.7	46	16.7	AV	N	GND
4.625000	32.70	13.4	46	13.3	AV	N	GND
5.405000	32.60	13.1	50	17.4	AV	N	GND

## 5 - RADIATED DISTURBANCES

### 5.1 Limit of Radiated Disturbances

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB $\mu$ V/m)
30 ~ 88	3	40
88~216	3	43.5
216 ~ 960	3	46
960 ~ 1000	3	54

Note:

(1) The tighter limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.


### 5.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15 Subpart B limits.

The EUT was placed on the center of the test table.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

Below 1 GHz



### 5.3 Test Receiver Setup

According to FCC Part 15 rule, the frequency was investigated from 30 to 1000 MHz. During the radiated emission test, the test receiver was set with the following configurations:

Test Receiver Setting:

Detector.....Peak & Quasi-Peak  
IF Band Width.....120KHz  
Frequency Range.....30MHz to 1000MHz  
Turntable Rotated.....0 to 360 degrees

Antenna Position:

Height.....1m to 4m  
Polarity.....Horizontal and Vertical

### 5.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -10 dB $\mu$ V of specification limits), and are distinguished with a "QP" in the data table.

### 5.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Subpart B. The equation for margin calculation is as follows:

Margin = Limit – Corr. Ampl.

### 5.6 Radiated Emissions Test Result

Temperature ( °C ) : 22~23	EUT: MVOICE SPEAKERPHONE
Humidity (%RH) : 50~54	M/N: MVOICE 5000
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Normal operation


**PASS**

## Radiated Emission Test Data (30~1000M):

EUT: MVOICE SPEAKERPHONE  
M/N: MVOICE 5000  
Operating Condition: Normal operation  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 5V/1A from micro USB  
Comment: Polarization: Horizontal

### ***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency 30.0 MHz	Frequency 1.0 GHz	MaxPeak	Coupled	100 kHz	9163-2015



### ***MEASUREMENT RESULT:***


Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
169.680000	30.60	12.6	40.0	9.4	QP	100.0	0.00	HORIZONTAL
191.020000	36.70	13.6	40.0	3.3	QP	100.0	0.00	HORIZONTAL
206.540000	32.60	14.1	40.0	7.4	QP	100.0	0.00	HORIZONTAL
229.820000	32.00	13.4	40.0	8.0	QP	100.0	0.00	HORIZONTAL
491.720000	38.00	19.4	47.0	9.0	QP	100.0	0.00	HORIZONTAL
924.340000	38.40	25.8	47.0	8.6	QP	100.0	0.00	HORIZONTAL

## Radiated Emission Test Data (30~1000M):

EUT: MVOICE SPEAKERPHONE  
M/N: MVOICE 5000  
Operating Condition: Normal operation  
Test Site: 3m CHAMBER  
Operator: Chen  
Test Specification: DC 5V/1A from micro USB  
Comment: Polarization: Vertical

### ***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency 30.0 MHz	Frequency 1.0 GHz	MaxPeak	Coupled	100 kHz	9163-2015



### ***MEASUREMENT RESULT:***

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
37.760000	28.30	13.7	40.0	11.7	QP	100.0	0.00	VERTICAL
55.220000	26.70	15.1	40.0	13.3	QP	100.0	0.00	VERTICAL
169.680000	29.80	12.6	40.0	10.2	QP	100.0	0.00	VERTICAL
191.020000	33.00	13.6	40.0	7.0	QP	100.0	0.00	VERTICAL
551.860000	32.30	20.5	47.0	14.7	QP	100.0	0.00	VERTICAL
992.240000	38.40	25.9	47.0	8.6	QP	100.0	0.00	VERTICAL