

FCC Part 15B

Measurement and Test Report

For

Shenzhen Qianhai Gole Technology Co., Ltd.

Rm 402, Bldg 29th, Wisdomland Park, Guankou 2nd Road, Nantou,

Nanshan Distirct, Shenzhen, China

FCC ID: 2AJKL-GOLE1

Test Rule(s): FCC Part 15 Subpart B

Product Description: Mini PC

Tested Model: GOLE1

Report No.: STR16088052I-4

Tested Date: 2016-08-06 to 2016-11-03

Issued Date: 2016-11-04

Tested By: Neil Wang / Engineer

Neil Wong.

Reviewed By: Silin Chen / EMC Manager

Silin chen

Approved & Authorized By: Jandy So / PSQ Manager

Jandyso

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND OPERATION MODE	5
1.6 MEASUREMENT UNCERTAINTY	5
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. CONDUCTED EMISSIONS	8
3.1 TEST PROCEDURE.....	8
3.2 BASIC TEST SETUP BLOCK DIAGRAM.....	8
3.3 ENVIRONMENTAL CONDITIONS	8
3.4 SUMMARY OF TEST RESULTS/PLOTS	8
3.5 CONDUCTED EMISSIONS TEST DATA.....	9
4. RADIATED EMISSIONS	11
4.1 TEST PROCEDURE.....	11
4.2 TEST RECEIVER SETUP	12
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
4.4 ENVIRONMENTAL CONDITIONS	12
4.5 SUMMARY OF TEST RESULTS/PLOTS	12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Qianhai Gole Technology Co., Ltd.
Address of applicant: Rm 402, Bldg 29th, Wisdomland Park, Guankou 2nd Road, Nantou, Nanshan Distirct, Shenzhen, China

Manufacturer: Shenzhen Qianhai Gole Technology Co., Ltd.
Address of manufacturer: Rm 402, Bldg 29th, Wisdomland Park, Guankou 2nd Road, Nantou, Nanshan Distirct, Shenzhen, China

General Description of EUT	
Product Name:	Mini PC
Brand Name:	GOLE
Model No.:	GOLE1
Adding Model(s):	GOLE2, GOLE3, GOLE5, F1, F2, F3, F4, F5
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model GOLE1, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Rated Voltage:	DC 3.7V by battery
Battery Capacity:	2600mAh
Rated Power:	/
Power Adapter Model:	KA24-0503000EU I/P: AC100-240V, 50/60Hz; O/P: DC 5V/3A
Lowest Internal Frequency:	32.768kHz
Highest Internal Frequency:	1.84GHz

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Qianhai Gole Technology Co., Ltd. in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging & Working	Connected to Monitor with HDMI, USB Disk, Mouse, Keyboard, Network
TM2	/	/

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
DC Cable	1.0	Unshielded	Without Core

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Monitor	Dell	/	/
USB Disk	Kinston	/	/
Mouse	Dell	/	/
Keyboard	Dell	/	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Mouse Cable	1.5	Unshielded	Without Core
Keyboard Cable	1.5	Unshielded	Without Core
HDMI Cable	1.0	Shielded	Without Core
RJ45 Cabel	4.0	Shielded	Without Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant


N/A: not applicable

3. Conducted Emissions

3.1 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.2 Basic Test Setup Block Diagram



3.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.4 Summary of Test Results/Plots

According to the data in section 3.6, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:


-1.94 dB at 2.7100 MHz in the Line, QP detector, 0.15-30MHz

3.5 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Mini PC
 Tested Model: GOLE1
 Operating Condition: TM1
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1955	49.83	9.50	59.33	63.80	-4.47	QP
2	0.1980	27.85	9.50	37.35	53.69	-16.34	AVG
3	1.4020	22.03	9.74	31.77	46.00	-14.23	AVG
4	1.4300	39.58	9.74	49.32	56.00	-6.68	QP
5*	2.7180	43.13	9.92	53.05	56.00	-2.95	QP
6	2.7180	26.08	9.92	36.00	46.00	-10.00	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1940	32.18	5.81	37.99	53.86	-15.87	AVG
2	0.2260	52.96	5.80	58.76	62.59	-3.83	QP
3	0.4700	43.47	5.80	49.27	56.51	-7.24	QP
4	0.4700	27.86	5.80	33.66	46.51	-12.85	AVG
5*	2.7100	48.34	5.72	54.06	56.00	-1.94	QP
6	2.7300	33.79	5.72	39.51	46.00	-6.49	AVG


4. Radiated Emissions

4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.2 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.4 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

4.5 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:


-2.53 dB at 726.8052 MHz in the Horizontal polarization, TM1 Mode, 30MHz to 9.2 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the external antenna was manipulated. Then the worst case position data was reported.

Plot of Radiated Emissions Test Data


EUT: Mini PC
Tested Model: GOLE1
Operating Condition: TM1
Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.0251	26.28	5.04	31.32	40.00	-8.68	45	100	QP
2	164.9074	33.90	2.44	36.34	43.50	-7.16	68	100	QP
3	339.5887	31.28	11.38	42.66	46.00	-3.34	45	100	QP
4	482.2155	29.64	12.65	42.29	46.00	-3.71	129	100	QP
5	595.1327	23.85	17.85	41.70	46.00	-4.30	246	100	QP
6	726.8052	25.25	18.22	43.47	46.00	-2.53	45	100	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	59.6492	24.96	5.03	29.99	40.00	-10.01	54	100	QP
2	121.5485	29.46	4.69	34.15	43.50	-9.35	258	100	QP
3	158.6676	33.07	2.44	35.51	43.50	-7.99	64	100	QP
4	330.1949	26.28	11.64	37.92	46.00	-8.08	67	100	QP
5	462.3455	27.00	12.96	39.96	46.00	-6.04	91	100	QP
6	687.1507	24.63	18.14	42.77	46.00	-3.23	197	100	QP

Note: Testing is carried out with frequency rang 30MHz to the 9.2GHz, which above 1GHz are attenuated more than 20 dB below the permissible value and are not showed in the test report.

***** END OF REPORT *****