

Redpine RSIA15 PCB Antenna

Performance Specifications

Version 1.3

February 2016

Redpine Signals, Inc.

2107 N. First Street, #680 San Jose, CA95131. Tel: (408) 748-3385 Fax: (408) 705-2019

Email: info@redpinesignals.com
Website: www.redpinesignals.com



About this Document

This document lists the performance specifications of the Dual band PCB Antenna used for FCC, IC, ETSI/CE and other regulatory certifications of the RS9113 and RS9116 Single and Dual band Modules. This document will be discontinued in the future and the specifications listed here will be part of the main Datasheet of the modules.

Disclaimer:

The information in this document pertains to information related to Redpine Signals, Inc. products. This information is provided as a service to our customers, and may be used for information purposes only. Redpine assumes no liabilities or responsibilities for errors or omissions in this document. This document may be changed at any time at Redpine's sole discretion without any prior notice to anyone. Redpine is not committed to updating this document in the future.

Copyright © 2016 Redpine Signals, Inc. All rights reserved.



Table Of Contents

L	Ove	erview	5
2	PCB	B Antenna Performance Specifications	6
		Return Loss Characteristic of the Antenna	
		Module Reference Orientation	
		2D Gain Plots	
	2.3.1		
		3.1.1 XY at 2.415 GHz	
		3.1.2 YZ at 2.415 GHz	
		.3.1.3 ZX at 2415 GHz	
	2.3.2		
		3.2.1 XY at 2.43 GHz	
		.3.2.2 YZ at 2.43 GHz	
		.3.2.3 ZX at 2.43 GHz	
	2.3.3		
		.3.3.1 XY at 2.480 GHz	
		.3.3.2 YZ at 2.480 GHz	
		.3.3.3 ZX at 2480 GHz	
	2.3.4		
		.3.4.1 XY at 5.180 GHz	
		.3.4.2 YZ at 5.180 GHz	
		.3.4.3 ZX at 5.180 GHz	
	2.3.5		
		.3.5.1 XY at 5.49 GHz	_
		.3.5.2 YZ at 5.49 GHz	
	2.3.6	.3.5.3 ZX at 5.49 GHz	
		3.6.1 XY at 5.750 GHz	
		.3.6.2 YZ at 5.750 GHz	
		.3.6.3 ZX at 5.750 GHz	
		Peak Gain	
		Antenna Parameters	
3	Med	chanical Characteristics	17
-:.	1. 5	Table of Figures	,
٠	•	Return Loss Characteristic of the Antenna	6
		Module Reference Orientation	
•	•		
		2D Gain Plot for YZ at 2.415 GHz	
•	•	2D Gain Plot for ZX at 2.415 GHz	
		2D Gain Plot for XY at 2.43 GHz	
	gure /: 2	3D Cain Blot for V7 at 3.43 CU-	
_		2D Gain Plot for YZ at 2.43 GHz	
	-	2D Gain Plot for ZX at 2.43 GHz	9
•	gure 9: 2	2D Gain Plot for ZX at 2.43 GHz2D Gain Plot for XY at 2.480 GHz	9 10
Fig	gure 9: 2 gure 10:	2D Gain Plot for ZX at 2.43 GHz 2D Gain Plot for XY at 2.480 GHz 2: 2D Gain Plot for YZ at 2.480 GHz	9 10 10
Fig Fig	gure 9: 2 gure 10: gure 11:	2D Gain Plot for ZX at 2.43 GHz 2D Gain Plot for XY at 2.480 GHz 2: 2D Gain Plot for YZ at 2.480 GHz 1: 2D Gain Plot for ZX at 2.480 GHz	9 10 10
Fig Fig Fig	gure 9: 2 gure 10: gure 11: gure 12:	2D Gain Plot for ZX at 2.43 GHz 2D Gain Plot for XY at 2.480 GHz 2: 2D Gain Plot for YZ at 2.480 GHz 1: 2D Gain Plot for ZX at 2.480 GHz 2: 2D Gain Plot for XY at 5.180 GHz	
Fig Fig Fig	gure 9: 2 gure 10: gure 11: gure 12:	2D Gain Plot for ZX at 2.43 GHz 2D Gain Plot for XY at 2.480 GHz 2: 2D Gain Plot for YZ at 2.480 GHz 1: 2D Gain Plot for ZX at 2.480 GHz	



Figure 14: 2D Gain Plot for ZX at 5.180 GHz	12
Figure 15: 2D Gain Plot for XY at 5.49 GHz	13
Figure 16: 2D Gain Plot for YZ at 5.49 GHz	13
Figure 17: 2D Gain Plot for ZX at 5.49 GHz	14
Figure 18: 2D Gain Plot for XY at 5.750 GHz	
Figure 19: 2D Gain Plot for YZ at 5.750 GHz	
Figure 20: 2D Gain Plot for ZX at 5.750 GHz	
Figure 21: Peak Gain at frequencies 2.4 to 2.5GHz	
Figure 22: Peak Gain at frequencies 5 to 6GHz	
<u>Table of Tables</u>	
Table 1: Antenna Parameters	16



1 Overview

Following sections list down the performance specifications of the PCB antenna.



2 PCB Antenna Performance Specifications

2.1 Return Loss Characteristic of the Antenna




Figure 1: Return Loss Characteristic of the Antenna

2.2 Module Reference Orientation




Figure 2: Module Reference Orientation



2.3 2D Gain Plots

2.3.1 2D Gain Plots at 2.415 GHz

2.3.1.1 XY at 2.415 GHz




Figure 3: 2D Gain Plot for XY at 2.415 GHz

2.3.1.2 YZ at 2.415 GHz






Figure 4: 2D Gain Plot for YZ at 2.415 GHz

2.3.1.3 ZX at 2415 GHz




Figure 5: 2D Gain Plot for ZX at 2.415 GHz

2.3.2 2D Gain Plots at 2.430 GHz

2.3.2.1 XY at 2.43 GHz




Figure 6: 2D Gain Plot for XY at 2.43 GHz



2.3.2.2 YZ at 2.43 GHz




Figure 7: 2D Gain Plot for YZ at 2.43 GHz

2.3.2.3 ZX at 2.43 GHz




Figure 8: 2D Gain Plot for ZX at 2.43 GHz



2.3.3 2D Gain Plots at 2.480 GHz

2.3.3.1 XY at 2.480 GHz




Figure 9: 2D Gain Plot for XY at 2.480 GHz

2.3.3.2 YZ at 2.480 GHz




Figure 10: 2D Gain Plot for YZ at 2.480 GHz



2.3.3.3 ZX at 2480 GHz




Figure 11: 2D Gain Plot for ZX at 2.480 GHz

2.3.4 2D Gain Plots at 5.180 GHz

2.3.4.1 XY at 5.180 GHz




Figure 12: 2D Gain Plot for XY at 5.180 GHz



2.3.4.2 YZ at 5.180 GHz




Figure 13: 2D Gain Plot for YZ at 5.180 GHz

2.3.4.3 ZX at 5.180 GHz




Figure 14: 2D Gain Plot for ZX at 5.180 GHz



2.3.5 2D Gain Plots at 5.49 GHz

2.3.5.1 XY at 5.49 GHz




Figure 15: 2D Gain Plot for XY at 5.49 GHz

2.3.5.2 YZ at 5.49 GHz




Figure 16: 2D Gain Plot for YZ at 5.49 GHz



2.3.5.3 ZX at 5.49 GHz




Figure 17: 2D Gain Plot for ZX at 5.49 GHz

2.3.6 2D Gain Plots at 5.750 GHz

2.3.6.1 XY at 5.750 GHz




Figure 18: 2D Gain Plot for XY at 5.750 GHz



2.3.6.2 YZ at 5.750 GHz




Figure 19: 2D Gain Plot for YZ at 5.750 GHz

2.3.6.3 ZX at 5.750 GHz




Figure 20: 2D Gain Plot for ZX at 5.750 GHz



2.4 Peak Gain




Figure 21: Peak Gain at frequencies 2.4 to 2.5GHz




Figure 22: Peak Gain at frequencies 5 to 6GHz

2.5 Antenna Parameters

Parameter	2400 - 2500MHz	5000 - 6000MHz
Peak Gain	0.99 dBi	4.42 dBi
Efficiency	87 %	85 %

Table 1: Antenna Parameters



3 Mechanical Characteristics

Parameter	Value (L X W)	Units
Antenna Dimensions	16 x 6.5	mm
Tolerance	±0.1	mm

Table 2: Mechanical Characteristics



Revision History

S.No.	Ver. No.	Date	Changes
1.	1.0	September 2014	Initial Version
2.	1.1	July 2015	 Added antenna dimensions information. Added the frequency range for the peak gain parameters. Updated peak gain for the antenna.
3.	1.2	August 2015	Changed the units for Antenna Peak Gain from dB to dBi.
4.	1.3	February 2016	Added 2D Gain Plots for Low and High Channels in 2.4 GHz and 5 GHz bands.