



FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AJKQSY-5D

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

Module 1

IEEE 802.11b

max possible output power (AV,conducted) : 14±1dbm

IEEE 802.11g

max possible output power (AV,conducted) : 12±1dbm

IEEE 802.11n(20)

max possible output power (AV,conducted) : 11±1dbm

IEEE 802.11n(40)

max possible output power (AV,conducted) : 10±1dbm



The max possible output power (AV,conducted) of All (IEEE 802.11b , IEEE 802.11g, IEEE 802.11n(20/40)) is IEEE 802.11b.

Module 2

ANT .1 and ANT.2

IEEE 802.11b

max possible output power (AV,conducted) : 12 ± 1 dbm

IEEE 802.11g

max possible output power (AV,conducted) : 11 ± 1 dbm

IEEE 802.11n(20)

max possible output power (AV,conducted) : 10 ± 1 dbm

IEEE 802.11n(40)

max possible output power (AV,conducted) : 9 ± 1 dbm

The max possible output power (AV,conducted) of All (IEEE 802.11b , IEEE 802.11g, IEEE 802.11n(20/40)) is IEEE 802.11b.

ANT .1+ANT.2 Total

IEEE 802.11n(20)

max possible output power (AV,conducted) : 13 ± 1 dbm

IEEE 802.11n(40)

max possible output power (AV,conducted) : 12 ± 1 dbm

The max possible output power (AV,conducted) of All (IEEE 802.11n(20/40)) is IEEE 802.11n20



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

Module 1

	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Total Output power to antenna (mW)	Antenna Gain(dBi)	Total Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	14±1.0	15	31.62	1.0 (1.258)	0.007918	1.0	Pass

Module 2

		Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Total Output power to antenna (mW)	Antenna Gain(dBi)	Total Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
ANT. 1	802.11b	12±1.0	13	19.95	1.0 (1.258)	0.004995	1.0	Pass
ANT. 2	802.11b	12±1.0	13	19.95	1.0 (1.258)	0.004995	1.0	Pass
ANT. 1 +ANT.2 Total	802.11n (20)	13±1	14	25.11	1.0 (1.258)	0.006287	1.0	Pass

Conclusion:

For the max result: $0.007918 \leq 3.0$ for 1g SAR, No SAR is required.