

Report Number: F690501/RF-RTL011750 Page: 1 of 6

# **TEST REPORT**

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AJKSKG-FLIP-B01

Equipment Under Test : Interactive Flip Book

Model Name : KG-FLIP-B01

Applicant : Kum Oh Electronics Co., Ltd.

Manufacturer : Kum Oh Electronics Co., Ltd.

Date of Receipt : 2017.08.02

Date of Test(s) : 2017.08.03 ~ 2017.08.10

Date of Issue : 2017.08.21

In the configuration tested, the EUT complied with the standards specified above.

Jinhyoung Cho

Jungmin Yang

Tested By:

2017.08.21

Technical

Manager:

Date:

Date:

2017.08.21

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL011750 Page: 2 of 6

## **INDEX**

| Table of Contents         | Page |
|---------------------------|------|
| 1. General Information    | 3    |
| 2. RF Exposure Evaluation | 5    |



Report Number: F690501/RF-RTL011750 Page: of 6

### 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

: Kum Oh Electronics Co., Ltd. Applicant

Address 35, Gilju-ro 444beon-gil, Bucheon-si, Gyeonggi-do, 14556, Korea

Contact Person : Park, Chan-Hong Phone No. : +82 10 4407 6607

### 1.3. Details of manufacturer

Kum Oh Electronics Co., Ltd.

Address 35, Gilju-ro 444beon-gil, Bucheon-si, Gyeonggi-do, 14556, Korea

### 1.4. Description of EUT

| Kind of Product      | Interactive Flip Book                    |  |  |
|----------------------|--|--|--|
| Model Name           | KG-FLIP-B01                              |  |  |
| Power Supply         | DC 12.0 V                                |  |  |
| Frequency Range      | 2 402 吨 ~ 2 480 吨 (Bluetooth Low Energy) |  |  |
| Modulation Technique | GFSK                                     |  |  |
| Number of Channels   | 40 channels (Bluetooth Low Energy)       |  |  |
| Antenna Type         | tenna Type PCB Antenna                   |  |  |
| Antenna Gain         | 3.1 dBi                                  |  |  |
| H/W Version          | 1.1                                      |  |  |
| S/W Version          | 0.1                                      |  |  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL011750 Page: 4 of 6

## 1.5. Test report revision

| Revision | Report number        | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0        | F690501/RF-RTL011750 | 2017.08.21    | Initial     |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL011750 Page: 5 of 6

## 2. RF Exposure Evaluation

## 2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range   | Electric Field<br>Strength(V/m) | Magnetic Field<br>Strength<br>(A/m) | Power Density<br>(⊪W/c㎡) | Average Time |  |
|---|---------------------------------|-------------------------------------|--------------------------|--------------|--|
| (A) Limits for Occupational/Controlled Exposure         |                                 |                                     |                          |              |  |
| 0.3 – 3.0   | 614                             | 1.63                                | *100                     | 6            |  |
| 3.0 – 30  | 1842/f                          | 4.89/f                              | *900/f <sup>2</sup>      | 6            |  |
| 30 – 300  | 61.4                            | 0.163                               | 1.0                      | 6            |  |
| 300 – 1 500   | -                               | -                                   | f/300                    | 6            |  |
| 1 500 – 100 000   | -                               | -                                   | 5                        | 6            |  |
| (B) Limits for General Population/Uncontrolled Exposure |                                 |                                     |                          |              |  |
| 0.3 – 1.34  | 614                             | 1.63                                | *100                     | 30           |  |
| 1.34 – 30   | 824/f                           | 2.19/f                              | *180/f <sup>2</sup>      | 30           |  |
| 30 – 300  | 27.5                            | 0.073                               | 0.2                      | 30           |  |
| 300 – 1 500   | -                               | -                                   | f/1500                   | 30           |  |
| <u>1 500 – 100 000</u>                                  | -                               | -                                   | <u>1.0</u>               | <u>30</u>    |  |

### 2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL011750 Page: 6 of 6

### 2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

### 2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

### **Bluetooth Low Energy**

- Maximum tune up tolerance

| Operating<br>Frequency<br>(脈) | Output Average<br>Power to Antenna<br>(dB m) | Antenna<br>Gain<br>(dB i) | Power<br>Density<br>at 20 cm (mW/cm²) | Limits<br>(mW/cm²) |
|-------------------------------|--|---------------------------|---------------------------------------|--------------------|
| 2 402 ~ 2 480                 | 2.5  | 3.1                       | 0.000 722                             | 1                  |

#### Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than  $6\,\mathrm{dB}\,\mathrm{i}$  and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

### - End of the Test Report -