

# FCC Part 15C Measurement and Test Report

For

**Uonmap International Limited**

**Unit 1010, 10/F, Miramar Tower, 132 Nathan Road, Tsim Sha Tsui, Kowloon,**

**Hong Kong**

**FCC ID: 2AJMAU-100**

**FCC Rule(s):** FCC Part 15.247

**Product Description:** CarDroid

**Tested Model:** U-100

**Report No.:** STR16068341I-3

**Tested Date:** 2016-06-28 to 2016-08-15

**Issued Date:** 2016-08-15

**Tested By:** Leo Lee / Engineer

*Leo Lee*

**Reviewed By:** Silin Chen / EMC Manager

*Silin Chen*

**Approved & Authorized By:** Jandy So / PSQ Manager

*Jandy So*

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING .....	4
1.5 EUT OPERATING DURING TEST .....	4
1.6 TEST FACILITY .....	5
1.7 EUT SETUP AND TEST MODE.....	5
1.8 MEASUREMENT UNCERTAINTY .....	6
1.9 TEST EQUIPMENT LIST AND DETAILS .....	6
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>3. RF EXPOSURE .....</b>	<b>8</b>
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
<b>4. ANTENNA REQUIREMENT .....</b>	<b>9</b>
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION .....	9
<b>5. POWER SPECTRAL DENSITY .....</b>	<b>10</b>
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS .....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS .....	10
<b>6. 6DB BANDWIDTH .....</b>	<b>13</b>
6.1 STANDARD APPLICABLE.....	13
6.2 TEST PROCEDURE.....	13
6.3 ENVIRONMENTAL CONDITIONS .....	13
6.4 SUMMARY OF TEST RESULTS/PLOTS .....	13
<b>7. RF OUTPUT POWER .....</b>	<b>16</b>
7.1 STANDARD APPLICABLE.....	16
7.2 TEST PROCEDURE.....	16
7.3 ENVIRONMENTAL CONDITIONS .....	16
7.4 SUMMARY OF TEST RESULTS/PLOTS .....	16
<b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>	<b>17</b>
8.1 STANDARD APPLICABLE.....	17
8.2 TEST PROCEDURE.....	17
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
8.4 ENVIRONMENTAL CONDITIONS .....	18
8.5 SUMMARY OF TEST RESULTS/PLOTS .....	19
<b>9. OUT OF BAND EMISSIONS.....</b>	<b>26</b>
9.1 STANDARD APPLICABLE.....	26
9.2 TEST PROCEDURE.....	26
9.3 ENVIRONMENTAL CONDITIONS .....	27
9.4 SUMMARY OF TEST RESULTS/PLOTS .....	27
<b>10. CONDUCTED EMISSIONS .....</b>	<b>32</b>
10.1 TEST PROCEDURE.....	32
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	32
10.3 ENVIRONMENTAL CONDITIONS .....	32
10.4 TEST RECEIVER SETUP .....	33
10.5 SUMMARY OF TEST RESULTS/PLOTS .....	33
10.6 CONDUCTED EMISSIONS TEST DATA.....	33

## 1. GENERAL INFORMATION

### Client Information

Applicant: Uonmap International Limited  
Address of applicant: Unit 1010, 10/F, Miramar Tower, 132 Nathan Road,  
Tsim Sha Tsui, Kowloon, Hong Kong

Manufacturer: Shenzhen Ptah Technology Co., Ltd  
Address of manufacturer: 4/F, D Block, Xinda Technonogy Innovation Park,  
Baotian 2rd Road, XiXiang, Bao'an, Shenzhen,  
China

General Description of EUT	
Product Name:	CarDroid
Trade Name:	UonMap
Model No.:	U-100
Adding Model(s):	U-200, U-300, U-400, U-500, U-600
Rated Voltage:	DC 3.8V by battery
Battery:	2150mAh
Device Category:	Mobile Device
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model U-100, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT(IC Model: MT6627)	
Bluetooth Version:	V4.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	-5.584dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral
Antenna Gain:	0dBi
Lowest Internal Frequency:	32.768kHz

## 1.2 Test Standards

The following report is prepared on behalf of the Uonmap International Limited in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r05 for digital transmission systems shall be performed also.

## 1.4 Table for parameters of Test Software setting

The test utility software used during testing was “RFTestTool APK”. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)		
	2402	2442	2480
BLE	42	42	42

## 1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under WIN7 were executed.

## 1.6 Test Facility

### FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GFSK(BLE)	2402MHz, 2442MHz, 2480MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

## 1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

## 1.9 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an integral antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v03r05, the test method of power spectral density as below:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set the VBW  $\geq 3 \times \text{RBW}$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	2402	-20.46	8
	2442	-20.34	8
	2480	-21.63	8

Please refer to the following test plots:


# Low Channel



# Middle Channel



## High Channel



## 6. 6dB Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Environmental Conditions

Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


### 6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
GFSK(BLE)	2402	742.179	1053.8	$\geq 500$
	2442	740.786	1052.2	$\geq 500$
	2480	736.706	1050.5	$\geq 500$


Please refer to the following test plots:

For BLE


Low Channel:



Middle Channel:



High Channel:



## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to section KDB-558074 D01 v03r05 section 9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW  $\geq$  DTS bandwidth.
- Set VBW  $\geq 3 \times$  RBW.
- Set span  $\geq 3 \times$  RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

### 7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

### 7.4 Summary of Test Results/Plots

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	-5.584	0.28	1000
	2442	-5.661	0.27	1000
	2480	-6.613	0.22	1000

*Note: the antenna gain of 0dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*



## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

### Plot of Radiated Emissions Test Data


EUT: CarDroid  
 Tested Model: U-100  
 Operating Condition: Transmitting-Low channel (2402MHz)  
 Comment: DC 3.8V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	35.4992	22.88	-8.90	13.98	40.00	-26.02	0	100	peak
2	102.7192	22.02	-10.97	11.05	43.50	-32.45	0	100	peak
3	131.2965	23.36	-12.07	11.29	43.50	-32.21	0	100	peak
4	263.8190	21.67	-6.79	14.88	46.00	-31.12	0	100	peak
5	478.8455	21.40	-1.13	20.27	46.00	-25.73	0	100	peak
6	776.8777	22.56	2.73	25.29	46.00	-20.71	0	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	31.9545	27.17	-9.81	17.36	40.00	-22.64	0	100	peak
2	48.5016	23.68	-8.22	15.46	40.00	-24.54	0	100	peak
3	114.5146	23.34	-11.29	12.05	43.50	-31.45	0	100	peak
4	322.1886	21.96	-4.66	17.30	46.00	-28.70	0	100	peak
5	627.2738	22.23	1.05	23.28	46.00	-22.72	0	100	peak
6	900.1473	22.29	3.15	25.44	46.00	-20.56	0	100	peak

### Plot of Radiated Emissions Test Data


EUT: CarDroid

Tested Model: U-100

Operating Condition: Transmitting-Middle channel (2442MHz)


Comment: DC 3.8V

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	41.2764	23.03	-7.75	15.28	40.00	-24.72	0	100	peak
2	61.1315	22.41	-9.94	12.47	40.00	-27.53	0	100	peak
3	102.7192	21.69	-10.97	10.72	43.50	-32.78	0	100	peak
4	214.5142	21.81	-8.79	13.02	43.50	-30.48	0	100	peak
5	381.2486	21.43	-2.17	19.26	46.00	-26.74	0	100	peak
6	771.4486	21.48	2.43	23.91	46.00	-22.09	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	31.9545	27.40	-9.81	17.59	40.00	-22.41	0	100	peak
2	41.8596	23.11	-7.79	15.32	40.00	-24.68	0	100	peak
3	79.8002	25.24	-12.01	13.23	40.00	-26.77	0	100	peak
4	214.5142	23.99	-8.79	15.20	43.50	-28.30	0	100	peak
5	374.6225	21.93	-2.41	19.52	46.00	-26.48	0	100	peak
6	782.3452	21.73	2.78	24.51	46.00	-21.49	0	100	peak

### Plot of Radiated Emissions Test Data


EUT: *CarDroid*  
 Tested Model: *U-100*  
 Operating Condition: *Transmitting-High channel (2480MHz)*  
 Comment: *DC 3.8V*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	35.0048	23.05	-9.04	14.01	40.00	-25.99	0	100	peak
2	54.4515	23.39	-8.88	14.51	40.00	-25.49	0	100	peak
3	104.1701	22.24	-11.01	11.23	43.50	-32.27	0	100	peak
4	258.3263	22.54	-7.07	15.47	46.00	-30.53	0	100	peak
5	622.8899	21.83	1.16	22.99	46.00	-23.01	0	100	peak
6	896.9964	23.66	3.14	26.80	46.00	-19.20	0	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	31.9545	28.13	-9.81	18.32	40.00	-21.68	0	100	peak
2	80.0806	25.09	-12.00	13.09	40.00	-26.91	0	100	peak
3	143.3260	26.00	-12.51	13.49	43.50	-30.01	0	100	peak
4	274.1938	22.34	-6.35	15.99	46.00	-30.01	0	100	peak
5	392.0951	22.79	-2.73	20.06	46.00	-25.94	0	100	peak
6	972.3374	22.32	3.76	26.08	54.00	-27.92	0	100	peak



### Spurious Emissions Above 1GHz

Transmitting: BLE mode:

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	55.45	-3.59	51.86	74	-22.14	H	PK
4804	50.00	-3.59	46.41	54	-7.59	H	AV
7206	55.45	-0.52	54.93	74	-19.07	H	PK
7206	49.09	-0.52	48.57	54	-5.43	H	AV
4804	57.27	-3.59	53.68	74	-20.32	V	PK
4804	41.82	-3.59	38.23	54	-15.77	V	AV
7206	57.27	-0.52	56.75	74	-17.25	V	PK
7206	48.18	-0.52	47.66	54	-6.34	V	AV
Middle Channel-2442MHz							
4884	53.64	-3.49	50.15	74	-23.85	H	PK
4884	50.00	-3.49	46.51	54	-7.49	H	AV
7326	59.09	-0.47	58.62	74	-15.38	H	PK
7326	41.82	-0.47	41.35	54	-12.65	H	AV
4884	58.18	-3.49	54.69	74	-19.31	V	PK
4884	41.82	-3.49	38.33	54	-15.67	V	AV
7326	56.36	-0.47	55.89	74	-18.11	V	PK
7326	45.45	-0.47	44.98	54	-9.02	V	AV
High Channel-2480MHz							
4960	52.73	-3.41	49.32	74	-24.68	H	PK
4960	44.55	-3.41	41.14	54	-12.86	H	AV
7440	52.73	-0.42	52.31	74	-21.69	H	PK
7440	40.00	-0.42	39.58	54	-14.42	H	AV
4960	56.36	-3.41	52.95	74	-21.05	V	PK
4960	48.18	-3.41	44.77	54	-9.23	V	AV
7440	57.27	-0.42	56.85	74	-17.15	V	PK
7440	45.45	-0.42	45.03	54	-8.97	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

---

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v03r05, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 9.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots

Bandedge (Radiated)

Lowest Bandedge-BLE


Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	38.26	-3.80	34.46	54.00	-19.54	Average Detector
	2310.000	48.27	-3.80	44.47	74.00	-29.53	Peak Detector
2	2390.000	39.08	-3.00	36.08	54.00	-17.92	Average Detector
	2390.000	48.62	-3.00	45.62	74.00	-28.38	Peak Detector

Highest Bandedge-BLE



Horizontal (Worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.145	71.78	-2.50	69.28	54.00	15.28	Average Detector
	2479.705	84.19	-2.50	81.69	74.00	7.69	Peak Detector
2	2483.500	Delta=32.78dBc		36.51	54.00	-17.49	Average Detector
	2483.500			50.13	74.00	-23.87	Peak Detector
3	2500.000	37.34	-2.40	34.94	54.00	-19.06	Average Detector
	2500.000	47.42	-2.40	45.02	74.00	-28.98	Peak Detector

Bandedge (Conducted)



Lowest



Middle:



Highest




## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar



## 10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode .....	Normal

## 10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


**-4.57 dB at 0.1540 MHz** in the **Neutral, Peak** detector, 0.15-30MHz

## 10.6 Conducted Emissions Test Data

### Plot of Conducted Emissions Test Data


EUT: CarDroid  
 Tested Model: U-100  
 Operating Condition: Transmitting  
 Comment: AC 120V/60Hz; USB 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	51.71	9.50	61.21	65.78	-4.57	peak
2	0.1700	26.95	9.50	36.45	54.96	-18.51	AVG
3	0.1820	49.85	9.50	59.35	64.39	-5.04	peak
4	0.2180	23.28	9.50	32.78	52.89	-20.11	AVG
5	1.9820	27.51	9.82	37.33	56.00	-18.67	peak
6	2.1500	15.75	9.84	25.59	46.00	-20.41	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1660	51.02	9.50	60.52	65.16	-4.64	peak
2	0.1700	24.92	9.50	34.42	54.96	-20.54	AVG
3	0.1980	48.29	9.50	57.79	63.69	-5.90	peak
4	0.2100	21.91	9.50	31.41	53.21	-21.80	AVG
5	2.0100	27.88	9.82	37.70	56.00	-18.30	peak
6	2.0580	14.18	9.83	24.01	46.00	-21.99	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*