Request for Modular Approval FCC ID: 2AJMTWIPY01R.

Item	Requirements	EUT
1	•	Device is equipped with metal shielding
_	Have its own RF shielding	to cover RF section. Refer to external
		photos.
2	Have buffered modulation/data	All inputs to the modules are buffered
	inputs (if such inputs are provided)	through logic and microprocessor
2		inputs.
3	Have its own power supply regulation	Module chipset incorporates voltage
4	NA - ch the content of	regulation to transceiver circuitry The device has a ceramic antenna and a
	Meet the antenna requirements of	dedicated antenna. Device is tested in a test fixture in a standalone configuration
	section 15.203	
5	Demonstrate compliance in a	
	stand-alone configuration	
6	The licensed module must have a FCC	FCC ID label format will be included in the filling. Host ID label will be displayed on the host system.
	ID label on the module itself. That FCC	
	ID label must be visible through a	
	window on the final device or it must	
	be visible when an access panel, door	
	or cover is easily removed. If not, a	
	second label must be placed on the	
	outside of the final device that	
	contains the following text: Contains	
	"FCC ID: 2AMVP-VCB601"	
7	The module must comply with all	Please refer to "User Manual" Exhibit
	specific rules applicable to the	
	transmitter. The grantee must	
	provide comprehensive instructions	
	to explain compliance requirements.	
8	The module must comply with RF	RF exposure evaluation is exempted
	exposure requirements. See FCC	because of low output power.
	Rules. Spread Spectrum transmitters	
	must comply with RF exposure limits	
	in 15.247.	

in 15.247.

Thank you for your attention to this matter.

Yours Sincerely,

ly Zhu, Certification Manager