



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247 TEST REPORT

For

Pycom Ltd

High Point 9 Sydenham Road, Guildford Surrey GU1 3RX, Surrey, United Kingdom

FCC ID: 2AJMTGPY01R

Report Type: Original Report	Product Type: GPy
Test Engineer: Max Min <i>Max Min</i>	
Report Number: RSHA180108008-00B	
Report Date: 2018-06-30	
Reviewed By:	Oscar Ye <i>Oscar Ye</i> RF Leader
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	9
TEST EQUIPMENT LIST	10
FCC §1.1307 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
FCC §15.203 – ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
CORRECTED FACTOR & MARGIN CALCULATION	16
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER SETUP.....	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST RESULTS SUMMARY	20
TEST DATA	21
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38

TEST DATA	38
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	44
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST DATA	47
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST DATA	63
FCC §15.247(d) - BAND EDGES TESTING	69
APPLICABLE STANDARD	69
TEST PROCEDURE	69
TEST DATA	69

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Pycom Ltd
Tested Model	GPy 1.0
Product Type	GPy
Dimension	55mm (L)* 20 mm (W)*10 mm(H)
Power Supply	DC 3.5V-5.5V

**All measurement and test data in this report was gathered from production sample serial number: 20180108008.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2018-01-08)*

Objective

This test report is prepared on behalf of *Pycom Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS and Part 27 TNB submissions with FCC ID: 2AJMTGPY01R.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403
...
...	...	77	2479
39	2441	78	2480

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test tool: putty

GFSK Power level: 6

$\pi/4$ -DQPSK Power level: 6

8DPSK Power level: 6

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
Pycom Ltd	Expansion board	V2.1A	1630000932

External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.8	Expansion board	Notebook

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Narda	Pre-amplifier	AFS42-00101800	2001270	2017-10-22	2018-10-21
QuinStar	Amplifier	QLW-18405536-J0	15964001009	2017-10-22	2018-10-21
MICRO-TRONICS	Band notch Filter	BRM50702	/	2017-08-05	2018-08-04
Narda	Attenuator/10dB	10dB	/	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2017-07-22	2018-07-21
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
Pycom Ltd	RF Cable	/	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ENV216	3560655016	2017-11-15	2018-11-14
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2017-08-15	2018-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE ratio
		(dBi)	(numeric)	(dBm)	(mW)				
802.11b	2412~2462	1.30	1.35	23.0	199.53	20	0.0536	1.0000	0.0536
802.11g		1.30	1.35	21.0	125.89	20	0.0338	1.0000	0.0338
802.11n-HT20		1.30	1.35	21.0	125.89	20	0.0338	1.0000	0.0338
802.11n-HT40	2422~2452	1.30	1.35	21.0	125.89	20	0.0338	1.0000	0.0338
BLE	2402-2480	1.30	1.35	5.0	3.16	20	0.0008	1.0000	0.0008
BT 3.0	2402~2480	1.30	1.35	6.5	4.47	20	0.0012	1.0000	0.0012

Calculation of maximum antenna gain based on ERP/EIRP

Mode	Max Tune-up power (dBm)	ERP/EIRP Limit (dBm)	Max Antenna Gain (dBi)
FDD (Band 4)	23.00	30.00	7.00
FDD (Band 12)	23.50	34.77	11.27
FDD (Band 13)	23.00	34.77	11.77

Calculation of maximum antenna gain based on MPE Ratio

Mode	Frequency Range	Antenna Gain		Tune-up Conducted Power		Evaluation Distance	Power Density	MPE Limit	MPE ratio
	(MHz)	(dBi)	(numeric)	(dBm)	(mW)				
FDD (Band 4)	1710~1755	13.77	23.82	23.00	199.53	20	0.9454	1.0000	0.9454
FDD (Band 12)	699~716	9.95	9.89	23.50	223.87	20	0.4404	0.4660	0.9451
FDD (Band 13)	777~787	10.91	12.33	23.00	199.53	20	0.4894	0.5180	0.9448

Note: Wi-Fi and FDD can transmit simultaneously; the worst condition is 802.11b of Wi-Fi & FDD (Band 4), as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0536 + 0.9454 = \mathbf{0.9990} < \mathbf{1.0}$$

Mode	Max Allow Antenna Gain (dBi)
FDD (Band 4) Uplink Frequency: 1710 MHz~1755 MHz	7.00
FDD (Band 12) Uplink Frequency: 699 MHz~716MHz	9.95
FDD (Band 13) Uplink Frequency: 777 MHz~787 MHz	10.91

Result: For FDD mode, to meet RF exposure & ERP/ERIP, the maximum net gains of antennas allowed are 7.00 dBi @ FDD (Band 4), 9.95 @ FDD (Band 12) and 10.91 @ FDD (Band 13). The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT with a ceramic antenna for Bluetooth, which the antenna gain is 1.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa


The testing was performed by Max Min on 2018-02-22.

EUT operation mode: Transmitting in low channel of 8DPSK mode (worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	43.46	QP	9.000	L1	16.06	66.00	22.54	Compliance
0.150	28.37	AV	9.000	L1	16.06	56.00	27.63	Compliance
0.245	39.59	QP	9.000	L1	16.02	63.29	23.70	Compliance
0.245	26.52	AV	9.000	L1	16.02	53.29	26.77	Compliance
0.395	39.44	QP	9.000	L1	16.06	59.00	19.56	Compliance
0.395	36.22	AV	9.000	L1	16.06	49.00	12.78	Compliance
3.700	31.08	QP	9.000	L1	15.85	56.00	24.92	Compliance
3.700	23.03	AV	9.000	L1	15.85	46.00	22.97	Compliance
7.300	36.78	QP	9.000	L1	15.99	60.00	23.22	Compliance
7.300	31.55	AV	9.000	L1	15.99	50.00	18.45	Compliance
20.900	37.92	QP	9.000	L1	16.44	60.00	22.08	Compliance
20.750	31.80	AV	9.000	L1	16.44	50.00	18.20	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	44.49	QP	9.000	N	16.06	66.00	21.51	Compliance
0.150	29.07	AV	9.000	N	16.06	56.00	26.93	Compliance
0.245	40.32	QP	9.000	N	16.06	63.29	22.97	Compliance
0.245	25.34	AV	9.000	N	16.06	53.29	27.95	Compliance
0.395	39.27	QP	9.000	N	16.09	59.00	19.73	Compliance
0.395	36.61	AV	9.000	N	16.09	49.00	12.39	Compliance
3.000	30.65	QP	9.000	N	15.90	56.00	25.35	Compliance
3.000	21.69	AV	9.000	N	15.90	46.00	24.31	Compliance
7.150	36.79	QP	9.000	N	15.92	60.00	23.21	Compliance
7.100	31.11	AV	9.000	N	15.92	50.00	18.89	Compliance
21.000	40.71	QP	9.000	N	16.18	60.00	19.29	Compliance
21.200	35.09	AV	9.000	N	16.18	50.00	14.91	Compliance

Note:

- 1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Max Min from 2018-02-05 to 2018-06-29.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case **low channel of 8DPSK Mode in X-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
39.093750	27.12	101.0	V	273.0	-10.6	40.00	12.88
88.685000	18.95	101.0	V	218.0	-17.9	43.50	24.55
99.840000	29.52	101.0	V	209.0	-15.4	43.50	13.98
132.820000	28.56	101.0	V	94.0	-12.1	43.50	14.94
303.540000	23.86	101.0	H	256.0	-10.9	46.00	22.14
385.020000	29.87	101.0	H	189.0	-9.0	46.00	16.13

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case 8DPSK Mode in X-axis of orientation was recorded

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.600000	39.61	---	150.0	V	184.0	-0.6	74.00	34.39
1591.600000	---	30.55	150.0	V	184.0	-0.6	54.00	23.45
3281.400000	---	42.01	100.0	H	99.0	6.7	54.00	11.99
3281.400000	52.12	---	100.0	H	99.0	6.7	74.00	21.88
4804.000000	---	38.60	200.0	V	16.0	10.7	54.00	15.40
4804.000000	46.91	---	200.0	V	16.0	10.7	74.00	27.09
7206.000000	---	42.41	150.0	V	199.0	15.2	54.00	11.59
7206.000000	52.78	---	150.0	V	199.0	15.2	74.00	21.22
11047.000000	54.75	---	250.0	H	75.0	19.0	74.00	19.25
11047.000000	---	47.77	250.0	H	75.0	19.0	54.00	6.23
17755.200000	55.66	---	150.0	V	252.0	18.8	74.00	18.34
17755.200000	---	46.46	150.0	V	252.0	18.8	54.00	7.54

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1207.400000	---	27.52	200.0	V	104.0	-3.0	54.00	26.48
1207.400000	37.29	---	200.0	V	104.0	-3.0	74.00	36.71
3281.400000	---	40.89	100.0	H	304.0	6.7	54.00	13.11
3281.400000	51.44	---	100.0	H	304.0	6.7	74.00	22.56
4882.000000	---	38.74	100.0	V	281.0	11.1	54.00	15.26
4882.000000	48.22	---	100.0	V	281.0	11.1	74.00	25.78
7323.000000	---	43.15	200.0	V	66.0	15.4	54.00	10.85
7323.000000	51.82	---	200.0	V	66.0	15.4	74.00	22.18
11033.400000	57.09	---	150.0	V	301.0	19.0	74.00	16.91
11033.400000	---	47.80	150.0	V	301.0	19.0	54.00	6.20
17836.800000	55.25	---	200.0	V	8.0	19.0	74.00	18.75
17836.800000	---	46.71	200.0	V	8.0	19.0	54.00	7.29

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1438.600000	38.51	---	100.0	V	33.0	-1.6	74.00	35.49
1438.600000	---	29.56	100.0	V	33.0	-1.6	54.00	24.44
3305.200000	51.56	---	100.0	H	212.0	6.8	74.00	22.44
3305.200000	---	41.43	100.0	H	212.0	6.8	54.00	12.57
4960.000000	47.12	---	200.0	V	197.0	11.5	74.00	26.88
4960.000000	---	40.21	200.0	V	197.0	11.5	54.00	13.79
7440.000000	52.55	---	100.0	V	106.0	15.6	74.00	21.45
7440.000000	---	43.09	100.0	V	106.0	15.6	54.00	10.91
11210.200000	53.82	---	250.0	V	167.0	18.8	74.00	20.18
11210.200000	---	47.63	250.0	V	167.0	18.8	54.00	6.37
17928.600000	55.42	---	100.0	V	320.0	19.1	74.00	18.58
17928.600000	---	46.48	100.0	V	320.0	19.1	54.00	7.52

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case low channel of 8DPSK Mode in X-axis of orientation was recorded

Horizontal

Date: 13.JUN.2018 20:01:07

Vertical

Date: 13.JUN.2018 20:10:37

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case 8DPSK Mode in X-axis of orientation was recorded


Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	97.75	---	150.0	V	339.0	5.1	/	/
2402.000000	---	96.31	150.0	V	339.0	5.1	/	/
2402.000000	95.64	---	100.0	H	208.0	5.1	/	/
2402.000000	---	94.17	100.0	H	208.0	5.1	/	/
2390.000000	50.42	---	200.0	V	358.0	5.1	74.00	23.58
2390.000000	---	39.53	200.0	V	358.0	5.1	54.00	14.47
Middle Channel: 2441MHz								
2441.000000	96.63	---	100.0	V	140.0	5.2	/	/
2441.000000	---	95.27	100.0	V	140.0	5.2	/	/
2441.000000	94.47	---	200.0	H	209.0	5.2	/	/
2441.000000	---	93.18	200.0	H	209.0	5.2	/	/
High Channel: 2480MHz								
2480.000000	95.01	---	100.0	V	210.0	5.3	/	/
2480.000000	---	93.66	100.0	V	210.0	5.3	/	/
2480.000000	92.89	---	150.0	H	283.0	5.3	/	/
2480.000000	---	91.57	150.0	H	283.0	5.3	/	/
2483.500000	48.59	---	250.0	V	125.0	5.3	74.00	25.41
2483.500000	---	40.24	250.0	V	125.0	5.3	54.00	13.76


Conducted Spurious Emissions at Antenna Port**BDR (GFSK): Low Channel**

Date: 5.FEB.2018 13:01:47


BDR (GFSK): Middle Channel

Date: 5.FEB.2018 13:04:13


BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



Date: 5.FEB.2018 13:21:14

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) \geq RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data**Environmental Conditions**

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Max Min on 2018-02-04.


EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.003	0.929	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.929	Pass
	Adjacent	2442			
	High	2480	1.003	0.929	Pass
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	1.003	0.863	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.859	Pass
	Adjacent	2442			
	High	2480	1.003	0.859	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.003	0.848	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.848	Pass
	Adjacent	2442			
	High	2480	1.003	0.848	Pass
	Adjacent	2479			

Note: For BDR mode, Limit = 20 dB bandwidth; For EDR mode, Limit = 20 dB bandwidth*2/3


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel


EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2018-02-04.

EUT operation mode: Transmitting


Test Result: Compliance.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.929
	Middle	2441	0.929
	High	2480	0.929
EDR ($\pi/4$-DQPSK)	Low	2402	1.294
	Middle	2441	1.289
	High	2480	1.289
EDR (8DPSK)	Low	2402	1.272
	Middle	2441	1.272
	High	2480	1.272


BDR (GFSK): Low Channel



Date: 4 FEB 2018 14:50:36



BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel**EDR($\pi/4$ -DQPSK): Middle Channel**

EDR ($\pi/4$ -DQPSK): High Channel**EDR (8DPSK): Low Channel**

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW \geq RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2018-02-04.

EUT operation mode: Hopping


Test Result: Compliance.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15


BDR (GFSK): Number of Hopping Channels

Date: 4.FEB.2018 15:21:04

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Zero span, centered on a hopping channel.
- b. RBW shall be \leq channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d. Detector function: Peak.
- e. Trace: Max hold.


Test Data**Environmental Conditions**

Temperature:	23.4 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Max Min on 2018-02-05.

EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.388	0.124	0.4	Pass
		Middle	0.388	0.124	0.4	Pass
		High	0.388	0.124	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.653	0.264	0.4	Pass
		Middle	1.653	0.264	0.4	Pass
		High	1.653	0.264	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.907	0.31	0.4	Pass
		Middle	2.907	0.31	0.4	Pass
		High	2.907	0.31	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.401	0.128	0.4	Pass
		Middle	0.401	0.128	0.4	Pass
		High	0.401	0.128	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.662	0.266	0.4	Pass
		Middle	1.662	0.266	0.4	Pass
		High	1.662	0.266	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.919	0.311	0.4	Pass
		Middle	2.919	0.311	0.4	Pass
		High	2.919	0.311	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.401	0.128	0.4	Pass
		Middle	0.401	0.128	0.4	Pass
		High	0.401	0.128	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.662	0.266	0.4	Pass
		Middle	1.662	0.266	0.4	Pass
		High	1.662	0.266	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.919	0.311	0.4	Pass
		Middle	2.919	0.311	0.4	Pass
		High	2.919	0.311	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1

Date: 5.FEB.2018 11:21:11


BDR (GFSK): Pulse time, Middle Channel, DH1

Date: 5.FEB.2018 11:22:21


BDR (GFSK): Pulse time, High Channel, DH1




BDR (GFSK): Pulse time, Low Channel, DH3




BDR (GFSK): Pulse time, Middle Channel, DH3




BDR (GFSK): Pulse time, High Channel, DH3




BDR (GFSK): Pulse time, Low Channel, DH5




BDR (GFSK): Pulse time, Middle Channel, DH5



BDR (GFSK): Pulse time, High Channel, DH5



EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1



Spectrum

Ref Level 17.50 dBm Offset 7.50 dB RBW 1 MHz

Att 20 dB SWT 1 ms VBW 3 MHz

SGL TRG:VID

1Pk Clrw

10 dBm

0 dBm

-10 dBm TRG -11.500 dBm

-20 dBm

-30 dBm

-40 dBm

-50 dBm

-60 dBm

-70 dBm

-80 dBm

D1[1] -1.34 dB

M1[1] 400.70 μ s

-61.88 dBm

-4.35 μ s

CF 2.441 GHz 691 pts 100.0 μ s

Date: 5.FEB.2018 11:24:20

Spectrum

Ref Level 17.50 dBm Offset 7.50 dB RBW 1 MHz
Att 20 dB SWT 1 ms VBW 3 MHz
SGL TRG:VID

● 1Pk Clrw


D1[1] -3.18 dB
M1[1] -61.61 dBm
-4.35 μs

TRG -11.500 dBm


CF 2.48 GHz 691 pts 100.0 μs/

Date: 5.FEB.2018 11:25:00


EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3







EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5**

EDR (8DPSK): Pulse time, Low Channel, 3DH1**EDR (8DPSK): Pulse time, Middle Channel, 3DH1**


EDR (8DPSK): Pulse time, High Channel, 3DH1




EDR (8DPSK): Pulse time, Low Channel, 3DH3




EDR (8DPSK): Pulse time, Middle Channel, 3DH3




EDR (8DPSK): Pulse time, High Channel, 3DH3




EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



Date: 5.FEB.2018 11:49:27

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2018-02-05.

EUT operation mode: Transmitting


Test Result: Compliance.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	3.52	2.25	1000
	2441	3.14	2.06	1000
	2480	1.21	1.32	1000
EDR ($\pi/4$-DQPSK)	2402	5.73	3.74	125
	2441	5.26	3.36	125
	2480	3.36	2.17	125
EDR (8DPSK)	2402	6.17	4.14	125
	2441	5.66	3.68	125
	2480	3.80	2.40	125


BDR (GFSK): 2402MHz

Date: 5.FEB.2018 10:06:18


BDR (GFSK): 2441MHz




BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




EDR($\pi/4$ -DQPSK): 2441MHz




EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Max Min on 2018-02-05.

EUT operation mode: Transmitting & Hopping


Test Result: Compliance.



Band Edge

BDR (GFSK): Left Side




BDR (GFSK): Right Side






EDR ($\pi/4$ -DQPSK): Left SideEDR ($\pi/4$ -DQPSK): Right Side



EDR (8DPSK): Left Side




EDR (8DPSK): Right Side




BDR (GFSK): Left Side - Hopping**BDR (GFSK): Right Side- Hopping**

EDR ($\pi/4$ -DQPSK): Left Side- Hopping**EDR ($\pi/4$ -DQPSK): Right Side- Hopping**

EDR (8DPSK): Left Side- Hopping



EDR (8DPSK): Right Side- Hopping



***** END OF REPORT *****