



FCC Part 1 Subpart I  
FCC Part 2 Subpart J

**RF EXPOSURE REPORT**

**FOR**

**GROUND BASED UNIT**

**MODEL NUMBER: RRH**

**FCC ID: 2AJN8-GS1**

**REPORT NUMBER: R11150849-E2**

**ISSUE DATE: 2016-09-28**

*Prepared for*  
**HARRIS**  
**2400 PALM BAY ROAD NE**  
**PALM BAY**  
**FLORIDA, 32905, USA**

*Prepared by*  
**UL LLC**  
**12 LABORATORY DR.**  
**RESEARCH TRIANGLE PARK, NC 27709 USA**  
**TEL: (919) 549-1400**



NVLAP Lab code: 200246-0

Revision History

Ver.	Issue Date	Revisions	Revised By
1	2016-09-08	Initial Issue	M. Heckrotte
2	2016-09-28	Corrected some power values in result table (Chains 1, 7, 8).	Jeff Moser

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION .....	5
5. EUT DESCRIPTION .....	5
6. MAXIMUM PERMISSIBLE RF EXPOSURE .....	6
6.1. FCC RULES .....	6
6.2. LIMITS .....	6
6.3. EQUATIONS .....	7
6.4. RESULTS .....	8

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** HARRIS  
2400 PALM BAY ROAD NE  
PALM BAY, FLORIDA, 32905, USA

**EUT DESCRIPTION:** GROUND BASED UNIT

**MODEL:** RRH, P/N 1523K0007

**SERIAL NUMBER:** Non-serialized

**DATE TESTED:** 2016-02-02 – 2016-03-03

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	PASS

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Verification Services Inc. By:

Prepared By:



MICHAEL HECKROTTE  
PRINCIPAL ENGINEER  
UL Verification Services Inc.



JEFF MOSER  
EMC PROGRAM MANAGER  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01.

## 3. REFERENCES

All measurements were made as documented in test report R11150849-E1.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 12 Laboratory Dr., Research Triangle Park, NC 27709, USA and 2800 Suite B Perimeter Park Dr., Morrisville, NC 27560.

UL LLC (RTP) is accredited by NVLAP, Laboratory Code 200246-0. The full scope of accreditation can be viewed at <http://www.nist.gov/nvlap/>.

## 5. EUT DESCRIPTION

The EUT is a ground-based 2.4 GHz transceiver intended to communicate with airborne stations.

Other details regarding the EUT are documented in the applicable test reports and product documentation.

## 6. MAXIMUM PERMISSIBLE RF EXPOSURE

### 6.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

### 6.2. LIMITS

For operation in the 2.4 GHz band:

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup>

### **6.3. EQUATIONS**

#### **DISTANCE**

Distance is given by:

$$D = \text{SQRT} ( \text{EIRP} / (4 * \text{Pi} * S) )$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

#### **MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{EIRP1}) + (\text{EIRP2}) + \dots + (\text{EIRPn})$$

where

EIRPx = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

## 6.4. RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

Multiple chain or colocated transmitters						
Chain for MIMO	FCC Limit (mW/cm <sup>2</sup> )	Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	Separation Distance (cm)
1		11.36	19.70	31.06	1276.4	
2		12.60	19.90	32.50	1778.3	
3		15.70	20.00	35.70	3715.4	
4		13.80	20.20	34.00	2511.9	
5		14.58	20.20	34.78	3006.1	
6		13.67	20.10	33.77	2382.3	
7		12.05	19.90	31.95	1566.8	
8		9.63	19.60	29.23	837.5	
Combined	1.00				17074.6	36.87

**END OF REPORT**