

# TEST REPORT No. I18Z62335-WMD06

for

#### **HMD Global OY**

# Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

GSM 850,900,1800,1900 WCDMA:1,5,8 LTE:1,3,

5,7,8,20,28,38,40,41(120MHz)mobile phone, Bluetooth 4.2, WIFI

802.11 b/g/n

Model Name: TA-1157 FCC ID: 2AJOTTA-1157

with

Hardware Version: 89571\_1\_12 Software Version: 00XX\_1\_XXX

Issued Date: 2019-01-23



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

## Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: <a href="mailto:cttl\_terminals@caict.ac.cn">cttl\_terminals@caict.ac.cn</a>, website: www.caict.ac.cn

# **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I18Z62335-WMD06	Rev.0	1 <sup>st</sup> edition	2019-01-23



# **CONTENTS**

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCII	
	6
	D DURING THE TEST6
	DURING THE TEST6
	6
4. REFERENCE DOCUMENTS	
5. LABORATORY ENVIRONMENT	
6. SUMMARY OF TEST RESULTS	
	9 10
7. TEST EQUIPMENTS UTILIZED	
ANNEX A: MEASUREMENT RESULTS	12
A.1 OUTPUT POWER	
A.2 EMISSION LIMIT	
A.4 OCCUPIED BANDWIDTH	
A.4 OCCUPIED BANDWIDTH	
A.6 BAND EDGE COMPLIANCE	
A.7 CONDUCTED SPURIOUS EMISSION	
A.8 PEAK-TO-AVERAGE POWER RATIO	
ANNEX B: ACCREDITATION CERTIFICATE	112



# 1. Test Laboratory

## 1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191

Location 3:CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology

Development Area, Beijing, P. R. China 100176

# 1.2. <u>Testing Environment</u>

Normal Temperature:  $15-35^{\circ}$ C Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2019-01-02 Testing End Date: 2019-01-16

1.4. Signature

**Dong Yuan** 

(Prepared this test report)

太宇

Zhou Yu

(Reviewed this test report)

Zhao Hui Lin

赵慧麟

Deputy Director of the laboratory

(Approved this test report)



# 2. Client Information

# 2.1. Applicant Information

Company Name: HMD Global OY

Address /Post: Bertel Jungin aukio 9,02600 ESPOO,FINLAND

Contact: Rosario Casillo

Email: Rosario.Casillo@hmdglobal.com

Telephone: NA Fax: NA

# 2.2. Manufacturer Information

Company Name: HMD Global OY

Address /Post: Bertel Jungin aukio 9,02600 ESPOO,FINLAND

Contact: Rosario Casillo

Email: Rosario.Casillo@hmdglobal.com

Telephone: NA Fax: NA



# 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

GSM 850,900,1800,1900 WCDMA:1,5,8 LTE:1,3,

5,7,8,20,28,38,40,41(120MHz)mobile phone, Bluetooth 4.2, WIFI

802.11 b/g/n

Model Name TA-1157

FCC ID 2AJOTTA-1157 Antenna Embedded

Output power 23.67dBm maximum EIRP measured for Band 7

Extreme vol. Limits 3.6VDC to 4.4VDC (nominal: 3.9VDC)

Extreme temp. Tolerance -10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	<b>HW Version</b>	SW Version	Date of receipt
UT04a	352900100018840	89571_1_12	00XX_1_XXX	2018-12-28
UT49a	352900100025225	89571_1_12	00XX_1_XXX	2018-12-28

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

# AE ID\* Description AE1 Battery AE2 Battery

AE1

Model WT330

Manufacturer Jiade Energy Technology(Zhuhai) Co.,Ltd.

Capacitance 3000mAh(rated)

Nominal Voltage 3.85V

AE2

Model WT330

Manufacturer Sunwoda Electronic Co.,Ltd

Capacitance 3000mAh(rated)

Nominal Voltage 3.85V

#### 3.4. General Description

The Equipment Under Test (EUT) is a model of Multi-band GSM/WCDMA/LTE phone with Bluetooth,WLAN,GSM:850,900,1800,1900WCDMA:1,5,8LTE:1,3,5,7,8,20,28,38,40,41(120MHz) mobile phone,Bluetooth 4.2,WIFI 802.11 b/g/n with embedded antenna. Manual and specifications of the EUT were provided to fulfil the test.

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.



# 4. Reference Documents

# 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18
		Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS	10-1-18
	SERVICES	Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
TIA-102.CAAA-E	DIGITAL C4FMCQPSK TRANSCEIVER MEASUREMENT	2016
	METHODS	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	



# 5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C	
Relative humidity	Min. = 35 %, Max. = 60 %	
Shielding effectiveness	> 110 dB	
Electrical insulation	>2 MΩ	
Ground system resistance	<1 Ω	
Site voltage standing-wave ratio	Between 0 and 6 dB, from 1GHz to 18GHz	
$(S_{VSWR})$		
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz	

**Fully-anechoic chamber FAC-3** (9 meters × 6.5 meters × 4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB;
	1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio (S <sub>VSWR</sub> )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz



# 6. SUMMARY OF TEST RESULTS

# 6.1. Summary of test results

Abbreviations used in this clause:		
	Р	Pass
Verdict Column F NA	Fail	
	NA	Not applicable
NM		Not measured
Location Column		The test is performed in test location A, B, C or D
Location Column	A/B/C/D	which are described in section 1.1 of this report

#### LTE Band 5

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	A.1	Р
2	Emission Limit	22.917, 2.1051	A.2	Р
3	Frequency Stability	22.235, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	22.917(b)	A.5	Р
6	Band Edge Compliance	22.917(b)	A.6	Р
7	Conducted Spurious Emission	22.917, 2.1057	A.7	Р

#### LTE Band 7

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(h)(2)	A.1	Р
2	Emission Limit	27.53(m), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(m)	A.5	Р
6	Band Edge Compliance	27.53(m)	A.6	Р
7	Conducted Spurious Emission	27.53(m), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р



#### LTE Band 41

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(h)(2)	A.1	Р
2	Emission Limit	27.53(m), 2.1051	A.2	Р
3	Frequency Stability	27.54, 2.1055	A.3	Р
4	Occupied Bandwidth	2.1049(h)(i)	A.4	Р
5	Emission Bandwidth	27.53(m)	A.5	Р
6	Band Edge Compliance	27.53(m)	A.6	Р
7	Conducted Spurious Emission	27.53(m), 2.1057	A.7	Р
8	Peak to Average Power Ratio	27.50(a)	A.8	Р

#### 6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by CTTL according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1. This report only deals with the LTE functions among the features described in section 3.



# 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2019-11-20	1 year
2	EMI Antenna	3117	00058889	ETS-Lindgren	2020-01-12	3 years
3	EMI Antenna	3117	00119024	ETS-Lindgren	2020-01-21	3 years
4	Universal Radio Communication Tester	CMW500	159082	R&S	2019-12-25	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2019-06-04	1 year
6	EMI Antenna	9117	167	Schwarzbeck	2019-04-13	1 year
7	Signal Generator	N5183A	MY49060052	Agilent	2019-03-31	1 year
8	Climate chamber	SH-242	93008556	ESPEC	2019-12-21	2 year
9	Loop Antenna	HFH2-Z2	829324/007	R&S	2018-12-14	3 year
10	Test Receiver	E4440A	MY48250642	Agilent	2019-03-31	1 year
11	Universal Radio Communication Tester	CMW500	143008	R&S	2019-11-26	1 year
12	Power Amplifier	5S1G4	0341863	AR	1	
13	Universal Radio Communication Tester	MT8821C	6201623363	Anritsu	2019-07-21	1 year



# **ANNEX A: MEASUREMENT RESULTS**

#### **A.1 OUTPUT POWER**

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

# A.1.2.2 Measurement result

#### LTE band 5

Bandwidth	RB size/offset	Fraguanay (MHz)		Power(dBm)	
Danuwidin	RD SIZE/OIISEL	Frequency (MHz)	QPSK	16QAM	64QAM
		848.3	24.28	23.39	22.48
	1 RB high	836.5	24.30	23.32	22.07
		824.7	24.20	23.86	22.65
		848.3	24.13	23.31	22.45
	1 RB low	836.5	24.43	23.31	22.34
4 4 1 1 1 -		824.7	24.35	22.86	22.21
1.4MHz		848.3	24.33	23.56	22.54
	50% RB mid	836.5	24.46	23.13	22.06
		824.7	24.33	22.81	21.97
		848.3	23.42	22.69	21.56
	100% RB	836.5	23.51	22.27	21.28
		824.7	23.29	22.22	21.50
		847.5	24.28	23.26	22.15
	1 RB high	836.5	24.37	23.42	22.13
		825.5	24.33	23.88	22.30
		847.5	24.26	23.34	22.35
	1 RB low	836.5	24.36	23.31	22.47
3MHz		825.5	24.32	23.00	22.32
		847.5	23.41	22.23	21.56
	50% RB mid	836.5	23.33	22.17	21.41
		825.5	23.35	22.48	21.48
	1000/ DD	847.5	23.14	21.92	21.49
	100% RB	836.5	23.30	22.16	21.45




		825.5	23.29	22.37	21.50
		846.5	24.19	22.69	22.23
	1 RB high	836.5	24.00	22.77	22.58
		826.5	24.08	23.14	22.18
		846.5	24.30	22.63	22.55
	1 RB low	836.5	24.19	22.65	22.36
		826.5	24.12	22.97	22.28
5MHz		846.5	23.36	22.45	21.38
	50% RB mid	836.5	23.35	22.31	21.50
		826.5	23.39	22.40	21.45
		846.5	23.21	22.22	21.23
	100% RB	836.5	23.29	22.30	21.38
		826.5	23.35	22.38	21.56
		844.0	24.38	23.43	22.58
	1 RB high	836.5	24.16	23.58	22.17
		829.0	24.18	23.17	22.47
		844.0	24.34	23.47	22.30
	1 RB low	836.5	24.35	22.78	22.14
10MHz		829.0	24.35	23.44	22.29
TUIVITZ		844.0	23.26	22.27	21.51
	50% RB mid	836.5	23.33	22.39	21.52
		829.0	23.34	22.57	21.67
		844.0	23.23	22.23	21.46
	100% RB	836.5	23.36	22.42	21.39
		829.0	23.38	22.35	21.52



#### LTE band 7

Dandwidth	DP oizo/offoot	Fraguenov (MUz)		Power(dBm)	
Bandwidth	RB size/offset	Frequency (MHz)	QPSK	16QAM	64QAM
		2567.5	22.98	21.57	21.03
	1 RB high	2535	23.06	22.27	21.38
		2502.5	23.32	22.27	21.77
		2567.5	23.15	21.86	21.36
	1 RB low	2535	23.31	22.19	21.55
5MHz		2502.5	23.43	22.11	21.73
JIVII IZ		2567.5	22.12	21.16	20.33
	50% RB mid	2535	22.41	21.45	20.52
		2502.5	22.64	21.56	20.64
		2567.5	22.05	21.32	20.19
	100% RB	2535	22.44	21.39	20.72
		2502.5	22.46	21.40	20.72
		2565	23.16	22.23	21.12
	1 RB high	2535	23.32	22.80	21.44
		2505	23.61	22.06	21.51
		2565	23.28	22.28	21.15
	1 RB low	2535	23.65	22.86	21.69
10MHz		2505	23.64	22.31	21.98
TOIVII IZ		2565	22.14	21.40	20.23
	50% RB mid	2535	22.45	21.72	20.76
		2505	22.52	21.64	20.57
		2565	22.08	21.15	20.42
	100% RB	2535	22.43	21.55	20.63
		2505	22.54	21.56	20.91
		2562.5	23.21	22.24	21.32
	1 RB high	2535	23.09	22.41	21.43
		2507.5	23.41	22.64	21.81
		2562.5	23.57	22.53	21.21
	1 RB low	2535	23.34	22.56	21.57
		2507.5	23.42	22.76	21.52
15MHz		2562.5	22.16	21.14	20.44
	50% RB mid	2535	22.38	21.50	20.53
		2507.5	22.49	21.52	20.64
		2562.5	22.12	21.11	20.41
	100% RB	2535	22.33	21.35	20.77
		2507.5	22.51	21.49	20.93
20MHz	1 RB high	2560	22.78	21.74	21.02

©Copyright. All rights reserved by CTTL.






	2535	23.21	21.95	21.36
	2510	23.10	22.04	21.53
	2560	23.07	21.81	21.36
1 RB low	2535	23.60	22.13	21.26
	2510	23.28	22.40	21.79
	2560	22.16	21.23	20.41
50% RB mid	2535	22.44	21.24	20.53
	2510	22.53	21.56	20.83
	2560	22.17	21.26	20.32
100% RB	2535	22.43	21.40	20.46
	2510	22.30	21.46	20.82



# LTE band 41

Bandwidth	RB size/offset	Frequency (MHz)		Power(dBm)	
Danuwiutii	RD SIZE/OIISEL	Frequency (MHZ)	QPSK	16QAM	64QAM
		2652.5	23.56	22.81	21.56
	1 RB high	2575.0	23.62	22.52	21.45
		2537.5	23.85	22.97	21.47
		2652.5	23.76	22.91	21.63
	1 RB low	2575.0	23.70	22.45	21.37
5MHz		2537.5	23.84	22.63	21.48
JIVII IZ		2652.5	23.03	22.12	21.23
	50% RB mid	2575.0	23.14	21.94	21.05
		2537.5	23.07	21.77	21.33
		2652.5	22.95	21.82	21.43
	100% RB	2575.0	22.87	21.83	21.21
		2537.5	23.20	21.92	21.40
		2650.0	24.02	23.17	21.64
	1 RB high	2575.5	23.76	24.12	21.35
		2540.0	23.79	23.25	21.59
		2650.0	23.84	23.19	21.81
	1 RB low	2575.5	23.76	24.07	21.45
10MHz		2540.0	23.91	23.38	21.62
TOWN IZ		2650.0	23.06	22.17	21.57
	50% RB mid	2575.5	23.13	22.17	21.19
		2540.0	23.23	22.22	21.53
		2650.0	23.06	22.05	21.25
	100% RB	2575.5	23.09	21.82	21.09
		2540.0	23.18	22.28	21.41
		2647.5	23.71	22.44	21.69
	1 RB high	2577.0	23.69	23.02	21.54
		2540.0	23.63	22.37	21.75
		2647.5	23.67	22.36	21.63
	1 RB low	2577.0	23.76	23.15	21.47
,		2540.0	23.83	22.44	21.71
15MHz		2647.5	23.18	22.10	21.23
	50% RB mid	2577.0	23.20	21.96	20.97
		2540.0	23.27	22.15	21.18
		2647.5	23.01	22.07	21.16
	100% RB	2577.0	22.88	21.93	20.97
		2540.0	23.14	22.06	21.27
20MHz	1 RB high	2645.0	23.83	22.45	21.60

©Copyright. All rights reserved by CTTL.





	2577.5	23.64	22.85	21.44
	2545.0	23.67	22.27	21.31
	2645.0	23.99	22.40	21.75
1 RB low	2577.5	23.75	22.90	21.36
	2545.0	23.91	22.82	21.63
	2645.0	23.23	22.15	21.38
50% RB mid	2577.5	23.21	21.86	21.12
	2545.0	23.10	22.11	21.24
	2645.0	22.96	22.02	21.49
100% RB	2577.5	22.90	21.96	21.12
	2545.0	22.97	22.08	21.31



#### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP.".


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{\text{Mea}}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_{\text{r}}$ ). The power of signal source ( $P_{\text{Mea}}$ ) is recorded.



The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.

The cable loss (P<sub>cl</sub>), the substitution antenna Gain (G<sub>a</sub>) and the amplifier Gain (P<sub>Ag</sub>) should be recorded after test.

The measurement results are obtained as described below:

Power (EIRP) =  $P_{Mea} - P_{Ag} - P_{cl} - G_a$ 

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15.



#### A.1.3.3 Measurement result

LTE Band 5- ERP 22.913(a) Limits: ≤38.45dBm (7W) LTE Band 5\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-22.39	2.26	45.79	0.95	2.15	19.94	38.45	18.51	Н
836.50	-22.55	2.26	45.66	0.82	2.15	19.52	38.45	18.93	Н
848.30	-23.13	2.27	45.55	0.80	2.15	18.80	38.45	19.65	Н

# LTE Band 5\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-22.78	2.26	45.79	0.94	2.15	19.54	38.45	18.91	Н
836.50	-22.75	2.26	45.66	0.82	2.15	19.32	38.45	19.13	Н
847.50	-23.31	2.27	45.56	0.81	2.15	18.64	38.45	19.81	Н

#### LTE Band 5\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-22.28	2.25	45.77	0.93	2.15	20.02	38.45	18.43	Н
836.50	-22.66	2.26	45.66	0.82	2.15	19.41	38.45	19.04	Н
846.50	-23.43	2.26	45.56	0.82	2.15	18.54	38.45	19.91	Н

#### LTE Band 5\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-22.39	2.13	45.74	0.90	2.15	19.97	38.45	18.48	Н
836.50	-22.11	2.26	45.66	0.82	2.15	19.96	38.45	18.49	Н
844.00	-22.83	2.26	45.59	0.82	2.15	19.17	38.45	19.28	Н



# LTE Band 5\_1.4MHz\_16QAM

Eroguopov(MHz)	uency(MHz) $P_{Mea}(dBm)$ $P_{cl}(dB)$	D (dD)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization	
Frequency(MHz) P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (ub)	P <sub>Ag</sub> (dB)	Gain(dBi)	(dB)	ERP(dBIII)	Lillill(dBill)	iviargin(ub)	i olalization	
824.70	-23.54	2.26	45.79	0.95	2.15	18.79	38.45	19.66	Н
836.50	-23.55	2.26	45.66	0.82	2.15	18.52	38.45	19.93	Н
848.30	-24.10	2.27	45.55	0.80	2.15	17.83	38.45	20.62	Н

# LTE Band 5\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-23.56	2.26	45.79	0.94	2.15	18.76	38.45	19.69	Н
836.50	-23.65	2.26	45.66	0.82	2.15	18.42	38.45	20.03	Н
847.50	-24.68	2.27	45.56	0.81	2.15	17.27	38.45	21.18	Н

#### LTE Band 5\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Aq</sub> (dB)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
	· Wea( ··· ·)	1 ((42)	· /g(/	Gain(dBi)	(dB)		(*,		
826.50	-23.57	2.25	45.77	0.93	2.15	18.73	38.45	19.72	Н
836.50	-23.65	2.26	45.66	0.82	2.15	18.42	38.45	20.03	Н
846.50	-24.26	2.26	45.56	0.82	2.15	17.71	38.45	20.74	Н

# LTE Band 5\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-23.91	2.13	45.74	0.90	2.15	18.45	38.45	20.00	Н
836.50	-23.57	2.26	45.66	0.82	2.15	18.50	38.45	19.95	Н
844.00	-24.20	2.26	45.59	0.82	2.15	17.80	38.45	20.65	Н



# LTE Band 5\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-24.42	2.26	45.79	0.95	2.15	17.91	38.45	20.54	Н
836.50	-24.50	2.26	45.66	0.82	2.15	17.57	38.45	20.88	Н
848.30	-24.92	2.27	45.55	0.80	2.15	17.01	38.45	21.44	Н

# LTE Band 5\_3MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-24.55	2.26	45.79	0.94	2.15	17.77	38.45	20.68	Н
836.50	-24.19	2.26	45.66	0.82	2.15	17.88	38.45	20.57	Н
847.50	-25.17	2.27	45.56	0.81	2.15	16.78	38.45	21.67	Н

# LTE Band 5\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-24.20	2.25	45.77	0.93	2.15	18.10	38.45	20.35	Н
836.50	-24.51	2.26	45.66	0.82	2.15	17.56	38.45	20.89	Н
846.50	-25.27	2.26	45.56	0.82	2.15	16.70	38.45	21.75	Н

# LTE Band 5\_10MHz\_64QAM

Frequency(MHz)	P., (dRm)	P <sub>Mea</sub> (dBm) P <sub>cl</sub> (dB)	P <sub>cl</sub> (dB) P <sub>Aq</sub> (dB)	Ga Antenna	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Frequency(wiriz)	F Mea(UDIII)	r <sub>cl</sub> (ub)	F <sub>Ag</sub> (ub)	Gain(dBi)	(dB)	ERF(UBIII)	Lillii((dBill)	wargin(ub)	Polarization
829.00	-24.25	2.13	45.74	0.90	2.15	18.11	38.45	20.34	Н
836.50	-24.07	2.26	45.66	0.82	2.15	18.00	38.45	20.45	Н
844.00	-24.85	2.26	45.59	0.82	2.15	17.15	38.45	21.30	Н



# LTE Band 7- EIRP Part 27.50(h)(2)

Limits: ≤33dBm (2W) LTE Band 7\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-24.94	3.58	45.68	6.10	23.26	33.00	9.74	Н
2535.00	-23.68	3.63	44.82	6.16	23.67	33.00	9.33	Н
2567.50	-24.68	3.65	44.92	6.22	22.81	33.00	10.19	Н

# LTE Band 7\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-25.04	3.59	45.64	6.11	23.12	33.00	9.88	Н
2535.00	-24.32	3.63	44.82	6.16	23.03	33.00	9.97	Н
2565.00	-24.37	3.65	44.97	6.22	23.17	33.00	9.83	Н

#### LTE Band 7\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-24.81	3.59	44.92	6.11	22.63	33.00	10.37	Н
2535.00	-24.41	3.63	44.82	6.16	22.94	33.00	10.06	Н
2562.50	-24.90	3.65	45.67	6.21	23.33	33.00	9.67	Н

#### LTE Band 7\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-25.15	3.58	45.36	6.12	22.75	33.00	10.25	Н
2535.00	-24.31	3.63	44.82	6.16	23.04	33.00	9.96	Н
2560.00	-24.92	3.64	45.98	6.21	23.63	33.00	9.37	Н



# LTE Band 7\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-26.21	3.58	45.68	6.10	21.99	33.00	11.01	Н
2535.00	-25.36	3.63	44.82	6.16	21.99	33.00	11.01	Н
2567.50	-25.21	3.65	44.92	6.22	22.28	33.00	10.72	Н

# LTE Band 7\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-26.28	3.59	45.64	6.11	21.88	33.00	11.12	Н
2535.00	-25.20	3.63	44.82	6.16	22.15	33.00	10.85	Н
2565.00	-25.31	3.65	44.97	6.22	22.23	33.00	10.77	Н

# LTE Band 7\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-24.97	3.59	44.92	6.11	22.47	33.00	10.53	Н
2535.00	-25.34	3.63	44.82	6.16	22.01	33.00	10.99	Н
2562.50	-26.32	3.65	45.67	6.21	21.91	33.00	11.09	Н

# LTE Band 7\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-25.92	3.58	45.36	6.12	21.98	33.00	11.02	Н
2535.00	-25.53	3.63	44.82	6.16	21.82	33.00	11.18	Н
2560.00	-25.53	3.64	45.98	6.21	23.02	33.00	9.98	Н



# LTE Band 7\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-27.49	3.58	45.68	6.10	20.71	33.00	12.29	Н
2535.00	-25.98	3.63	44.82	6.16	21.37	33.00	11.63	Н
2567.50	-26.30	3.65	44.92	6.22	21.19	33.00	11.81	Н

# LTE Band 7\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-27.55	3.59	45.64	6.11	20.61	33.00	12.39	Н
2535.00	-25.99	3.63	44.82	6.16	21.36	33.00	11.64	Н
2565.00	-26.52	3.65	44.97	6.22	21.02	33.00	11.98	Н

# LTE Band 7\_15MHz\_64QAM

Fr	requency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
	2507.50	-26.56	3.59	44.92	6.11	20.88	33.00	12.12	Н
	2535.00	-26.08	3.63	44.82	6.16	21.27	33.00	11.73	Н
	2562.50	-27.00	3.65	45.67	6.21	21.23	33.00	11.77	Н

# LTE Band 7\_20MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-26.99	3.58	45.36	6.12	20.91	33.00	12.09	Н
2535.00	-26.07	3.63	44.82	6.16	21.28	33.00	11.72	Н
2560.00	-27.28	3.64	45.98	6.21	21.27	33.00	11.73	Н



# LTE Band 41- EIRP Part 27.50(h)(2)

**Limits:** ≤33dBm (2W)

# LTE Band 41\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2537.50	-30.20	3.58	45.59	6.10	17.91	33.00	15.09	Н
2575.00	-29.60	3.69	44.93	6.27	17.91	33.00	15.09	Н
2652.50	-28.62	3.73	44.98	6.44	19.07	33.00	13.93	Н

# LTE Band 41\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2540.00	-29.87	3.58	45.65	6.10	18.30	33.00	14.70	Н
2575.50	-29.45	3.69	44.93	6.27	18.06	33.00	14.94	Н
2650.00	-28.92	3.73	44.98	6.43	18.76	33.00	14.24	Н

#### LTE Band 41\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2542.50	-29.67	3.58	45.65	6.11	18.51	33.00	14.49	Н
2577.00	-29.50	3.69	44.93	6.27	18.01	33.00	14.99	Н
2647.50	-29.45	3.73	44.98	6.43	18.23	33.00	14.77	Н

#### LTE Band 41\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2545.00	-29.13	3.59	45.15	6.11	18.54	33.00	14.46	Н
2577.50	-29.58	3.69	44.93	6.27	17.93	33.00	15.07	Н
2645.00	-29.03	3.73	44.97	6.42	18.63	33.00	14.37	Н



# LTE Band 41\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2537.50	-31.48	3.58	45.59	6.10	16.63	33.00	16.37	Н
2575.00	-31.07	3.69	44.93	6.27	16.44	33.00	16.56	Н
2652.50	-30.07	3.73	44.98	6.44	17.62	33.00	15.38	Н

# LTE Band 41\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2540.00	-31.24	3.58	45.65	6.10	16.93	33.00	16.07	Н
2575.50	-31.01	3.69	44.93	6.27	16.50	33.00	16.50	Н
2650.00	-30.46	3.73	44.98	6.43	17.22	33.00	15.78	Н

# LTE Band 41\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2542.50	-31.06	3.58	45.65	6.11	17.12	33.00	15.88	Н
2577.00	-31.25	3.69	44.93	6.27	16.26	33.00	16.74	Н
2647.50	-30.89	3.73	44.98	6.43	16.79	33.00	16.21	Н

# LTE Band 41\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2545.00	-30.42	3.59	45.15	6.11	17.25	33.00	15.75	Н
2577.50	-30.97	3.69	44.93	6.27	16.54	33.00	16.46	Н
2645.00	-30.40	3.73	44.97	6.42	17.26	33.00	15.74	Н



#### LTE Band 41\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2537.50	-32.25	3.58	45.59	6.10	15.86	33.00	17.14	Н
2575.00	-31.91	3.69	44.93	6.27	15.60	33.00	17.40	Н
2652.50	-30.16	3.73	44.98	6.44	17.53	33.00	15.47	Н

#### LTE Band 41\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2540.00	-32.23	3.58	45.65	6.10	15.94	33.00	17.06	Н
2575.50	-31.84	3.69	44.93	6.27	15.67	33.00	17.33	Н
2650.00	-31.44	3.73	44.98	6.43	16.24	33.00	16.76	Н

#### LTE Band 41\_15MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2542.50	-32.19	3.58	45.65	6.11	15.99	33.00	17.01	Н
2577.00	-32.10	3.69	44.93	6.27	15.41	33.00	17.59	Н
2647.50	-31.78	3.73	44.98	6.43	15.90	33.00	17.10	Н

#### LTE Band 41\_20MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga Antenna Gain(dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2545.00	-31.23	3.59	45.15	6.11	16.44	33.00	16.56	Н
2577.50	-32.02	3.69	44.93	6.27	15.49	33.00	17.51	Н
2645.00	-31.47	3.73	44.97	6.42	16.19	33.00	16.81	Н

Peak EIRP(dBm) =  $P_{Mea}$ (-23.68dBm) -  $G_a$  (-6.16dBi) -  $P_{Ag}$  (-44.82dB) -  $P_{cl}$  (3.63dB) =23.67dBm Note: Expanded measurement uncertainty is U = 2.84 dB, k = 2.



# **A.2 EMISSION LIMIT**


#### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 5 7 41.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power  $(P_{Mea})$  is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the



receiver reaches the previously recorded  $(P_r)$ . The power of signal source  $(P_{Mea})$  is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP)= $P_{Mea}$ +  $P_{pl}$  +  $G_a$ 

- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dB.

#### A.2.2 Measurement Limit

Part 22.917, Part 27.53(g), Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 5 7 41. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 5 7 41 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.



# LTE Band 5, 1.4MHz, QPSK, Channel 20407

Frequency(MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
r requericy(ivii iz) F Meat	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1650.01	-56.82	3.57	5.23	2.15	-57.31	-13.00	44.31	V
2474.00	-40.96	4.60	6.02	2.15	-41.69	-13.00	28.69	V
3304.02	-55.44	5.29	7.73	2.15	-55.15	-13.00	42.15	Н
4130.02	-56.00	6.05	9.03	2.15	-55.17	-13.00	42.17	Н
4955.01	-54.60	6.68	9.86	2.15	-53.57	-13.00	40.57	Н
5772.01	-53.72	7.23	10.55	2.15	-52.55	-13.00	39.55	V

#### LTE Band 5, 1.4MHz, QPSK, Channel 20525

Fraguanov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization	
1673.01	-58.04	3.58	5.19	2.15	-58.58	-13.00	45.58	Н	
2510.00	-46.62	4.63	6.12	2.15	-47.28	-13.00	34.28	Н	
3333.02	-54.59	5.30	7.80	2.15	-54.24	-13.00	41.24	Н	
4183.02	-54.22	6.17	9.08	2.15	-53.46	-13.00	40.46	V	
5026.01	-52.68	6.56	9.94	2.15	-51.45	-13.00	38.45	Н	
5856.01	-54.02	7.25	10.53	2.15	-52.89	-13.00	39.89	Н	

# LTE Band 5, 1.4MHz, QPSK, Channel 20643

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1697.01	-58.92	3.60	5.15	2.15	-59.52	-13.00	46.52	V
2545.00	-42.18	4.66	6.18	2.15	-42.81	-13.00	29.81	Н
3382.02	-55.10	5.35	7.92	2.15	-54.68	-13.00	41.68	V
4246.02	-51.26	6.24	9.15	2.15	-50.50	-13.00	37.50	Н
5094.01	-53.11	6.76	10.03	2.15	-51.99	-13.00	38.99	Н
5929.01	-52.60	7.47	10.51	2.15	-51.71	-13.00	38.71	Н



# LTE Band 5, 1.4MHz, 16QAM, Channel 20407

Fragues 24/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Dolorization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1650.01	-55.13	3.57	5.23	2.15	-55.62	-13.00	42.62	Н
2474.00	-43.68	4.60	6.02	2.15	-44.41	-13.00	31.41	Н
3287.02	-55.20	5.28	7.69	2.15	-54.94	-13.00	41.94	V
4131.02	-55.36	6.05	9.03	2.15	-54.53	-13.00	41.53	V
4944.01	-54.45	6.70	9.84	2.15	-53.46	-13.00	40.46	Н
5761.01	-53.48	7.25	10.55	2.15	-52.33	-13.00	39.33	V

#### LTE Band 5, 1.4MHz, 16QAM, Channel 20525

Fraguenov/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Dolorization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization	
1673.01	-58.37	3.58	5.19	2.15	-58.91	-13.00	45.91	Н	
2510.00	-45.11	4.63	6.12	2.15	-45.77	-13.00	32.77	Н	
3354.02	-54.06	5.32	7.85	2.15	-53.68	-13.00	40.68	Н	
4179.02	-55.58	6.16	9.08	2.15	-54.81	-13.00	41.81	V	
5025.01	-54.20	6.56	9.94	2.15	-52.97	-13.00	39.97	Н	
5861.01	-53.36	7.27	10.53	2.15	-52.25	-13.00	39.25	Н	

# LTE Band 5, 1.4MHz, 16QAM, Channel 20643

Fragues av/MII=)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Delerization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization	
1697.01	-59.73	3.60	5.15	2.15	-60.33	-13.00	47.33	V	
2545.00	-37.94	4.66	6.18	2.15	-38.57	-13.00	25.57	Н	
3391.02	-55.39	5.35	7.94	2.15	-54.95	-13.00	41.95	Н	
4246.02	-53.17	6.24	9.15	2.15	-52.41	-13.00	39.41	Н	
5093.01	-53.68	6.75	10.03	2.15	-52.55	-13.00	39.55	V	
5935.01	-52.99	7.47	10.51	2.15	-52.10	-13.00	39.10	Н	



# LTE Band 5, 1.4MHz, 64QAM, Channel 20407

Fraguanov/MUz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1650.01	-56.18	3.57	5.23	2.15	-56.67	-13.00	43.67	V
2474.00	-39.50	4.60	6.02	2.15	-40.23	-13.00	27.23	Н
3308.02	-54.68	5.29	7.74	2.15	-54.38	-13.00	41.38	Н
4127.02	-56.18	6.04	9.03	2.15	-55.34	-13.00	42.34	Н
4953.01	-54.10	6.68	9.85	2.15	-53.08	-13.00	40.08	Н
5787.01	-54.76	7.21	10.54	2.15	-53.58	-13.00	40.58	Н

#### LTE Band 5, 1.4MHz, 64QAM, Channel 20525

Fragues 20/MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Fulanzation	
1673.01	-57.86	3.58	5.19	2.15	-58.40	-13.00	45.40	Н	
2510.00	-37.47	4.63	6.12	2.15	-38.13	-13.00	25.13	Н	
3354.02	-54.68	5.32	7.85	2.15	-54.30	-13.00	41.30	Н	
4187.02	-54.35	6.18	9.09	2.15	-53.59	-13.00	40.59	Н	
5024.01	-51.14	6.56	9.93	2.15	-49.92	-13.00	36.92	Н	
5854.01	-54.22	7.25	10.53	2.15	-53.09	-13.00	40.09	Н	

# LTE Band 5, 1.4MHz, 64QAM, Channel 20643

Eroguepov(MHz)	D (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1709.01	-58.30	3.61	5.12	2.15	-58.94	-13.00	45.94	V
2545.00	-45.80	4.66	6.18	2.15	-46.43	-13.00	33.43	Н
3379.02	-55.02	5.34	7.91	2.15	-54.60	-13.00	41.60	V
4245.02	-52.76	6.24	9.15	2.15	-52.00	-13.00	39.00	Н
5093.01	-52.52	6.75	10.03	2.15	-51.39	-13.00	38.39	Н
5953.01	-53.07	7.47	10.51	2.15	-52.18	-13.00	39.18	Н



# LTE Band 7- EIRP 27.50(h)(2)

**Limits:** ≤33 dBm (2W)

RSE1\_S30\_LB7\_5MHz\_CH20775\_QPSK\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5006.02	-44.34	6.59	9.91	-41.02	-25.00	16.02	V
7509.01	-52.77	8.36	12.21	-48.92	-25.00	23.92	V
10013.01	-41.74	9.22	12.91	-38.05	-25.00	13.05	V
12497.01	-49.91	10.18	13.20	-46.89	-25.00	21.89	Н
15013.00	-45.61	11.23	13.99	-42.85	-25.00	17.85	V
17525.00	-43.52	12.82	14.94	-41.40	-25.00	16.40	Н

# RSE1\_S30\_LB7\_5MHz\_CH21100\_QPSK\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5074.02	-42.44	6.70	10.00	-39.14	-25.00	14.14	Н
7611.01	-52.78	8.02	12.29	-48.51	-25.00	23.51	Н
10147.01	-44.34	9.39	12.96	-40.77	-25.00	15.77	V
12662.01	-49.68	10.36	13.30	-46.74	-25.00	21.74	Н
15228.00	-45.82	11.37	13.86	-43.33	-25.00	18.33	V
17738.00	-43.93	12.39	15.23	-41.09	-25.00	16.09	Н

#### RSE1\_S30\_LB7\_5MHz\_CH21425\_QPSK\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5136.02	-46.69	6.86	10.09	-43.46	-25.00	18.46	V
7704.01	-48.11	8.42	12.36	-44.17	-25.00	19.17	V
10273.01	-44.06	9.55	13.01	-40.60	-25.00	15.60	V
12846.01	-49.53	10.65	13.41	-46.77	-25.00	21.77	Н
15388.00	-45.21	11.38	13.77	-42.82	-25.00	17.82	V
17988.00	-43.31	12.90	15.58	-40.63	-25.00	15.63	Н



# RSE1\_S30\_LB7\_5MHz\_CH20775\_16QAM\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5009.02	-42.01	6.59	9.91	-38.69	-25.00	13.69	Н
7512.01	-51.56	8.34	12.21	-47.69	-25.00	22.69	Н
10020.01	-41.30	9.24	12.91	-37.63	-25.00	12.63	V
12525.01	-50.11	10.25	13.22	-47.14	-25.00	22.14	Н
15016.00	-46.16	11.24	13.99	-43.41	-25.00	18.41	V
17515.00	-43.24	12.78	14.92	-41.10	-25.00	16.10	Н

# RSE1\_S30\_LB7\_5MHz\_CH21100\_16QAM\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5074.02	-43.22	6.70	10.00	-39.92	-25.00	14.92	Н
7609.01	-52.99	8.01	12.29	-48.71	-25.00	23.71	Н
10147.01	-45.09	9.39	12.96	-41.52	-25.00	16.52	V
12663.01	-49.34	10.36	13.30	-46.40	-25.00	21.40	Н
15209.00	-45.27	11.39	13.87	-42.79	-25.00	17.79	Н
17739.00	-44.24	12.40	15.23	-41.41	-25.00	16.41	V

# RSE1\_S30\_LB7\_5MHz\_CH21425\_16QAM\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5136.02	-47.94	6.86	10.09	-44.71	-25.00	19.71	V
7704.01	-48.23	8.42	12.36	-44.29	-25.00	19.29	V
10274.01	-44.50	9.55	13.01	-41.04	-25.00	16.04	V
12823.01	-50.13	10.71	13.39	-47.45	-25.00	22.45	Н
15410.00	-44.93	11.41	13.75	-42.59	-25.00	17.59	V
17970.00	-43.56	12.89	15.56	-40.89	-25.00	15.89	Н



# RSE1\_S30\_LB7\_5MHz\_CH20775\_64QAM\_1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5009.02	-39.83	6.59	9.91	-36.51	-25.00	11.51	Н
7512.01	-50.49	8.34	12.21	-46.62	-25.00	21.62	Н
10020.01	-41.38	9.24	12.91	-37.71	-25.00	12.71	V
12498.01	-50.38	10.18	13.20	-47.36	-25.00	22.36	V
15003.00	-46.00	11.22	14.00	-43.22	-25.00	18.22	Н
17524.00	-42.93	12.82	14.93	-40.82	-25.00	15.82	Н

#### RSE1 S30 LB7 5MHz CH21100 64QAM 1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
				(dBm)			
5074.02	-43.50	6.70	10.00	-40.20	-25.00	15.20	Н
7612.01	-51.73	8.03	12.29	-47.47	-25.00	22.47	Н
10146.01	-44.62	9.39	12.96	-41.05	-25.00	16.05	V
12690.01	-49.05	10.31	13.31	-46.05	-25.00	21.05	V
15200.00	-45.43	11.40	13.88	-42.95	-25.00	17.95	V
17761.00	-43.95	12.52	15.27	-41.20	-25.00	16.20	V

#### RSE1 S30 LB7 5MHz CH21425 64QAM 1P

Frequency	SG	CableLoss	AntennaGain	Peak	Limit	Margin	Polorization
(MHz)	(dBm)	(dB)	(dBi)	EIRP	(dBm)	(dB)	
	, ,		,	(dBm)	, ,		
5139.02	-42.28	6.86	10.09	-39.05	-25.00	14.05	Н
7705.01	-49.99	8.42	12.36	-46.05	-25.00	21.05	V
10283.01	-43.85	9.58	13.01	-40.42	-25.00	15.42	V
12838.01	-49.86	10.67	13.40	-47.13	-25.00	22.13	Н
15389.00	-46.15	11.38	13.77	-43.76	-25.00	18.76	V
17984.00	-43.09	12.90	15.58	-40.41	-25.00	15.41	Н



## LTE Band 41, 5MHz, QPSK, Channel 39675

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit	Margin(dB)	Polarization
1 requeriey(wiriz)	i Mea(GDIII)	Loss	Loss Gain EIRP(dBm) (dBm)		1 Glarization		
5075.02	-44.37	6.70	10.01	-41.06	-13.00	28.06	Н
10161.01	-42.86	9.36	12.96	-39.26	-13.00	26.26	Н
12683.01	-50.05	10.3 3	13.31	-47.07	-13.00	34.07	Н
15248.00	-45.77	11.3 4	13.85	-43.26	-13.00	30.26	V
16470.00	-44.58	11.9 3	13.61	-42.90	-13.00	29.90	Н
17781.00	-42.99	12.6 3	15.29	-40.33	-13.00	27.33	Н

## LTE Band 41, 5MHz, QPSK, Channel 40620

	D (dD:ss)	Path	Antenna	Peak	Limit	Manaia (dD)	Dalarination
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(dB)	Polarization
7725.01	-48.13	8.39	12.38	-44.14	-13.00	31.14	V
10301.01	-42.69	9.64	13.02	-39.31	-13.00	26.31	V
12876.01	-49.61	10.5 7	13.43	-46.75	-13.00	33.75	V
15473.00	-46.06	11.5 0	13.72	-43.84	-13.00	30.84	V
16764.00	-42.64	11.9 8	13.71	-40.91	-13.00	27.91	Н
17995.00	-43.97	12.9 0	15.59	-41.28	-13.00	28.28	Н

### LTE Band 41, 5MHz, QPSK, Channel 41565

ETE Band 41, Olim E, Qi Ott, Onamici 41000									
Frequency(MHz)	D (dDm)	Path	Antenna	Peak	Limit	Margin(dD)	Polarization		
i requeriey(Wiriz)   1 Me	P <sub>Mea</sub> (dBm)	Loss	oss Gain EIRP(dBm) (dBm)		Margin(dB)	Folarization			
5307.02	-47.83	6.99	10.33	-44.49	-13.00	31.49	Н		
7952.01	-50.24	8.37	12.56	-46.05	-13.00	33.05	V		
10613.01	-48.20	9.28	13.12	-44.36	-13.00	31.36	Н		
13275.01	-48.97	10.5 6	13.89	-45.64	-13.00	32.64	V		
15930.00	-46.00	11.6 8	13.70	-43.98	-13.00	30.98	V		
17250.00	-43.33	12.3 6	14.35	-41.34	-13.00	28.34	V		



## LTE Band 41 5MHz, 16QAM, Channel 39675

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit	Margin(dB)	Polarization	
Frequency(MHZ)	Mea(ubiii)	Loss	Gain	EIRP(dBm)	(dBm)	ivialyili(ub)	Polarization	
7607.01	-50.08	8.00	12.29	-45.79	-13.00	32.79	Н	
10157.01	-42.77	9.37	12.96	-39.18	-13.00	26.18	Н	
12690.01	-50.09	10.3 1	13.31	-47.09	-13.00	34.09	Н	
15236.00	-46.32	11.3 6	13.86	-43.82	-13.00	30.82	Н	
16508.00	-43.44	11.9 9	13.60	-41.83	-13.00	28.83	Н	
17783.00	-43.53	12.6 4	15.30	-40.87	-13.00	27.87	V	

## LTE Band 41, 5MHz, 16QAM, Channel 40620

Fraguenov/MHz)	D (dDm)	Path	Antenna	Peak	Limit	Margin(dD)	Dolorization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(dB)	Polarization
5150.02	-51.59	6.88	10.11	-48.36	-13.00	35.36	V
10303.01	-44.25	9.65	13.02	-40.88	-13.00	27.88	V
12860.01	-49.17	10.6 1	13.42	-46.36	-13.00	33.36	V
15449.00	-45.44	11.4 6	13.73	-43.17	-13.00	30.17	V
16765.00	-41.99	11.9 8	13.71	-40.26	-13.00	27.26	Н
17998.00	-44.66	12.9 0	15.60	-41.96	-13.00	28.96	Н

# LTE Band 41, 5MHz, 16QAM, Channel 41565

Fraguanov/MUz)	D (dDm)	Path	Antenna	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(dB)	Polarization
5301.02	-48.02	6.99	10.32	-44.69	-13.00	31.69	Н
7952.01	-49.49	8.37	12.56	-45.30	-13.00	32.30	V
10609.01	-48.81	9.28	13.12	-44.97	-13.00	31.97	Н
13244.01	-48.51	10.5	13.84	-45.20	-13.00	32.20	V
10244.01	- <del>1</del> 0.51	3	10.04	-43.20	-10.00	32.20	V
15935.00	-45.48	11.6	13.70	-43.47	-13.00	30.47	V
10000.00	40.40	9	10.70	40.47	10.00	00.47	V
17265.00	-43.00	12.3	14.38	-40.98	-13.00	27.98	Н
17203.00	<del>-4</del> 5.00	6	17.50	-40.30	-13.00	21.90	11



## LTE Band 41 5MHz, 64QAM, Channel 39675

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5076.02	-55.22	6.70	10.01	-51.91	-13.00	38.91	V
7605.01	-55.27	8.00	12.28	-50.99	-13.00	37.99	V
10162.01	-42.72	9.36	12.96	-39.12	-13.00	26.12	Н
12699.01	-49.72	10.3 0	13.32	-46.70	-13.00	33.70	Н
15223.00	-45.76	11.3 7	13.87	-43.26	-13.00	30.26	V
16470.00	-44.35	11.9 3	13.61	-42.67	-13.00	29.67	Н

### LTE Band 41, 5MHz, 64QAM, Channel 40620

Fraguanov/MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (ubiii)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(dB)	Polarization
5157.02	-51.02	6.89	10.12	-47.79	-13.00	34.79	Н
7798.01	-55.29	8.29	12.44	-51.14	-13.00	38.14	Н
9092.01	-54.28	8.96	13.16	-50.08	-13.00	37.08	Н
11649.01	-50.70	9.71	13.07	-47.34	-13.00	34.34	Н
14253.00	-45.79	10.9 3	14.45	-42.27	-13.00	29.27	V
16860.00	-41.62	12.0 4	13.74	-39.92	-13.00	26.92	V

#### LTE Band 41, 5MHz, 64QAM, Channel 41565

	212 Bana 11, 6mm2, 614, mm, 614, mm									
Frequency(MHz) P <sub>Mea</sub> (c	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit	Margin(dB)	Polarization			
	Mea(ubiii)	Loss	Gain	EIRP(dBm)	(dBm)	Margin(ub)	Polarization			
5306.02	-47.40	6.99	10.33	-44.06	-13.00	31.06	Н			
7959.01	-53.33	8.37	12.57	-49.13	-13.00	36.13	Н			
10617.01	-49.72	9.28	13.12	-45.88	-13.00	32.88	V			
13269.01	-48.58	10.5 5	13.88	-45.25	-13.00	32.25	V			
15911.00	-45.76	11.6 4	13.70	-43.70	-13.00	30.70	Н			
17220.00	-42.82	12.3 5	14.28	-40.89	-13.00	27.89	V			

Note: The maximum value of expanded measurement uncertainty for this test item is U = 5.16 dB, k = 2.



## A.3 FREQUENCY STABILITY

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -10℃.
- 3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 5 7 41, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10  $^{\circ}$ C increments from -10 $^{\circ}$ C to +50 $^{\circ}$ C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5 °C during the measurement procedure.

#### A.3.2 Measurement Limit

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d) (2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.4VDC, with a nominal voltage of 3.9VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. For the purposes of measuring frequency stability these voltage limits are to be used.



#### A.3.3 Measurement results

## LTE Band 5, 1.4MHz bandwidth (worst case of all bandwidths)

# Frequency Error vs Voltage

Voltage	Fred	quency error (F	Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.6	4.28	-23.25	-0.90	0.0051	0.0278	0.001	
3.9	-3.78	-23.35	-1.70	0.0045	0.0279	0.002	
4.4	-4.02	-24.79	-2.50	0.0048	0.0296	0.003	

## **Frequency Error vs Temperature**

Temperature	Freq	uency error (H	Hz)	Frequency error (ppm)			
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
50	-3.32	-24.68	-0.50	0.0040	0.0295	0.001	
40	-3.89	-23.86	0.60	0.0047	0.0285	0.001	
30	-4.19	-25.51	0.80	0.0050	0.0305	0.001	
20	-2.90	-24.78	0.00	0.0035	0.0296	0.000	
10	-3.43	-23.90	-0.60	0.0041	0.0286	0.001	
0	-3.88	-24.09	-1.50	0.0046	0.0288	0.002	
- 10	-2.89	-22.72	-0.20	0.0035	0.0272	0.000	

## LTE Band 7, 10MHz bandwidth (worst case of all bandwidths)

### Frequency Error vs Voltage

Voltage	Fred	quency error (I	Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.6	-7.62	-12.13	-4.60	0.0030	0.0048	0.002	
3.9	-6.09	-11.57	-5.80	0.0024	0.0046	0.002	
4.4	-8.40	-14.03	-4.70	0.0033	0.0055	0.002	

### **Frequency Error vs Temperature**

Administration to temperature						
Temperature	Freq	Frequency error (Hz)		Freque	ency error (p	pm)
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
50	-7.04	-13.53	-4.10	0.0028	0.0053	0.002
40	-9.18	-10.13	0.00	0.0036	0.0040	0.000
30	-8.97	-11.13	-2.70	0.0035	0.0044	0.001
20	-6.81	-10.36	-3.10	0.0027	0.0041	0.001
10	-5.99	-9.97	-0.20	0.0024	0.0039	0.000
0	-7.54	-13.68	-2.40	0.0030	0.0054	0.001
- 10	-5.45	-11.84	-3.90	0.0021	0.0047	0.002



# LTE Band 41, 5MHz bandwidth (worst case of all bandwidths)

## Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Freq	uency error	(ppm)	
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3.6	4.62	11.39	2.70	0.002	0.004	0.001
3.9	-2.03	2.72	3.30	0.001	0.001	0.001
4.4	5.54	7.93	2.60	0.002	0.003	0.001

# **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)		Temperature Freq		Freq	uency error	(ppm)
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
50°	-1.47	3.58	-3.10	0.001	0.001	0.001	
40°	0.17	1.80	0.20	0.000	0.001	0.000	
30°	-4.31	-0.44	1.50	0.002	0.000	0.001	
20°	3.68	-4.38	0.40	0.001	0.002	0.000	
10°	4.72	3.68	1.10	0.002	0.001	0.000	
0°	3.15	8.98	5.10	0.001	0.003	0.002	
- 10°	8.10	5.89	2.90	0.003	0.002	0.001	



# A.4 OCCUPIED BANDWIDTH

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- d) Set the detection mode to peak, and the trace mode to max hold.
- e) Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



#### LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
836.5	QPSK	16QAM	64QAM	
	1089.74	1097.76	1089.74	

### LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:34:58


## LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:36:22



# LTE band 5, 1.4MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:15:42



#### LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
836.5	QPSK	16QAM	64QAM	
	2692.31	2708.33	2692.31	

### LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:37:48


## LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:39:12



# LTE band 5, 3MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:17:55



#### LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
836.5	QPSK	16QAM	64QAM	
	4519.23	4519.23	4495.19	

### LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:40:38


## LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:42:02



# LTE band 5, 5MHz Bandwidth,64QAM (99% BW)




Date: 11.JAN.2019 14:19:09



#### LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
836.5	QPSK	16QAM	64QAM	
	8990.38	8942.31	8990.38	

### LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:43:28


## LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:44:52



# LTE band 5, 10MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:20:42



#### LTE band 7, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
2535.0	QPSK	16QAM	64QAM	
	4519.23	4519.23	4495.19	

### LTE band 7, 5MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:46:19


## LTE band 7, 5MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:47:43



# LTE band 7, 5MHz Bandwidth,64QAM (99% BW)




Date: 11.JAN.2019 14:23:56



#### LTE band 7, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
2535.0	QPSK	16QAM	64QAM	
	8942.31	8990.38	8942.31	

## LTE band 7, 10MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:49:09


## LTE band 7, 10MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:50:33



## LTE band 7, 10MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:25:21



### LTE band 7, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
2535.0	QPSK	16QAM	64QAM	
	13485.58	13485.58	13485.58	

## LTE band 7, 15MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:51:59


# LTE band 7, 15MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:53:23



# LTE band 7, 15MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:26:32



### LTE band 7, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
2535.0	QPSK	16QAM	64QAM	
	17884.62	17884.62	17980.77	

### LTE band 7, 20MHz Bandwidth, QPSK (99% BW)



Date: 7.JAN.2019 11:54:49


## LTE band 7, 20MHz Bandwidth, 16QAM (99% BW)



Date: 7.JAN.2019 11:56:13



# LTE band 7, 20MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:28:03



#### LTE band 41, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
2575.0	QPSK	16QAM	64QAM	
	4519.23	4471.15	4471.15	

### LTE band 41, 5MHz Bandwidth, QPSK (99% BW)



Date: 11.JAN.2019 10:22:10


## LTE band 41, 5MHz Bandwidth,16QAM (99% BW)



Date: 11.JAN.2019 10:22:25



## LTE band 41, 5MHz Bandwidth,64QAM (99% BW)




Date: 11.JAN.2019 14:31:43



#### LTE band 41, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
2575.5	QPSK	16QAM	64QAM
	8990.38	8942.31	8942.31

### LTE band 41, 10MHz Bandwidth, QPSK (99% BW)



Date: 11.JAN.2019 10:29:05


### LTE band 41, 10MHz Bandwidth, 16QAM (99% BW)



Date: 11.JAN.2019 10:29:20



# LTE band 41, 10MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:34:29



#### LTE band 41, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
2577.0	QPSK	16QAM	64QAM
	13485.6	13485.6	13485.6

### LTE band 41, 15MHz Bandwidth, QPSK (99% BW)



Date: 11.JAN.2019 10:38:10


### LTE band 41, 15MHz Bandwidth, 16QAM (99% BW)



Date: 11.JAN.2019 10:38:25



# LTE band 41, 15MHz Bandwidth, 64QAM (99% BW)




Date: 11.JAN.2019 14:36:34



#### LTE band 41, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
2577.5	QPSK	16QAM	64QAM
	17884.6	17884.6	17884.6

### LTE band 41, 20MHz Bandwidth, QPSK (99% BW)



Date: 11.JAN.2019 10:45:47


### LTE band 41, 20MHz Bandwidth, 16QAM (99% BW)



Date: 11.JAN.2019 10:46:03



# LTE band 41, 20MHz Bandwidth, 64QAM (99% BW)



Date: 11.JAN.2019 14:38:41



# A.5 EMISSION BANDWIDTH


#### A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

#### LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	1274.04	1306.09	1290.06

#### LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)




Date: 7.JAN.2019 12:54:27

### LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)





# LTE band 5, 1.4MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:16:31



#### LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	2948.72	2980.77	2964.74

### LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 12:57:17


# LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)



Date: 7.JAN.2019 12:58:41



# LTE band 5, 3MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:18:18



#### LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	4951.92	5000.00	4903.85

### LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:00:07


### LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)



Date: 7.JAN.2019 13:01:31



# LTE band 5, 5MHz Bandwidth,64QAM (-26dBc BW)




Date: 11.JAN.2019 14:19:54



#### LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
930.5	QPSK	16QAM	64QAM
836.5	9807.69	9807.69	9711.54

## LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:02:57


## LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 7.JAN.2019 13:04:21



# LTE band 5, 10MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:21:29



#### LTE band 7, 5MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2535.0	QPSK	16QAM	64QAM
2535.0	4975.96	5048.08	4927.88

## LTE band 7, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:05:48


# LTE band 7, 5MHz Bandwidth,16QAM (-26dBc BW)



Date: 7.JAN.2019 13:07:13



# LTE band 7, 5MHz Bandwidth,64QAM (-26dBc BW)




Date: 11.JAN.2019 14:24:28



#### LTE band 7, 10MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2535.0	QPSK	16QAM	64QAM
2555.0	9903.85	9903.85	9759.62

## LTE band 7, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:08:38


# LTE band 7, 10MHz Bandwidth,16QAM (-26dBc BW)



Date: 7.JAN.2019 13:10:03



# LTE band 7, 10MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:25:41



#### LTE band 7, 15MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2525.0	QPSK	16QAM	64QAM
2535.0	14855.77	14783.65	14711.5

## LTE band 7, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:11:29


# LTE band 7, 15MHz Bandwidth,16QAM (-26dBc BW)



Date: 7.JAN.2019 13:12:53



# LTE band 7, 15MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:27:10



#### LTE band 7, 20MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2535.0	QPSK	16QAM	64QAM
2555.0	19326.92	19326.92	19134.6

## LTE band 7, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 7.JAN.2019 13:14:19


# LTE band 7, 20MHz Bandwidth,16QAM (-26dBc BW)



Date: 7.JAN.2019 13:15:43



# LTE band 7, 20MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:28:23



#### LTE band 41, 5MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2575.0	QPSK	16QAM	64QAM
2575.0	4951.92	4879.81	4903.85

## LTE band 41, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 11.JAN.2019 10:23:20


# LTE band 41, 5MHz Bandwidth,16QAM (-26dBc BW)



Date: 11.JAN.2019 10:23:37



# LTE band 41, 5MHz Bandwidth,64QAM (-26dBc BW)




Date: 11.JAN.2019 14:32:26



#### LTE band 41, 10MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2575.5	QPSK	16QAM	64QAM
25/5.5	9711.54	9663.46	9663.46

## LTE band 41, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 11.JAN.2019 10:30:15


## LTE band 41, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 11.JAN.2019 10:30:32



# LTE band 41, 10MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:35:31



#### LTE band 41, 15MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2577.0	QPSK	16QAM	64QAM
2577.0	14711.5	14639.4	14495.2

## LTE band 41, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 11.JAN.2019 10:39:20


## LTE band 41, 15MHz Bandwidth, 16QAM (-26dBc BW)



Date: 11.JAN.2019 10:39:37



# LTE band 41, 15MHz Bandwidth, 64QAM (-26dBc BW)




Date: 11.JAN.2019 14:36:59



#### LTE band 41, 20MHz (-26dBc)


Frequency(MHz)	Emission Bandwidth (-26dBc)( kHz)		
2577.5	QPSK	16QAM	64QAM
2577.5	19326.9	19134.6	19326.9

## LTE band 41, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 11.JAN.2019 10:46:58


## LTE band 41, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 11.JAN.2019 10:47:15



# LTE band 41, 20MHz Bandwidth, 64QAM (-26dBc BW)



Date: 11.JAN.2019 14:39:43



## A.6 BAND EDGE COMPLIANCE

#### A.6.1 Measurement limit

Part 22.917(b), states that on any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log (P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.


According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

Part 27.53(m) states that for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.




#### LTE band 5

## OBW: 1RB-low\_offset



Date: 9.JAN.2019 16:14:22


# LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 9.JAN.2019 16:14:37




# OBW: 1RB-high\_offset



Date: 9.JAN.2019 16:16:29


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 9.JAN.2019 16:16:45




## LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 14.JAN.2019 11:02:00

## HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 14.JAN.2019 11:04:03




#### LTE band 7

## **OBW: 1RB-low\_offset**



Date: 14.JAN.2019 11:08:03


# LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 14.JAN.2019 11:08:24








Date: 14.JAN.2019 11:08:39




# OBW: 1RB-high\_offset




Date: 14.JAN.2019 11:11:34


# HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 14.JAN.2019 11:11:55









Date: 14.JAN.2019 11:12:10



## LOW BAND EDGE BLOCK-20MHz-100%RB




Date: 14.JAN.2019 11:09:15




Date: 14.JAN.2019 11:09:30



#### HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 14.JAN.2019 11:12:45




Date: 14.JAN.2019 11:13:00




#### LTE band 41

## **OBW: 1RB-low\_offset**




Date: 14.JAN.2019 11:26:52

## LOW BAND EDGE BLOCK-1RB-low\_offset



Date: 14.JAN.2019 11:27:13






Date: 14.JAN.2019 11:27:28




# OBW: 1RB-high\_offset




Date: 14.JAN.2019 13:33:33


## HIGH BAND EDGE BLOCK-1RB-high\_offset



Date: 14.JAN.2019 13:33:54









Date: 14.JAN.2019 13:34:09



# LOW BAND EDGE BLOCK-20MHz-100%RB




Date: 14.JAN.2019 13:36:03




Date: 14.JAN.2019 13:36:18



## HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 14.JAN.2019 13:38:05



Date: 14.JAN.2019 13:38:19



## A.7 CONDUCTED SPURIOUS EMISSION

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

#### A. 7.2 Measurement Limit

Part 22.917 specifies that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.




#### A. 7.3 Measurement result

# Only worst case result is given below

## LTE band 5: 30MHz - 10GHz






Date: 9.JAN.2019 16:29:47

#### LTE band 7: 30MHz - 26GHz

Spurious emission limit –25dBm.




Date: 14.JAN.2019 13:51:24



## LTE band 41: 30MHz - 26GHz

Spurious emission limit -25dBm.



Date: 17.JAN.2019 15:00:17



## A.8 PEAK-TO-AVERAGE POWER RATIO

#### Reference

FCC: CFR Part 27.50(a)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

#### According to KDB 971168 5.7.1:

- a)Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e)Record the maximum PAPR level associated with a probability of 0.1%

#### A.8.1 Measurement limit

not exceed 13 dB

#### A.8.2 Measurement results

#### LTE band 7, 20MHz

Frequency(MHz)	PAPR(dB)		
2510.0	QPSK	16QAM	64QAM
2510.0	6.70	7.31	7.24

#### LTE band 41 20MHz

Frequency(MHz)	PAPR(dB)		
2577.5	QPSK	16QAM	64QAM
2577.5	7.21	7.92	8.59



# **ANNEX B: Accreditation Certificate**

United States Department of Commerce National Institute of Standards and Technology



# Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

#### Telecommunication Technology Labs, CAICT

Beijing China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

#### **Electromagnetic Compatibility & Telecommunications**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2018-09-28 through 2019-09-30

Effective Dates



For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*