FCC Test Report

APPLICANT : HMD global Oy EQUIPMENT : Mobile Phone

BRAND NAME : Nokia MODEL NAME : TA-1184

FCC ID : 2AJOTTA-1184

STANDARD : 47 CFR Part 15 Subpart B

CLASSIFICATION: Certification

The product was received on Mar. 05, 2019 and testing was completed on Apr. 03, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Journes Huarg

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 1 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

TABLE OF CONTENTS

RE	REVISION HISTORY3				
50	WWAK	Y OF TEST RESULT	4		
1.	GENE	RAL DESCRIPTION	5		
	1.1.	Applicant			
	1.2.	Manufacturer			
	1.3.	Product Feature of Equipment Under Test			
	1.4.	Product Specification of Equipment Under Test			
	1.5.	Modification of EUT			
	1.6.	Test Location			
	1.7.	Applicable Standards	8		
2.	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9		
	2.1.	Test Mode	9		
	2.2.	Connection Diagram of Test System	11		
	2.3.	Support Unit used in test configuration and system			
	2.4.	EUT Operation Test Setup	12		
3.	TEST	RESULT	13		
	3.1.	Test of AC Conducted Emission Measurement	13		
	3.2.	Test of Radiated Emission Measurement			
4.	LIST	OF MEASURING EQUIPMENT	22		
5.	UNCE	RTAINTY OF EVALUATION	23		
ΑP	PENDI	X A. SETUP PHOTOGRAPHS			

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 2 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC930509-01	Rev. 01	Initial issue of report	Apr. 16, 2019

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 3 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
					Under limit
3.1	15.107	07 AC Conducted Emission	< 15.107 limits	PASS	3.84 dB at
					0.152 MHz
					Under limit
2.0	15.109 Radiated Emission	45 400 limita	PASS	3.09 dB at	
3.2		< 15.109 limits		480.080 MHz	
					for Quasi-Peak

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 4 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

1. General Description

1.1. Applicant

HMD global Oy

Bertel Jungin aukio 9, 02600 Espoo, Finland

1.2. Manufacturer

HMD global Oy

Bertel Jungin aukio 9, 02600 Espoo, Finland

1.3. Product Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Phone
Brand Name	Nokia
Model Name	TA-1184
FCC ID	2AJOTTA-1184
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR / EDR / LE FM Receiver/GNSS
IMEI Code	Conduction: 352916100002667/352916100002675 for Sample 1 352916100004168/352916100004176 for Sample 2 Radiation: 352916100002840/352916100002857 for Sample 1 352916100002386/352916100002394 for Sample 1 352916100004168/352916100004101 for Sample 2
HW Version	DVT_0.2
SW Version	00WW_0_095
EUT Stage	Identical Prototype

Remark:

- **1.** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT. According to the difference, choose sample 1 to perform full test, sample 2 to verify worst cases.

Object	Sample 1 with Du	ıal SIMs(TA-1184)	Sample 2 with Dual SIMs(TA-1184)	
Object	Specifications	Supplier	Specifications	Supplier
Memory	3+32G	Kingston	3+32G	Foresee
TP+LCD	HQ23201454000	K&D	HQ23201454000	Holitech
Battery Cover	HQ20704757000	Goodmark-new	HQ20746201000	Zhiyin

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 5 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report No.: FC930509-01

Front Camera	HQ20207233000	Jinkang	HQ20207233000	Tianshi
Rear Camera HQ20207234000 Tianshi		HQ20207234000	Guangzhen	
Speaker	HQ20312058000	Xichun	HQ20312058000	Xinrongda
Receiver	HQ20321087000	Dongsheng	HQ20321087000	Xinrongda
MIC	HQ12030105000	Knowles	HQ12030105000	Minxinwei
Motor	HQ20400123000	Kunwang	HQ20400123000	Jinlangda

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 6 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification			
	GSM850: 824.2 MHz ~ 848.8 MHz		
	GSM1900: 1850.2 MHz ~ 1909.8MHz		
	WCDMA Band V: 826.4 MHz ~ 846.6 MHz		
	WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz		
	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz		
	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz		
Tx Frequency	LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz		
TX Frequency	LTE Band 5 : 824.7 MHz ~ 848.3 MHz		
	LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz		
	LTE Band 12 : 699.7 MHz ~ 715.3 MHz		
	LTE Band 17: 706.5 MHz ~ 713.5 MHz		
	802.11b/g/n: 2412 MHz ~ 2462 MHz		
	Bluetooth: 2402 MHz ~ 2480 MHz		
	GSM850: 869.2 MHz ~ 893.8 MHz		
	GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz		
	WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz		
	WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz		
	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz		
B. F.,	LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz		
Rx Frequency	LTE Band 5 : 869.7 MHz ~ 893.3 MHz		
	LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz		
	LTE Band 12 : 729.7 MHz ~ 745.3 MHz		
	LTE Band 17 : 736.5 MHz ~ 743.5 MHz		
	802.11b/g/n: 2412 MHz ~ 2462 MHz		
	Bluetooth: 2402 MHz ~ 2480 MHz		
	GNSS: 1559 MHz ~ 1610 MHz		
	FM: 88 MHz - 108 MHz		
	WWAN : Loop Antenna		
	WLAN : IFA Antenna		
Antenna Type	Bluetooth : IFA Antenna		
	GNSS: IFA Antenna		
	FM : External Handset Antenna		
	GSM: GMSK		
	GPRS: GMSK		
	EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK		
	WCDMA: BPSK (Uplink)		
	HSDPA/DC-HSDPA: QPSK (Uplink)		
	HSUPA: QPSK (Uplink)		
	HSPA+: 16QAM		
	DC-HSDPA: 64QAM		
Type of Modulation	LTE: QPSK / 16QAM / 64QAM		
	802.11b: DSSS (DBPSK / DQPSK / CCK)		
	802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)		
	Bluetooth LE: GFSK		
	Bluetooth (1Mbps) : GFSK		
	Bluetooth (2Mbps) : 3/4-DQPSK		
	Bluetooth (3Mbps) : 8-DPSK		
	GNSS: BPSK		
	0.100 . Di Oit		

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 7 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International (Kunshan) Inc is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.				
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone,				
Test Site Location	Jiangsu Province 215335, China				
rest Site Location	TEL: 86-512-57900158				
	FAX: 86-512-5790095	8			
	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.		
Test Site No.	CO01-KS	CN5013	630927		
	03CH02-KS	C143013	030927		

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 8 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
	Mode 1: GSM850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Rear) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 2: PCS1900 Rx + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Front) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 3: LTE Band 12 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
AC Conducted Emission	Mode 4: LTE Band 17 Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(98MHz) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 5: WCDMA Band V Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Battery 1 for Sample 1
	Mode 6: GSM850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Rear) + USB Cable (Charging from Adapter) + Battery 2 for Sample 2
	Mode 7: WCDMA Band V Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Battery 2 for Sample 2

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 9 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

	Mode 1: GSM850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Rear) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 2: PCS1900 Rx + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Front) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 3: LTE Band 12 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
Radiated Emissions	Mode 4: LTE Band 17 Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx(88MHz) + USB Cable (Charging from Adapter) + Battery 1 for Sample 1
	Mode 5: WCDMA Band V Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Battery 1 for Sample 1
	Mode 6: WCDMA Band V Rx(High) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable (Data Link with Notebook) + Battery 2 for Sample 2
	Mode 7: GSM850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera (Rear) + USB Cable (Charging from Adapter) + Battery 2 for Sample 2
_	


Remark:

- 1. The worst case of AC is mode 1; only the test data of this mode is reported.
- 2. The worst case of RE is mode 5; only the test data of this mode is reported.
- **3.** Data Link with Notebook means data application transferred mode between EUT and Notebook.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 10 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
3.	Signal Generator	R&S	GSS7000	NA	NA	Unshielded,1.8m
4.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded,1.8m
5.	WLAN AP	TP-LINK	TL-WDR5600	N/A	N/A	Unshielded,1.8m
6.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
7.	Bluetooth Earphone	Lenevo	LYEJ02LM	N/A	N/A	N/A
8.	Notebook	Lenovo	G480	PRC4	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
9.	Notebook	DELL	MT320	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
10.	iPod	Apple	A1199	N/A	N/A	N/A
11.	SD Card	Kingston	8GB	N/A	N/A	N/A
12.	SD Card	SanDisk	Uitra	N/A	N/A	N/A

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 11 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

- 1. Data application is transferred between Notebook and EUT via USB cable.
- 2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
- 3. Turn on camera to capture images.
- 4. Turn on MPEG4 function.
- 5. Turn on FM receiver function to make the EUT receive continuous signals from FM station

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 12 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission	Conducted	limit (dBuV)
(MHz)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 14 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

3.1.5 Test Result of AC Conducted Emission




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 15 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

FCC Test Report No.: FC930509-01

Test Engineer :	Amos Zhana	Temperature: 25.3	
rest Engineer.	Amos Zhang	Relative Humidity :	28~30%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
_			

Remark: All emissions not reported here are more than 10 dB below the prescribed limit.



Condition : FCC CLASS-B LISN-N-181119-060105 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read	LISN Factor	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.153	59.55	-6.27	65.82	48.90	0.18	10.47	OP
2	0.153		-10.97	55.82	34.20	0.18		Average
3	0.171		-22.70	64.90	31.59	0.18	10.43	
4	0.171	25.10	-29.80	54.90	14.49	0.18		Äverage
5	0.186	46.07	-18.13	64.20	35.51	0.17	10.39	_
6	0.186	25.77	-28.43	54.20	15.21	0.17	10.39	Average
7	0.215	54.13	-8.88	63.01	43.61	0.17	10.35	QP
8	0.215	40.83	-12.18	53.01	30.31	0.17	10.35	Average
9	0.249	47.10	-14.68	61.78	36.60	0.17	10.33	QP
10	0.249	23.80	-27.98	51.78	13.30	0.17	10.33	Average
11	0.291	49.07	-11.43	60.50	38.60	0.16	10.31	QP
12	0.291	36.67	-13.83	50.50	26.20	0.16	10.31	Average
13	0.363	48.64	-10.01	58.65	38.20	0.16	10.28	QP
14	0.363	41.74	-6.91	48.65	31.30	0.16	10.28	Average
15	0.437	47.01	-10.10	57.11	36.61	0.15	10.25	QP
16	0.437	37.61	-9.50	47.11	27.21	0.15	10.25	Average
17	0.507	45.58	-10.42	56.00	35.19	0.15	10.24	QP

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 16 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 17 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0

3.2.3. Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest radiation.
- 4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- 5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
- 6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
- 7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
- 8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
- 9. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 18 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01


Report Template No.: BU5-FD15B Version 2.0

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 19 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report No.: FC930509-01

3.2.5. Test Result of Radiated Emission




TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 20 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report No.: FC930509-01

Report No.: FC930509-01

Test Engineer : Jack Guo	22°C
Relative Humidity: 41~4	2%
Test Distance : 3m Polarization : Verti	cal

Remark: #7 is system simulator signal which can be ignored.



: 03CH02-KS Site

: FCC CLASS-B 3m LF 23182-3M VERTICAL : (FC)930509-01 : 5 Condition

Project

Mode

	Free	Level	Over Limit					Preamp Factor		T/Pos	Remark
	MH	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	38.7	33.90	-6.10	40.00	46.49	18.66	0.71	31.96			Peak
2	152.2	36.10	-7.40	43.50	50.26	16.36	1.42	31.94			Peak
3	! 193.9	39.17	-4.33	43.50	54.03	15.43	1.61	31.90	100	0	Peak
4	314.2	36.15	-9.85	46.00	46.64	19.52	2.01	32.02			Peak
5	! 480.08	42.22	-3.78	46.00	48.95	23.02	2.49	32.24			Peak
6	576.13	36.77	-9.23	46.00	41.68	24.79	2.68	32.38			Peak
7	* 892.3	53.03			54.36	26.75	3.43	31.51			Peak
8	1592.00	41.20	-32.80	74.00	45.04	29.02	4.52	37.38			Peak
9	4056.00	44.75	-29.25	74.00	39.44	34.23	7.53	36.45			Peak
10	6640.00	46.08	-27.92	74.00	38.07	35.01	9.73	36.73			Peak
11	8400.00	47.31	-26.69	74.00	37.36	35.88	11.04	36.97			Peak
12	11241.00	42.68	-31.32	74.00	28.29	37.82	13.48	36.91			Peak
13	14868.00	43.97	-30.03	74.00	23.88	40.34	15.61	35.86			Peak

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184

Page Number : 21 of 23 Report Issued Date: Apr. 16, 2019 Report Version : Rev. 01

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Mar. 30, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Mar. 30, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Mar. 30, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Mar. 30, 2019	Oct. 11, 2019	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 06, 2018	Apr. 03, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150204	10Hz-44G,MAX 30dB	Apr. 17, 2018	Apr. 03, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Dec. 29, 2018	Apr. 03, 2019	Dec. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Apr. 03, 2019	Jan. 26, 2020	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Apr. 03, 2019	Jan.04, 2020	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2018	Apr. 03, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5G Hz	Apr. 18, 2018	Apr. 03, 2019	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18~40GHz	Jan. 14, 2019	Apr. 03, 2019	Jan. 13, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Apr. 03, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Apr. 03, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Apr. 03, 2019	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 22 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report No.: FC930509-01

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.9 dB
of 95% (U = 2Uc(y))	2.9 UD

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	4.8 dB
of 95% (U = 2Uc(y))	4.0 UB

<u>Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.2 dB
of 95% (U = 2Uc(y))	3.2 UB

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1184 Page Number : 23 of 23
Report Issued Date : Apr. 16, 2019
Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 2.0