



**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 26.OCT.2018 00:17:57

**CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 26.OCT.2018 00:18:24




&lt;2Mbps&gt;

**CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 25.OCT.2018 23:31:23

**CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 25.OCT.2018 23:31:50

**CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 25.OCT.2018 23:37:56

**CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 25.OCT.2018 23:38:35

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 25.OCT.2018 23:52:02

**CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 25.OCT.2018 23:52:37

**<3Mbps>****CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 25.OCT.2018 23:14:09

**CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**



Date: 25.OCT.2018 23:14:38

**CSE Plot on Ch 39 between 30MHz ~ 3 GHz**

Date: 25.OCT.2018 23:20:25

**CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**

Date: 25.OCT.2018 23:20:52

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

**CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
$$\text{On time} = N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$$
  
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.8.7 Duty Cycle

Please refer to Appendix E.

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix C and D.

### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	N/A	Dec. 20, 2017	Oct. 16, 2018~ Oct. 26, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	50MHz~18GHz	Dec. 20, 2017	Oct. 16, 2018~ Oct. 26, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Oct. 16, 2018~ Oct. 26, 2018	Nov. 20, 2018	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 09, 2017	Oct. 16, 2018~ Oct. 26, 2018	Nov. 08, 2018	Conducted (TH05-HY)
BT Base Station (Measure)	Rohde & Schwarz	CBT	101136	BT 3.0	Sep. 27, 2018	Oct. 16, 2018~ Oct. 26, 2018	Sep. 26, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Oct. 16, 2018~ Oct. 26, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 16, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Oct. 16, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Oct. 16, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 16, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Oct. 16, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Oct. 16, 2018	Jan. 02, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Filter	Microwave	H3G018G1	SN477219	3.0G High Pass	Nov. 21, 2017	Oct. 19, 2018~ Oct. 20, 2018	Nov. 20, 2018	Radiation (03CH13-HY)
Filter	Microwave	H3G018G1	SN477219	3.0G High Pass	Nov. 02, 2018	Jan. 08, 2019~ Jan. 09, 2019	Nov. 01, 2019	Radiation (03CH13-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	Oct. 19, 2018~ Oct. 20, 2018	Nov. 09, 2018	Radiation (03CH13-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2018	Jan. 08, 2019~ Jan. 09, 2019	Nov. 22, 2019	Radiation (03CH13-HY)
Filter	Wainwright	WLKS1200-8 SS	SN3	1.2G Low Pass	Nov. 21, 2017	Oct. 19, 2018~ Oct. 20, 2018	Nov. 20, 2018	Radiation (03CH13-HY)
Filter	Wainwright	WLKS1200-8 SS	SN3	1.2G Low Pass	Nov. 02, 2018	Jan. 08, 2019~ Jan. 09, 2019	Nov. 01, 2019	Radiation (03CH13-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Oct. 19, 2018~ Jan. 09, 2019	Jul. 15, 2019	Radiation (03CH13-HY)
Amplifier	Sonoma-Instru ment	310 N	187282	9KHz~1GHz	Dec. 21, 2016	Oct. 19, 2018~ Oct. 20, 2018	Dec. 20, 2018	Radiation (03CH13-HY)
Amplifier	Sonoma-Instru ment	310 N	187282	9KHz~1GHz	Dec. 18, 2018	Jan. 08, 2019~ Jan. 09, 2019	Dec. 17, 2019	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	40103&07	30MHz to 1GHz	Jan. 10, 2018	Oct. 19, 2018~ Oct. 20, 2018	Jan. 09, 2019	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-0 6	35414&AT-N06 02	30MHz to 1GHz	Oct. 13, 2018	Jan. 08, 2019~ Jan. 09, 2019	Oct. 12, 2019	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jun. 29, 2018	Oct. 19, 2018~ Jan. 09, 2019	Jun. 28, 2019	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 21, 2018	Oct. 19, 2018~ Jan. 09, 2019	May 20, 2019	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Feb. 02, 2018	Oct. 19, 2018~ Jan. 09, 2019	Feb. 01, 2019	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 15, 2018	Oct. 19, 2018~ Jan. 09, 2019	Mar. 14, 2019	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Oct. 19, 2018~ Jan. 09, 2019	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Oct. 19, 2018~ Jan. 09, 2019	N/A	Radiation (03CH13-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	Oct. 19, 2018~ Oct. 20, 2018	Jan. 15, 2019	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Oct. 19, 2018~ Oct. 20, 2018	Nov. 26, 2018	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 20, 2018	Jan. 08, 2019~ Jan. 09, 2019	Nov. 19, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Jan. 22, 2018	Oct. 19, 2018~ Jan. 09, 2019	Jan. 21, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	335041/4	30M-18G	Jan. 22, 2018	Oct. 19, 2018~ Jan. 09, 2019	Jan. 21, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M~18GHz	Jan. 22, 2018	Oct. 19, 2018~ Jan. 09, 2019	Jan. 21, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Mar. 14, 2018	Oct. 19, 2018~ Jan. 09, 2019	Mar. 13, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30M~40GHz	Mar. 14, 2018	Oct. 19, 2018~ Jan. 09, 2019	Mar. 13, 2019	Radiation (03CH13-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	Oct. 19, 2018~ Jan. 09, 2019	N/A	Radiation (03CH13-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.2
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.9
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.4
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.3
---	-----

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Allen Lin/Derek Hsu	Temperature:	21~25	°C
Test Date:	2018/10/16~2018/10/26	Relative Humidity:	51~54	%

**TEST RESULTS DATA****20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.883	0.886	0.999	0.5885	Pass
DH	1Mbps	1	39	2441	0.935	0.883	1.003	0.6233	Pass
DH	1Mbps	1	78	2480	0.932	0.883	0.999	0.6213	Pass
2DH	2Mbps	1	0	2402	1.259	1.166	1.007	0.8393	Pass
2DH	2Mbps	1	39	2441	1.259	1.161	1.007	0.8393	Pass
2DH	2Mbps	1	78	2480	1.259	1.164	1.146	0.8393	Pass
3DH	3Mbps	1	0	2402	1.233	1.146	1.003	0.8220	Pass
3DH	3Mbps	1	39	2441	1.233	1.146	1.025	0.8220	Pass
3DH	3Mbps	1	78	2480	1.233	1.149	0.990	0.8220	Pass

**TEST RESULTS DATA****Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

**TEST RESULTS DATA****Peak Power Table**

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	8.70	20.97	Pass
	39	1	<b>9.66</b>	20.97	Pass
	78	1	8.18	20.97	Pass
2DH1	0	1	9.60	20.97	Pass
	39	1	<b>10.57</b>	20.97	Pass
	78	1	9.05	20.97	Pass
3DH1	0	1	10.00	20.97	Pass
	39	1	<b>10.91</b>	20.97	Pass
	78	1	9.45	20.97	Pass

**TEST RESULTS DATA****Average Power Table****(Reporting Only)**

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	8.50	5.21
	39	1	<b>9.42</b>	5.21
	78	1	7.94	5.21
2DH1	0	1	7.14	5.12
	39	1	<b>8.05</b>	5.12
	78	1	6.58	5.12
3DH1	0	1	7.16	5.12
	39	1	<b>8.05</b>	5.12
	78	1	6.58	5.12

**TEST RESULTS DATA****Number of Hopping Frequency**

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Rick Lin	Temperature :	22~24°C
		Relative Humidity :	61~63%

## EUT Information

Report NO : 8O1133  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.61	55.88	27.27	L1	OFF	19.5
0.152250	43.44	---	65.88	22.44	L1	OFF	19.5
0.386250	---	24.84	48.14	23.30	L1	OFF	19.5
0.386250	32.52	---	58.14	25.62	L1	OFF	19.5
0.773250	---	34.58	46.00	11.42	L1	OFF	19.6
0.773250	38.03	---	56.00	17.97	L1	OFF	19.6
1.468500	---	27.08	46.00	18.92	L1	OFF	19.6
1.468500	36.90	---	56.00	19.10	L1	OFF	19.6
1.898250	---	26.22	46.00	19.78	L1	OFF	19.6
1.898250	33.92	---	56.00	22.08	L1	OFF	19.6
3.255000	---	24.84	46.00	21.16	L1	OFF	19.7
3.255000	30.09	---	56.00	25.91	L1	OFF	19.7

# EUT Information

Report NO : 8O1133  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	30.39	55.88	25.49	N	OFF	19.5
0.152250	48.12	---	65.88	17.76	N	OFF	19.5
0.642750	---	25.59	46.00	20.41	N	OFF	19.6
0.642750	35.25	---	56.00	20.75	N	OFF	19.6
0.777750	---	33.09	46.00	12.91	N	OFF	19.6
0.777750	37.82	---	56.00	18.18	N	OFF	19.6
0.840750	---	27.09	46.00	18.91	N	OFF	19.6
0.840750	36.61	---	56.00	19.39	N	OFF	19.6
2.004000	---	26.03	46.00	19.97	N	OFF	19.6
2.004000	34.88	---	56.00	21.12	N	OFF	19.6
3.237000	---	25.62	46.00	20.38	N	OFF	19.6
3.237000	31.31	---	56.00	24.69	N	OFF	19.6



## Appendix C. Radiated Spurious Emission

Test Engineer :	Alex Jheng, Fu Chen, and Wilson Wu	Temperature :	24.5~24.8°C
		Relative Humidity :	50~51%

&lt;Sample 1&gt;

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preampl Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2372.16	42.83	-31.17	74	40	27.19	5.54	29.9	335	186	P	H
		2372.16	18.07	-35.93	54	-	-	-	-	-	-	A	H
	*	2402	101.01	-	-	98.09	27.23	5.58	29.89	335	186	P	H
	*	2402	76.25	-	-	-	-	-	-	-	-	A	H
													H
		2362.29	44.59	-29.41	74	41.82	27.14	5.54	29.91	254	309	P	V
		2362.29	19.83	-34.17	54	-	-	-	-	-	-	A	V
	*	2402	103.77	-	-	100.85	27.23	5.58	29.89	254	309	P	V
	*	2402	79.01	-	-	-	-	-	-	-	-	A	V
													V
BT CH 39 2441MHz		2379.3	43.85	-30.15	74	41	27.19	5.56	29.9	369	160	P	H
		2379.3	19.09	-34.91	54	-	-	-	-	-	-	A	H
	*	2441	103.81	-	-	100.7	27.37	5.62	29.88	369	160	P	H
	*	2441	79.05	-	-	-	-	-	-	-	-	A	H
		2496.15	44.08	-29.92	74	40.77	27.5	5.68	29.87	369	160	P	H
		2496.15	19.32	-34.68	54	-	-	-	-	-	-	A	H
		2376.92	43.67	-30.33	74	40.82	27.19	5.56	29.9	246	302	P	V
		2376.92	18.91	-35.09	54	-	-	-	-	-	-	A	V
	*	2441	105.59	-	-	102.48	27.37	5.62	29.88	246	302	P	V
	*	2441	80.83	-	-	-	-	-	-	-	-	A	V
		2489.08	43.86	-30.14	74	40.56	27.5	5.68	29.88	246	302	P	V
		2489.08	19.1	-34.9	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	103.17	-	-	99.93	27.46	5.66	29.88	398	163	P	H
	*	2480	78.41	-	-	-	-	-	-	-	-	A	H
		2483.52	50.05	-23.95	74	46.79	27.46	5.68	29.88	398	163	P	H
		2483.52	25.29	-28.71	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	103.7	-	-	100.46	27.46	5.66	29.88	269	296	P	V
	*	2480	78.94	-	-	-	-	-	-	-	-	A	V
		2483.52	50.51	-23.49	74	47.25	27.46	5.68	29.88	269	296	P	V
		2483.52	25.75	-28.25	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	35.98	-38.02	74	53.14	31.22	8.2	56.58	100	0	P	H
		4804	11.22	-42.78	54	-	-	-	-	-	-	A	H
													H
													H
		4804	35.1	-38.9	74	52.26	31.22	8.2	56.58	100	0	P	V
		4804	10.34	-43.66	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	36.77	-37.23	74	53.47	31.36	8.49	56.55	100	0	P	H
		4882	12.01	-41.99	54	-	-	-	-	-	-	A	H
		7323	42.58	-31.42	74	51.89	36.22	10.68	56.21	100	0	P	H
		7323	17.82	-36.18	54	-	-	-	-	-	-	A	H
		4882	36.18	-37.82	74	52.88	31.36	8.49	56.55	100	0	P	V
		4882	11.42	-42.58	54	-	-	-	-	-	-	A	V
		7323	41.55	-32.45	74	50.86	36.22	10.68	56.21	100	0	P	V
		7323	16.79	-37.21	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	37.15	-36.85	74	53.34	31.53	8.79	56.51	100	0	P	H
		4960	12.39	-41.61	54	-	-	-	-	-	-	A	H
		7440	43.04	-30.96	74	51.87	36.49	10.74	56.06	100	0	P	H
		7440	18.28	-35.72	54	-	-	-	-	-	-	A	H
		4960	37.03	-36.97	74	53.22	31.53	8.79	56.51	100	0	P	V
		4960	12.27	-41.73	54	-	-	-	-	-	-	A	V
		7440	41.91	-32.09	74	50.74	36.49	10.74	56.06	100	0	P	V
		7440	17.15	-36.85	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BT LF		48.36	30.55	-9.45	40	46.58	15.3	0.99	32.32	100	0	P	H
		102.09	28.66	-14.84	43.5	43.29	16.3	1.36	32.29	-	-	P	H
		161.22	32.2	-11.3	43.5	46.35	16.57	1.56	32.28	-	-	P	H
		746.6	29.84	-16.16	46	30.75	27.95	3.23	32.09	-	-	P	H
		896.4	36.3	-9.7	46	35.26	29.02	3.55	31.53	-	-	P	H
		956.6	33.39	-12.61	46	29.71	30.96	3.71	30.99	-	-	P	H
													H
													H
													H
													H
													H
													H
		31.35	33.6	-6.4	40	41.19	23.96	0.79	32.34	-	-	P	V
		44.04	35.86	-4.14	40	49.78	17.41	1	32.33	100	0	P	V
		103.98	29.68	-13.82	43.5	44.18	16.45	1.34	32.29	-	-	P	V
		756.4	30.95	-15.05	46	31.72	28.07	3.23	32.07	-	-	P	V
		896.4	38.23	-7.77	46	37.19	29.02	3.55	31.53	-	-	P	V
		958	33.47	-12.53	46	29.67	31.07	3.71	30.98	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



&lt;Sample 2&gt;

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamplifier Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH 78 2480MHz	*	2480	101.59	-	-	98.34	27.46	5.67	29.88	103	74	P	H
	*	2480	76.83	-	-	-	-	-	-	-	-	A	H
		2483.56	49.61	-24.39	74	46.36	27.46	5.67	29.88	103	74	P	H
		2483.56	24.85	-29.15	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	98.03	-	-	94.78	27.46	5.67	29.88	400	239	P	V
	*	2480	73.27	-	-	-	-	-	-	-	-	A	V
		2483.76	45.65	-28.35	74	42.4	27.46	5.67	29.88	400	239	P	V
		2483.76	20.89	-33.11	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**2.4GHz 2400~2483.5MHz****BT (Harmonic @ 3m)**

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
<b>BT CH 78 2480MHz</b>		4960	38.19	-35.81	74	55.11	31.53	8.83	57.28	100	0	P	H
		4960	13.43	-40.57	54	-	-	-	-	-	-	A	H
		7440	42.52	-31.48	74	52.72	36.49	10.74	57.43	100	0	P	H
		7440	17.76	-36.24	54	-	-	-	-	-	-	A	H
		4960	37.13	-36.87	74	54.05	31.53	8.83	57.28	100	0	P	V
		4960	12.37	-41.63	54	-	-	-	-	-	-	A	V
		7440	42.53	-31.47	74	52.73	36.49	10.74	57.43	100	0	P	V
		7440	17.77	-36.23	54	-	-	-	-	-	-	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BT LF		31.62	22.56	-17.44	40	30.41	23.7	0.74	32.29	-	-	P	H
		64.56	22.54	-17.46	40	41.68	12.03	1.1	32.27	-	-	P	H
		101.82	23.67	-19.83	43.5	38.2	16.31	1.37	32.21	-	-	P	H
		344.1	28.39	-17.61	46	37.98	20.3	2.26	32.15	-	-	P	H
		717.2	31.01	-14.99	46	32.92	26.98	3.17	32.06	-	-	P	H
		841.1	31.98	-14.02	46	31.21	28.96	3.5	31.69	100	0	P	H
													H
													H
													H
													H
													H
													H
		52.41	27.52	-12.48	40	45.29	13.56	0.96	32.29	-	-	P	V
		56.73	33.71	-6.29	40	52.67	12.35	0.97	32.28	100	0	P	V
		64.02	26.55	-13.45	40	45.69	12.04	1.09	32.27	-	-	P	V
		628.3	28.36	-17.64	46	31.43	26.1	3.03	32.2	-	-	P	V
		744.5	30.57	-15.43	46	31.42	27.93	3.22	32	-	-	P	V
		858.6	32.87	-13.13	46	31.84	29.11	3.53	31.61	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical

**A calculation example for radiated spurious emission is shown as below:**

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Alex Jheng, Fu Chen, and Wilson Wu	Temperature :	24.5~24.8°C
		Relative Humidity :	50~51%



Note symbol

-L	Low channel location
-R	High channel location



&lt;Sample 1&gt;

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)




BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : B01133 Mode : 1</p>	 <p>Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : B01133 Mode : 1</p>






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	<div><p>Site : 03CH13-4V Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : RO1133 Mode : 1</p></div>	<div><p>Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : RO1133 Mode : 1</p></div>







BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
Peak	<div><p>Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>	<div><p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>
	<div><p>Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	<div><p>Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>	<div><p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>
	<div><p>Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : 2</p></div>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	<div><p>Site : 03CH13-1V Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZ.ONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O1133 Mode : 3</p></div>	<div><p>Site : 03CH13-1V Condition : PEAK_74 3m HORN_91200_1241 HORIZ.ONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O1133 Mode : 3</p></div>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	<div><p>Site : 03CH13-1V Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O1133 Mode : 3</p></div>	<div><p>Site : 03CH13-1V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8O1133 Mode : 3</p></div>



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 8O1133 Mode : 1</p>	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 8O1133 Mode : 1</p>

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
<b>Peak Avg.</b>	<p>           Site : 03CH13-4V            Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL            Detector : Peak            Project : 8O1133            Mode : 2         </p>	<p>           Site : 03CH13-4V            Condition : PEAK_74 3m HORN_91200_1241 VERTICAL            Detector : Peak            Project : 8O1133            Mode : 2         </p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : BO1133 Mode : 3</p>	<p>Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : BO1133 Mode : 3</p>

**Emission below 1GHz**
**2.4GHz BT (LF)**

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
<b>QP / Peak</b>	 <p>           Site : 03CH13-HY            Condition : QP 3m BTLOG_40103 HORIZONTAL            Detector : Peak            Project : 801133            Mode : 4         </p>	 <p>           Site : 03CH13-HY            Condition : QP 3m BTLOG_40103 VERTICAL            Detector : Peak            Project : 801133            Mode : 4         </p>





&lt;Sample 2&gt;

2.4GHz 2400~2483.5MHz



BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8C1133 Mode : Z2</p>	<p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 8C1133 Mode : Z2</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	<div><p>Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : Z2</p></div>	<div><p>Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 801133 Mode : Z2</p></div>

**2.4GHz 2400~2483.5MHz**
**BT (Harmonic @ 3m)**

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
<b>Peak</b>  <b>Avg.</b>	 <p>           Site : 03CH13-HY            Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL            Detector : Peak            Project : 801133            Mode : 22         </p>	 <p>           Site : 03CH13-HY            Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL            Detector : Peak            Project : 801133            Mode : 22         </p>


**Emission below 1GHz**
**2.4GHz BT (LF)**

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
<b>QP / Peak</b>	 <p>Site : 03CH13-HY Condition : QP 3m B1LOG_40103 HORIZONTAL Detector : Peak Project : 801133 Mode : Z3</p>	 <p>Site : 03CH13-HY Condition : QP 3m B1LOG_40103 VERTICAL Detector : Peak Project : 801133 Mode : Z3</p>


## Appendix E. Duty Cycle Plots

<Sample 1>

**3DH5 on time (One Pulse) Plot on Channel 39**





**on time (Count Pulses) Plot on Channel 39**



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. **3DH5** has the highest duty cycle worst case and is reported.

**<Sample 2>**
**3DH5 on time (One Pulse) Plot on Channel 39**

**on time (Count Pulses) Plot on Channel 39**

**Note:**

4. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.89 / 100 = 5.78 \%$
5. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
6. **3DH5** has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.89 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100\text{ms}) = -24.76 \text{ dB}$$