

Report No.: FG852420-01A



FCC RADIO TEST REPORT

FCC ID : 2AJOTTA-1112 Equipment : Smart Phone

Brand Name : NOKIA **Model Name** : TA-1112

: HMD Global Oy **Applicant**

Karaportti 2, 02610 Espoo, Finland

Manufacturer: HMD Global Oy

Karaportti 2, 02610 Espoo, Finland

Standard : 47 CFR Part 2, 22(H), 24(E), 27(L)

The product was received on May 24, 2018 and testing was started from Jun. 16, 2018 and completed on Jul. 03, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERTIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

TEL: 886-3-327-3456

(Jones Tsai)

SPORTON INTERTIONAL INC. EMC & Wireless Communications Laboratory

Page Number

: 1 of 20

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018 : 01

Table of Contents

Report No. : FG852420-01A

His	tory o	of this test report	3
Su	mmar	y of Test Result	4
1	Gene	eral Description	5
	1.1	Product Feature of Equipment Under Test	5
	1.2	Modification of EUT	5
	1.3	Testing Location	5
	1.4	Applicable Standards	6
2	Test	Configuration of Equipment Under Test	7
	2.1	Test Mode	7
	2.2	Connection Diagram of Test System	8
	2.3	Support Unit used in test configuration	8
	2.4	Measurement Results Explanation Example	8
	2.5	Frequency List of Low/Middle/High Channels	9
3	Cond	ducted Test Result	10
	3.1	Measuring Instruments	10
	3.2	Conducted Output Power and ERP/EIRP	11
	3.3	Peak-to-Average Ratio	12
	3.4	99% Occupied Bandwidth and 26dB Bandwidth Measurement	13
	3.5	Conducted Band Edge	14
	3.6	Conducted Spurious Emission	15
	3.7	Frequency Stability	16
4	Radia	ated Test Items	17
	4.1	Measuring Instruments	17
	4.2	Test Setup	17
	4.3	Test Result of Radiated Test	17
	4.4	Field Strength of Spurious Radiation Measurement	18
5	List o	of Measuring Equipment	19
6	Unce	ertainty of Evaluation	20
Аp	pendi	x A. Test Results of Conducted Test	
Аp	pendi	x B. Test Results of ERP/EIRP and Radiated Test	
Аp	pendi	x C. Test Setup Photographs	

TEL: 886-3-327-3456 Page Number : 2 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018 : 01

History of this test report

Report No. : FG852420-01A

Report No.	Version	Description	Issued Date
FG852420-01A	01	Initial issue of report	Jul. 05, 2018

TEL: 886-3-327-3456 Page Number : 3 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

Summary of Test Result

Report No.: FG852420-01A

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark	
	§2.1046	Conducted Output Power			
	§22.913 (a)(2)	Effective Radiated Power			
3.2	§24.232 (c)	Equivalent Isotropic Radiated Power	Pass	-	
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power			
3.3	§24.232 (d)	Peak-to-Average Ratio	Pass	-	
3.4	§2.1049 §22.917 (b) §24.238 (b) §27.53 (g)	Occupied Bandwidth	Pass	-	
3.5	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Band Edge Measurement	Pass	-	
3.6	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Conducted Emission	Pass	-	
	§2.1055 §22.355			-	
3.7	§2.1055 §24.235 §27.54	Frequency Stability Temperature & Voltage	Pass	-	
4.4	§2.1053 §22.917 (a) §24.238 (a) §27.53 (h)	Field Strength of Spurious Radiation	Pass	Under limit 21.12 dB at 2472.000 MHz	

Remark: This is a variant report which can be referred Product Equality Declaration. Since the test result is not affected by the changes, the FG852420-01A test report reuses test data from the FG852420A test report.

Reviewed by: Joseph Lin

Report Producer: Maggie Chiang

TEL: 886-3-327-3456 Page Number : 4 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, FM Receiver, and GNSS

Report No.: FG852420-01A

Product Specification subjective to this standard				
	WWAN: Monopole Antenna			
	WLAN: Monopole Antenna			
Antenna Type	Bluetooth: Monopole Antenna			
	GPS/Glonass/BDS/Galileo: PIFA Antenna			
	FM: using earphone as antenna			

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

TEL: 886-3-327-3456 Page Number : 5 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Report No.: FG852420-01A

- + ANSI C63.26-2015
- ANSI / TIA-603-E
- 47 CFR Part 2, 22(H), 24(E), 27(L)
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

- **1.** All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 886-3-327-3456 Page Number : 6 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Report No.: FG852420-01A

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

Radiated emissions were investigated as following frequency range:

- 1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
- 30 MHz to 18000 MHz for WCDMA Band IV.
- 3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.


Test modes are chosen to be reported as the worst case configuration below:

Test Modes								
Band	Radiated TCs	Conducted TCs						
GSM 850	■ GPRS Class 8 Link	■ GPRS Class 8 Link						
GSIVI 650	■ EDGE Class 8 Link	■ EDGE Class 8 Link						
CCM 4000	■ GPRS Class 8 Link	■ GPRS Class 8 Link						
GSM 1900	■ EDGE Class 8 Link	■ EDGE Class 8 Link						
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link						
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link						
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link						

Remark: All the radiated emission test cases were performed with Adapter 1.

TEL: 886-3-327-3456 Page Number : 7 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

2.2 Connection Diagram of Test System



Report No.: FG852420-01A

2.3 Support Unit used in test configuration

ltem	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example:

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

TEL: 886-3-327-3456 Page Number : 8 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

2.5 Frequency List of Low/Middle/High Channels

	Frequency List						
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest			
CCMOEO	Channel	128	189	251			
GSM850	Frequency	824.2	836.4	848.8			
WCDMA	Channel	4132	4182	4233			
Band V	Frequency	826.4	836.4	846.6			
GSM1900	Channel	512	661	810			
GSW1900	Frequency	1850.2	1880.0	1909.8			
WCDMA	Channel	9262	9400	9538			
Band II	Frequency	1852.4	1880.0	1907.6			
WCDMA	Channel	1312	1413	1513			
Band IV	Frequency	1712.4	1732.6	1752.6			

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : 9 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.


3.1.1 Test Setup

3.1.2 Conducted Output Power




Report No.: FG852420-01A

3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 10 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

Report No.: FG852420-01A

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

 $EIRP = P_T + G_T - L_C$, ERP = EIRP - 2.15, where

 P_T = transmitter output power in dBm

 G_T = gain of the transmitting antenna in dBi

 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

 TEL: 886-3-327-3456
 Page Number
 : 11 of 20

 FAX: 886-3-328-4978
 Issued Date
 : Jul. 05, 2018

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 5.7.1

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. Set EUT to transmit at maximum output power.
- 3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.

Report No.: FG852420-01A

- 4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
- 5. Record the maximum PAPR level associated with a probability of 0.1%.

TEL: 886-3-327-3456 Page Number : 12 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

Report No.: FG852420-01A

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 4.2

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
 The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- 3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- 4. Set the detection mode to peak, and the trace mode to max hold.
- Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
- 6. Determine the "-26 dB down amplitude" as equal to (Reference Value X).
- 7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- 8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

TEL: 886-3-327-3456 Page Number : 13 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

Report No.: FG852420-01A

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

- 1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. The band edges of low and high channels for the highest RF powers were measured.
- 4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 5. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

TEL: 886-3-327-3456 Page Number : 14 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

Report No.: FG852420-01A

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

- 1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

TEL: 886-3-327-3456 Page Number : 15 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

Report No.: FG852420-01A

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

- 1. The EUT was set up in the thermal chamber and connected with the system simulator.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 3. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

- 1. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
- 2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 3. The variation in frequency was measured for the worst case.

TEL: 886-3-327-3456 Page Number : 16 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018


4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.


4.2 Test Setup

For radiated test from 30MHz to 1GHz



Report No.: FG852420-01A

For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 17 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

Report No.: FG852420-01A

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI / TIA-603-E Section 2.2.12.

- 1. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

TEL: 886-3-327-3456 Page Number : 18 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	Jun. 16, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Dec. 06, 2017	Jun. 16, 2018	Dec. 05, 2019	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL883644	Voltage:0~20V; Current:0~5A	Dec. 06, 2017	Jun. 16, 2018	Dec. 05, 2019	Conducted (TH03-HY)
Base Station (Measure)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 09, 2017	Jun. 16, 2018	Aug. 08, 2018	Conducted (TH03-HY)
Amplifier	MITEQ	TTA1840- 35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Jun. 23, 2018~ Jul. 03, 2018	Jul. 17, 2018	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 10, 2016	Jun. 23, 2018~ Jul. 03, 2018	Nov. 09, 2018	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT- N0602	30MHz~1GHz	Oct. 14, 2017	Jun. 23, 2018~ Jul. 03, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 16, 2017	Jun. 23, 2018~ Jul. 03, 2018	Oct. 15, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 20, 2017	Jun. 23, 2018~ Jul. 03, 2018	Oct. 19, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Jun. 23, 2018~ Jul. 03, 2018	Nov. 22, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 10, 2016	Jun. 23, 2018~ Jul. 03, 2018	Nov. 09, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2017	Jun. 23, 2018~ Jul. 03, 2018	Oct. 18, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-1080 -1200-1500-60 SS	SN2	1.2G High Pass	Sep. 18, 2017	Jun. 23, 2018~ Jul. 03, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 0SS	SN3	2.7G High Pass	Sep. 18, 2017	Jun. 23, 2018~ Jul. 03, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jun. 23, 2018~ Jul. 03, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jun. 23, 2018~ Jul. 03, 2018	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Nov. 02, 2017	Jun. 23, 2018~ Jul. 03, 2018	Nov. 01, 2018	Radiation (03CH11-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 21, 2018	Jun. 23, 2018~ Jul. 03, 2018	May 20, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Nov. 27, 2017	Jun. 23, 2018~ Jul. 03, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Jun. 23, 2018~ Jul. 03, 2018	N/A	Radiation (03CH11-HY)

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : 19 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	3.37
Confidence of 95% (U = 2Uc(y))	3.37

Report No.: FG852420-01A

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	3.67
Confidence of 95% (U = 2Uc(y))	0.01

<u>Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)</u>

Measuring Uncertainty for a Level of	4.03
Confidence of 95% (U = 2Uc(y))	4.03

TEL: 886-3-327-3456 Page Number : 20 of 20 FAX: 886-3-328-4978 Issued Date : Jul. 05, 2018



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850		GSM1900			
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	33.59	33.61	33.60	30.85	30.81	30.79
GPRS class 8	33.62	33.66	33.63	30.87	30.82	30.79
GPRS class 10	30.33	30.41	30.40	27.03	27.19	27.34
GPRS class 11	28.46	28.54	28.50	24.92	25.09	25.25
GPRS class 12	27.37	27.45	27.45	23.89	24.05	24.22
EGPRS class 8	25.92	25.94	25.93	26.24	26.25	26.24
EGPRS class 10	23.92	23.91	23.93	24.42	24.43	24.41
EGPRS class 11	22.05	22.04	22.05	22.45	22.43	22.46
EGPRS class 12	20.99	20.99	21.03	21.40	21.32	21.34

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	24.02	23.95	23.86	24.70	24.69	24.65
HSDPA Subtest-1	23.72	23.66	23.58	24.21	24.25	24.17
HSDPA Subtest-2	23.71	23.59	23.58	24.15	24.13	24.04
HSDPA Subtest-3	23.19	23.08	23.04	23.58	23.67	23.53
HSDPA Subtest-4	23.21	23.04	22.94	23.54	23.64	23.53
HSUPA Subtest-1	21.71	21.64	21.59	22.76	22.31	22.21
HSUPA Subtest-2	21.71	21.62	21.55	22.21	22.25	22.12
HSUPA Subtest-3	22.68	22.63	22.61	23.28	23.22	23.19
HSUPA Subtest-4	21.18	21.16	21.01	21.73	21.71	21.66
HSUPA Subtest-5	22.70	22.60	22.60	23.20	23.20	23.10



FCC RF RADIO TEST REPORT

Conducted Power (*Unit: dBm)					
Band		WCDMA Band IV			
Channel	1312	1413	1513		
Frequency	1712.4	1732.6	1752.6		
RMC 12.2K	24.85	24.99	25.00		
HSDPA Subtest-1	24.08	24.13	24.25		
HSDPA Subtest-2	24.01	24.11	24.23		
HSDPA Subtest-3	23.49	23.62	23.79		
HSDPA Subtest-4	23.50	23.61	23.79		
HSUPA Subtest-1	22.07	22.15	22.20		
HSUPA Subtest-2	21.97	22.13	22.10		
HSUPA Subtest-3	23.00	23.14	22.99		
HSUPA Subtest-4	21.66	21.71	21.00		
HSUPA Subtest-5	22.90	23.00	22.70		

Report No. : FG852420-01A

A2. GSM

Peak-to-Average Ratio

Mode	GSI	Limit: 13dB	
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.24	3.28	
Middle CH	0.20	3.48	PASS
Highest CH	0.20	3.52	
Mode	GSM	Limit: 13dB	
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.24	3.20	
Middle CH	0.24	3.00	PASS
Highest CH	0.24	3.00	

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-1 of 15

GSM850 (GPRS class 8) GSM850 (EDGE class 8) **Lowest Channel Lowest Channel** * * Mean Peak Crest Mean Peak Crest 10 % 1 % .1 % 0.20 dB 0.24 dB 0.24 dB 0.24 dB Date: 16.JUN.2018 10:04:26 Date: 16.JUN.2018 09:37:11 **Middle Channel Middle Channel** Trace 1
31.88 dBm
32.08 dBm
0.20 dB 10 % 1 % .1 % 0.20 dB 0.20 dB 0.20 dB 0.20 dB 10 % 1 % .1 % 2.72 dB 3.36 dB 3.48 dB 3.60 dB **Highest Channel Highest Channel** * * Trace 1 31.98 dBm 32.22 dBm 0.24 dB Date: 16.JUN.2018 10:04:58 Date: 16.JUN.2018 09:37:50

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-2 of 15

GSM1900 (GPRS class 8) GSM1900 (EDGE class 8) **Lowest Channel Lowest Channel** * * Trace 1 24.76 dBm 28.05 dBm 3.30 dB Mean Peak Crest Mean Peak Crest 10 % 1 % .1 % 0.20 dB 0.24 dB 0.24 dB 0.24 dB Date: 16.JUN.2018 09:51:49 Date: 16.JUN.2018 09:11:21 **Middle Channel Middle Channel** Trace 1
28.60 dBm
28.83 dBm
0.24 dB Trace 1 25.00 dBm 28.05 dBm 3.05 dB 10 % 1 % .1 % 0.16 dB 0.24 dB 0.24 dB 0.24 dB 10 % 1 % .1 % **Highest Channel Highest Channel** * * Trace 1 28.68 dBm 28.90 dBm 0.22 dB

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-3 of 15

Date: 16.JUN.2018 09:12:01

FAX: 886-3-328-4978

Date: 16.JUN.2018 09:52:23

26dB Bandwidth

Mode	GSM850			
Mod.	GPRS class 8	EDGE class 8		
Lowest CH	0.304	0.299		
Middle CH	0.313	0.302		
Highest CH	0.316	0.308		
Mode	GSM	GSM1900		
Mod.	GPRS class 8	EDGE class 8		
Lowest CH	0.317	0.315		
Middle CH	0.314	0.307		
Highest CH	0.309	0.308		

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-4 of 15

GSM850 (GPRS class 8) GSM850 (EDGE class 8) **Lowest Channel Lowest Channel** Date: 16.JUN.2018 09:30:21 **Middle Channel Middle Channel Highest Channel Highest Channel** * *

Report No. : FG852420-01A


TEL: 886-3-327-3456 Page Number : A2-5 of 15

FAX: 886-3-328-4978

Date: 16.JUN.2018 09:59:44

GSM1900 (GPRS class 8) GSM1900 (EDGE class 8) **Lowest Channel Lowest Channel Middle Channel Middle Channel** * **Highest Channel Highest Channel** *

Report No. : FG852420-01A



TEL: 886-3-327-3456 Page Number : A2-6 of 15

Occupied Bandwidth

Mode	GSM850			
Mod.	GPRS class 8	EDGE class 8		
Lowest CH	0.248	0.244		
Middle CH	0.243	0.245		
Highest CH	0.247	0.248		
Mode	GSM	GSM1900		
Mod.	GPRS class 8	EDGE class 8		
Lowest CH	0.244	0.245		
Middle CH	0.249	0.248		
Highest CH	0.246	0.249		

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-7 of 15

GSM850 (GPRS class 8) GSM850 (EDGE class 8) **Lowest Channel Lowest Channel** * Date: 16.JUN.2018 09:34:57 **Middle Channel Middle Channel Highest Channel Highest Channel** * *

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-8 of 15

FAX: 886-3-328-4978

Date: 16.JUN.2018 10:01:31

Date: 16.JUN.2018 09:48:43


FAX: 886-3-328-4978

GSM1900 (GPRS class 8) GSM1900 (EDGE class 8) **Lowest Channel Lowest Channel** * Date: 16.JUN.2018 09:12:41 **Middle Channel Middle Channel Highest Channel Highest Channel** * *

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-9 of 15

Conducted Band Edge



Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number: A2-10 of 15


GSM1900 (GPRS class 8) **Lowest Band Edge Highest Band Edge %** Date: 16.JUN.2018 09:54:18 Date: 16.JUN.2018 09:55:49 GSM1900 (EDGE class 8) **Lowest Band Edge Highest Band Edge** Date: 16.JUN.2018 09:15:23

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-11 of 15

Date: 16.JUN.2018 09:17:11

Conducted Spurious Emission



Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-12 of 15

GSM1900 (EDGE class 8) GSM1900 (GPRS class 8) **Lowest Channel Lowest Channel** * Date: 16.JUN.2018 09:49:44 Date: 16.JUN.2018 09:09:06 **Middle Channel Middle Channel Highest Channel Highest Channel** * **%**

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-13 of 15

FAX: 886-3-328-4978

Date: 16.JUN.2018 09:51:24

Frequency Stability

Test Conditions	Middle Channel	GSM850	GSM850	Limit
		(GPRS class 8)	(EDGE class 8)	2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation	on (ppm)	Result
50	Normal Voltage	0.0024	0.0287	
40	Normal Voltage	0.0000	0.0036	
30	Normal Voltage	0.0024	0.0323	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0024	0.0048	
0	Normal Voltage	0.0012	0.0036	DACC
-10	Normal Voltage	0.0024	0.0048	PASS
-20	Normal Voltage	0.0060	0.0227	
-30	Normal Voltage	0.0000	0.0024	
20	Maximum Voltage	0.0036	0.0048	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0096	0.0012	

Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A2-14 of 15

Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation	on (ppm)	Result
50	Normal Voltage	0.0000	0.0021	
40	Normal Voltage	0.0000	0.0000	
30	Normal Voltage	0.0112	0.0122	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0000	0.0122]
0	Normal Voltage	0.0101	0.0112	DACC
-10	Normal Voltage	0.0112	0.0027	PASS
-20	Normal Voltage	0.0128	0.0144	
-30	Normal Voltage	0.0261	0.0128	
20	Maximum Voltage	0.0106	0.0165	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0005	0.0011	

Report No.: FG852420-01A

Note:

- 1. Normal Voltage = 3.8 V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V
- 2. The frequency fundamental emissions stay within the authorized frequency block.

TEL: 886-3-327-3456 Page Number : A2-15 of 15

A3. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.24	3.20	3.08	
Middle CH	3.08	3.12	2.92	PASS
Highest CH	3.36	3.24	3.08	

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-1 of 15

WCDMA Band V (RMC 12.2Kbps) WCDMA Band II (RMC 12.2Kbps) **Lowest Channel Lowest Channel** * * Trace 1 22.58 dBm 26.16 dBm 3.58 dB Mean Peak Crest Mean Peak Crest 10 % 1 % .1 % Date: 16.JUN.2018 10:48:37 Date: 16.JUN.2018 10:18:35 **Middle Channel Middle Channel** Trace 1
22.75 dBm
26.30 dBm
3.55 dB 10 % 1 % .1 % 1.76 dB 2.60 dB 3.08 dB 3.32 dB 10 % 1 % .1 % **Highest Channel Highest Channel** * * Trace 1 22.83 dBm 26.51 dBm 3.68 dB


Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-2 of 15

FAX: 886-3-328-4978

Date: 16.JUN.2018 10:49:06

C RADIO TEST REPORT Report No. : FG852420-01A




TEL: 886-3-327-3456 Page Number: A3-3 of 15

26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	
Lowest CH	4.72	4.70	4.70	
Middle CH	4.70	4.71	4.70	
Highest CH	4.70	4.71	4.70	

Report No. : FG852420-01A


TEL: 886-3-327-3456 Page Number : A3-4 of 15



Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number: A3-5 of 15





TEL: 886-3-327-3456 Page Number: A3-6 of 15

Occupied Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	
Lowest CH	4.18	4.17	4.17	
Middle CH	4.17	4.18	4.16	
Highest CH	4.17	4.17	4.18	

Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-7 of 15

Date: 16.JUN.2018 10:45:40

FAX: 886-3-328-4978

WCDMA Band V (RMC 12.2Kbps) WCDMA Band II (RMC 12.2Kbps) **Lowest Channel Lowest Channel** * **Middle Channel Middle Channel Highest Channel Highest Channel** * * 1 PE MAXH


Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-8 of 15

Date: 16.JUN.2018 10:15:46




Report No. : FG852420-01A




TEL: 886-3-327-3456 Page Number: A3-9 of 15

Conducted Band Edge



Report No.: FG852420-01A


TEL: 886-3-327-3456 Page Number : A3-10 of 15



Report No. : FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-11 of 15

Conducted Spurious Emission



Report No.: FG852420-01A

TEL: 886-3-327-3456 Page Number : A3-12 of 15



Report No. : FG852420-01A WCDMA Band IV (RMC 12.2Kbps) **Lowest Channel** * Date: 16.JUN.2018 10:31:04 **Middle Channel Highest Channel** *

TEL: 886-3-327-3456 Page Number : A3-13 of 15

Date: 16.JUN.2018 10:32:43

Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0012	
40	Normal Voltage	0.0012	
30	Normal Voltage	0.0036	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	Normal Voltage 0.0000	
0	Normal Voltage	0.0036	D4.00
-10	Normal Voltage	0.0024	PASS
-20	Normal Voltage	0.0012	
-30	Normal Voltage	0.0036	
20	Maximum Voltage	0.0036	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0024	

Report No.: FG852420-01A

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0000	
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0005	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0027	DA CC
-10	Normal Voltage	0.0032	PASS
-20	Normal Voltage	0.0011	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0069	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0021	

TEL: 886-3-327-3456 Page Number : A3-14 of 15

Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0000	
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0005	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0027	DACC
-10	Normal Voltage	0.0032	PASS
-20	Normal Voltage	0.0011	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0069	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0021	

Report No.: FG852420-01A

Note:

- 1. Normal Voltage = 3.8V. ; Battery End Point (BEP) = 3.5V. ; Maximum Voltage =4.2 V
- 2. The frequency fundamental emissions stay within the authorized frequency block

TEL: 886-3-327-3456 Page Number : A3-15 of 15



Appendix B. Test Results of ERP/EIRP and Radiated Test

ERP/EIRP

Channel	Mode	Cond	ucted	ERP		
Chamilei	Wode	Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)	
Lowest	GSM850	33.62	2.3014	29.19	0.8299	
Middle	GPRS class 8	33.66	2.3227	29.23	0.8375	
Highest	GT - LC = -2.28 dB	33.63	2.3067	29.20	0.8318	
Lowest	GSM850	25.92	0.3908	21.49	0.1409	
Middle	EDGE class 8	25.94	0.3926	21.51	0.1416	
Highest	GT - LC = -2.28 dB	25.93	0.3917	21.50	0.1413	
Lowest	WCDMA Band V	24.02	0.2523	19.59	0.0910	
Middle	RMC 12.2Kbps	23.95	0.2483	19.52	0.0895	
Highest	GT - LC = -2.28 dB	23.86	0.2432	19.43	0.0877	
Limit	ERP < 7W	Result		PASS		

Channel	Mode	Cond	ucted	EIRP		
Channel	Wiode	Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)	
Lowest	GSM1900	30.87	1.2218	32.49	1.7742	
Middle	GPRS class 8	30.82	1.2078	32.44	1.7539	
Highest	(GT - LC = 1.62 dB)	30.79	1.1995	32.41	1.7418	
Lowest	GSM1900	26.24	0.4207	27.86	0.6109	
Middle	EDGE class 8	26.25	0.4217	27.87	0.6124	
Highest	(GT - LC = 1.62 dB)	26.24	0.4207	27.86	0.6109	
Lowest	WCDMA Band II	24.70	0.2951	26.32	0.4285	
Middle	RMC 12.2Kbps	24.69	0.2944	26.31	0.4276	
Highest	(GT - LC = 1.62 dB)	24.65	0.2917	26.27	0.4236	
Limit	EIRP < 2W	Result		PASS		

Channel	Mode	Cond	ucted	EIRP		
Chamilei	IVIOGE	Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)	
Lowest	WCDMA Band IV	24.85	0.3055	24.54	0.2844	
Middle	RMC 12.2Kbps	24.99	0.3155	24.68	0.2938	
Highest	GT - LC = -0.31 dB	25.00	0.3162	24.69	0.2944	
Limit	EIRP < 1W	Result		PASS		

Radiated Spurious Emission

<Main Antenna>

GPRS 850

Report No. : FG852420-01A

	GPRS 850								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1648	-49.35	-13	-36.35	-59.12	-56.3	0.53	9.63	Н
	2472	-34.12	-13	-21.12	-47.34	-42.1	0.65	10.78	Н
	3296	-58.42	-13	-45.42	-74.54	-67.5	0.76	11.99	Н
Lowest									Н
Lowest	1648	-42.35	-13	-29.35	-51.24	-49.3	0.53	9.63	V
	2472	-37.92	-13	-24.92	-51.4	-45.9	0.65	10.78	V
	3296	-58.72	-13	-45.72	-74.42	-67.8	0.76	11.99	V
									V
	1672	-47.10	-13	-34.10	-56.91	-54.1	0.53	9.68	Н
	2512	-42.20	-13	-29.20	-55.76	-50.2	0.66	10.81	Н
	3344	-53.88	-13	-40.88	-69.7	-63.1	0.76	12.13	Н
N 4: -l -ll -									Н
Middle	1672	-38.90	-13	-25.90	-48.44	-45.9	0.53	9.68	V
	2512	-40.90	-13	-27.90	-54.52	-48.9	0.66	10.81	V
	3344	-56.88	-13	-43.88	-72.41	-66.1	0.76	12.13	V
									V
	1696	-45.15	-13	-32.15	-55.27	-52.2	0.53	9.73	Н
	2544	-46.09	-13	-33.09	-58.89	-54.1	0.67	10.83	Н
	3392	-55.44	-13	-42.44	-71.72	-64.8	0.77	12.28	Н
د - حاسنا ا									Н
Highest	1696	-38.45	-13	-25.45	-48.11	-45.5	0.53	9.73	V
	2544	-46.69	-13	-33.69	-60.52	-54.7	0.67	10.83	V
	3392	-56.84	-13	-43.84	-72.56	-66.2	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-1 of 10

EDGE 850

Report No. : FG852420-01A

EDGE 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1648	-59.65	-13	-46.65	-69.72	-66.6	0.53	9.63	Н
	2472	-48.02	-13	-35.02	-60.85	-56	0.65	10.78	Н
	3296	-56.82	-13	-43.82	-72.84	-65.9	0.76	11.99	Н
Lowest									Н
Lowest	1648	-55.65	-13	-42.65	-65.22	-62.6	0.53	9.63	V
	2472	-48.32	-13	-35.32	-62.03	-56.3	0.65	10.78	V
	3296	-48.32	-13	-35.32	-74.26	-57.4	0.76	11.99	V
									V
	1672	-57.60	-13	-44.60	-67.47	-64.6	0.53	9.68	Н
	2512	-49.40	-13	-36.40	-62.75	-57.4	0.66	10.81	Н
	3344	-58.88	-13	-45.88	-74.53	-68.1	0.76	12.13	Н
Middle									Н
Middle	1672	-56.80	-13	-43.80	-66.4	-63.8	0.53	9.68	V
	2512	-51.60	-13	-38.60	-64.86	-59.6	0.66	10.81	V
	3344	-58.48	-13	-45.48	-74.51	-67.7	0.76	12.13	V
									V
	1696	-54.95	-13	-41.95	-64.96	-62	0.53	9.73	Н
	2544	-52.09	-13	-39.09	-65.11	-60.1	0.67	10.83	Н
	3392	-58.94	-13	-45.94	-74.6	-68.3	0.77	12.28	Н
Llighoot									Н
Highest	1696	-52.85	-13	-39.85	-62.26	-59.9	0.53	9.73	V
	2544	-55.49	-13	-42.49	-68.07	-63.5	0.67	10.83	V
	3392	-59.24	-13	-46.24	-74.81	-68.6	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-2 of 10

WCDMA 850

Report No. : FG852420-01A

				WCD	MA 850				
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1656	-58.13	-13	-45.13	-67.75	-65.1	0.53	9.64	Н
	2480	-59.58	-13	-46.58	-72.96	-67.56	0.65	10.78	Н
	3304	-58.40	-13	-45.40	-74.16	-67.5	0.76	12.01	Н
Lowest									Н
Lowest	1656	-57.73	-13	-44.73	-67.19	-64.7	0.53	9.64	V
	2480	-57.32	-13	-44.32	-70.97	-65.3	0.65	10.78	V
	3304	-57.60	-13	-44.60	-73.55	-66.7	0.76	12.01	V
									V
	1672	-57.30	-13	-44.30	-67.26	-64.3	0.53	9.68	Н
	2512	-59.10	-13	-46.10	-72.31	-67.1	0.66	10.81	Н
	3344	-57.68	-13	-44.68	-73.56	-66.9	0.76	12.13	Н
Middle									Н
Middle	1672	-58.40	-13	-45.40	-68.02	-65.4	0.53	9.68	V
	2512	-58.20	-13	-45.20	-71.74	-66.2	0.66	10.81	V
	3344	-57.18	-13	-44.18	-72.89	-66.4	0.76	12.13	V
									V
	1696	-56.25	-13	-43.25	-66.05	-63.3	0.53	9.73	Н
	2544	-59.19	-13	-46.19	-72.08	-67.2	0.67	10.83	Н
	3384	-56.77	-13	-43.77	-72.91	-66.1	0.77	12.25	Н
l limb oot									Н
Highest	1696	-60.85	-13	-47.85	-70.53	-67.9	0.53	9.73	V
	2544	-57.39	-13	-44.39	-70.87	-65.4	0.67	10.83	V
	3384	-55.77	-13	-42.77	-71.34	-65.1	0.77	12.25	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-3 of 10

WCDMA 1700

Report No. : FG852420-01A

				WCDI	MA 1700				
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	3426	-51.05	-13	-38.05	-68.21	-62.65	0.77	12.38	Н
	5136	-51.17	-13	-38.17	-71.87	-62.67	0.97	12.47	Н
	6852	-50.56	-13	-37.56	-74.29	-61.35	0.83	11.63	Н
Lowest									Н
Lowest	3426	-55.46	-13	-42.46	-72.43	-67.06	0.77	12.38	V
	5136	-54.82	-13	-41.82	-75.69	-66.32	0.97	12.47	V
	6852	-51.04	-13	-38.04	-75.22	-61.83	0.83	11.63	V
									V
	3462	-53.04	-13	-40.04	-70.24	-64.75	0.78	12.49	Н
	5202	-52.96	-13	-39.96	-73.78	-64.57	0.99	12.60	Н
	6930	-51.99	-13	-38.99	-75.86	-62.44	1.01	11.45	Н
Middle									Н
Middle	3462	-55.03	-13	-42.03	-72.62	-66.74	0.78	12.49	V
	5202	-55.42	-13	-42.42	-76.4	-67.03	0.99	12.60	V
	6930	-52.24	-13	-39.24	-76.49	-62.69	1.01	11.45	V
									V
	3504	-50.25	-13	-37.25	-67.5	-62.07	0.78	12.60	Н
	5256	-48.19	-13	-35.19	-69.16	-59.89	1.01	12.71	Н
	7014	-49.60	-13	-36.60	-73.71	-59.71	1.17	11.27	Н
l liab oot									Н
Highest	3504	-54.55	-13	-41.55	-72.77	-66.37	0.78	12.60	V
	5256	-54.02	-13	-41.02	-75.13	-65.72	1.01	12.71	V
	7014	-50.33	-13	-37.33	-74.73	-60.44	1.17	11.27	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number : B2-4 of 10

GPRS 1900

Report No. : FG852420-01A

				GPR	S 1900				
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	3702	-53.61	-13	-40.61	-70.42	-65.4	0.72	12.52	Н
	5550	-51.73	-13	-38.73	-73.57	-63.9	1.00	13.17	Н
	7404	-51.71	-13	-38.71	-76.39	-61.1	1.18	10.57	Н
	9252	-36.89	-13	-23.89	-66.16	-47.4	1.39	11.89	Н
Lowest									Н
Lowest	3702	-54.51	-13	-41.51	-72.74	-66.3	0.72	12.52	V
	5550	-53.83	-13	-40.83	-75.26	-66	1.00	13.17	V
	7404	-52.41	-13	-39.41	-76.8	-61.8	1.18	10.57	V
	9252	-44.29	-13	-31.29	-73.3	-54.8	1.39	11.89	V
									V
	1672	-47.10	-13	-34.10	-56.91	-54.1	0.53	9.68	Н
	2512	-42.20	-13	-29.20	-55.76	-50.2	0.66	10.81	Н
	3344	-53.88	-13	-40.88	-69.7	-63.1	0.76	12.13	Н
N 4: al all a									Н
Middle	1672	-38.90	-13	-25.90	-48.44	-45.9	0.53	9.68	V
	2512	-40.90	-13	-27.90	-54.52	-48.9	0.66	10.81	V
	3344	-56.88	-13	-43.88	-72.41	-66.1	0.76	12.13	V
									V
	1696	-45.15	-13	-32.15	-55.27	-52.2	0.53	9.73	Н
	2544	-46.09	-13	-33.09	-58.89	-54.1	0.67	10.83	Н
	3392	-55.44	-13	-42.44	-71.72	-64.8	0.77	12.28	Н
ند د جاستا ا									Н
Highest	1696	-38.45	-13	-25.45	-48.11	-45.5	0.53	9.73	V
	2544	-46.69	-13	-33.69	-60.52	-54.7	0.67	10.83	V
	3392	-56.84	-13	-43.84	-72.56	-66.2	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-5 of 10

EDGE1900

Report No. : FG852420-01A

				EDG	E 1900				
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	3702	-55.81	-13	-42.81	-72.02	-67.6	0.72	12.52	Н
	5550	-53.93	-13	-40.93	-75.27	-66.1	1.00	13.17	Н
	7404	-51.91	-13	-38.91	-76.69	-61.3	1.18	10.57	Н
	9252	-38.19	-13	-25.19	-67.26	-48.7	1.39	11.89	Н
Lowest									Н
Lowest	3702	-54.81	-13	-41.81	-72.74	-66.6	0.72	12.52	V
	5550	-54.63	-13	-41.63	-76.21	-66.8	1.00	13.17	V
	7404	-52.81	-13	-39.81	-77.2	-62.2	1.18	10.57	V
	9252	-44.19	-13	-31.19	-73.3	-54.7	1.39	11.89	V
									V
	1672	-57.60	-13	-44.60	-67.47	-64.6	0.53	9.68	Н
	2512	-49.40	-13	-36.40	-62.75	-57.4	0.66	10.81	Н
	3344	-58.88	-13	-45.88	-74.53	-68.1	0.76	12.13	Н
Middle									Н
Middle	1672	-56.80	-13	-43.80	-66.4	-63.8	0.53	9.68	V
	2512	-51.60	-13	-38.60	-64.86	-59.6	0.66	10.81	V
	3344	-58.48	-13	-45.48	-74.51	-67.7	0.76	12.13	V
									V
	1696	-54.95	-13	-41.95	-64.96	-62	0.53	9.73	Н
	2544	-52.09	-13	-39.09	-65.11	-60.1	0.67	10.83	Н
	3392	-58.94	-13	-45.94	-74.6	-68.3	0.77	12.28	Н
∐igh oot									Н
Highest	1696	-52.85	-13	-39.85	-62.26	-59.9	0.53	9.73	V
	2544	-55.49	-13	-42.49	-68.07	-63.5	0.67	10.83	V
	3392	-59.24	-13	-46.24	-74.81	-68.6	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number : B2-6 of 10

WCDMA 1900

Report No. : FG852420-01A

				WCDI	/IA 1900				
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	3705	-49.11	-13	-36.11	-66.04	-60.9	0.72	12.52	Н
	5562	-45.83	-13	-32.83	-67.36	-58	1.00	13.16	Н
	7416	-49.83	-13	-36.83	-74.47	-59.2	1.18	10.55	Н
	9252	-44.69	-13	-31.69	-74.11	-55.2	1.39	11.89	Н
Lowest									Н
Lowest	3705	-52.01	-13	-39.01	-70.05	-63.8	0.72	12.52	V
	5562	-52.33	-13	-39.33	-73.5	-64.5	1.00	13.16	V
	7416	-52.83	-13	-39.83	-77.01	-62.2	1.18	10.55	V
	9252	-46.09	-13	-33.09	-74.94	-56.6	1.39	11.89	V
									V
	1672	-57.30	-13	-44.30	-67.26	-64.3	0.53	9.68	Н
	2512	-59.10	-13	-46.10	-72.31	-67.1	0.66	10.81	Н
	3344	-57.68	-13	-44.68	-73.56	-66.9	0.76	12.13	Н
Middle									Н
Middle	1672	-58.40	-13	-45.40	-68.02	-65.4	0.53	9.68	V
	2512	-58.20	-13	-45.20	-71.74	-66.2	0.66	10.81	V
	3344	-57.18	-13	-44.18	-72.89	-66.4	0.76	12.13	V
									V
	1696	-56.25	-13	-43.25	-66.05	-63.3	0.53	9.73	Н
	2544	-59.19	-13	-46.19	-72.08	-67.2	0.67	10.83	Н
	3384	-56.77	-13	-43.77	-72.91	-66.1	0.77	12.25	Н
Lligh oot									Н
Highest	1696	-60.85	-13	-47.85	-70.53	-67.9	0.53	9.73	V
	2544	-57.39	-13	-44.39	-70.87	-65.4	0.67	10.83	V
	3384	-55.77	-13	-42.77	-71.34	-65.1	0.77	12.25	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-7 of 10

<Aux. Antenna>

GPRS 850

Report No. : FG852420-01A

				GPR	S 850				
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1648	-57.25	-13	-44.25	-66.84	-64.2	0.53	9.63	Н
	2472	-49.12	-13	-36.12	-62.35	-57.1	0.65	10.78	Н
	3296	-54.62	-13	-41.62	-70.55	-63.7	0.76	11.99	Н
Lowest									Н
Lowest	1648	-57.45	-13	-44.45	-66.98	-64.4	0.53	9.63	V
	2472	-40.72	-13	-27.72	-54.5	-48.7	0.65	10.78	V
	3296	-55.42	-13	-42.42	-71.11	-64.5	0.76	11.99	V
									V
	1672	-55.90	-13	-42.90	-65.97	-62.9	0.53	9.68	Н
	2512	-46.50	-13	-33.50	-59.97	-54.5	0.66	10.81	Н
	3344	-50.48	-13	-37.48	-69.38	-59.7	0.76	12.13	Н
Middle									Н
Middle	1672	-56.60	-13	-43.60	-66.04	-63.6	0.53	9.68	V
	2512	-42.80	-13	-29.80	-56.61	-50.8	0.66	10.81	V
	3344	-55.68	-13	-42.68	-71.26	-64.9	0.76	12.13	V
									V
	1696	-53.45	-13	-40.45	-63.47	-60.5	0.53	9.73	Н
	2544	-50.19	-13	-37.19	-63.26	-58.2	0.67	10.83	Н
	3392	-54.74	-13	-41.74	-70.63	-64.1	0.77	12.28	Н
Highoot									Н
Highest	1696	-56.25	-13	-43.25	-65.6	-63.3	0.53	9.73	V
	2544	-42.09	-13	-29.09	-55.41	-50.1	0.67	10.83	V
	3392	-58.14	-13	-45.14	-73.97	-67.5	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-8 of 10

EDGE 850

Report No. : FG852420-01A

				EDG	E 850				
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1648	-59.55	-13	-46.55	-69.44	-66.5	0.53	9.63	Н
	2472	-58.92	-13	-45.92	-72.21	-66.9	0.65	10.78	Н
	3296	-58.02	-13	-45.02	-73.84	-67.1	0.76	11.99	Н
Lowest									Н
Lowest	1648	-60.75	-13	-47.75	-70.26	-67.7	0.53	9.63	V
	2472	-55.52	-13	-42.52	-69	-63.5	0.65	10.78	V
	3296	-58.32	-13	-45.32	-74.43	-67.4	0.76	11.99	V
									V
	1672	-61.90	-13	-48.90	-71.96	-68.9	0.53	9.68	Н
	2512	-58.80	-13	-45.80	-71.77	-66.8	0.66	10.81	Н
	3344	-57.88	-13	-44.88	-73.46	-67.1	0.76	12.13	Н
Middle									Н
Middle	1672	-59.30	-13	-46.30	-68.71	-66.3	0.53	9.68	V
	2512	-54.20	-13	-41.20	-67.56	-62.2	0.66	10.81	V
	3344	-58.68	-13	-45.68	-74.69	-67.9	0.76	12.13	V
									V
	1696	-60.65	-13	-47.65	-70.98	-67.7	0.53	9.73	Н
	2544	-59.19	-13	-46.19	-72.16	-67.2	0.67	10.83	Н
	3392	-56.74	-13	-43.74	-72.65	-66.1	0.77	12.28	Н
l limb oot									Н
Highest	1696	-57.05	-13	-44.05	-66.59	-64.1	0.53	9.73	V
	2544	-50.79	-13	-37.79	-64.58	-58.8	0.67	10.83	V
	3392	-59.14	-13	-46.14	-74.78	-68.5	0.77	12.28	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number: B2-9 of 10

WCDMA 850

Report No. : FG852420-01A

				WCD	MA 850				
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
	1656	-57.63	-13	-44.63	-67.3	-64.6	0.53	9.64	Н
	2480	-59.62	-13	-46.62	-72.97	-67.6	0.65	10.78	Н
	3304	-58.10	-13	-45.10	-73.66	-67.2	0.76	12.01	Н
Lowest									Н
Lowest	1656	-58.53	-13	-45.53	-68.15	-65.5	0.53	9.64	V
	2480	-57.82	-13	-44.82	-71.4	-65.8	0.65	10.78	V
	3304	-58.10	-13	-45.10	-74.12	-67.2	0.76	12.01	V
									V
	1672	-56.60	-13	-43.60	-66.47	-63.6	0.53	9.68	Н
	2512	-59.60	-13	-46.60	-72.77	-67.6	0.66	10.81	Н
	3344	-57.88	-13	-44.88	-73.5	-67.1	0.76	12.13	Н
Middle									Н
Middle	1672	-58.60	-13	-45.60	-67.87	-65.6	0.53	9.68	V
	2512	-57.90	-13	-44.90	-71.71	-65.9	0.66	10.81	V
	3344	-58.18	-13	-45.18	-73.84	-67.4	0.76	12.13	V
									V
	1696	-55.35	-13	-42.35	-65.55	-62.4	0.53	9.73	Н
	2544	-59.29	-13	-46.29	-72.25	-67.3	0.67	10.83	Н
	3384	-56.97	-13	-43.97	-71	-66.3	0.77	12.25	Н
Llighoot									Н
Highest	1696	-60.05	-13	-47.05	-69.58	-67.1	0.53	9.73	V
	2544	-57.59	-13	-44.59	-71.1	-65.6	0.67	10.83	V
	3384	-55.57	-13	-42.57	-71.35	-64.9	0.77	12.25	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 886-3-327-3456 Page Number : B2-10 of 10