

**FCC PART 15.247
TEST REPORT**

For

COTO C.I.C.S.A.

PAYSANDU 1842, BUENOS AIRES - ARGENTINA

FCC ID: 2AJP4L4506

Report Type: Original Report	Product Type: 4G Smart Phone
Report Number: RSZ170622001-00B	
Report Date: 2017-07-26	
Oscar Ye 	
Reviewed By: Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 – ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED FACTOR & MARGIN CALCULATION	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATA	20
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52
FCC §15.247(d) - BAND EDGES TESTING	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST DATA	53

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *COTO C.I.C.S.A.* 's product, model number: *L4506 (FCC ID: 2AJP4L4506)* in this report is a *4G Smart Phone* which was measured approximately: 13.2 cm (L) * 6.4 cm (W) * 1.1 cm (H), rated with input voltage: DC 3.8 V battery or DC 5.0V from adapter.

Adapter Information:

Model: HJ-050100-AR

Input: AC 100-240V, 50/60Hz, 0.15A

Output: DC 5.0V, 1A

** All measurement and test data in this report was gathered from production sample serial number: 1701447 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-06-22.*

Objective

This test report is prepared on behalf of *COTO C.I.C.S.A.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H & 24E & 27 PCE, FCC Part 15.247 DTS and Part 15B JBP submissions with FCC ID: 2AJP4L4506.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		±3.26 dB
RF conducted test with spectrum		±0.9dB
RF Output Power with Power meter		±0.5dB
Radiated emission	30MHz~1GHz	±5.91dB
	Above 1G	±4.92dB
Occupied Bandwidth		±0.5kHz
Temperature		±1.0℃
Humidity		±6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Bay Area Compliance Laboratories Corp. (Kunshan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L9963). And accredited to ISO/IEC 17025 by A2LA(Lab code: 4323.01), the FCC Designation No. CN1185 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Kunshan) was registered with ISED Canada under ISED Canada Registration Number 3062E.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

No exercise software was used

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
N/A	N/A	N/A	N/A

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.5	EUT	Adapter
Un-shielding Detachable Earphone Cable	1.1	EUT	Earphone

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2016-11-25	2017-11-25
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2016-10-10	2017-10-10
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2017-06-19	2018-06-18
MICRO-COAX	Coaxial line	UFB-293B-1-0480-50X50	97F0173	2016-09-08	2017-09-08
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	NCR	NCR
Radiation test					
Sonoma Instrunent	Amplifier	330	171377	2016-12-12	2017-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-15
WEINSCHEL	10dB Attenuator	5328	N/A	2017-06-18	2018-06-18
Agilent	Power Meter	N1912A	MY5000492	2016-11-17	2017-11-16
Agilent	Power Sensor	N1921A	MY54210024	2016-11-17	2017-11-16
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum conducted Tune-up power		Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
	Power (dBm)	Power (mW)				
2480	3.5	2.24	5	0.7	3.0	Yes

Result: No SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for bluetooth which was permanently attached and the antenna gain is 0.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-07-20.

EUT operation mode: Transmitting

AC 120V/60 Hz, Line:


Full Spectrum



Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.160000	40.97	---	9.000	L1	10.1	24.49	65.46	Compliance
0.160000	---	26.95	9.000	L1	10.1	28.51	55.46	Compliance
0.260000	33.47	---	9.000	L1	10.1	27.96	61.43	Compliance
0.260000	---	17.04	9.000	L1	10.1	34.39	51.43	Compliance
0.460000	33.83	---	9.000	L1	10.1	22.86	56.69	Compliance
0.460000	---	23.94	9.000	L1	10.1	22.75	46.69	Compliance
0.750000	---	19.66	9.000	L1	9.9	26.34	46.00	Compliance
0.750000	31.05	---	9.000	L1	9.9	24.95	56.00	Compliance
0.910000	---	19.76	9.000	L1	9.9	26.24	46.00	Compliance
0.910000	32.82	---	9.000	L1	9.9	23.18	56.00	Compliance
16.810000	---	16.10	9.000	L1	10.1	33.90	50.00	Compliance
16.810000	28.16	---	9.000	L1	10.1	31.84	60.00	Compliance

AC 120V/60 Hz, Neutral

Full Spectrum



Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.160000	---	23.38	9.000	L1	10.1	32.08	55.46	Compliance
0.160000	38.37	---	9.000	L1	10.1	27.09	65.46	Compliance
0.690000	---	14.59	9.000	L1	10.0	31.41	46.00	Compliance
0.690000	27.53	---	9.000	L1	10.0	28.47	56.00	Compliance
0.710000	---	16.78	9.000	L1	9.9	29.22	46.00	Compliance
0.710000	30.04	---	9.000	L1	9.9	25.96	56.00	Compliance
0.830000	---	14.60	9.000	L1	9.9	31.40	46.00	Compliance
0.830000	28.29	---	9.000	L1	9.9	27.71	56.00	Compliance
0.900000	---	8.71	9.000	L1	9.9	37.29	46.00	Compliance
0.900000	30.49	---	9.000	L1	9.9	25.51	56.00	Compliance
0.970000	---	16.11	9.000	L1	9.9	29.89	46.00	Compliance
0.970000	29.69	---	9.000	L1	9.9	26.31	56.00	Compliance

Note:

- 1) Corrected Amplitude = Reading + Correction Factor
- 2) Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, 205 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cisp}}r$$

In BAEL, $U_{(L_m)}$ is less than $U_{\text{cisp}}r$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-07-20.

EUT operation mode: Transmitting

30 MHz -25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
180.24	34.65	QP	179	1.5	H	-2.01	32.64	43.5	10.86
2402.00	98.91	PK	271	2.2	H	-6.19	92.72	/	/
2402.00	86.34	Ave.	271	2.2	H	-6.19	80.15	/	/
2402.00	95.86	PK	54	1.4	V	-6.19	89.67	/	/
2402.00	83.71	Ave.	54	1.4	V	-6.19	77.52	/	/
2321.86	67.95	PK	346	1.9	V	-6.42	61.53	74	12.47
2321.86	54.16	Ave.	346	1.9	V	-6.42	47.74	54	6.26
2361.14	68.08	PK	202	1.0	V	-6.19	61.89	74	12.11
2361.14	54.04	Ave.	202	1.0	V	-6.19	47.85	54	6.15
2497.85	67.18	PK	309	2.5	V	-5.97	61.21	74	12.79
2497.85	53.38	Ave.	309	2.5	V	-5.97	47.41	54	6.59
4804.00	48.17	PK	7	2.4	H	1.6	49.77	74	24.23
4804.00	33.34	Ave.	7	2.4	H	1.6	34.94	54	19.06
7206.00	40.67	PK	246	2.2	H	7.54	48.21	74	25.79
7206.00	30.03	Ave.	246	2.2	H	7.54	37.57	54	16.43

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2441 MHz)									
180.24	34.74	QP	275	1.8	H	-2.01	32.73	43.5	10.27
2441.00	96.51	PK	131	2.0	H	-6.19	90.32	/	/
2441.00	84.87	Ave.	131	2.0	H	-6.19	78.68	/	/
2441.00	96.57	PK	272	1.3	V	-6.19	90.38	/	/
2441.00	84.28	Ave.	272	1.3	V	-6.19	78.09	/	/
2327.79	68.73	PK	127	1.6	V	-6.42	62.31	74	11.69
2327.79	54.17	Ave.	127	1.6	V	-6.42	47.75	54	6.25
2341.9	68.39	PK	149	1.8	V	-6.42	61.97	74	12.03
2341.9	54.13	Ave.	149	1.8	V	-6.42	47.71	54	6.29
2486.34	68	PK	101	1.5	V	-5.97	62.03	74	11.97
2486.34	53.38	Ave.	101	1.5	V	-5.97	47.41	54	6.59
4882.00	48.77	PK	175	2.1	H	1.83	50.60	74	23.40
4882.00	33.72	Ave.	175	2.1	H	1.83	35.55	54	18.45
7323.00	40.73	PK	253	1.7	H	7.54	48.27	74	25.73
7323.00	29.48	Ave.	253	1.7	H	7.54	37.02	54	16.98
High Channel (2480 MHz)									
180.24	32.66	QP	302	1.8	H	-2.01	30.65	43.5	12.85
2480.00	98.32	PK	35	1.3	H	-5.97	92.35	/	/
2480.00	86.34	Ave.	35	1.3	H	-5.97	80.37	/	/
2480.00	94.97	PK	180	2.4	V	-5.97	89.00	/	/
2480.00	83.78	Ave.	180	2.4	V	-5.97	77.81	/	/
2355.05	67.7	PK	94	2.1	V	-6.19	61.51	74	12.49
2355.05	54	Ave.	94	2.1	V	-6.19	47.81	54	6.19
2486.97	66.81	PK	190	1.4	V	-5.97	60.84	74	13.16
2486.97	53.46	Ave.	190	1.4	V	-5.97	47.49	54	6.51
2497.98	67.61	PK	206	1.9	V	-5.97	61.64	74	12.36
2497.98	53.37	Ave.	206	1.9	V	-5.97	47.40	54	6.60
4960.00	49.57	PK	205	2.1	H	2.06	51.63	74	22.37
4960.00	34.7	Ave.	205	2.1	H	2.06	36.76	54	17.24
7440.00	39.75	PK	121	2.2	H	7.54	47.29	74	26.71
7440.00	28.35	Ave.	121	2.2	H	7.54	35.89	54	18.11

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Poboo Li on 2017-07-12.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.631	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.625	Pass
	Adjacent	2442			
	High	2480	1.004	0.625	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.004	0.842	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.850	Pass
	Adjacent	2442			
	High	2480	1.004	0.847	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.004	0.853	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.850	Pass
	Adjacent	2442			
	High	2480	1.004	0.855	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



Ref Lvl 23.5 dBm
 Marker 1 [T1] 2.47883567 GHz
 RBW 30 kHz
 VBW 100 kHz
 RF Att 30 dB
 Unit dBm
 SWT 8.5 ms

10.5 dB Offset
 2.47883567 GHz
 -1.54 dBm
 -12.12 dBm
 1.00400802 MHz

Center 2.4795 GHz
 300 kHz/
 Span 3 MHz

Date: 12.JUL.2017 16:58:36

Delta 1 [T1] 0.41 dB RBW 30 kHz RF Att 30 dB

Ref Lvl 23.5 dBm 1.00400802 MHz SWT 8.5 ms Unit dBm


10.5 dB Offset

2.40184168 GHz -2.65 dBm


1.00400802 MHz -1.00 dBm

Center 2.4025 GHz 300 kHz/ Span 3 MHz


Date: 12.JUL.2017 16:59:38

EDR ($\pi/4$ -DQPSK): Middle Channel**EDR ($\pi/4$ -DQPSK): High Channel**

EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa


The testing was performed by Poboo Li on 2017-07-12.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.946
	Middle	2441	0.938
	High	2480	0.938
EDR ($\pi/4$-DQPSK)	Low	2402	1.263
	Middle	2441	1.275
	High	2480	1.271
EDR (8DPSK)	Low	2402	1.279
	Middle	2441	1.275
	High	2480	1.283

BDR (GFSK): Low Channel



Delta 1 [T1]

Ref Lvl -2.21 dB

23.5 dBm 937.87575150 kHz

RBW 30 kHz RF Att 40 dB

SWT 6 ms Unit dBm

10.5 dB Offset

D1 -0.48 dBm

D2 -20.48 dBm

1 [T1] -19.43 dBm

1 [T1] -2.21 dB

2.44055311 GHz

937.87575150 kHz



Center 2.441 GHz



200 kHz/

Span 2 MHz


Date: 12.JUL.2017 16:37:18

[illegible]


EDR ($\pi/4$ -DQPSK): Low ChannelEDR ($\pi/4$ -DQPSK): Middle Channel

EDR ($\pi/4$ -DQPSK): High Channel**EDR (8DPSK): Low Channel**

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa


The testing was performed by Poboo Li on 2017-07-12.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15


BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa


The testing was performed by Poboo Li on 2017-07-12.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following table and plots.

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.383	0.123	0.4	Pass
		Middle	0.389	0.124	0.4	Pass
		High	0.381	0.122	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	DH 3	Low	1.653	0.264	0.4	Pass
		Middle	1.653	0.264	0.4	Pass
		High	1.653	0.264	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	DH 5	Low	2.926	0.312	0.4	Pass
		Middle	2.936	0.313	0.4	Pass
		High	2.936	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR ($\pi/4$ -DQPSK)	2DH 1	Low	0.395	0.126	0.4	Pass
		Middle	0.399	0.128	0.4	Pass
		High	0.393	0.126	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	2DH 3	Low	1.653	0.264	0.4	Pass
		Middle	1.659	0.265	0.4	Pass
		High	1.659	0.265	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	2DH 5	Low	2.936	0.313	0.4	Pass
		Middle	2.936	0.313	0.4	Pass
		High	2.926	0.312	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR (8DPSK)	3DH 1	Low	0.391	0.125	0.4	Pass
		Middle	0.393	0.126	0.4	Pass
		High	0.395	0.126	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	3DH 3	Low	1.665	0.266	0.4	Pass
		Middle	1.677	0.268	0.4	Pass
		High	1.683	0.269	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	3DH 5	Low	2.926	0.312	0.4	Pass
		Middle	2.916	0.311	0.4	Pass
		High	2.946	0.314	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				

BDR (GFSK): Pulse time, Low Channel, DH1




Pulse time, Middle Channel, DH1




Ref Lvl 23.5 dBm
 Marker 1 [T1] -44.34 dBm
 RBW 1 MHz
 VBW 3 MHz
 RF Att 30 dB
 Unit dBm
 -20.641283 μ s
 SWT 3 ms
 10.5 dB Offset
 1 [T1] -44.34 dBm
 1 [T1] -20.641283 μ s
 1 [T1] 0.62 dB
 1 [T1] 1.653307 ms
 TR
 Center 2.402 GHz
 300 μ s/


Pulse time, Middle Channel, DH3




Pulse time, High Channel, DH3




Pulse time, Low Channel, DH5




Pulse time, Middle Channel, DH5



Pulse time, High Channel, DH5



EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1



Delta 1 [T1]

Ref Lvl 1.97 dB

23.5 dBm 398.797595 μ s

RBW 1 MHz RF Att 30 dB

VBW 3 MHz

SWT 1 ms Unit dBm

10.5 dB Offset

23.5

20

10

0

-10

-20

-30

-40

-50

-60

-70

-76.5

Center 2.441 GHz

100 μ s/

1 [T1] -49.38 dBm

1 [T1] -7.414830 μ s

1 [T1] 1.97 dB

398.797595 μ s

1MAX

1MA

TR

Date: 12.JUL.2017 17:07:35

Delta 1 [T1]

RBW 1 MHz RF Att 30 dB

Ref Lvl 0.46 dB VBW 3 MHz

23.5 dBm 392.785571 μ s SWT 1 ms Unit dBm

10.5 dB Offset

23.5

20

10

0

-10

-20

-30

-40

-50

-60

-70

-76.5

Center 2.48 GHz

100 μ s/

1 [T1] -48.54 dBm

1 [T1] -9.418838 μ s

1 [T1] 0.46 dB

1 [T1] 392.785571 μ s

TR

1MA

1A

1SGL

1TRG

1MAX

1MIN

1P1

1P2

1P3

1P4

1P5

1P6

1P7

1P8

1P9

1P10

1P11

1P12

1P13

1P14

1P15

1P16

1P17

1P18

1P19

1P20

1P21

1P22

1P23

1P24

1P25

1P26

1P27

1P28

1P29

1P30

1P31

1P32

1P33

1P34

1P35

1P36

1P37

1P38

1P39

1P40

1P41

1P42

1P43

1P44

1P45

1P46

1P47

1P48

1P49

1P50

1P51

1P52

1P53

1P54

1P55

1P56

1P57

1P58

1P59

1P60

1P61

1P62

1P63

1P64

1P65

1P66

1P67

1P68

1P69

1P70

1P71

1P72

1P73

1P74

1P75

1P76

1P77

1P78

1P79

1P80

1P81

1P82

1P83

1P84

1P85

1P86

1P87

1P88

1P89

1P90

1P91

1P92

1P93

1P94

1P95

1P96

1P97

1P98

1P99

1P100

1P101

1P102

1P103

1P104

1P105

1P106

1P107

1P108

1P109

1P110

1P111

1P112

1P113

1P114

1P115

1P116

1P117

1P118

1P119

1P120

1P121

1P122

1P123

1P124

1P125

1P126

1P127

1P128

1P129

1P130

1P131

1P132

1P133

1P134

1P135

1P136

1P137

1P138

1P139

1P140

1P141

1P142

1P143

1P144

1P145

1P146

1P147

1P148

1P149

1P150

1P151

1P152

1P153

1P154

1P155

1P156

1P157

1P158

1P159

1P160

1P161

1P162

1P163

1P164

1P165

1P166

1P167

1P168

1P169

1P170

1P171

1P172

1P173

1P174

1P175

1P176

1P177

1P178

1P179

1P180

1P181

1P182

1P183

1P184

1P185

1P186

1P187

1P188

1P189

1P190

1P191

1P192

1P193

1P194

1P195

1P196

1P197

1P198

1P199

1P200

1P201

1P202

1P203

1P204

1P205

1P206

1P207

1P208

1P209

1P210

1P211

1P212

1P213

1P214

1P215

1P216

1P217

1P218

1P219

1P220

1P221

1P222

1P223

1P224

1P225

1P226

1P227

1P228

1P229

1P230

1P231

1P232

1P233

1P234

1P235

1P236

1P237

1P238

1P239

1P240

1P241

1P242

1P243

1P244

1P245

1P246

1P247

1P248

1P249

1P250

1P251

1P252

1P253

1P254

1P255

1P256

1P257

1P258

1P259

1P260

1P261

1P262

1P263

1P264

1P265

1P266

1P267

1P268

1P269

1P270

1P271

1P272

1P273

1P274

1P275

1P276

1P277

1P278

1P279

1P280

1P281

1P282

1P283

1P284

1P285

1P286

1P287

1P288

1P289

1P290

1P291

1P292

1P293

1P294

1P295

1P296

1P297

1P298

1P299

1P300

1P301

1P302

1P303

1P304

1P305

1P306

1P307

1P308

1P309

1P310

1P311

1P312

1P313

1P314

1P315

1P316

1P317

1P318

1P319

1P320

1P321

1P322

1P323

1P324

1P325

1P326

1P327

1P328

1P329

1P330


1P331

1P332


1P333

1P334

Pulse time, Low Channel, 2DH3



Pulse time, Middle Channel, 2DH3



Marker 1 [T1]
 -44.81 dBm
 -20.641283 V/s
 1.659319 ms

RBW 1 MHz RF Att 30 dB
 VBW 3 MHz
 SWT 3 ms Unit dBm

Ref Lvl 23.5 dBm
 10.5 dB Offset

Center 2.48 GHz
 300 V/s

Date: 12.JUL.2017 17:11:57

Delta 1 [T1]

Ref Lvl -1.54 dB

23.5 dBm 2.935872 ms

RBW 1 MHz RF Att 30 dB

VBW 3 MHz

SWT 5 ms Unit dBm

10.5 dB Offset

-42.31 dBm

-37.875752 V/s

-1.54 dB


2.935872 ms

Center 2.402 GHz


500 V/s/

Date: 12.JUL.2017 17:14:57


Pulse time, Middle Channel, 2DH5




Pulse time, High Channel, 2DH5




EDR (8DPSK): Pulse time, Low Channel, 3DH1




Pulse time, Middle Channel, 3DH1




Pulse time, High Channel, 3DH1




Pulse time, Low Channel, 3DH3




Pulse time, Middle Channel, 3DH3




Pulse time, High Channel, 3DH3




Pulse time, Low Channel, 3DH5



Pulse time, Middle Channel, 3DH5



Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Poboo Li on 2017-07-12.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit (mW)
BDR (GFSK)	Low	2402	-0.39	0.91	1000
	Middle	2441	1.19	1.32	1000
	Middle	2480	0.14	1.03	1000
	High	2460	3.32	2.15	1000
EDR ($\pi/4$-DQPSK)	Low	2402	-1.30	0.74	1000
	Middle	2441	0.46	1.11	1000
	Middle	2480	-0.38	0.92	1000
	High	2460	2.40	1.74	1000
EDR (8DPSK)	Low	2402	-1.05	0.79	1000
	Middle	2441	0.89	1.23	1000
	Middle	2480	-0.31	0.93	1000
	High	2457	2.74	1.88	1000

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Poboo Li on 2017-07-12.


EUT operation mode: Transmitting



Test Result: Compliance. Please refer to following plots.

BDR (GFSK): Band Edge-Left Side




BDR (GFSK): Band Edge-Right Side




EDR ($\pi/4$ -DQPSK): Band Edge-Left Side**EDR ($\pi/4$ -DQPSK): Band Edge-Right Side**

EDR (8DPSK): Band Edge-Left Side



BDR (8DPSK): Band Edge-Right Side



***** END OF REPORT *****