



# FCC PART 15.247 TEST REPORT

For

**Shanghai LeXiang Technology Co., Ltd.**

Floor 6, Building 8, Yanjiaqiao Road, Pudong Area , Shanghai, China

**FCC ID: 2AJPQ-P1**

<b>Report Type:</b> Original Report	<b>Product Type:</b> DPVR Personal Cinema
<b>Test Engineer:</b> Max Min	
<b>Report Number:</b> RSHA180815008-00B	
<b>Report Date:</b> 2018-09-28	
<b>Reviewed By:</b> Oscar Ye RF Leader	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS.....</b>	<b>9</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>10</b>
<b>FCC§15.247 (i), §1.1310&amp; §2.1093 –RF EXPOSURE .....</b>	<b>11</b>
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
ANTENNA CONNECTOR CONSTRUCTION .....	13
<b>FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS.....</b>	<b>14</b>
APPLICABLE STANDARD .....	14
EUT SETUP .....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE .....	14
CORRECTED FACTOR & MARGIN CALCULATION .....	15
TEST RESULTS SUMMARY .....	15
TEST DATA .....	15
<b>FCC §15.205, §15.209 &amp; §15.247(d) - RADIATED EMISSIONS .....</b>	<b>18</b>
APPLICABLE STANDARD .....	18
EUT SETUP.....	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE .....	19
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	19
TEST RESULTS SUMMARY .....	19
TEST DATA .....	20
<b>FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST DATA .....	31
<b>FCC §15.247(a) (1) - 20 dB EMISSION BANDWIDTH .....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST DATA .....	37
<b>FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>43</b>
APPLICABLE STANDARD .....	43
TEST PROCEDURE .....	43

TEST DATA .....	43
<b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>46</b>
APPLICABLE STANDARD .....	46
TEST PROCEDURE .....	46
TEST DATA .....	46
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>62</b>
APPLICABLE STANDARD .....	62
TEST PROCEDURE .....	62
TEST DATA .....	62
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>68</b>
APPLICABLE STANDARD .....	68
TEST PROCEDURE .....	68
TEST DATA .....	68

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	Shanghai LeXiang Technology Co., Ltd.
Tested Model:	DPVR P1
Product Type:	DPVR Personal Cinema
Dimension:	212.5mm(L)*106.3mm(W)*133.3mm(H)
Power Supply:	DC 3.8V from Li-ion battery and DC 5.0V charging by adapter

#### Adapter Information:

Model: S010WU0500200

Input: AC 100-240V, 50/60Hz, 400mA

Output: DC 5.0V, 2000mA

*\*All measurement and test data in this report was gathered from production sample serial number: 20180815008.  
(Assigned by the BACL. The EUT supplied by the applicant was received on 2018-08-15)*

### Objective

This test report is prepared on behalf of *Shanghai LeXiang Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS and Part 15.407 NII submittals with FCC ID: 2AJPQ-P1.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

Channel list for Bluetooth

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

### EUT Exercise Software

RF test tool: Ampak RFTestTool

Power level: N/A (software default)

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Apple	Earphone	/	/

### External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.8	EUT	Adapter

## Block Diagram of Test Setup

For Conducted Emissions:




For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):

Turntable  
2m Diameter





**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §1.1310& §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test (Chamber 1#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
<b>Radiated Emission Test (Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-26	2019-08-25
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-26	2019-08-25
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band notch Filter	BRM50702	/	2018-08-05	2019-08-04
Narda	Attenuator/10dB	10dB	/	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
<b>RF Conducted Test</b>					
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2018-07-23	2019-07-22
Shanghai LeXiang	RF Cable	LeXiangC01	C01	Each Time	Each Time
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2017-11-12	2018-11-11
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.247 (i), §1.1310& §2.1093 –RF EXPOSURE**

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### **Measurement Result**

Mode	Frequency Range (MHz)	Target Output Power		Minimum test separation distance required for the exposure conditions (mm)
		(dBm)	(mW)	
BT3.0	2402-2480	6.0	3.98	5.00
BLE	2402-2480	3.0	2.00	5.00
2.4G Wi-Fi	2412-2462	9.7	9.33	5.00
5G Wi-Fi	5150-5250	3.4	2.19	5.00
	5725-5850	3.2	2.09	5.00

**Note:** 1. The target output power was declared by the manufacturer.

2. BT3.0, BLE, 2.4 GHz & 5 GHz Wi-Fi share a same antenna and can't transmit simultaneously.

**Result:**

**For BT3.0:** [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√ f(GHz)] =  $3.98/5 \cdot \sqrt{2.48} = 1.3 < 3.0$ .

**For BLE:** [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√ f(GHz)] =  $2.00/5 \cdot \sqrt{2.48} = 0.6 < 3.0$

**For 2.4G Wi-Fi:** [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√ f(GHz)] =  $9.33/5 \cdot \sqrt{2.462} = 2.9 < 3.0$

**For 5G Wi-Fi:** [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√ f(GHz)] =  $2.09/5 \cdot \sqrt{5.85} = 1.0 < 3.0$

**So the stand-alone SAR evaluation is not necessary.**

---

**FCC §15.203 - ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**Antenna Connector Construction**

The EUT has a FPC antenna for Bluetooth and the antenna gain is 2.79dBi, which uses a unique coupling to the intentional radiator; fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz - 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	23.4 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	101.1 kPa

*The testing was performed by Max Min on 2018-09-06.*


*EUT operation mode: Transmitting in low channel of 8DPSK mode (Worst case)*

## AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.170	51.23	QP	9.000	L1	16.04	64.96	13.73	Compliance
0.170	36.16	AV	9.000	L1	16.04	54.96	18.80	Compliance
0.295	40.89	QP	9.000	L1	16.03	60.38	19.49	Compliance
0.295	26.42	AV	9.000	L1	16.03	50.38	23.96	Compliance
0.545	34.22	QP	9.000	L1	16.05	56.00	21.78	Compliance
0.545	21.77	AV	9.000	L1	16.05	46.00	24.23	Compliance
0.920	29.15	QP	9.000	L1	15.90	56.00	26.85	Compliance
0.920	19.55	AV	9.000	L1	15.90	46.00	26.45	Compliance
11.950	38.96	QP	9.000	L1	16.12	60.00	21.04	Compliance
12.000	27.28	AV	9.000	L1	16.12	50.00	22.72	Compliance
21.400	37.85	QP	9.000	L1	16.45	60.00	22.15	Compliance
21.500	22.50	AV	9.000	L1	16.45	50.00	27.50	Compliance



**AC 120V/60 Hz, Neutral**

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	39.99	QP	9.000	N	16.06	66.00	26.01	Compliance
0.150	26.67	AV	9.000	N	16.06	56.00	29.33	Compliance
0.260	29.09	QP	9.000	N	16.06	61.43	32.34	Compliance
0.260	18.86	AV	9.000	N	16.06	51.43	32.57	Compliance
0.505	29.56	QP	9.000	N	16.11	56.00	26.44	Compliance
0.505	23.23	AV	9.000	N	16.11	46.00	22.77	Compliance
1.150	29.19	QP	9.000	N	15.94	56.00	26.81	Compliance
1.150	22.74	AV	9.000	N	15.94	46.00	23.26	Compliance
11.200	41.08	QP	9.000	N	15.99	60.00	18.92	Compliance
11.200	28.41	AV	9.000	N	15.99	50.00	21.59	Compliance
18.850	31.48	QP	9.000	N	16.13	60.00	28.52	Compliance
18.700	21.85	AV	9.000	N	16.12	50.00	28.15	Compliance



**Note:**

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) - Corrected Amplitude (dBμV)

**FCC §15.205, §15.209 & §15.247(d) - RADIATED EMISSIONS****Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

**EUT Setup****Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz - 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	23.3-24.4 °C
<b>Relative Humidity:</b>	49-50 %
<b>ATM Pressure:</b>	101.1-101.2 kPa

The testing was performed by Max Min on 2018-08-31 & 2018-09-16.

EUT operation mode: Transmitting

**Spurious Emission Test:****30MHz-1GHz:**

Pre-Scan with GFSK,  $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
45.368200	36.94	101.0	V	121.0	-14.4	40.00	3.06
45.844650	36.94	101.0	V	210.0	-14.7	40.00	3.06
74.955450	27.36	101.0	V	174.0	-17.5	40.00	12.64
83.612800	27.29	101.0	V	153.0	-17.7	40.00	12.71
139.408400	25.15	199.0	H	200.0	-11.9	43.50	18.35
150.190100	24.30	199.0	V	84.0	-12.3	43.50	19.20

**1GHz-18GHz:**


*Pre-Scan with GFSK,  $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded*

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)  
 Corrected Amplitude (dB $\mu$ V /m) = Corrected Factor (dB/m) + Reading (dB $\mu$ V)  
 Margin (dB) = Limit (dB $\mu$ V/m) - Corrected Amplitude (dB $\mu$ V /m)

**Low Channel: 2402MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1374.000000	37.73	---	100.0	H	127.0	-2.0	74.00	36.27
1374.000000	---	28.89	100.0	H	127.0	-2.0	54.00	25.11
3026.400000	44.42	---	100.0	V	107.0	6.1	74.00	29.58
3026.400000	---	33.86	100.0	V	107.0	6.1	54.00	20.14
4804.000000	---	37.91	200.0	V	85.0	10.7	54.00	16.09
4804.000000	46.97	---	200.0	V	85.0	10.7	74.00	27.03
7206.000000	---	42.30	100.0	V	246.0	15.2	54.00	11.70
7206.000000	51.49	---	100.0	V	246.0	15.2	74.00	22.51
10890.600000	---	45.78	250.0	V	304.0	18.8	54.00	8.22
10890.600000	56.11	---	250.0	V	304.0	18.8	74.00	17.89
17180.600000	---	45.34	150.0	V	112.0	18.2	54.00	8.66
17180.600000	55.43	---	150.0	V	112.0	18.2	74.00	18.57

**Middle Channel: 2441MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1520.200000	---	29.06	250.0	V	247.0	-1.1	54.00	24.94
1520.200000	39.42	---	250.0	V	247.0	-1.1	74.00	34.58
2842.800000	---	33.61	100.0	V	265.0	5.1	54.00	20.39
2842.800000	44.67	---	100.0	V	265.0	5.1	74.00	29.33
4882.000000	---	38.43	100.0	V	250.0	11.1	54.00	15.57
4882.000000	47.05	---	100.0	V	250.0	11.1	74.00	26.95
7323.000000	---	42.67	200.0	V	275.0	15.4	54.00	11.33
7323.000000	52.26	---	200.0	V	275.0	15.4	74.00	21.74
11036.800000	---	45.42	100.0	V	44.0	19.0	54.00	8.58
11036.800000	56.70	---	100.0	V	44.0	19.0	74.00	17.30
17442.400000	---	45.41	250.0	V	313.0	18.4	54.00	8.59
17442.400000	56.35	---	250.0	V	313.0	18.4	74.00	17.65

**High Channel: 2480MHz**


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	MaxPeak (dB $\mu$ V /m)	Average (dB $\mu$ V /m)	Height (cm)	Polar (H/V)				
1459.000000	---	28.22	200.0	V	112.0	-1.5	54.00	25.78
1459.000000	38.44	---	200.0	V	112.0	-1.5	74.00	35.56
3029.800000	---	35.15	100.0	V	216.0	6.1	54.00	18.85
3029.800000	45.11	---	100.0	V	216.0	6.1	74.00	28.89
4960.000000	---	38.91	250.0	V	333.0	11.5	54.00	15.09
4960.000000	48.11	---	250.0	V	333.0	11.5	74.00	25.89
7440.000000	---	43.02	200.0	V	284.0	15.6	54.00	10.98
7440.000000	52.93	---	200.0	V	284.0	15.6	74.00	21.07
10945.000000	---	46.36	100.0	V	4.0	18.9	54.00	7.64
10945.000000	56.01	---	100.0	V	4.0	18.9	74.00	17.99
16028.000000	---	44.91	200.0	H	50.0	18.3	54.00	9.09
16028.000000	55.46	---	200.0	H	50.0	18.3	74.00	18.54

**18GHz-25GHz:**

*Pre-Scan with GFSK,  $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded*

**Horizontal**

Date: 16.SEP.2018 17:40:11

**Vertical**

Date: 16.SEP.2018 18:00:55



**Fundamental Test & Restricted Bands Emissions:**

*Pre-Scan with GFSK,  $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded*


Note:

- Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)  
 Corrected Amplitude (dB $\mu$ V /m) = Corrected Factor (dB/m) + Reading (dB $\mu$ V)  
 Margin (dB) = Limit (dB $\mu$ V/m) - Corrected Amplitude (dB $\mu$ V /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	100.74	---	150.0	V	312.0	2.9	/	/
2402.000000	---	100.34	150.0	V	312.0	2.9	/	/
2402.000000	98.62	---	200.0	H	213.0	2.9	/	/
2402.000000	---	98.19	200.0	H	213.0	2.9	/	/
2390.000000	50.35	---	150.0	V	137.0	2.8	74.00	23.65
2390.000000	---	42.71	150.0	V	137.0	2.8	54.00	11.29
Middle Channel: 2441MHz								
2441.000000	99.77	---	150.0	V	94.0	3.0	/	/
2441.000000	---	99.36	150.0	V	94.0	3.0	/	/
2441.000000	97.66	---	200.0	H	189.0	3.0	/	/
2441.000000	---	97.23	200.0	H	189.0	3.0	/	/
High Channel: 2480MHz								
2480.000000	98.73	---	150.0	V	341.0	3.0	/	/
2480.000000	---	98.35	150.0	V	341.0	3.0	/	/
2480.000000	96.56	---	200.0	H	111.0	3.0	/	/
2480.000000	---	96.19	200.0	H	111.0	3.0	/	/
2483.500000	45.71	---	150.0	V	278.0	3.0	74.00	28.29
2483.500000	---	44.96	150.0	V	278.0	3.0	54.00	9.04


## Conducted Spurious Emissions at Antenna Port

### BDR (GFSK): Low Channel




Date: 31.AUG.2018 10:31:18

### BDR (GFSK): Middle Channel




Date: 31.AUG.2018 10:35:11

### BDR (GFSK): High Channel




Date: 31 AUG 2018 10:39:48

### EDR ( $\pi/4$ -DQPSK): Low Channel




Date: 31 AUG 2018 09:45:26

### EDR ( $\pi/4$ -DQPSK): Middle Channel




Date: 31 AUG 2018 09:41:16

### EDR ( $\pi/4$ -DQPSK): High Channel




Date: 31 AUG 2018 09:55:32

### EDR (8DPSK): Low Channel




Date: 31 AUG 2018 10:02:01

### EDR (8DPSK): Middle Channel



Date: 31 AUG 2018 10:07:08

# EDR (8DPSK): High Channel



Date: 31 AUG 2018 10:25:59

**FCC §15.247(a) (1) - CHANNEL SEPARATION TEST****Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

**Test Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW)  $\geq$  RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	23.4 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	101.1 kPa

*The testing was performed by Max Min on 2018-08-31.*


*EUT operation mode: Transmitting*

*Test Result: Compliance.*

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
<b>BDR (GFSK)</b>	Low	2402	0.999	$\geq 0.697$	Pass
	Adjacent	2403			
	Middle	2441	0.999	$\geq 0.697$	Pass
	Adjacent	2442			
	High	2480	0.999	$\geq 0.697$	Pass
	Adjacent	2479			
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	0.999	$\geq 0.906$	Pass
	Adjacent	2403			
	Middle	2441	0.999	$\geq 0.906$	Pass
	Adjacent	2442			
	High	2480	0.999	$\geq 0.903$	Pass
	Adjacent	2479			
<b>EDR (8DPSK)</b>	Low	2402	0.999	$\geq 0.886$	Pass
	Adjacent	2403			
	Middle	2441	0.999	$\geq 0.886$	Pass
	Adjacent	2442			
	High	2480	0.999	$\geq 0.883$	Pass
	Adjacent	2479			


Note: Limit = 20 dB bandwidth\*2/3

### BDR (GFSK): Low Channel






### BDR (GFSK): Middle Channel




Date: 31.AUG.2018 13:32:53

### BDR (GFSK): High Channel




Date: 31.AUG.2018 13:33:33


### EDR ( $\pi/4$ -DQPSK): Low Channel



### EDR ( $\pi/4$ -DQPSK): Middle Channel




### EDR ( $\pi/4$ -DQPSK): High Channel




Date: 31 AUG 2018 12:45:11

### EDR (8DPSK): Low Channel




Date: 31 AUG 2018 13:10:47

### EDR (8DPSK): Middle Channel



### EDR (8DPSK): High Channel



## **FCC §15.247(a) (1) - 20 dB EMISSION BANDWIDTH**

### **Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400 - 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	23.2 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.3 kPa


*The testing was performed by Max Min on 2018-08-31.*

*EUT operation mode: Transmitting*


*Test Result: Compliance.*

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
<b>BDR (GFSK)</b>	Low	2402	1.046
	Middle	2441	1.046
	High	2480	1.046
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	1.359
	Middle	2441	1.359
	High	2480	1.355
<b>EDR (8DPSK)</b>	Low	2402	1.329
	Middle	2441	1.329
	High	2480	1.324

**BDR (GFSK): Low Channel**


**BDR (GFSK): Middle Channel**

Date: 31 AUG 2018 10:34:06


**BDR (GFSK): High Channel**

Date: 31 AUG 2018 10:37:52


### EDR ( $\pi/4$ -DQPSK): Low Channel




### EDR( $\pi/4$ -DQPSK): Middle Channel






**EDR ( $\pi/4$ -DQPSK): High Channel**

Date: 31 AUG 2018 09:52:41


**EDR (8DPSK): Low Channel**

Date: 31 AUG 2018 09:59:19

### EDR (8DPSK): Middle Channel



### EDR (8DPSK): High Channel



**FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST****Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW  $\geq$  RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	23.2 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.3 kPa

*The testing was performed by Max Min on 2018-08-31.*

*EUT operation mode: Hopping*


*Test Result: Compliance.*

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400 - 2483.5	79	≥ 15
EDR ( $\pi/4$ -DQPSK)	2400 - 2483.5	79	≥ 15
EDR (8DPSK)	2400 - 2483.5	79	≥ 15


**BDR (GFSK): Number of Hopping Channels**

Date: 31 AUG 2018 13:35:29

### EDR ( $\pi/4$ -DQPSK): Number of Hopping Channels



### EDR (8DPSK): Number of Hopping Channels



**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**

---

**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

1 Span: Zero span, centered on a hopping channel.

2 RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\geq 1 / T$ , where T is the expected dwell time per channel.

3 Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4 Detector function: Peak.

5 Trace: Max hold.

**Test Data****Environmental Conditions**


<b>Temperature:</b>	23.4 °C
<b>Relative Humidity:</b>	51 %
<b>ATM Pressure:</b>	101.2 kPa

*The testing was performed by Max Min on 2018-08-31.*


*EUT operation mode: Hopping*

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.425	0.136	0.4	Pass
		Middle	0.425	0.136	0.4	Pass
		High	0.425	0.136	0.4	Pass
		Note: DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.935	0.313	0.4	Pass
		Middle	2.935	0.313	0.4	Pass
		High	2.935	0.313	0.4	Pass
		Note: DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ( $\pi/4$ -DQPSK)	2DH1	Low	0.43	0.138	0.4	Pass
		Middle	0.43	0.138	0.4	Pass
		High	0.43	0.138	0.4	Pass
		Note: 2DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: 2DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.946	0.314	0.4	Pass
		Middle	2.946	0.314	0.4	Pass
		High	2.946	0.314	0.4	Pass
		Note: 2DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.43	0.138	0.4	Pass
		Middle	0.43	0.138	0.4	Pass
		High	0.43	0.138	0.4	Pass
		Note: 3 DH1: Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: 3DH3: Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.946	0.314	0.4	Pass
		Middle	2.946	0.314	0.4	Pass
		High	2.946	0.314	0.4	Pass
		Note: 3DH5: Dwell time = Pulse time*(1600/6/79)*31.6S				

### BDR (GFSK): Pulse time, Low Channel, DH1




### BDR (GFSK): Pulse time, Middle Channel, DH1







### BDR (GFSK): Pulse time, High Channel, DH1




### BDR (GFSK): Pulse time, Low Channel, DH3




### BDR (GFSK): Pulse time, Middle Channel, DH3




### BDR (GFSK): Pulse time, High Channel, DH3







### BDR (GFSK): Pulse time, Low Channel, DH5




### BDR (GFSK): Pulse time, Middle Channel, DH5



**BDR (GFSK): Pulse time, High Channel, DH5****EDR ( $\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1**


**EDR ( $\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1****EDR ( $\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1**

### EDR ( $\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3







Date: 31 AUG 2018 13:55:46

### EDR ( $\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3




Date: 31 AUG 2018 13:55:19


**EDR ( $\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3****EDR ( $\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5**

**EDR ( $\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5****EDR ( $\pi/4$ -DQPSK): Pulse time, High Channel, 2DH5**




**EDR (8DPSK): Pulse time, Low Channel, 3DH1**

Date: 31 AUG 2018 13:17:58


**EDR (8DPSK): Pulse time, Middle Channel, 3DH1**

Date: 31 AUG 2018 13:18:41


### EDR (8DPSK): Pulse time, High Channel, 3DH1




### EDR (8DPSK): Pulse time, Low Channel, 3DH3




### EDR (8DPSK): Pulse time, Middle Channel, 3DH3




### EDR (8DPSK): Pulse time, High Channel, 3DH3




### EDR (8DPSK): Pulse time, Low Channel, 3DH5



### EDR (8DPSK): Pulse time, Middle Channel, 3DH5



**EDR (8DPSK): Pulse time, High Channel, 3DH5**



Date: 31 AUG 2018 14:10:34

## **FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**

### **Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### **Test Procedure**

- a. Use the following spectrum analyzer settings:
  - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
  - 2) RBW > 20 dB bandwidth of the emission being measured.
  - 3) VBW  $\geq$  RBW.
  - 4) Sweep: Auto.
  - 5) Detector function: Peak.
  - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	23.2 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.2 kPa

*The testing was performed by Max Min on 2018-08-31 & 2018-09-28.*

*EUT operation mode: Transmitting*


*Test Result: Compliance.*

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
<b>BDR (GFSK)</b>	2402	4.57	2.86	≤ 125
	2441	4.13	2.59	≤ 125
	2480	3.44	2.21	≤ 125
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	2402	5.47	3.52	≤ 125
	2441	4.71	2.96	≤ 125
	2480	4.22	2.64	≤ 125
<b>EDR (8DPSK)</b>	2402	5.97	3.95	≤ 125
	2441	5.23	3.33	≤ 125
	2480	4.75	2.99	≤ 125


**BDR (GFSK): 2402MHz**

Date: 28 SEP 2018 20:38:01

### BDR (GFSK): 2441MHz




### BDR (GFSK): 2480MHz






**EDR( $\pi/4$ -DQPSK): 2402MHz**




Date: 31 AUG 2018 09:25:02

**EDR( $\pi/4$ -DQPSK): 2441MHz**




Date: 31 AUG 2018 09:31:47


### EDR( $\pi/4$ -DQPSK): 2480MHz




### EDR(8DPSK): 2402MHz



### EDR(8DPSK): 2441MHz



### EDR(8DPSK): 2480MHz



## **FCC §15.247(d) - BAND EDGES TESTING**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	23.2 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.3 kPa


*The testing was performed by Max Min on 2018-08-31.*

*EUT operation mode: Transmitting & Hopping*

*Test Result: Compliance.*


# Band Edge

## BDR (GFSK): Left Side




Date: 31 AUG 2018 10:29:48


## BDR (GFSK): Right Side



Date: 31 AUG 2018 10:38:55


EDR ( $\pi/4$ -DQPSK): Left Side

Date: 31 AUG 2018 09:28:23


EDR ( $\pi/4$ -DQPSK): Right Side

Date: 31 AUG 2018 09:54:10


### EDR (8DPSK): Left Side




### EDR (8DPSK): Right Side



### BDR (GFSK): Left Side - Hopping




### BDR (GFSK): Right Side- Hopping







### EDR ( $\pi/4$ -DQPSK): Left Side- Hopping




### EDR ( $\pi/4$ -DQPSK): Right Side- Hopping



### EDR (8DPSK): Left Side - Hopping



### EDR (8DPSK): Right Side - Hopping



\*\*\*\*\* END OF REPORT \*\*\*\*\*