

FCC PART 15.407



TEST REPORT

For

Shanghai LeXiang Technology Co., Ltd.

Floor 6,Building 8,Yanjiaqiao Road,Pudong Area ,Shanghai ,China

FCC ID: 2AJPQ-P1PRO

Report Type: Original Report		Product Type: DPVR VR All-in-one Headset	
Test Engineer:	Max Min		
Report Number:	RSHA190130005-00D		
Report Date:	2019-03-22		
Reviewed By:	Oscar Ye RF Leader		
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn		

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	21
SUPPORT EQUIPMENT LIST AND DETAILS	21
EXTERNAL I/O CABLE.....	21
BLOCK DIAGRAM OF TEST SETUP	21
SUMMARY OF TEST RESULTS	23
TEST EQUIPMENT LIST	24
§1.1310 & §2.1093 –RF EXPOSURE	26
FCC §15.203 – ANTENNA REQUIREMENT	28
APPLICABLE STANDARD	28
ANTENNA CONNECTOR CONSTRUCTION	28
FCC §15.407 (b) (6) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS	29
APPLICABLE STANDARD	29
EUT SETUP	29
EMI TEST RECEIVER SETUP.....	29
TEST PROCEDURE	30
CORRECTED FACTOR & MARGIN CALCULATION	30
TEST RESULTS SUMMARY	30
TEST DATA	30
§15.205 & §15.209 & §15.407(B) (1),(6),(7) – UNDESIRABLE EMISSION & RESTRICTED BANDS.....	33
APPLICABLE STANDARD	33
EUT SETUP	33
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	35
TEST PROCEDURE	35
CORRECTED AMPLITUDE & MARGIN CALCULATION	35
TEST DATA	36
FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH.....	88
APPLICABLE STANDARD	88
TEST PROCEDURE	88
TEST DATA	89
FCC §15.407(a) (1) – CONDUCTED TRANSMITTER OUTPUT POWER.....	133
APPLICABLE STANDARD	133
TEST PROCEDURE	133
TEST DATA	133
FCC §15.407(a) (1) (5) - POWER SPECTRAL DENSITY	135

APPLICABLE STANDARD	135
TEST PROCEDURE	135
TEST DATA	135

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Shanghai LeXiang Technology Co., Ltd.
Tested Model	DPVR P1 PRO
Product Type	DPVR VR All-in-one Headset
Dimension	212.5mm(L)*106.3mm(W)*133.3mm(H)
Power Supply	DC 3.8V from battery and DC 5.0V charging by Adapter

**All measurement and test data in this report was gathered from production sample serial number: 20190130005.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2019-01-30)*

Objective

This type approval report is prepared on behalf of Shanghai LeXiang Technology Co., Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, FCC Part 15.247 DTS submissions with FCC ID: 2AJPQ-P1PRO.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan).

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

In **5150~5250 MHz** band, test channel list is as below,

802.11a/802.11ac20/n20 mode Channel 36, 40, 48 were tested.

802.11n40/802.11ac40 mode Channel 38, 46 were tested.

802.11ac80 mode Channel 42 was tested

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 5725~5850 MHz band,

802.11a/802.11ac20/n20 mode Channel 149, 157, 165 were tested.

802.11n40/802.11ac40 mode Channel 151, 159 were tested.

802.11ac80 mode Channel 155 was tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
155	5775	/	/
157	5785	/	/

For Conducted Test:

802.11a: each transmit chains were tested

802.11ac: each transmit chains were tested

802.11n: each transmit chains were tested

For Radiated Test:

For 802.11a: SISO for each transmit chain

For 802.11ac: MIMO for two transmit chains

For 802.11n: MIMO for two transmit chains

EUT Exercise Software

RF test tool: QRCT


The worst case was performed under:

Mode	Data rate	Power level	
		5150-5250 Band	5725-5850 Band
802.11a	6 Mbps	6	6
802.11ac20	MCS0	5	5
802.11n-HT20	MCS0	5	5
802.11ac40	MCS0	5	5
802.11n-HT40	MCS0	5	5
802.11ac80	MCS0	5	5


Duty Cycle

5150MHz-5250MHz Band-chain0:


802.11a mode




802.11ac20 mode




802.11n-HT20 mode




802.11 ac40 mode



802.11n-HT40 mode




802.11 ac80 mode




5150MHz-5250MHz Band-chain1:

802.11a mode



802.11ac20 mode




Marker 1 [T1]
 Ref Lvl 10.58 dBm RBW 10 MHz RF Att 20 dB
 20 dBm 14.629259 ms SWT 100 ms Unit dBm

10.5 dB Offset
 1
 10.58 dBm
 14.629259 ms


Center 5.19 GHz 10 ms/

Date: 6.MAR.2019 17:17:44

802.11n-HT40 mode




802.11 ac80 mode




5725MHz-5850MHz Band-chain0:


802.11a mode




802.11ac20 mode




802.11n-HT20 mode




802.11 ac40 mode



802.11n-HT40 mode




802.11n- ac80 mode




5725MHz-5850MHz Band-chain1:


802.11a mode




802.11ac20 mode




802.11n-HT20 mode




802.11 ac40 mode



802.11n-HT40 mode



802.11n- ac80 mode



Mode	Frequency Range (MHz)	Duty Cycle (%)	T (ms)	1/T (kHz)	10log(1/x)
802.11a	5150-5250	100	/	/	0
802.11ac20		100	/	/	0
802.11n-HT20		100	/	/	0
802.11ac40		100	/	/	0
802.11n-HT40		100	/	/	0
802.11ac80		100	/	/	0
802.11a	5725-5850	100	/	/	0
802.11ac20		100	/	/	0
802.11n-HT20		100	/	/	0
802.11ac40		100	/	/	0
802.11n-HT40		100	/	/	0
802.11ac80		100	/	/	0

Note: “x” means duty cycle.

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
HUAWEI	Earphone	AM116	/

External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.8	Adapter	EUT

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
FCC §15.207 & §15.407(b) (6)	AC Power Line Conducted Emissions	Compliant
§15.205 & §15.209 & §15.407(b) (1) ,(6) ,(7)	Undesirable Emission & Restricted Bands	Compliant
§15.407(a)(1) (5) & §15.407 (e)	Emission Bandwidth	Compliant
§15.407 (a)(1) (3)	Conducted Transmitter Output Power	Compliant
§15.407 (a)(1) (3)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-12	2019-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-27	2019-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2019-01-11	2022-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band Reject Filter	BRC50703	G094	2018-08-05	2019-08-04
MICRO-TRONICS	Band Reject Filter	BRC50705	G085	2018-08-05	2019-08-04
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-12	2019-11-11
Agilent	Power Meter	N1912A	MY5000492	2018-11-18	2019-11-17
Agilent	Power Sensor	N1921A	MY54210024	2018-11-18	2019-11-17
Narda	Attenuator/10dB	10dB	/	2019-01-10	2020-01-09
BACL	Temperature & Humidity Chamber	BTH-150	30023	2018-07-20	2019-07-19
EAST	Regulated DC Power Supply	MCH-303D-II	14070562	2018-07-20	2019-07-19
LeXiang	RF Cable	LeXiang C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2018-11-12	2019-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2018-11-12	2019-11-11
BACL	Auto test Software	BACL-EMC	CE001	N/A	N/A
Narda	Attenuator/6dB	10690812-2	26850-6	2019-01-10	2020-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

§1.1310 & §2.1093 – RF EXPOSURE

Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Measurement Result

For worst case

Mode	Frequency Range (MHz)	Frequency (MHz)	Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g)	SAR Test Exclusion
			(dBm)	(mW)				
Bluetooth	2402-2480	2480	2.00	1.58	5.00	0.50	3.00	Yes
BLE	2402-2480	2480	4.00	2.51	5.00	0.79	3.00	Yes
802.11b	2412~2462	2462	9.50	8.91	5.00	2.80	3.00	Yes
802.11g	2412~2462	2462	5.50	3.55	5.00	1.11	3.00	Yes
802.11n20	2412~2462	2462	8.00	6.31	5.00	1.98	3.00	Yes
802.11a	5150~5250	5250	6.00	3.98	5.00	1.82	3.00	Yes
	5725~5850	5850	6.50	4.47	5.00	2.16	3.00	Yes
802.11ac20	5150~5250	5250	6.50	4.47	5.00	2.05	3.00	Yes
	5725~5850	5850	7.00	5.01	5.00	2.42	3.00	Yes
802.11n20	5150~5250	5250	7.50	5.62	5.00	2.58	3.00	Yes
	5725~5850	5850	7.90	6.17	5.00	2.98	3.00	Yes
802.11ac40	5150~5250	5250	6.50	4.47	5.00	2.05	3.00	Yes
	5725~5850	5850	7.00	5.01	5.00	2.42	3.00	Yes
802.11n40	5150~5250	5250	7.50	5.62	5.00	2.58	3.00	Yes
	5725~5850	5850	7.90	6.17	5.00	2.98	3.00	Yes
802.11ac80	5210	5210	7.00	5.01	5.00	2.29	3.00	Yes
	5775	5775	7.00	5.01	5.00	2.41	3.00	Yes

Note: 1. The tune-up output power was declared by the manufacturer.

2. Bluetooth, BLE, 2.4 GHz & 5 GHz Wi-Fi can't transmit simultaneously.

3. For 802.11b, 802.11g, 802.11a, the Tune-up power is based on SISO mode

For 802.11n20/ac20/n40/ac40/ac80, the Tune-up power is based on MIMO mode

So the stand-alone SAR evaluation is not necessary

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407, if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has two FPC antennas for 5G Wi-Fi which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.

Chain	Antenna Type	Max. Antenna Gain
0	FPC	2.13 dBi
1	FPC	2.13 dBi


Result: Compliant.

FCC §15.407 (b) (6) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	20.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa


The testing was performed by Max Min on 2019-03-06.

EUT operation mode: Transmitting in 802.11n-HT20 mode middle channel of 5725-5850MHz (worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.160	34.75	QP	9.000	L1	16.06	65.46	30.71	Compliance
0.160	20.55	AV	9.000	L1	16.06	55.46	34.91	Compliance
0.545	36.42	QP	9.000	L1	16.08	56.00	19.58	Compliance
0.545	24.51	AV	9.000	L1	16.08	46.00	21.49	Compliance
1.100	29.49	QP	9.000	L1	15.94	56.00	26.51	Compliance
1.100	18.34	AV	9.000	L1	15.94	46.00	27.66	Compliance
3.300	27.64	QP	9.000	L1	15.89	56.00	28.36	Compliance
3.300	16.67	AV	9.000	L1	15.89	46.00	29.33	Compliance
10.900	40.17	QP	9.000	L1	15.99	60.00	19.83	Compliance
10.900	28.32	AV	9.000	L1	15.99	50.00	21.68	Compliance
17.000	32.79	QP	9.000	L1	16.07	60.00	27.21	Compliance
17.000	21.57	AV	9.000	L1	16.07	50.00	28.43	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	39.65	PK	9.000	N	16.06	66.00	26.35	Compliance
0.150	25.13	AV	9.000	N	16.06	56.00	30.87	Compliance
0.190	36.41	PK	9.000	N	16.05	64.04	27.63	Compliance
0.190	20.22	AV	9.000	N	16.05	54.04	33.82	Compliance
0.570	36.91	PK	9.000	N	16.07	56.00	19.09	Compliance
0.570	28.48	AV	9.000	N	16.07	46.00	17.52	Compliance
0.915	29.81	PK	9.000	N	15.95	56.00	26.19	Compliance
0.915	21.40	AV	9.000	N	15.95	46.00	24.60	Compliance
11.950	34.46	PK	9.000	N	16.00	60.00	25.54	Compliance
11.950	24.23	AV	9.000	N	16.00	50.00	25.77	Compliance
22.000	32.74	PK	9.000	N	16.19	60.00	27.26	Compliance
22.000	20.30	AV	9.000	N	16.19	50.00	29.70	Compliance

Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

§15.205 & §15.209 & §15.407(B) (1),(6),(7) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Applicable Standard

FCC §15.407 (b) (1), (6), (7); §15.209; §15.205;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27dBm/MHz


For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000MHz shall be performed using a minimum resolution bandwidth of 1MHz.


According to 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E \text{ [dB}\mu\text{V/m]} = \text{EIRP [dBm]} + 95.2$, for $d = 3$ meters.

EUT Setup

Below 1 GHz:



1 GHz-40GHz:



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Extrapolation result}$$

Test Data**Environmental Conditions**


Temperature:	20.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2019-03-20.

Test Mode: Transmitting

Spurious Emission Test**30MHz-1GHz(5150-5250MHz Band):**


Pre-scan with 802.11a, 802.11a c20, 802.11n-HT20, 802.11a c40, 802.11n-HT40 and 802.11 a c80 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in channel 5180 in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
43.830150	32.43	101.0	V	175.0	-13.3	40.00	7.57
81.303850	23.87	101.0	V	134.0	-17.7	40.00	16.13
134.086350	25.69	101.0	V	245.0	-11.7	43.50	17.81
150.743000	23.04	101.0	V	245.0	-12.4	43.50	20.46
189.776600	27.33	101.0	V	200.0	-13.0	43.50	16.17
239.290600	15.78	101.0	V	235.0	-12.1	46.00	30.22

30MHz-1GHz(5725-5850MHz Band):

Pre-scan with 802.11a and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case 802.11a mode in channel 5745 in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
33.733250	25.19	101.0	V	145.0	-6.5	40.00	14.81
44.906050	32.80	101.0	V	217.0	-14.1	40.00	7.20
80.583750	21.86	199.0	V	199.0	-17.8	40.00	18.14
134.517650	25.43	101.0	V	212.0	-11.8	43.50	18.07
185.983300	27.19	101.0	V	186.0	-13.2	43.50	16.31
196.081750	26.74	101.0	V	197.0	-12.6	43.50	16.76

1GHz-18GHz (5150-5250MHz Band):**802.11a Mode(chain0):**


(Pre-scan in the X, Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1731.000000	37.48	---	150.0	V	230.0	-9.1	68.20	30.72
3454.800000	47.19	---	150.0	V	242.0	-3.6	68.20	21.02
5518.600000	45.99	---	150.0	V	230.0	1.4	68.20	22.21
7762.600000	48.90	---	150.0	H	73.0	6.6	68.20	19.30
10360.000000	47.46	---	150.0	H	216.0	8.8	68.20	20.74
15540.400000	---	41.45	150.0	H	191.0	11.2	54.00	12.55
15540.400000	52.00	---	150.0	H	191.0	11.2	74.00	22.00

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1591.600000	---	27.11	150.0	V	339.0	-9.6	54.00	26.89
1591.600000	38.95	---	150.0	V	339.0	-9.6	74.00	35.05
5549.200000	45.04	---	150.0	V	232.0	1.5	68.20	23.16
7715.000000	---	38.27	150.0	H	232.0	6.5	54.00	15.73
7715.000000	49.01	---	150.0	H	232.0	6.5	74.00	24.99
10400.000000	46.43	---	150.0	H	150.0	8.8	68.20	21.77
15600.000000	---	40.11	150.0	H	221.0	11.2	54.00	13.89
15600.000000	50.70	---	150.0	H	221.0	11.2	74.00	23.30

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1635.800000	39.29	---	150.0	V	3.0	-9.5	68.20	28.91
3454.800000	46.61	---	150.0	V	241.0	-3.6	68.20	21.59
5528.800000	45.78	---	150.0	V	159.0	1.5	68.20	22.42
7721.800000	---	40.43	150.0	V	241.0	6.5	54.00	13.57
7721.800000	47.99	---	150.0	V	241.0	6.5	74.00	26.01
10480.000000	47.81	---	150.0	V	148.0	8.9	68.20	20.39
15720.000000	---	39.82	150.0	H	283.0	11.3	54.00	14.18
15720.000000	49.40	---	150.0	H	283.0	11.3	74.00	24.60

802.11a Mode(chain1):


(Pre-scan in the X, Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1656.200000	37.68	---	150.0	V	220.0	-9.4	68.20	30.52
3454.800000	46.08	---	150.0	V	244.0	-3.6	68.20	22.12
5552.600000	44.45	---	150.0	H	320.0	1.5	68.20	23.75
6905.800000	49.28	---	150.0	V	220.0	5.2	68.20	18.92
10360.000000	48.99	---	150.0	V	33.0	8.8	68.20	19.21
15540.000000	---	41.56	150.0	V	138.0	11.2	54.00	12.44
15540.000000	50.09	---	150.0	V	138.0	11.2	74.00	23.91

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1625.600000	38.76	---	150.0	V	127.0	-9.5	68.20	29.44
3454.800000	45.81	---	150.0	V	246.0	-3.6	68.20	22.39
5528.800000	43.65	---	150.0	V	329.0	1.5	68.20	24.55
6933.000000	50.34	---	150.0	H	170.0	5.2	68.20	17.86
10400.000000	48.30	---	150.0	V	187.0	8.8	68.20	19.90
15600.000000	---	40.21	150.0	H	281.0	11.3	54.00	13.79
15600.000000	51.99	---	150.0	H	281.0	11.3	74.00	22.01

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1731.000000	36.18	---	150.0	V	293.0	-9.1	68.20	32.02
3454.800000	46.84	---	150.0	V	246.0	-3.6	68.20	21.36
5617.200000	44.53	---	150.0	V	293.0	1.6	68.20	23.67
6987.400000	50.04	---	150.0	V	235.0	5.3	68.20	18.16
10480.000000	46.90	---	150.0	V	1.0	9.0	68.20	21.30
15720.000000	---	40.93	150.0	V	121.0	11.3	54.00	13.07
15720.000000	49.74	---	150.0	V	121.0	11.3	74.00	24.26

802.11ac20 Mode(chain0+chain1):


(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1727.600000	38.33	---	150.0	V	293.0	-9.2	68.20	29.87
3454.800000	45.42	---	150.0	V	242.0	-3.6	68.20	22.78
5518.600000	44.77	---	150.0	V	23.0	1.4	68.20	23.43
6905.800000	50.88	---	150.0	V	218.0	5.2	68.20	17.32
10360.000000	49.10	---	150.0	H	0.0	8.8	68.20	19.10
15540.000000	---	41.96	150.0	V	230.0	11.2	54.00	12.04
15540.000000	51.06	---	150.0	V	230.0	11.2	74.00	22.94

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1656.200000	36.59	---	150.0	V	216.0	-9.4	68.20	31.61
3454.800000	45.71	---	150.0	V	240.0	-3.6	68.20	22.49
5760.000000	45.55	---	150.0	V	52.0	1.9	68.20	22.65
6933.000000	48.76	---	150.0	V	216.0	5.2	68.20	19.44
10400.000000	47.18	---	150.0	H	329.0	8.8	68.20	21.02
15600.000000	---	41.13	150.0	V	40.0	11.2	54.00	12.87
15600.000000	49.33	---	150.0	V	40.0	11.2	74.00	24.67

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1731.000000	38.44	---	150.0	V	251.0	-9.1	68.20	29.76
3454.800000	45.79	---	150.0	V	239.0	-3.6	68.20	22.41
5610.400000	45.00	---	150.0	V	16.0	1.6	68.20	23.20
6987.400000	49.13	---	150.0	V	215.0	5.3	68.20	19.07
10480.000000	46.71	---	150.0	H	276.0	8.9	68.20	21.49
15720.000000	---	40.25	150.0	H	216.0	11.3	54.00	13.75
15720.000000	49.31	---	150.0	H	216.0	11.3	74.00	24.69

802.11n-HT20 Mode(chain0+chain1):


Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5180MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1805.800000	38.30	---	150.0	V	1.0	-8.9	68.20	29.90
3454.800000	44.60	---	150.0	V	244.0	-3.6	68.20	23.60
5763.400000	44.89	---	150.0	V	173.0	1.9	68.20	23.31
6905.800000	49.23	---	150.0	V	220.0	5.2	68.20	18.97
10360.000000	47.86	---	150.0	V	80.0	8.8	68.20	20.34
15540.000000	---	40.38	150.0	H	304.0	11.2	54.00	13.62
15540.000000	48.90	---	150.0	H	304.0	11.2	74.00	25.10

Middle Channel: 5200MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1724.200000	36.25	---	150.0	V	292.0	-9.2	68.20	31.95
3454.800000	45.47	---	150.0	V	238.0	-3.6	68.20	22.73
5664.800000	45.28	---	150.0	V	279.0	1.7	68.20	22.92
6933.000000	48.47	---	150.0	H	169.0	5.2	68.20	19.73
10400.000000	46.66	---	150.0	V	213.0	8.8	68.20	21.54
15600.000000	---	39.61	150.0	V	7.0	11.2	54.00	14.39
15600.000000	50.82	---	150.0	V	7.0	11.2	74.00	23.18

High Channel: 5240MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1724.200000	36.99	---	150.0	V	256.0	-9.2	68.20	31.21
3454.800000	45.67	---	150.0	V	244.0	-3.6	68.20	22.53
5756.600000	46.57	---	150.0	V	185.0	1.9	68.20	21.63
7412.400000	---	37.44	150.0	V	1.0	6.0	54.00	16.56
7412.400000	47.87	---	150.0	V	1.0	6.0	74.00	26.13
10480.000000	48.37	---	150.0	H	116.0	9.0	68.20	19.83
15720.000000	---	40.31	150.0	V	11.0	11.3	54.00	13.69
15720.000000	49.33	---	150.0	V	11.0	11.3	74.00	24.67

802.11ac40 Mode(chain0+chain1):


(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5190MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1625.600000	40.68	---	150.0	V	346.0	-9.5	68.20	27.52
2128.800000	46.80	---	150.0	H	269.0	-7.9	68.20	21.40
3454.800000	46.88	---	150.0	V	241.0	-3.6	68.20	21.32
6919.400000	48.44	---	150.0	V	216.0	5.2	68.20	19.76
10380.000000	46.51	---	150.0	H	22.0	8.8	68.20	21.69
15570.000000	---	39.86	150.0	V	204.0	11.2	54.00	14.14
15570.000000	48.97	---	150.0	V	204.0	11.2	74.00	25.03

High Channel: 5230MHz- chain0+chain1

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1595.000000	40.40	---	150.0	V	338.0	-9.6	74.00	33.60
1595.000000	---	27.32	150.0	V	338.0	-9.6	54.00	26.68
3454.800000	45.58	---	150.0	V	238.0	-3.6	68.20	22.62
5705.600000	45.11	---	150.0	V	316.0	1.8	68.20	23.09
6973.800000	49.06	---	150.0	V	214.0	5.3	68.20	19.14
10460.000000	46.44	---	150.0	H	0.0	8.9	68.20	21.76
15690.000000	---	39.95	150.0	H	211.0	11.3	54.00	14.05
15690.000000	48.94	---	150.0	H	211.0	11.3	74.00	25.06

802.11n-HT40 Mode(chain0+chain1):


Pre-scan with X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5190MHz- chain0+chain1


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1646.000000	38.60	---	150.0	V	347.0	-9.4	74.00	35.40
1646.000000	---	25.49	150.0	V	347.0	-9.4	54.00	28.51
3454.800000	46.17	---	150.0	V	238.0	-3.6	68.20	22.03
5528.800000	44.25	---	150.0	V	226.0	1.5	68.20	23.95
6919.400000	48.64	---	150.0	H	215.0	5.2	68.20	19.56
10380.000000	47.48	---	150.0	H	145.0	8.8	68.20	20.72
15570.000000	---	40.23	150.0	V	166.0	11.2	54.00	13.77
15570.000000	49.07	---	150.0	V	166.0	11.2	74.00	24.93

High Channel: 5230MHz- chain0+chain1

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1799.000000	40.68	---	150.0	V	353.0	-8.9	68.20	27.52
3454.800000	46.32	---	150.0	V	244.0	-3.6	68.20	21.88
5569.600000	44.86	---	150.0	V	90.0	1.5	68.20	23.34
6973.800000	49.85	---	150.0	H	152.0	5.3	68.20	18.35
10460.000000	46.41	---	150.0	V	0.0	8.9	68.20	21.79
15690.000000	---	39.44	150.0	H	0.0	11.3	54.00	14.56
15690.000000	48.62	---	150.0	H	0.0	11.3	74.00	25.38

5725-5850MHz Band:**1GHz-18GHz:****802.11a Mode(chain0):**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1805.800000	40.08	---	150.0	V	225.0	-8.9	68.20	28.12
2128.800000	46.36	---	150.0	V	1.0	-7.9	68.20	21.84
3454.800000	45.66	---	150.0	V	237.0	-3.6	68.20	22.54
7347.800000	---	37.80	150.0	V	155.0	5.9	54.00	16.20
7347.800000	48.62	---	150.0	V	155.0	5.9	74.00	25.38
11490.000000	---	37.89	150.0	H	321.0	9.8	54.00	16.11
11490.000000	46.34	---	150.0	H	321.0	9.8	74.00	27.66
17235.000000	50.37	---	150.0	H	24.0	12.9	68.20	17.83

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1724.200000	37.04	---	150.0	V	238.0	-9.2	68.20	31.16
3454.800000	45.39	---	150.0	V	238.0	-3.6	68.20	22.81
5226.200000	44.33	---	150.0	V	238.0	0.5	68.20	23.87
8044.800000	48.82	---	150.0	H	167.0	7.0	68.20	19.38
11570.000000	---	37.55	150.0	V	1.0	9.8	54.00	31.16
11570.000000	46.11	---	150.0	V	1.0	9.8	74.00	27.89
17355.000000	51.68	---	150.0	V	86.0	13.6	68.20	16.52

High Channel: 5825MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1727.600000	36.16	---	150.0	V	249.0	-9.2	68.20	32.04
3454.800000	44.68	---	150.0	V	238.0	-3.6	68.20	23.52
5525.400000	45.09	---	150.0	V	20.0	1.5	68.20	23.11
8799.600000	48.88	---	150.0	V	20.0	7.1	68.20	19.32
11650.000000	48.54	---	150.0	H	221.0	9.9	74.00	25.46
11650.000000	---	39.07	150.0	H	221.0	9.9	54.00	14.93
17475.000000	51.21	---	150.0	V	11.0	14.1	68.20	16.99

802.11a Mode(chain1):

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:


1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1724.200000	37.31	---	150.0	V	240.0	-9.2	68.20	30.89
3454.800000	45.15	---	150.0	V	240.0	-3.6	68.20	23.05
6586.200000	47.25	---	150.0	H	169.0	4.6	68.20	20.95
8976.400000	49.25	---	150.0	V	75.0	7.6	68.20	18.95
11490.000000	---	37.91	150.0	H	354.0	9.8	54.00	16.09
11490.000000	48.52	---	150.0	H	354.0	9.8	74.00	25.48
17235.000000	50.41	---	150.0	H	354.0	12.9	68.20	17.79

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1727.600000	37.95	---	150.0	V	249.0	-9.2	68.20	30.25
2128.800000	44.58	---	150.0	V	202.0	-7.9	68.20	23.62
3454.800000	46.12	---	150.0	V	237.0	-3.6	68.20	22.08
6283.600000	47.27	---	150.0	V	13.0	3.5	68.20	20.93
11570.000000	---	38.06	150.0	H	341.0	9.8	54.00	15.94
11570.000000	47.21	---	150.0	H	341.0	9.8	74.00	26.79
17355.000000	50.38	---	150.0	V	13.0	13.5	68.20	17.82

High Channel: 5825MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1571.200000	---	27.60	150.0	V	339.0	-9.7	54.00	26.40
1571.200000	40.20	---	150.0	V	339.0	-9.7	74.00	33.80
2125.400000	39.85	---	150.0	V	19.0	-7.9	68.20	28.35
3454.800000	47.50	---	150.0	V	246.0	-3.6	68.20	20.70
6661.000000	47.06	---	150.0	V	19.0	4.7	68.20	21.14
11650.000000	---	39.89	150.0	V	294.0	9.9	54.00	14.11
11650.000000	48.47	---	150.0	V	294.0	9.9	74.00	25.53
17475.000000	51.74	---	150.0	V	30.0	14.1	68.20	16.46

802.11ac20 Mode(chain0+chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	26.09	150.0	V	338.0	-9.6	54.00	27.91
1595.000000	38.86	---	150.0	V	338.0	-9.6	74.00	35.14
3454.800000	45.74	---	150.0	V	240.0	-3.6	68.20	22.46
5413.200000	---	34.03	150.0	V	205.0	1.1	54.00	19.97
5413.200000	44.70	---	150.0	V	205.0	1.1	74.00	29.30
7721.800000	---	38.34	150.0	V	317.0	6.5	54.00	15.66
7721.800000	49.02	---	150.0	V	317.0	6.5	74.00	24.98
11490.000000	---	37.74	150.0	H	142.0	9.8	54.00	16.26
11490.000000	46.89	---	150.0	H	142.0	9.8	74.00	27.11
17235.000000	50.04	---	150.0	V	99.0	12.9	68.20	18.16

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1819.400000	41.08	---	150.0	V	228.0	-8.9	68.20	27.12
3454.800000	45.71	---	150.0	V	240.0	-3.6	68.20	22.49
6110.200000	47.22	---	150.0	V	182.0	2.8	68.20	20.98
8095.800000	---	38.40	150.0	H	355.0	6.9	54.00	15.60
8095.800000	48.91	---	150.0	H	291.0	6.9	74.00	25.09
11570.000000	---	37.69	150.0	H	359.0	9.8	54.00	16.31
11570.000000	46.48	---	150.0	H	359.0	9.8	74.00	27.52
17355.000000	50.90	---	150.0	H	256.0	13.5	68.20	17.30

High Channel: 5825MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1989.400000	---	28.71	150.0	V	140.0	-8.3	54.00	25.29
1989.400000	39.68	---	150.0	V	140.0	-8.3	74.00	34.32
3454.800000	46.19	---	150.0	V	245.0	-3.6	68.20	22.01
6531.800000	47.51	---	150.0	V	245.0	4.5	68.20	20.69
8024.400000	48.07	---	150.0	H	127.0	7.0	68.20	20.13
11650.000000	---	39.10	150.0	H	232.0	9.9	54.00	14.90
11650.000000	48.51	---	150.0	H	232.0	9.9	74.00	25.49
17475.000000	52.04	---	150.0	V	105.0	14.1	68.20	16.16

802.11n-HT20 Mode(chain0+chain1):


(Pre-scan with X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5745MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1724.200000	37.64	---	150.0	V	244.0	-9.2	68.20	30.56
2128.800000	41.58	---	150.0	V	2.0	-7.9	68.20	26.62
3454.800000	45.69	---	150.0	V	232.0	-3.6	68.20	22.51
7959.800000	48.29	---	150.0	V	221.0	7.0	68.20	19.91
11490.000000	46.29	---	150.0	H	24.0	9.8	74.00	27.71
11490.000000	---	37.83	150.0	H	24.0	9.8	54.00	16.17
17235.000000	50.52	---	150.0	V	2.0	12.9	68.20	17.68

Middle Channel: 5785MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1805.800000	39.40	---	150.0	V	0.0	-8.9	68.20	28.80
3454.800000	45.43	---	150.0	V	233.0	-3.6	68.20	22.77
5246.600000	44.85	---	150.0	V	280.0	0.6	68.20	23.35
8928.800000	49.21	---	150.0	H	222.0	7.5	68.20	18.99
11570.000000	---	37.49	150.0	H	29.0	9.8	54.00	16.51
11570.000000	46.70	---	150.0	H	29.0	9.8	74.00	27.30
17355.000000	52.60	---	150.0	V	187.0	13.5	68.20	15.60

High Channel: 5825MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1822.800000	40.95	---	150.0	V	353.0	-8.8	68.20	27.25
3454.800000	45.03	---	150.0	V	229.0	-3.6	68.20	23.17
5246.600000	44.34	---	150.0	V	276.0	0.6	68.20	23.86
8000.600000	48.57	---	150.0	V	0.0	7.1	68.20	19.63
11650.000000	49.06	---	150.0	V	0.0	9.9	74.00	24.94
11650.000000	---	40.29	150.0	V	0.0	9.9	54.00	13.71
17475.000000	50.79	---	150.0	H	111.0	14.2	68.20	17.41

802.11ac40 Mode(chain0+chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5755MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1799.000000	39.78	---	150.0	V	357.0	-8.9	68.20	28.42
3454.800000	47.33	---	150.0	V	232.0	-3.6	68.20	20.87
7419.200000	---	37.38	150.0	H	75.0	6.0	54.00	16.62
7419.200000	48.37	---	150.0	H	75.0	6.0	74.00	25.63
9010.400000	---	37.95	150.0	H	134.0	7.7	54.00	16.05
9010.400000	49.54	---	150.0	H	134.0	7.7	74.00	24.46
11510.000000	---	37.01	150.0	V	284.0	9.8	54.00	16.99
11510.000000	46.33	---	150.0	V	284.0	9.8	74.00	27.67
17265.000000	49.88	---	150.0	H	0.0	13.1	68.20	18.32

High Channel: 5795MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1727.600000	37.58	---	150.0	V	236.0	-9.2	68.20	30.62
3454.800000	47.36	---	150.0	V	236.0	-3.6	68.20	20.84
6586.200000	47.42	---	150.0	V	0.0	4.6	68.20	20.78
9377.600000	---	36.92	150.0	H	23.0	7.7	54.00	17.08
9377.600000	48.07	---	150.0	H	23.0	7.7	74.00	25.93
11590.000000	---	36.72	150.0	V	330.0	9.8	54.00	17.28
11590.000000	45.77	---	150.0	V	330.0	9.8	74.00	28.23
17385.000000	51.51	---	150.0	H	282.0	13.7	68.20	16.69

802.11n-HT40 Mode(chain0+chain1):


(Pre-scan with X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5755MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1724.200000	38.07	---	150.0	V	295.0	-9.2	68.20	30.13
3454.800000	46.41	---	150.0	V	237.0	-3.6	68.20	21.79
6712.000000	48.64	---	150.0	V	295.0	4.8	68.20	19.56
9942.000000	50.43	---	150.0	H	63.0	8.2	68.20	17.77
11510.000000	---	36.50	150.0	H	292.0	9.8	54.00	17.50
11510.000000	46.67	---	150.0	H	292.0	9.8	74.00	27.33
17265.000000	50.44	---	150.0	V	162.0	13.1	68.20	17.76

High Channel: 5795MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	25.70	150.0	V	220.0	-9.6	54.00	28.30
1595.000000	39.91	---	150.0	V	220.0	-9.6	74.00	34.09
2128.800000	46.67	---	150.0	V	351.0	-7.9	68.20	21.53
3454.800000	47.65	---	150.0	V	232.0	-3.6	68.20	20.55
5243.200000	45.46	---	150.0	V	279.0	0.5	68.20	22.74
11590.000000	---	37.34	150.0	H	295.0	9.8	54.00	16.66
11590.000000	47.21	---	150.0	H	295.0	9.8	74.00	26.79
17385.000000	51.78	---	150.0	V	208.0	13.7	68.20	16.42

802.11ac80 Mode(chain0+chain1):


(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:

1. This test was performed with the 5150-5250MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
 Corrected Amplitude = Corrected Factor + Reading
 Margin = Limit - Corrected. Amplitude

Low Channel: 5210MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1724.200000	36.51	---	150.0	V	242.0	-9.2	68.20	31.69
3454.800000	46.40	---	150.0	V	242.0	-3.6	68.20	21.80
5797.400000	45.45	---	150.0	H	178.0	1.9	68.20	22.75
6946.600000	50.06	---	150.0	V	217.0	5.2	68.20	18.14
10420.000000	46.89	---	150.0	V	116.0	8.9	68.20	21.31
15630.000000	---	40.98	150.0	V	5.0	11.3	54.00	13.02
15630.000000	49.57	---	150.0	V	5.0	11.3	74.00	24.43

802.11ac80 Mode(chain0+chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)

Note:

1. This test was performed with the 5725-5850MHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude

Low Channel: 5775MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1836.400000	40.45	---	150.0	V	0.0	-8.8	68.20	27.75
3454.800000	46.44	---	150.0	V	232.0	-3.6	68.20	21.76
5535.600000	44.25	---	150.0	V	150.0	1.5	68.20	23.95
7640.200000	---	37.64	150.0	H	42.0	6.4	54.00	16.36
7640.200000	49.15	---	150.0	H	42.0	6.4	74.00	24.85
11550.000000	---	37.80	150.0	V	302.0	9.8	54.00	16.20
11550.000000	47.19	---	150.0	V	302.0	9.8	74.00	26.81
17325.000000	50.39	---	150.0	H	135.0	13.4	68.20	17.81

18GHz-40GHz (5150-5250MHz Band):

Pre-scan with 802.11a and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11n-HT20 mode in Z-axis of orientation was recorded

Horizontal


Date: 20.MAR.2019 19:36:55

Vertical


Date: 20.MAR.2019 20:02:11

18GHz-40GHz (5725-5850 Band):

Pre-scan with 802.11a and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case middle channel of 802.11n-HT20 mode in Z-axis of orientation was recorded

Horizontal

Date: 20.MAR.2019 20:25:53

Vertical

Date: 20.MAR.2019 20:55:30

Fundamental Test & Restricted Bands Emissions Test (5150-5250MHz Band):

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

802.11a Mode-Chain0: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5180.000000	98.13	---	200.0	V	9.0	10.3	/	/
5180.000000	---	91.33	200.0	V	9.0	10.3	/	/
5180.000000	93.17	---	200.0	H	20.0	10.3	/	/
5180.000000	---	86.60	200.0	H	20.0	10.3	/	/
5150.000000	---	45.33	200.0	V	242.0	10.2	54.00	8.67
5150.000000	54.25	---	200.0	V	242.0	10.2	74.00	19.75
Middle Channel: 5200MHz								
5200.000000	98.66	---	100.0	V	41.0	10.4	/	/
5200.000000	---	91.69	100.0	V	41.0	10.4	/	/
5200.000000	93.85	---	100.0	H	213.0	10.4	/	/
5200.000000	---	86.84	100.0	H	213.0	10.4	/	/
High Channel: 5240MHz								
5240.000000	99.24	---	100.0	V	312.0	10.5	/	/
5240.000000	---	91.93	100.0	V	312.0	10.5	/	/
5240.000000	94.44	---	100.0	H	55.0	10.5	/	/
5240.000000	---	87.06	100.0	H	55.0	10.5	/	/
5350.000000	54.83	---	100.0	V	308.0	10.6	74.00	19.17
5350.000000	---	45.76	100.0	V	308.0	10.6	54.00	8.24

802.11a Mode-Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5180.000000	99.15	---	100.0	V	192.0	10.3	/	/
5180.000000	---	92.37	100.0	V	192.0	10.3	/	/
5180.000000	94.45	---	100.0	H	113.0	10.3	/	/
5180.000000	---	87.48	100.0	H	113.0	10.3	/	/
5150.000000	---	44.92	200.0	V	150.0	10.2	54.00	9.08
5150.000000	55.14	---	200.0	V	150.0	10.2	74.00	18.86
Middle Channel: 5200MHz								
5200.000000	99.35	---	100.0	V	286.0	10.4	/	/
5200.000000	---	92.53	100.0	V	286.0	10.4	/	/
5200.000000	94.63	---	100.0	H	193.0	10.4	/	/
5200.000000	---	87.63	100.0	H	193.0	10.4	/	/
High Channel: 5240MHz								
5240.000000	99.71	---	100.0	V	251.0	10.5	/	/
5240.000000	---	92.95	100.0	V	251.0	10.5	/	/
5240.000000	94.80	---	200.0	H	212.0	10.5	/	/
5240.000000	---	88.02	200.0	H	212.0	10.5	/	/
5350.000000	54.88	---	100.0	V	327.0	10.6	74.00	19.12
5350.000000	---	45.88	100.0	V	327.0	10.6	54.00	8.12

802.11ac20 Mode(Chain0+ Chain1): (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5180.000000	102.61	---	100.0	V	253.0	10.3	/	/
5180.000000	---	95.32	100.0	V	253.0	10.3	/	/
5180.000000	97.65	---	100.0	H	319.0	10.3	/	/
5180.000000	---	90.32	100.0	H	319.0	10.3	/	/
5150.000000	---	45.46	200.0	V	233.0	10.2	54.00	8.54
5150.000000	54.56	---	200.0	V	233.0	10.2	74.00	19.44
Middle Channel: 5200MHz								
5200.000000	102.31	---	100.0	V	84.0	10.4	/	/
5200.000000	---	94.99	100.0	V	84.0	10.4	/	/
5200.000000	97.37	---	200.0	H	10.0	10.4	/	/
5200.000000	---	90.03	200.0	H	10.0	10.4	/	/
High Channel: 5240MHz								
5240.000000	101.71	---	200.0	V	166.0	10.5	/	/
5240.000000	---	94.52	200.0	V	166.0	10.5	/	/
5240.000000	96.79	---	100.0	H	346.0	10.5	/	/
5240.000000	---	89.77	100.0	H	346.0	10.5	/	/
5350.000000	54.79	---	200.0	V	224.0	10.6	74.00	19.21
5350.000000	---	45.72	200.0	V	224.0	10.6	54.00	8.28

802.11n-HT20 Mode(Chain0+ Chain1): (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5180MHz								
5180.000000	102.95	---	200.0	V	256.0	10.3	/	/
5180.000000	---	95.76	200.0	V	256.0	10.3	/	/
5180.000000	98.01	---	100.0	H	169.0	10.3	/	/
5180.000000	---	90.95	100.0	H	169.0	10.3	/	/
5150.000000	---	45.44	100.0	V	4.0	10.2	54.00	8.56
5150.000000	56.37	---	100.0	V	4.0	10.2	74.00	17.63
Middle Channel: 5200MHz								
5200.000000	103.59	---	200.0	V	57.0	10.4	/	/
5200.000000	---	96.11	200.0	V	57.0	10.4	/	/
5200.000000	98.88	---	100.0	H	354.0	10.4	/	/
5200.000000	---	91.32	100.0	H	354.0	10.4	/	/
High Channel: 5240MHz								
5240.000000	104.07	---	200.0	V	101.0	10.5	/	/
5240.000000	---	97.15	200.0	V	101.0	10.5	/	/
5240.000000	99.29	---	100.0	H	149.0	10.5	/	/
5240.000000	---	92.41	100.0	H	149.0	10.5	/	/
5350.000000	56.75	---	100.0	V	291.0	10.6	74.00	17.25
5350.000000	---	45.87	100.0	V	291.0	10.6	54.00	8.13

802.11ac40 Mode(Chain0+ Chain1): (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5190.000000	---	91.99	100.0	V	159.0	10.4	/	/
5190.000000	99.07	---	100.0	V	159.0	10.4	/	/
5190.000000	---	87.15	100.0	H	228.0	10.4	/	/
5190.000000	94.17	---	100.0	H	228.0	10.4	/	/
5150.000000	---	45.17	100.0	V	219.0	10.2	54.00	8.83
5150.000000	55.86	---	100.0	V	219.0	10.2	74.00	18.14
High Channel: 5230MHz								
5230.000000	100.01	---	200.0	V	14.0	10.5	/	/
5230.000000	---	92.04	200.0	V	14.0	10.5	/	/
5230.000000	95.04	---	100.0	H	351.0	10.5	/	/
5230.000000	---	87.24	100.0	H	351.0	10.5	/	/
5350.000000	---	45.64	200.0	V	75.0	10.6	54.00	8.36
5350.000000	55.99	---	200.0	V	75.0	10.6	74.00	18.01

802.11n-HT40 Mode(Chain0+ Chain1): (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5190MHz								
5190.000000	100.21	---	200.0	V	18.0	10.4	/	/
5190.000000	---	93.27	200.0	V	18.0	10.4	/	/
5190.000000	95.29	---	100.0	H	94.0	10.4	/	/
5190.000000	---	88.48	100.0	H	94.0	10.4	/	/
5150.000000	---	45.24	200.0	V	311.0	10.2	54.00	8.76
5150.000000	59.83	---	200.0	V	311.0	10.2	74.00	14.17
Middle Channel: 5230MHz								
5230.000000	99.25	---	100.0	V	60.0	10.5	/	/
5230.000000	---	91.88	100.0	V	60.0	10.5	/	/
5230.000000	94.27	---	200.0	H	268.0	10.5	/	/
5230.000000	---	87.07	200.0	H	268.0	10.5	/	/
5350.000000	54.78	---	100.0	V	136.0	10.6	74.00	19.22
5350.000000	---	45.81	100.0	V	136.0	10.6	54.00	8.19

802.11ac80 Mode(Chain0+ Chain1): (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5210MHz								
5150.000000	---	46.85	100.0	V	168.0	10.2	54.00	7.15
5150.000000	55.35	---	100.0	V	168.0	10.2	74.00	18.65
5210.000000	---	84.05	100.0	V	174.0	10.4	/	/
5210.000000	95.60	---	100.0	V	174.0	10.4	/	/
5210.000000	---	87.90	100.0	H	222.0	10.4	/	/
5210.000000	90.67	---	100.0	H	222.0	10.4	/	/
5350.000000	---	45.86	100.0	V	184.0	10.6	54.00	8.14
5350.000000	54.89	---	100.0	V	184.0	10.6	74.00	19.11

Fundamental Test & Restricted Bands Emissions Test (5725-5850MHz band):

Note:

1. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
2. Corrected Amplitude = Corrected Factor + Reading
3. Margin = Limit - Corrected. Amplitude

802.11a Mode-chain0: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5745.000000	---	90.93	100.0	V	312.0	11.8	/	/
5745.000000	98.00	---	100.0	V	312.0	11.8	/	/
5745.000000	---	86.12	150.0	H	4.0	11.8	/	/
5745.000000	93.16	---	150.0	H	4.0	11.8	/	/
5650.000000	42.80	---	150.0	V	312.0	11.5	68.20	25.40
5700.000000	50.93	---	150.0	V	358.0	11.7	105.20	54.27
5720.000000	51.45	---	250.0	V	131.0	11.7	110.80	59.35
5725.000000	54.35	---	200.0	V	58.0	11.8	122.20	67.85
Middle Channel: 5785MHz								
5785.000000	97.89	---	100.0	V	211.0	12.7	/	/
5785.000000	---	90.67	100.0	V	211.0	12.7	/	/
5785.000000	93.14	---	250.0	H	238.0	12.7	/	/
5785.000000	---	85.70	250.0	H	238.0	12.7	/	/
High Channel: 5825MHz								
5825.000000	97.48	---	200.0	V	148.0	12.8	/	/
5825.000000	---	90.28	200.0	V	148.0	12.8	/	/
5825.000000	92.53	---	150.0	H	319.0	12.8	/	/
5825.000000	---	85.50	150.0	H	319.0	12.8	/	/
5850.000000	56.35	---	200.0	V	162.0	12.8	122.2	65.85
5855.000000	54.47	---	250.0	V	162.0	12.8	110.8	56.33
5875.000000	52.77	---	150.0	V	211.0	12.8	105.2	52.43
5925.000000	51.90	---	200.0	V	211.0	12.8	68.2	16.30

802.11a Mode-chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5745.000000	---	92.61	200.0	V	144.0	11.8	/	/
5745.000000	99.46	---	200.0	V	144.0	11.8	/	/
5745.000000	---	87.67	250.0	H	298.0	11.8	/	/
5745.000000	94.61	---	250.0	H	298.0	11.8	/	/
5650.000000	54.47	---	100.0	V	120.0	11.5	68.20	13.73
5700.000000	55.14	---	100.0	V	120.0	11.7	105.20	50.06
5720.000000	55.43	---	200.0	V	201.0	11.7	110.80	55.37
5725.000000	58.86	---	200.0	V	201.0	11.8	122.20	63.34
Middle Channel: 5785MHz								
5785.000000	98.56	---	200.0	V	218.0	11.9	/	/
5785.000000	---	92.01	200.0	V	218.0	11.9	/	/
5785.000000	93.60	---	150.0	H	159.0	11.9	/	/
5785.000000	---	87.06	150.0	H	159.0	11.9	/	/
High Channel: 5825MHz								
5825.000000	97.89	---	250.0	V	159.0	12.0	/	/
5825.000000	---	90.75	250.0	V	159.0	12.0	/	/
5825.000000	93.12	---	200.0	H	161.0	12.0	/	/
5825.000000	---	85.85	200.0	H	161.0	12.0	/	/
5850.000000	55.96	---	150.0	V	196.0	12.0	122.2	66.24
5855.000000	55.43	---	200.0	V	196.0	12.0	110.8	55.37
5875.000000	55.97	---	250.0	V	191.0	12.1	105.2	49.23
5925.000000	56.11	---	200.0	V	191.0	12.3	68.2	12.09

802.11ac20 Mode-Chain0+ Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5745.000000	---	92.79	150.0	V	17.0	11.8	/	/
5745.000000	99.96	---	150.0	V	17.0	11.8	/	/
5745.000000	---	88.06	200.0	H	54.0	11.8	/	/
5745.000000	95.18	---	200.0	H	54.0	11.8	/	/
5650.000000	55.11	---	250.0	V	6.0	11.5	68.20	13.09
5700.000000	55.67	---	150.0	V	6.0	11.7	105.20	49.53
5720.000000	55.84	---	200.0	V	249.0	11.7	110.80	54.96
5725.000000	55.95	---	250.0	V	249.0	11.8	122.20	66.25
Middle Channel: 5785MHz								
5785.000000	99.71	---	200.0	V	170.0	11.9	/	/
5785.000000	---	92.11	200.0	V	170.0	11.9	/	/
5785.000000	94.93	---	150.0	H	101.0	11.9	/	/
5785.000000	---	87.39	150.0	H	101.0	11.9	/	/
High Channel: 5825MHz								
5825.000000	99.58	---	200.0	V	310.0	12.0	/	/
5825.000000	---	91.51	200.0	V	310.0	12.0	/	/
5825.000000	94.61	---	150.0	H	1.0	12.0	/	/
5825.000000	---	86.52	150.0	H	1.0	12.0	/	/
5850.000000	55.85	---	250.0	V	259.0	12.0	122.2	66.35
5855.000000	55.96	---	200.0	V	259.0	12.0	110.8	54.84
5875.000000	56.06	---	250.0	V	197.0	12.1	105.2	49.14
5925.000000	56.29	---	150.0	V	197.0	12.3	68.2	11.91

802.11n-HT20 Mode- Chain0+ Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5745MHz								
5745.000000	---	92.91	200.0	V	135.0	11.8	/	/
5745.000000	101.33	---	200.0	V	135.0	11.8	/	/
5745.000000	---	88.08	150.0	H	168.0	11.8	/	/
5745.000000	96.53	---	150.0	H	168.0	11.8	/	/
5650.000000	55.14	---	150.0	V	348.0	11.5	68.20	13.06
5700.000000	55.43	---	250.0	V	348.0	11.7	105.20	49.77
5720.000000	57.36	---	200.0	V	315.0	11.7	110.80	53.44
5725.000000	59.19	---	250.0	V	315.0	11.8	122.20	63.01
Middle Channel: 5785MHz								
5785.000000	101.50	---	150.0	V	267.0	11.9	/	/
5785.000000	---	93.04	150.0	V	267.0	11.9	/	/
5785.000000	96.64	---	200.0	H	99.0	11.9	/	/
5785.000000	---	88.20	200.0	H	99.0	11.9	/	/
High Channel: 5825MHz								
5825.000000	101.70	---	200.0	V	285.0	12.0	/	/
5825.000000	---	93.12	200.0	V	285.0	12.0	/	/
5825.000000	96.77	---	200.0	H	246.0	12.0	/	/
5825.000000	---	88.29	200.0	H	246.0	12.0	/	/
5850.000000	55.98	---	150.0	V	357.0	12.0	122.2	66.22
5855.000000	55.37	---	200.0	V	357.0	12.0	110.8	55.43
5875.000000	55.64	---	100.0	V	99.0	12.1	105.2	49.56
5925.000000	55.83	---	200.0	V	99.0	12.3	68.2	12.37

802.11ac40 Mode- Chain0+ Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5755MHz								
5755.000000	---	89.24	200.0	V	23.0	11.9	/	/
5755.000000	96.49	---	200.0	V	23.0	11.9	/	/
5755.000000	---	84.24	150.0	H	121.0	11.9	/	/
5755.000000	91.79	---	150.0	H	121.0	11.9	/	/
5650.000000	55.02	---	250.0	V	102.0	11.5	68.20	13.18
5700.000000	55.34	---	250.0	V	102.0	11.7	105.20	49.86
5720.000000	55.67	---	200.0	V	51.0	11.7	110.80	55.13
5725.000000	56.97	---	150.0	V	51.0	11.8	122.20	65.23
High Channel: 5795MHz								
5795.000000	---	89.19	150.0	V	296.0	11.9	/	/
5795.000000	96.28	---	150.0	V	296.0	11.9	/	/
5795.000000	---	84.21	250.0	H	209.0	11.9	/	/
5795.000000	91.32	---	250.0	H	209.0	11.9	/	/
5850.000000	56.27	---	200.0	V	344.0	12.0	122.2	65.93
5855.000000	55.64	---	250.0	V	344.0	12.0	110.8	55.16
5875.000000	55.71	---	200.0	V	319.0	12.1	105.2	49.49
5925.000000	55.84	---	200.0	V	319.0	12.3	68.2	12.36

802.11n-HT40 Mode- Chain0+ Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5755MHz								
5745.000000	98.58	---	250.0	V	347.0	11.9	/	/
5745.000000	---	90.92	250.0	V	347.0	11.9	/	/
5745.000000	93.85	---	150.0	H	169.0	11.9	/	/
5745.000000	---	85.98	150.0	H	169.0	11.9	/	/
5650.000000	55.41	---	150.0	V	228.0	11.5	68.20	12.79
5700.000000	58.67	---	200.0	V	228.0	11.7	105.20	46.53
5720.000000	60.56	---	250.0	V	4.0	11.7	110.80	50.24
5725.000000	62.81	---	150.0	V	4.0	11.8	122.20	59.39
High Channel: 5795MHz								
5825.000000	---	90.64	150.0	V	190.0	11.9	/	/
5825.000000	97.64	---	150.0	V	190.0	11.9	/	/
5825.000000	---	85.70	200.0	H	159.0	11.9	/	/
5825.000000	92.82	---	200.0	H	159.0	11.9	/	/
5850.000000	55.76	---	250.0	V	283.0	12.0	122.2	66.44
5855.000000	55.37	---	200.0	V	283.0	12.0	110.8	55.43
5875.000000	55.67	---	200.0	V	112.0	12.1	105.2	49.53
5925.000000	55.89	---	150.0	V	112.0	12.3	68.2	12.31

802.11ac80 Mode- Chain0+ Chain1: (Pre-scan in the X, Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Correct Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 5775MHz								
5650.000000	55.13	---	250.0	V	358.0	11.5	68.20	13.07
5700.000000	55.49	---	150.0	V	358.0	11.7	105.20	49.71
5720.000000	55.89	---	200.0	V	266.0	11.7	110.80	54.91
5725.000000	57.12	---	200.0	V	266.0	11.8	122.20	65.08
5775.000000	53.40	---	150.0	V	46.0	11.9	/	/
5775.000000	---	85.58	250.0	H	46.0	11.9	/	/
5775.000000	93.19	---	250.0	H	336.0	11.9	/	/
5775.000000	---	80.83	250.0	H	336.0	11.9	/	/
5850.000000	55.94	---	150.0	V	30.0	12.0	122.2	66.26
5855.000000	55.43	---	200.0	V	30.0	12.0	110.8	55.37
5875.000000	55.87	---	250.0	V	197.0	12.1	105.2	49.33
5925.000000	55.96	---	200.0	V	197.0	12.3	68.2	12.24

FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data**Environmental Conditions**

Temperature:	23.5 °C~24.5 °C
Relative Humidity:	50 %~52 %
ATM Pressure:	101.2 kPa~101.4 kPa

The testing was performed by Max Min from 2019-03-06 to 2019-03-08.

Test Result: Pass.

5150-5250 MHz:

Test mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)		99% Bandwidth (MHz)	
			Chain0	Chain1	Chain0	Chain1
802.11a	Low	5180	23.006	22.605	17.074	17.234
	Middle	5200	22.525	22.886	17.074	17.074
	High	5240	22.926	22.926	17.074	17.074
802.11ac20	Low	5180	23.888	23.808	18.196	18.196
	Middle	5200	23.647	23.928	18.196	18.196
	High'	5240	24.048	23.968	18.116	18.196
802.11n-HT20	Low	5180	23.647	23.327	18.196	18.196
	Middle	5200	23.727	23.487	18.196	18.196
	High	5240	22.926	23.567	17.074	18.196
802.11ac40	Low	5190	42.565	42.926	36.794	36.914
	High'	5230	42.685	43.166	36.794	36.794
802.11n-HT40	Low	5190	42.565	43.166	36.794	36.794
	High	5230	42.445	42.926	36.794	36.794
802.11ac80	Low	5210	87.435	86.573	76.473	76.473

5725-5850MHz:

Test mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)		99% Bandwidth (MHz)		Limit (MHz)
			Chain0	Chain1	Chain0	Chain1	
802.11a	Low	5745	16.593	16.473	16.994	17.074	≥ 0.5
	Middle	5785	16.513	16.473	16.994	17.014	≥ 0.5
	High	5825	16.513	16.473	16.994	17.014	≥ 0.5
802.11ac20	Low	5745	17.715	17.715	18.116	18.116	≥ 0.5
	Middle	5785	17.715	17.715	18.036	18.116	≥ 0.5
	High	5825	17.715	17.715	18.036	18.116	≥ 0.5
802.11n-HT20	Low	5745	17.715	17.715	18.036	18.116	≥ 0.5
	Middle	5785	17.715	17.715	18.116	18.116	≥ 0.5
	High	5825	17.715	17.715	18.116	18.036	≥ 0.5
802.11ac40	Low	5755	36.653	36.673	36.794	36.794	≥ 0.5
	High	5795	36.673	36.713	36.794	36.794	≥ 0.5
802.11n-HT40	Low	5755	36.673	36.433	36.673	36.794	≥ 0.5
	High	5795	36.553	36.593	36.794	36.794	≥ 0.5
802.11ac80	Low	5775	76.132	76.473	76.473	76.473	≥ 0.5

Delta 1 [T1] 0.55 dB RBW 300 kHz RF Att 10 dB
 Ref Lvl 10 dBm VBW 1 MHz
 10 dBm 22.92585170 MHz SWT 5 ms Unit dBm

10.5 dB Offset

▼1 [T1] -31.73 dBm 5.22865731 GHz
 ▲1 [T1] 0.55 dB 22.92585170 MHz
 OPB T2 17.07414830 MHz
 ▼T1 [T1] -13.96 dBm 5.23146293 GHz
 ▼T2 [T1] -13.79 dBm 5.24853707 GHz

D1 -5.31 dBm
 D2 -31.31 dBm

1MAX

Center 5.24 GHz 4 MHz/ Span 40 MHz

Date: 6.MAR.2019 10:49:46

Delta 1 [T1] -0.52 dB

Ref Lvl 10 dBm

RBW 300 kHz RF Att 10 dB

VBW 1 MHz

SWT 5 ms Unit dBm

23.88777555 MHz

10.5 GHz Offset

▼1 [T1] -32.98 dBm

▲1 [T1] -0.52 dB

23.88777555 MHz

18.19639279 MHz

▼T1 [T1] -14.95 dBm

▼T2 [T1] -15.35 dBm

5.16785571 GHz

5.17090180 GHz

5.18909820 GHz

1MAX

D1 -6.89 dBm

D2 -32.89 dBm


Center 5.18 GHz

4 MHz/


Span 40 MHz

Date: 6.MAR.2019 10:40:13

802.11 ac20 mode, 5200MHz



802.11 ac20 mode, 5240MHz



Delta 1 [T1] 0.38 dB
 Ref Lvl 10 dBm
 10 dBm 23.64729459 MHz
 RBW 300 kHz RF Att 10 dB
 VBW 1 MHz
 SWT 5 ms Unit dBm

10.5 dB Offset
 -D1 -5.24 dBm
 1MAX
 -D2 -31.24 dBm
 Center 5.18 GHz 4 MHz/
 Span 40 MHz

▼1 [T1] -31.78 dBm
 5.16833667 GHz
 ▲1 [T1] 0.38 dB
 23.64729459 MHz
 OPB 12 18.19639279 MHz
 ▼T1 ▼T1 -13.55 dBm
 5.17090180 GHz
 ▼T2 [T1] -13.40 dBm
 5.18909820 GHz 1MAX

Delta 1 [T1]

Ref Lvl 1.25 dB

10 dBm

23.72745491 MHz

RBW 300 kHz

VBW 1 MHz

SWT 5 ms

RF Att 10 dB

Unit dBm

10.5 dB Offset

▼1 [T1] -32.17 dBm

5.18825651 GHz

▲1 [T1] 1.25 dB

23.72745491 MHz

OPB 12 18.19639279 MHz

▽T1 [T1] -13.76 dBm

5.19090180 GHz

▽T2 [T1] -13.45 dBm

5.20909820 GHz

D1 -5.11 dBm

D2 -31.11 dBm

1MAX

1MA

Center 5.2 GHz

4 MHz/

Span 40 MHz

Date: 6.MAR.2019 10:46:38

Ref Lvl 10 dBm Delta 1 [T1] 0.13 dB RBW 300 kHz RF Att 10 dB
 10 dBm 22.92585170 MHz VBW 1 MHz SWT 5 ms Unit dBm

10.5 dB Offset

▼1 [T1] -31.73 dBm
 5.22865731 GHz

▲1 [T1] 0.13 dB
 22.92585170 MHz

OPB 17.07414830 MHz

▼T1 [T1] -13.96 dBm
 5.23146293 GHz

▼T2 [T1] -14.75 dBm
 5.24853707 GHz

1MAX

D1 -5.31 dBm

D2 -31.31 dBm

Center 5.24 GHz 4 MHz/ Span 40 MHz

Date: 6.MAR.2019 10:49:31


Ref Lvl 10 dBm
 Delta 1 [T1] 0.01 dB
 RBW 500 kHz
 VBW 2 MHz
 RF Att 10 dB
 10 dBm
 42.56513026 MHz
 SWT 5 ms
 Unit dBm

10.5 dB Offset
 -D1 -6.15 dBm
 1MAX
 -D2 -32.15 dBm
 1MA


Center 5.19 GHz
 6 MHz/
 Span 60 MHz

1 [T1] -33.19 dBm
 5.16877756 GHz
 0.01 dB
 42.56513026 MHz
 16.79358717 MHz
 T1 [T1] -13.01 dBm
 5.17166333 GHz
 T2 [T1] -13.45 dBm
 5.20845691 GHz

802.11 ac40 mode, 5230MHz



802.11n-HT40 mode, 5190MHz




[illegible][illegible]


chain1:

26 Bandwidth&99% Occupied Bandwidth


802.11a mode, 5180MHz




802.11a mode, 5200MHz



802.11a mode, 5240MHz



802.11ac20 mode, 5180MHz



Delta 1 [T1] -0.79 dB

RBW 300 kHz RF Att 20 dB

Ref Lvl 10 dBm Unit dBm

SWT 5 ms

10.5 dB Offset

▼1 [T1] -31.80 dBm

▲1 [T1] -0.79 dBm

D1 -5.2 dBm

23.92785571 MHz

OPB 18.19639279 MHz

▽T1 [T1] -14.18 dBm

5.19090180 GHz

▽T2 [T1] -13.63 dBm

5.20909820 GHz

1MAX

D2 -31.2 dBm

Center 5.2 GHz 4 MHz/ Span 40 MHz

Date: 6.MAR.2019 17:39:15

Delta 1 [T1] -0.36 dB RBW 300 kHz RF Att 20 dB
 Ref Lvl 10 dBm BW 1 MHz Unit dBm

10.5 dB Offset

-D1 -5.59 dBm


1MAX

D2 -31.59 dBm


Center 5.24 GHz 4 MHz/ Span 40 MHz

Date: 6.MAR.2019 17:40:20

802.11n-HT20 mode, 5180MHz



802.11n-HT20 mode, 5200MHz



Delta 1 [T1] 0.37 dB

Ref Lvl 10 dBm

RBW 300 kHz RF Att 20 dB

SWT 1 ms

Unit dBm

10.5 dB Offset

D1 -4.35 dBm

1 [T1] -30.55 dBm

5.22833667 GHz

23.56713427 MHz

OPB T2 18.19639279 MHz

T1 T1 -12.91 dBm

5.23090180 GHz

T2 T1 -12.50 dBm

5.24909820 GHz

1MAX

D2 -30.35 dBm

Center 5.24 GHz

4 MHz/

Span 40 MHz

Date: 6.MAR.2019 17:33:49

[illegible]


Delta 1 [T1] 0.83 dB
 RBW 500 kHz RF Att 20 dB
 Ref Lvl 10 dBm VBW 2 MHz
 10 dBm SWT 5 ms Unit dBm

10.5 dB Offset
 -D1 -5.72 dBm
 1MAX
 -D2 -31.72 dBm
 Center 5.23 GHz 6 MHz/ Span 60 MHz


1 [T1] -32.47 dBm 5.20853707 GHz
 1 [T1] 0.83 dB 43.16633267 MHz
 OPB
 T1 [T1] -11.46 dBm 5.21166333 GHz
 T2 [T1] -12.57 dBm 5.24845691 GHz

[illegible]

802.11n-HT40 mode, 5230MHz



802.11ac80 mode, 5210MHz




5725-5850 MHz Band


chain0:

6 Bandwidth


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11ac20 mode, 5745MHz




802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz




802.11 ac40 mode, 5795MHz




802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz



802.11ac80 mode, 5775MHz



6 Bandwidth

Delta 1 [T1] -0.79 dB

RBW 100 kHz RF Att 10 dB

Ref Lvl 10 dBm

16.47294589 MHz

SWT 7.5 ms Unit dBm

10.5 dB Offset

▼ 1 [T1] -13.04 dBm

▲ 1 [T1] -0.79 dB

▼ 2 [T1] -50.36 dBm

▲ 2 [T1] -57.3000000 GHz

D1 -6.85 dBm

D2 -12.85 dBm

1MAX

Center 5.745 GHz

3 MHz/

Span 30 MHz

Date: 6.MAR.2019 20:18:14

[illegible]

Delta 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -0.46 dB VBW 300 kHz
 10 dBm 16.47294589 MHz SWT 7.5 ms Unit dBm

10.5 dB Offset ▼ 1 [T1] -13.90 dBm
 0 ▲ 1 [T1] -0.46 dB
 -10 ▼ 2 [T1] -51.27 dBm
 -13.46 dBm 5.81000000 GHz
 -20 1MAX 1MAX
 -30
 -40
 -50
 -60
 -70
 -80
 -90

Center 5.825 GHz 3 MHz/ Span 30 MHz

Date: 6.MAR.2019 20:20:42

Delta 1 [T1] 0.49 dB

Ref Lvl 10 dBm

RBW 100 kHz

VBW 300 kHz

SWT 10 ms

RF Att 10 dB

Unit dBm

10.5 dB Offset

-D1 -7.51 dBm

-D2 -13.51 dBm

1MAX

▼ 1 [T1] -14.29 dBm

▲ 1 [T1] 0.49 dB

17.71543086 MHz

5.73614228 GHz


Center 5.745 GHz

4 MHz/


Span 40 MHz

Date: 6.MAR.2019 18:29:41


802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz



802.11 ac40 mode, 5795MHz



802.11n-HT40 mode, 5755MHz



Delta 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl -2.01 dB VBW 300 kHz
 10 dBm 36.59318637 MHz SWT 15 ms Unit dBm

10.5 dB Offset ▼ 1 [T1] -15.53 dBm
▲ 1 [T1] -2.01 dB
36.59318637 MHz

-10 dBm 1
 -16 dBm 1
 1MAX 1MAX

Center 5.795 GHz 6 MHz/ Span 60 MHz

Date: 6.MAR.2019 18:10:44

Delta 1 [T1] 0.19 dB RBW 100 kHz RF Att 10 dB
 Ref Lvl 10 dBm BW 300 kHz Unit dBm
 10 dBm 76.47294589 MHz SWT 30 ms

10.5 dB Offset

▼ 1 [T1] -19.54 dBm
 5.73688377 GHz
 ▲ 1 [T1] 0.19 dB
 76.47294589 MHz


D1 -13.14 dBm
 D2 -19.14 dBm
 1MAX

Center 5.775 GHz 12 MHz/ Span 120 MHz


Date: 6.MAR.2019 18:06:43

99% Occupied Bandwidth-chain0


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11ac20 mode, 5745MHz




802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz




802.11 ac20 mode, 5795MHz




802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz




802.11n-HT80 mode, 5775MHz




99% Occupied Bandwidth-chain1


802.11a mode, 5745MHz




802.11a mode, 5785MHz




802.11a mode, 5825MHz




802.11ac20 mode, 5745MHz




802.11 ac20 mode, 5785MHz




802.11 ac20 mode, 5825MHz




802.11n-HT20 mode, 5745MHz




802.11n-HT20 mode, 5785MHz




802.11n-HT20 mode, 5825MHz




802.11ac40 mode, 5755MHz




802.11 ac20 mode, 5795MHz




802.11n-HT40 mode, 5755MHz



802.11n-HT40 mode, 5795MHz



802.11n-HT80 mode, 5775MHz



FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER**Applicable Standard**

According to §15.407(a)(1)


(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi..

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

**Test Data****Environmental Conditions**

Temperature:	23.5 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2019-03-08.

Test Mode: Transmitting

Test mode	Band	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)			Limit (dBm)	Result
				Chain0	Chain1	Total		
802.11a	5150-5250 MHz	Low	5180	2.2	5.85	/	24	PASS
		Middle	5200	2.13	5.56	/	24	PASS
		High	5240	2.39	5.43	/	24	PASS
	5725-5850 MHz	Low	5745	2.74	6.41	/	30	PASS
		Middle	5785	2.56	5.91	/	30	PASS
		High	5825	2.2	5.79	/	30	PASS
802.11n-HT20	5150-5250 MHz	Low	5180	2.12	5.69	7.27	24	PASS
		Middle	5200	2.17	5.68	7.28	24	PASS
		High	5240	2.44	5.42	7.19	24	PASS
	5725-5850 MHz	Low	5745	2.49	6.28	7.86	30	PASS
		Middle	5785	2.37	5.84	7.45	30	PASS
		High	5825	2.1	5.92	7.43	30	PASS
802.11n-HT40	5150-5250 MHz	Low	5190	2.2	5.5	7.17	24	PASS
		High	5230	2.4	5.34	7.12	24	PASS
	5725-5850 MHz	Low	5755	2.72	6.21	7.82	30	PASS
		High	5795	2.36	5.89	7.48	30	PASS
802.11ac20	5150-5250 MHz	Low	5180	1.07	4.75	6.30	24	PASS
		Middle	5200	1.15	4.59	6.21	24	PASS
		High	5240	1.42	4.38	6.16	24	PASS
	5725-5850 MHz	Low	5745	1.67	5.26	6.84	30	PASS
		Middle	5785	1.47	4.8	6.46	30	PASS
		High	5825	1.21	4.6	6.24	30	PASS
802.11ac40	5150-5250 MHz	Low	5190	1.11	4.52	6.15	24	PASS
		High	5230	1.34	4.49	6.20	24	PASS
	5725-5850 MHz	Low	5755	1.71	4.99	6.66	30	PASS
		High	5795	1.45	4.61	6.32	30	PASS
802.11ac80	5150-5250 MHz	/	5210	1.45	5.07	6.64	24	PASS
	5725-5850 MHz	/	5775	1.66	5.34	6.89	30	PASS

Note 1: The total output power= $10\log_{10}(10^{(\text{Chain 0}/10)}+10^{(\text{Chain 1}/10)})$

Note 2: The maximum antenna gain is 3.0 dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO

transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;

So:

Directional gain = GANT + Array Gain = 2.13dBi < 6dBi

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY**Applicable Standard**

According to §15.407(a) (1)

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.407(a) (3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

The measurements are base on FCC KDB 789033 D02 General UNII Test Proceдыres New Rules v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices section F: Maximum power spectral density (PPSD)

Test Data**Environmental Conditions**

Temperature:	22.5. °C~24.5 °C
Relative Humidity:	50 %~52 %
ATM Pressure:	101.2 kPa~101. 3 kPa

The testing was performed by Max Min from 2019-03-06 to 2019-03-07.

Test Mode: Transmitting

5150MHz-5250MHz:

Mode	Channel	Frequency (MHz)	PSD (dBm/MHz)			Limit (dBm/MHz)	Result
			Chain0	Chain1	Total		
802.11a	Low	5180	-9.14	-5.06	/	11	PASS
	Middle	5200	-9.30	-4.92	/	11	PASS
	High	5240	-8.57	-4.75	/	11	PASS
802.11ac20	Low	5180	-10.29	-6.13	-4.72	11	PASS
	Middle	5200	-10.51	-6.07	-4.74	11	PASS
	High	5240	-10.23	-6.40	-4.90	11	PASS
802.11n20	Low	5180	-10.30	-5.82	-4.50	11	PASS
	Middle	5200	-10.21	-6.43	-4.91	11	PASS
	High	5240	-10.15	-6.32	-4.82	11	PASS
802.11ac40	Low	5190	-13.04	-9.18	-7.68	11	PASS
	High	5230	-12.98	-8.83	-7.42	11	PASS
802.11n40	Low	5190	-13.24	-8.60	-7.32	11	PASS
	High	5230	-12.97	-8.87	-7.44	11	PASS
802.11ac80	/	5210	-15.35	-11.93	-10.30	11	PASS

5725MHz-5850MHz:

Mode	Channel	Frequency MHz	PSD (dBm/500kHz)			Limit (dBm/500kHz)	Result
			Chain0	Chain1	Total		
802.11a	Low	5745	-10.18	-6.28	/	30	PASS
	Middle	5785	-11.12	-6.98	/	30	PASS
	High	5825	-11.35	-6.88	/	30	PASS
802.11ac20	Low	5745	-12.02	-7.40	-6.11	30	PASS
	Middle	5785	-11.51	-8.23	-6.56	30	PASS
	High	5825	-12.06	-8.19	-6.70	30	PASS
802.11n20	Low	5745	-11.23	-7.04	-5.64	30	PASS
	Middle	5785	-11.85	-8.23	-6.66	30	PASS
	High	5825	-12.16	-7.35	-6.11	30	PASS
802.11ac40	Low	5755	-14.33	-9.89	-8.56	30	PASS
	High	5795	-14.74	-10.90	-9.40	30	PASS
802.11n40	Low	5755	-14.55	-10.10	-8.77	30	PASS
	High	5795	-14.74	-10.76	-9.30	30	PASS
802.11ac80	/	5775	-17.68	-13.18	-11.86	30	PASS



Note1: The total PSD= $10\log_{10}(10^{Chain\ 0/10}+10^{Chain\ 1/10})$

Note2: The maximum antenna gain is 2.13 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:


Array Gain = $10\log(N_{ANT}/N_{SS})$ dB.

So:


Directional gain = GANT + Array Gain = $2.13+10*\log(2/1)=5.13$ dBi

5150MHz-5250MHz Band-chain0 :**802.11a mode, Power spectral density-5180MHz****802.11a mode, Power spectral density-5200MHz**


802.11a mode, Power spectral density-5240MHz




802.11ac20 mode, Power spectral density-5180MHz




802.11 ac20 mode, Power spectral density-5200MHz




802.11ac20 mode, Power spectral density-5240MHz




802.11n-HT20 mode, Power spectral density-5180MHz




802.11n-HT20 mode, Power spectral density-5200MHz




802.11n-HT20 mode, Power spectral density-5240MHz




802.11ac40 mode, Power spectral density-5190MHz




802.11 ac20 mode, Power spectral density-5230MHz




802.11n-HT20 mode, Power spectral density-5190MHz





802.11n-HT20 mode, Power spectral density-5230MHz




802.11n- ac80 mode, Power spectral density-5210MHz




5150MHz-5250MHz Band-chain1 :**802.11a mode, Power spectral density-5180MHz****802.11a mode, Power spectral density-5200MHz**


802.11a mode, Power spectral density-5240MHz




802.11ac20 mode, Power spectral density-5180MHz




802.11 ac20 mode, Power spectral density-5200MHz




802.11ac20 mode, Power spectral density-5240MHz





802.11n-HT20 mode, Power spectral density-5180MHz




802.11n-HT20 mode, Power spectral density-5200MHz




802.11n-HT20 mode, Power spectral density-5240MHz**802.11ac40 mode, Power spectral density-5190MHz**


802.11 ac40 mode, Power spectral density-5230MHz




802.11n-HT40 mode, Power spectral density-5190MHz



802.11n-HT40 mode, Power spectral density-5230MHz




802.11n- ac80 mode, Power spectral density-5210MHz




5725MHz-5850 MHz Band-chain0:


802.11a mode, Power spectral density-5745MHz




802.11a mode, Power spectral density-5785MHz




802.11a mode, Power spectral density-5825MHz




802.11ac20 mode, Power spectral density-5745MHz





802.11 ac20 mode, Power spectral density-5785MHz




802.11 ac20 mode, Power spectral density-5825MHz






802.11n-HT20 mode, Power spectral density-5745MHz**802.11n-HT20 mode, Power spectral density-5785MHz**



802.11n-HT20 mode, Power spectral density-5825MHz




802.11ac40 mode, Power spectral density-5755MHz




802.11 ac40 mode, Power spectral density-5795MHz**802.11n-HT40 mode, Power spectral density-5755MHz**

802.11n-HT40 mode, Power spectral density-5795MHz**802.11 ac80 mode, Power spectral density-5775MHz**


802.11a mode, Power spectral density-5745MHz




802.11a mode, Power spectral density-5785MHz





802.11a mode, Power spectral density-5825MHz




802.11ac20 mode, Power spectral density-5745MHz




802.11 ac20 mode, Power spectral density-5785MHz**802.11 ac20 mode, Power spectral density-5825MHz**


802.11n-HT20 mode, Power spectral density-5745MHz




802.11n-HT20 mode, Power spectral density-5785MHz







802.11n-HT20 mode, Power spectral density-5825MHz



802.11ac40 mode, Power spectral density-5755MHz



802.11 ac40 mode, Power spectral density-5795MHz**802.11n-HT40 mode, Power spectral density-5755MHz**

802.11n-HT40 mode, Power spectral density-5795MHz**802.11 ac80 mode, Power spectral density-5775MHz**

***** END OF REPORT *****