
12*7cm





Ormation Acc MC2 Blastooth Speaker. ybeldere use and leep it for	Produ Blue Tole Aux Filin Aux card
9	Packs MCS Chie 3.5n User
Volume Up Forward Volume Deventilant	Techn
\geqslant	Open
_	Podu

kkage Contents C2 Blastcoth Speaker x1 herging cable x1 Sern AUX cable x1 ser manual x1

Moreouth Standard	196.1	Cepanity	1000145
Frequency Range	100Hz-200Hz	Speaker Specification	q52nn 4259
Operating Range	c104	Solos-Gynd Rein	18000
Operating Vollage	170	Christian Faster	THEMOSPIL
Charging Voltage	0C5V	Reporter Nets	580ma50
Product Dimension	30%0500mm	(by line	101
Product Weight	2950	Working Temperature	+10-6EC

Playing Music
Press the PlayPease button to play/passe y
Press the - button to go to the previous tradibutton to go to the next track.

Volume Adjustment Long press the • or + button to adjust volume

Long press the - or + button to adjust volume.

Playing Music via a 3.5 mm AUX Cable

Connect one end of the 3.5 mm AUX cable to the
species in AUX port and the other end to your de
can now play the music on your device.

Talphone Facility

1. Assembly as all Press the Telephone button to answer incoming of all Press the Telephone button to answer incoming of all.

2. Emeling as all. Press the Telephone button to and a still.

2. Emeling as all. Press the Telephone button to and a still.

2. Emeling as all. Press the Telephone button to sease an incoming of by obligation, instead of the speaker

phone matter.

Note: The measurem effective disease of the bull-inmaterial telephone button to a resident telephone

SO Card Music Piping

1. Not 50 can in the date insentful 50 card and the speaker

activating the FAH mode or tuning off the speaker.

Rechanging.

I sear the mirror USB and of the changing called into the
changing port to change the speaker.

2. The red indicator will be not wish is being changed and the
changing being the speaker of the change of the
lift changes.

3. When the battery is been than 10%, the red indicator will
shalf for 3 times every 10 seconds.

Spa. An entity prohibated for size with the detect. The equipment has been bened and found comply with the firm for c. Cland dispull device, powards to give a fine of the complex of the

Easy∆cc