

# TEST REPORT

**Reference No.**..... : WTS16S0961752-1E V1  
**FCC ID** ..... : 2AJXM-SERIE2  
**Applicant**..... : SUPERCOW TECHNOLOGY LIMITED  
**Address**..... : FLAT C 23/F LUCKY PLAZA 315-321 LOCKHART ROAD WAN  
CHAI HONG KONG  
**Manufacturer** ..... : HK Guang Shen Xin Electronics Technology Limited  
**Address**..... : Unit A5, 9/F, HK Spinners Ind. Bldg., Phase 6, 481 Castle Peak  
Road, Cheung Sha Wan, Kowloon, Hong Kong  
**Product Name**..... : Mobile Phone  
**Model No.**..... : Serie2  
**Brand**..... : GOMETEL  
**Standards**..... : FCC CFR47 Part 15.247:2015  
**Date of Receipt sample** .... : Sep. 27, 2016  
**Date of Test** ..... : Sep. 28 – Oct. 13, 2016  
**Date of Issue**..... : Oct. 24, 2016  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,  
Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

## 2 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious emissions	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
Conduct Emission	15.207	PASS
20dB Bandwidth	15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Antenna Requirement	15.203	Complies
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 REPORT REVISION HISTORY .....</b>	<b>5</b>
<b>5 GENERAL INFORMATION.....</b>	<b>6</b>
5.1 GENERAL DESCRIPTION OF E.U.T. ....	6
5.2 DETAILS OF E.U.T. ....	6
5.3 CHANNEL LIST .....	7
5.4 TEST MODE .....	7
5.5 TEST FACILITY .....	7
<b>6 EQUIPMENT USED DURING TEST .....</b>	<b>8</b>
6.1 EQUIPMENTS LIST .....	8
6.2 DESCRIPTION OF SUPPORT UNITS .....	9
6.3 MEASUREMENT UNCERTAINTY .....	9
6.4 TEST EQUIPMENT CALIBRATION .....	9
<b>7 CONDUCTED EMISSION .....</b>	<b>10</b>
7.1 E.U.T. OPERATION .....	10
7.2 EUT SETUP .....	10
7.3 MEASUREMENT DESCRIPTION .....	11
7.4 CONDUCTED EMISSION TEST RESULT .....	11
<b>8 RADIATED SPURIOUS EMISSIONS.....</b>	<b>13</b>
8.1 EUT OPERATION.....	13
8.2 TEST SETUP .....	14
8.3 SPECTRUM ANALYZER SETUP .....	15
8.4 TEST PROCEDURE .....	16
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	16
8.6 SUMMARY OF TEST RESULTS .....	17
<b>9 CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>20</b>
9.1 TEST PROCEDURE .....	20
9.2 TEST RESULT .....	21
<b>10 BAND EDGE MEASUREMENT .....</b>	<b>31</b>
10.1 TEST PROCEDURE.....	31
10.2 TEST RESULT .....	32
<b>11 20 DB BANDWIDTH MEASUREMENT .....</b>	<b>38</b>
11.1 TEST PROCEDURE.....	38
11.2 TEST RESULT .....	38
<b>12 MAXIMUM PEAK OUTPUT POWER .....</b>	<b>44</b>
12.1 TEST PROCEDURE.....	44
12.2 TEST RESULT .....	44
<b>13 HOPPING CHANNEL SEPARATION .....</b>	<b>50</b>
13.1 TEST PROCEDURE.....	50
13.2 TEST RESULT .....	50
<b>14 NUMBER OF HOPPING FREQUENCY.....</b>	<b>56</b>

14.1	TEST PROCEDURE.....	56
14.2	TEST RESULT .....	56
<b>15</b>	<b>DWELL TIME .....</b>	<b>58</b>
15.1	TEST PROCEDURE.....	58
15.2	TEST RESULT .....	58
<b>16</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>64</b>
<b>17</b>	<b>RF EXPOSURE.....</b>	<b>65</b>

## 4 Report Revision History

Report No.	Report Version	Description	Issue Date
WTS16S0961752-1E	NONE	Original	Oct. 14, 2016
WTS16S0961752-1E V1	V1	Version 1	Oct. 24, 2016

## 5 General Information

### 5.1 General Description of E.U.T.

Product Name	: Mobile Phone
Model No.	: Serie2
Model Description	: N/A
GSM Band(s)	: GSM 850/1900MHz
GPRS Class	: 12
WCDMA Band(s)	: N/A
LTE Bnad(s)	: N/A
Wi-Fi Specification	: N/A
Bluetooth Version	: Bluetooth v3.0+EDR
GPS	: N/A
Hardware Version	: KCX915_MAIN_PCB(V1.1)
Software Version	: C39_V09_0726
Storage Location	: Internal Storage

### 5.2 Details of E.U.T.

Operation Frequency	: GSM/GPRS 850: 824~849MHz PCS/GPRS 1900: 1850~1910MHz Bluetooth: 2402~2480MHz
Max. RF output power	: GSM 850: 32.60dBm PCS1900: 29.54dBm Bluetooth: 3.34dBm
Type of Modulation	: GSM,GPRS: GMSK Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK
Antenna installation	: GSM: internal permanent antenna Bluetooth: internal permanent antenna
Antenna Gain	:GSM 850: 1.0dBi PCS1900: 0.8dBi Bluetooth: 0.5dBi
Technical Data	: Battery DC 3.7V, 300mAh DC 5.7V, 0.8A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.125A)
Adapter	: Manufacture: Shenzhen ZhengHengda Technology Co. Ltd. Model No.: ZHD-002

### 5.3 Channel List

Normal

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	-	-

### 5.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests; the worst data were recorded and reported.

Test mode	Low channel	Middle channel	High channel
Transmitting	2402MHz	2441MHz	2480MHz

### 5.5 Test Facility

The test facility has a test site registered with the following organizations:

- IC – Registration No.: 7760A**  
 Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2015.
- FCC Test Site 1#– Registration No.: 880581**  
 Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.
- FCC Test Site 2#– Registration No.: 328995**  
 Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

## 6 Equipment Used during Test

### 6.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Mar.17,2016	Mar.16,2017
2.	LISN	R&S	ENV216	101215	Mar.17,2016	Mar.16,2017
3.	Cable	Top	TYPE16(3.5M)	-	Mar.17,2016	Mar.16,2017
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Mar.17,2016	Mar.16,2017
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Mar.17,2016	Mar.16,2017
3.	Limiter	York	MTS-IMP-136	261115-001-0024	Mar.17,2016	Mar.16,2017
4.	Cable	LARGE	RF300	-	Mar.17,2016	Mar.16,2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Mar.17,2016	Mar.16,2017
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Mar.17,2016	Mar.16,2017
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Mar.17,2016	Mar.16,2017
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Mar.17,2016	Mar.16,2017
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.18,2016	Apr.17,2017
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.18,2016	Apr.17,2017
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2016	Mar.16,2017
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.09,2016	Apr.08,2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Mar.17,2016	Mar.16,2017
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Mar.17,2016	Mar.16,2017
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Mar.17,2016	Mar.16,2017
4	Cable	HUBER+SUHNER	CBL2	525178	Mar.17,2016	Mar.16,2017



RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Mar.17,2016	Mar.16,2017
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Mar.17,2016	Mar.16,2017
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Mar.17,2016	Mar.16,2017

## 6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

## 6.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	$\pm 1.0$ dB
RF Power Density	$\pm 2.2$ dB
Radiated Spurious Emissions test	$\pm 5.03$ dB (Bilog antenna 30M~1000MHz)
	$\pm 5.47$ dB (Horn antenna 1000M~25000MHz)
Conducted Spurious Emissions test	$\pm 3.64$ dB (AC mains 150KHz~30MHz)

## 6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

## 7 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB $\mu$ V between 0.15MHz & 0.5MHz for QP Detector: 56-46 dB $\mu$ V between 0.15MHz & 0.5MHz for AV Detector: 56 dB $\mu$ V between 0.5MHz & 5MHz for QP Detector: 46 dB $\mu$ V between 0.5MHz & 5MHz for AV Detector: 60 dB $\mu$ V between 5MHz & 30MHz for QP Detector: 50 dB $\mu$ V between 5MHz & 30MHz for AV Detector:
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) QP for QP-scan(9kHz Resolution Bandwidth) AV for AV-scan(9kHz Resolution Bandwidth)

### 7.1 E.U.T. Operation

Operating Environment :


Temperature:	22.8 °C
Humidity:	52.6 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in BT link mode, the test data were shown in the report.

### 7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.




### 7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


### 7.4 Conducted Emission Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.3980	40.15	10.27	50.42	57.89	-7.47	QP	
2	0.3980	29.52	10.27	39.79	47.89	-8.10	AVG	
3	0.7019	33.72	10.36	44.08	56.00	-11.92	QP	
4	0.7019	23.10	10.36	33.46	46.00	-12.54	AVG	
5	0.9500	33.87	10.38	44.25	56.00	-11.75	QP	
6	0.9500	22.69	10.38	33.07	46.00	-12.93	AVG	
7	1.2579	34.36	10.41	44.77	56.00	-11.23	QP	
8	1.2579	22.90	10.41	33.31	46.00	-12.69	AVG	
9	2.1860	34.22	10.47	44.69	56.00	-11.31	QP	
10	2.1860	22.07	10.47	32.54	46.00	-13.46	AVG	
11	4.8500	32.97	10.53	43.50	56.00	-12.50	QP	
12	4.8500	22.31	10.53	32.84	46.00	-13.16	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.3940	37.25	10.27	47.52	57.98	-10.46	QP	
2	0.3940	28.58	10.27	38.85	47.98	-9.13	AVG	
3	0.4780	31.62	10.25	41.87	56.37	-14.50	QP	
4	0.4780	22.71	10.25	32.96	46.37	-13.41	AVG	
5	0.7220	31.13	10.36	41.49	56.00	-14.51	QP	
6	0.7220	22.05	10.36	32.41	46.00	-13.59	AVG	
7	1.0300	32.34	10.39	42.73	56.00	-13.27	QP	
8	1.0300	23.50	10.39	33.89	46.00	-12.11	AVG	
9	2.2180	30.42	10.47	40.89	56.00	-15.11	QP	
10	2.2180	21.29	10.47	31.76	46.00	-14.24	AVG	
11	4.8460	29.97	10.53	40.50	56.00	-15.50	QP	
12	4.8460	20.57	10.53	31.10	46.00	-14.90	AVG	

## 8 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

### 8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX Transmitting mode, the test data were shown in the report.


## 8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto  
 IF Bandwidth.....10kHz  
 Video Bandwidth.....10kHz  
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto  
 Detector .....PK  
 Resolution Bandwidth.....100kHz  
 Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed ..... Auto  
 Detector .....PK  
 Resolution Bandwidth.....1MHz  
 Video Bandwidth.....3MHz  
 Detector .....Ave.  
 Resolution Bandwidth.....1MHz  
 Video Bandwidth.....10Hz

## 8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.

## 8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$



## 8.6 Summary of Test Results

### Test Frequency: 9KHz~30MHz

Remark: only the worst data (GFSK modulation mode) were reported.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.325	25.60	QP	21.84	40.00	7.44	29.54	-22.10
8.304	26.17	QP	21.02	40.00	7.19	29.54	-22.35
26.127	24.02	QP	20.55	40.00	4.57	29.54	-24.97

### Test Frequency: 30MHz ~ 18GHz

Remark: only the worst data (GFSK modulation mode) were reported.

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel									
268.32	37.16	QP	141	1.8	H	-13.35	23.81	46.00	-22.19
268.32	40.36	QP	119	1.5	V	-13.35	27.01	46.00	-18.99
4804.00	45.16	PK	350	1.7	V	-1.06	44.10	74.00	-29.90
4804.00	42.56	Ave	350	1.7	V	-1.06	41.50	54.00	-12.50
7206.00	39.94	PK	232	1.9	H	1.33	41.27	74.00	-32.73
7206.00	35.85	Ave	232	1.9	H	1.33	37.18	54.00	-16.82
2326.16	46.19	PK	278	1.6	V	-13.19	33.00	74.00	-41.00
2326.16	37.12	Ave	278	1.6	V	-13.19	23.93	54.00	-30.07
2387.90	44.19	PK	190	1.5	H	-13.14	31.05	74.00	-42.95
2387.90	36.05	Ave	190	1.5	H	-13.14	22.91	54.00	-31.09
2488.69	42.65	PK	289	1.4	V	-13.08	29.57	74.00	-44.43
2488.69	36.49	Ave	289	1.4	V	-13.08	23.41	54.00	-30.59

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel									
268.32	36.33	QP	236	1.5	H	-13.35	22.98	46.00	-23.02
268.32	39.68	QP	240	1.9	V	-13.35	26.33	46.00	-19.67
4882.00	45.47	PK	233	1.2	V	-0.62	44.85	74.00	-29.15
4882.00	44.00	Ave	233	1.2	V	-0.62	43.38	54.00	-10.62
7323.00	39.80	PK	293	1.2	H	2.21	42.01	74.00	-31.99
7323.00	35.27	Ave	293	1.2	H	2.21	37.48	54.00	-16.52
2341.36	45.37	PK	153	1.8	V	-13.19	32.18	74.00	-41.82
2341.36	39.63	Ave	153	1.8	V	-13.19	26.44	54.00	-27.56
2373.69	42.95	PK	116	1.2	H	-13.14	29.81	74.00	-44.19
2373.69	38.82	Ave	116	1.2	H	-13.14	25.68	54.00	-28.32
2494.69	44.22	PK	126	1.4	V	-13.08	31.14	74.00	-42.86
2494.69	38.26	Ave	126	1.4	V	-13.08	25.18	54.00	-28.82

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel									
268.32	35.36	QP	297	1.2	H	-13.35	22.01	46.00	-23.99
268.32	38.31	QP	160	1.5	V	-13.35	24.96	46.00	-21.04
4960.00	45.88	PK	166	2.0	V	-0.24	45.64	74.00	-28.36
4960.00	44.41	Ave	166	2.0	V	-0.24	44.17	54.00	-9.83
7440.00	40.18	PK	106	1.1	H	2.84	43.02	74.00	-30.98
7440.00	35.76	Ave	106	1.1	H	2.84	38.60	54.00	-15.40
2345.33	45.70	PK	338	1.2	V	-13.19	32.51	74.00	-41.49
2345.33	38.54	Ave	338	1.2	V	-13.19	25.35	54.00	-28.65
2366.45	44.67	PK	180	1.4	H	-13.14	31.53	74.00	-42.47
2366.45	37.32	Ave	180	1.4	H	-13.14	24.18	54.00	-29.82
2489.08	43.54	PK	50	1.8	V	-13.08	30.46	74.00	-43.54
2489.08	38.63	Ave	50	1.8	V	-13.08	25.55	54.00	-28.45

**Test Frequency: 18GHz~25GHz**

The measurements were more than 20 dB below the limit and not reported

## 9 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10

Test Result: PASS



Limit:



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).



### 9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:  
RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold

9.2 Test Result









8DPSK


Low Channel



Middle Channel








30MHz – 25GHz  
GFSK Low Channel

Fundamental




GFSK Middle Channel

Fundamental



GFSK High Channel

Fundamental




Pi/4 DQPSK Low Channel

Fundamental




Pi/4 DQPSK Middle Channel

Fundamental




Pi/4 DQPSK High Channel


Fundamental



8DPSK Low Channel



8DPSK Middle Channel



8DPSK High Channel

Fundamental



## 10 Band Edge Measurement



Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

### 10.1 Test Procedure



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold



10.2 Test Result



Test plots



















## 11 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10

Test Mode: Test in fixing operating frequency at low, Middle, high channel.

### 11.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

### 11.2 Test Result


Modulation	Test Channel	Bandwidth(MHz)
GFSK	Low	1.036
GFSK	Middle	1.036
GFSK	High	1.036
Pi/4 DQPSK	Low	1.287
Pi/4 DQPSK	Middle	1.287
Pi/4 DQPSK	High	1.287
8DPSK	Low	1.287
8DPSK	Middle	1.287
8DPSK	High	1.287



Test plots

GFSK Low Channel







GFSK Middle Channel














## 12 Maximum Peak Output Power

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10
Test Limit:	Regulation 15.247 (b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test mode:	Test in fixing frequency transmitting mode.

### 12.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.///

### 12.2 Test Result


Modulation	Test Channel	Output Power (dBm)	Limit (dBm)
GFSK	Low	2.29	21
GFSK	Middle	2.63	21
GFSK	High	2.40	21
Pi/4 DQPSK	Low	2.20	21
Pi/4 DQPSK	Middle	2.52	21
Pi/4 DQPSK	High	2.31	21
8DPSK	Low	2.85	21
8DPSK	Middle	3.34	21
8DPSK	High	3.32	21



Test plots



GFSK Low Channel





GFSK Middle Channel














## 13 Hopping Channel Separation

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10
Test Limit:	Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.
Test Mode:	Test in hopping transmitting operating mode.

### 13.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

### 13.2 Test Result


Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	1.000	0.691	PASS
GFSK	Middle	1.000	0.691	PASS
GFSK	High	1.000	0.691	PASS
Pi/4 DQPSK	Low	1.000	0.858	PASS
Pi/4 DQPSK	Middle	1.000	0.858	PASS
Pi/4 DQPSK	High	1.000	0.858	PASS
8DPSK	Low	1.000	0.858	PASS
8DPSK	Middle	1.000	0.858	PASS
8DPSK	High	1.000	0.858	PASS



Test plots



GFSK Low Channel






GFSK Middle Channel












## 14 Number of Hopping Frequency

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10
Test Limit:	Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Test Mode:	Test in hopping transmitting operating mode.



### 14.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.483GHz. Sweep=auto;

### 14.2 Test Result







## 15 Dwell Time

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10
Test Limit:	Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Mode:	Test in hopping transmitting operating mode.

### 15.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

### 15.2 Test Result

DH5 Packet permit maximum  $1600 / 79 / 6$  hops per second in each channel (5 time slots RX, 1 time slot TX).


DH3 Packet permit maximum  $1600 / 79 / 4$  hops per second in each channel (3 time slots RX, 1 time slot TX).



DH1 Packet permit maximum  $1600 / 79 / 2$  hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:



Data Packet	Dwell Time(s)
DH5	$1600/79/6*0.4*79*(MkrDelta)/1000$
DH3	$1600/79/4*0.4*79*(MkrDelta)/1000$
DH1	$1600/79/2*0.4*79*(MkrDelta)/1000$
Remark: Mkr Delta is once pulse time.	



Modulation	Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	DH5	Low	2.866	0.306	0.4
		middle	2.866	0.306	0.4
		High	2.866	0.306	0.4
Pi/4DQPSK	DH5	Low	2.888	0.308	0.4
		middle	2.888	0.308	0.4
		High	2.888	0.308	0.4
8DPSK	DH5	Low	2.888	0.308	0.4
		middle	2.888	0.308	0.4
		High	2.888	0.308	0.4



Remark: Only the worst mode DH5 data were recorded.











## **16 Antenna Requirement**

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna, fulfil the requirement of this section.



## **17 RF Exposure**

Remark: refer to SAR test report: WTS16S0961753E

=====End of Report=====