

## 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091 Maximum Permissible Exposure Calculations

For Kinestral Technologies Inc M/N: GW100

## 802.15.4 Zigbee Transceiver

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of one ISM band radio transmitting operating over a range of: **2405 MHz to 2475 MHz** 

## MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure										
Frequency Ra (MHz)	angeElectric Strength (V	FieldMagnetic /m) Strength (A/r		ensityAveraging Ti (Minutes)	ime					
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824	/f 2.19/f	*(180/f2)	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

f = frequency in MHz; \* = Plane-wave equivalent power density

Gateway MPE Page 1 of 2



## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated as follows:

f (MHz)	Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)	Δ
2405	15.41	2.0	17.41	55.08	0.011	1000	999.98
2440	14.65	2.0	16.65	46.24	0.009	1000	999.99
2475	14.67	2.0	16.67	46.45	0.009	1000	999.99

**Result:** The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CRF §1.1310 and §2.1091.

Gateway MPE Page 2 of 2