Request for Modular Approval FCC ID: 2AJZ4-KK3003; IC: 23777-KK3003

Request for Modular Approval FCC ID: 2AJ24-KK3003; IC: 23777-KK3003		
Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with metal shielding
		to cover RF section. Refer to external photos.
2	Have buffered modulation/data	All inputs to the modules are buffered
_	inputs (if such inputs are provided)	through logic and microprocessor
	inputs (ii such inputs are provided)	inputs.
3	Have its own power supply regulation	Module chipset incorporates voltage
		regulation to transceiver circuitry
4	Meet the antenna requirements of	The device has a PCB antenna.
	section 15.203	
5	Demonstrate compliance in a	Device is tested in a test fixture in a standalone configuration
	stand-alone configuration	
6	The licensed module must have a FCC	FCC ID label format will be included in the filling. Host ID label will be displayed on the host system.
	ID label on the module itself. That FCC	
	ID label must be visible through a	
	window on the final device or it must	
	be visible when an access panel, door	
	or cover is easily removed. If not, a	
	second label must be placed on the	
	outside of the final device that	
	contains the following text: Contains	
	"FCC ID: KKI-F-6188"	
7	The module must comply with all	Please refer to "User Manual" Exhibit
	specific rules applicable to the	
	transmitter. The grantee must	
	provide comprehensive instructions	
	to explain compliance requirements.	
8	The module must comply with RF	RF exposure evaluation is exempted because of low output power.
	exposure requirements. See FCC	
	Rules. Spread Spectrum transmitters	
	must comply with RF exposure limits in 15.247.	
	111 ±J,6=77.	

Thank you for your attention to this matter. Yours Sincerely,

Corcherine . Chen.

Catherine Chen, Certification Manager