







## Conducted Spurious Emission

























## Frequency Stability

Test Conditions		LTE Band 2 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0048	PASS
40	Normal Voltage	0.0075	
30	Normal Voltage	0.0074	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0019	
-10	Normal Voltage	0.0006	
-20	Normal Voltage	0.0054	
-30	Normal Voltage	0.0016	
20	Maximum Voltage	0.0029	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0026	

**Note:**


1. Normal Voltage =3.8 V. ; Battery End Point (BEP) =3.4 V. ; Maximum Voltage =4.2 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.




## LTE Band 4

### Peak-to-Average Ratio

Mode	LTE Band 4 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.09	4.96	4.87	4.93	
Middle CH	5.01	4.96	5.77	5.01	PASS
Highest CH	5.22	4.72	5.94	4.7	





**26dB Bandwidth**

Mode	LTE Band 4 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.30	1.31	3.06	3.20	4.83	4.92	9.97	9.91	15.67	15.14	20.62	20.94
Middle CH	1.33	1.31	3.06	3.04	4.98	4.91	10.03	10.17	15.35	15.17	20.70	20.14
Highest CH	1.31	1.32	2.99	3.15	5.04	4.97	9.81	9.81	15.02	14.90	20.14	20.66

