Radio Frequency Exposure

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Smart Thermometer Patch
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.150GHz ~ 5.250GHz ☐ WLAN: 5.250GHz ~ 5.350GHz ☐ WLAN: 5.470GHz ~ 5.725GHz ☐ WLAN: 5.725GHz ~ 5.850GHz ☒ Bluetooth: 2.402GHz ~ 2.480 GHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm^2) ☒ General Population/Uncontrolled exposure (S=1mW/cm^2)

Antenna diversity	☐ Single antenna
	☒ Multiple antennas
	   ☐ Tx diversity
	   ☐ Rx diversity
	   ☒ Tx/Rx diversity

Max. output power	GFSK: -9.96dBm (0.101mW)
Antenna gain (Max)	-14.17dBi
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:
1. *The maximum output power is -9.96dBm (0.101 mW) at 2402 MHz (with numeric 1 antenna gain.)*
2. *DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.*
3. *For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.*

Note: Simultaneous transmission is not applicable for this EUT.

TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \dfrac{\sqrt{30 \times P \times G}}{d}$ & $S = \dfrac{E^2}{3770}$

> Where   E = Field strength in Volts / meter
> P = Power in Watts
> G = Numeric antenna gain
> d = Distance in meters
> S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

> P (mW) = P (W) / 1000 and
> d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \qquad \textbf{\textit{Equation 1}}$$

> Where   d = Distance in cm
> P = Power in mW
> G = Numeric antenna gain
> S = Power density in mW / cm^2

Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power (dBm)	Max. Conducted output power(mW)	Distance (cm)	SAR test exclusion thresholds (mW)
GFSK	2402-2480	-9.96	0.100925289	5	10.000