



FCC PART 15 B TEST REPORT

For

Shanghai Wanyoo Information Technology Co.,Ltd.

6F/7F,BlockC,Section2,Headquarters Park ,No.1528,GumeiRoad,Xuhui District,Shanghai, China

FCC ID: 2AK7T-YPC32

Report Type: Original Report	Product Name: All – in –One – PC
Test Engineer:	<i>Kevin hu</i>
Report Number:	RDG161114006
Report Date:	2017-03-08
Reviewed By:	Henry Ding EMC Leader <i>Henry Ding</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE.....	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION.....	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS	5
CONFIGURATION OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
FCC§15.107 - CONDUCTED EMISSIONS	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP	8
EMI TEST RECEIVER SETUP	9
TEST EQUIPMENT LIST AND DETAILS	9
TEST PROCEDURE	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST DATA	10
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	17
MEASUREMENT UNCERTAINTY	17
EUT SETUP	17
EMI TEST RECEIVER SETUP	18
TEST PROCEDURE	18
TEST EQUIPMENT LIST AND DETAILS	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST DATA	20

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The **Shanghai Wanyoo Information Technology Co.,Ltd.**'s product, model number: **yPC-32 (FCC ID: 2AK7T-YPC32)** (the "EUT") in this report was a **All – in – One – PC**, which was measured approximately: 77 cm (L) × 20 cm (W) × 54 cm (H), rated input voltage: DC19.0V from adapter. The highest operating frequency is 2480 MHz.

Switching Power Adapter Information:

Model No: FSP250-RBAN2

AC Input: 100-240Vac, 3.5A, 50/60Hz

DC Output: 19.0V 13.15A

*Note: The products, test model: yPC-32, multiple model: yPC ****. Their differences were presented in Product Difference Statement provided by the applicant. And we selected yPC-32 to fully test.*

**All measurement and test data in this report was gathered from final production sample, serial number: 161114006 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-11-18, and EUT conformed to test requirement.*

Objective

This test report is prepared on behalf of **Shanghai Wanyoo Information Technology Co.,Ltd.** in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

No related submittal(s)/grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The uncertainty of conducted disturbance at mains port is ± 3.17 dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz: ± 4.7 dB;

200M~1GHz: ± 6.0 dB;

1G~6GHz: ± 5.13 dB;

6G~25GHz: ± 5.47 dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user). When Test, the EUT run the test software "BurnIn.exe v5.3" to transmit data with HDD, and link with monitor via HDMI cable, the Screen Resolution was set to High Resolution (1920*1080), middle Resolution (1280*1024) and Low Resolution (800*600) for testing.

EUT Exercise Software

The software "BurnIn.exe v5.3" was used during test.

Equipment Modifications

No modification was made to the EUT tested.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
XI40MI	Earphone	T9	N/A
KINGSTON	USB Disk	101GB	N/A
QICAIHONG	MOUSE	C-K102	CK102091106646
TOSHIBA	HDD	V63700-A	1397FHOYSRE8
IBM	Keyboard	KM-110X	XBK133000993
PHILIPS	Monitor	227E3L	AU3A1140001077

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Mouse Cable	yes	No	1.5	USB Port of EUT	Mouse
Keyboard Cable	yes	No	1.5	USB Port of EUT	Keyboard
Earphone Cable	No	No	2	Audio Port of EUT	Earphone
Hard Disk USB Cable	No	No	0.4	USB Port of HDD	EUT
HDMI Cable	yes	yes	1.5	Monitor	EUT

Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ± 3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
N/A	Conducted Cable	NO.5	N/A	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions


Temperature:	24.4°C
Relative Humidity:	43 %
ATM Pressure:	100.9 kPa

The testing was performed by Kevin Hu on 2017-02-08.

Test Mode: Operating

Low Resolution


AC120V, 60Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	52.7	9.000	L1	19.7	11.8	64.5	Compliance
0.266226	45.7	9.000	L1	19.7	15.5	61.2	Compliance
0.351859	40.9	9.000	L1	19.7	18.0	58.9	Compliance
0.439808	38.5	9.000	L1	19.7	18.6	57.1	Compliance
0.703777	39.6	9.000	L1	19.7	16.4	56.0	Compliance
0.812315	37.1	9.000	L1	19.7	18.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.177322	37.1	9.000	L1	19.7	17.5	54.6	Compliance
0.266226	43.4	9.000	L1	19.7	7.8	51.2	Compliance
0.354674	34.8	9.000	L1	19.7	14.1	48.9	Compliance
0.532496	31.4	9.000	L1	19.7	14.6	46.0	Compliance
0.709407	31.0	9.000	L1	19.7	15.0	46.0	Compliance
1.239175	28.4	9.000	L1	19.7	17.6	46.0	Compliance

AC120V, 60Hz, Neutral:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	54.1	9.000	N	19.7	10.4	64.5	Compliance
0.266226	45.2	9.000	N	19.6	16.0	61.2	Compliance
0.709407	36.1	9.000	N	19.6	19.9	56.0	Compliance
1.239175	34.8	9.000	N	19.6	21.2	56.0	Compliance
4.614454	39.2	9.000	N	19.7	16.8	56.0	Compliance
4.802010	36.7	9.000	N	19.7	19.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.177322	37.8	9.000	N	19.7	16.8	54.6	Compliance
0.266226	42.8	9.000	N	19.6	8.4	51.2	Compliance
0.354674	33.2	9.000	N	19.6	15.7	48.9	Compliance
0.528270	30.6	9.000	N	19.6	15.4	46.0	Compliance
0.709407	28.5	9.000	N	19.6	17.5	46.0	Compliance
1.239175	28.6	9.000	N	19.6	17.4	46.0	Compliance

Middle Resolution


AC120V, 60Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	52.6	9.000	L1	19.7	11.9	64.5	Compliance
0.266226	45.7	9.000	L1	19.7	15.5	61.2	Compliance
0.351859	40.8	9.000	L1	19.7	18.1	58.9	Compliance
0.439808	38.5	9.000	L1	19.7	18.6	57.1	Compliance
0.709407	39.0	9.000	L1	19.7	17.0	56.0	Compliance
0.818813	38.2	9.000	L1	19.7	17.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.243884	34.2	9.000	L1	19.7	17.8	52.0	Compliance
0.266226	43.4	9.000	L1	19.7	7.8	51.2	Compliance
0.351859	34.3	9.000	L1	19.7	14.6	48.9	Compliance
0.532496	31.0	9.000	L1	19.7	15.0	46.0	Compliance
0.709407	31.0	9.000	L1	19.7	15.0	46.0	Compliance
1.239175	28.4	9.000	L1	19.7	17.6	46.0	Compliance

AC120V, 60Hz, Neutral:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	52.5	9.000	N	19.7	12.0	64.5	Compliance
0.266226	45.6	9.000	N	19.6	15.6	61.2	Compliance
0.709407	36.1	9.000	N	19.6	19.9	56.0	Compliance
0.812315	34.8	9.000	N	19.6	21.2	56.0	Compliance
4.434225	35.3	9.000	N	19.7	20.7	56.0	Compliance
4.763898	34.5	9.000	N	19.7	21.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.177322	37.5	9.000	N	19.7	17.1	54.6	Compliance
0.266226	43.5	9.000	N	19.6	7.7	51.2	Compliance
0.354674	33.9	9.000	N	19.6	15.0	48.9	Compliance
0.532496	30.6	9.000	N	19.6	15.4	46.0	Compliance
0.709407	30.0	9.000	N	19.6	16.0	46.0	Compliance
1.239175	28.5	9.000	N	19.6	17.5	46.0	Compliance

High Resolution


AC120V, 60Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178741	52.7	9.000	L1	19.7	11.8	64.5	Compliance
0.266226	45.7	9.000	L1	19.7	15.5	61.2	Compliance
0.349066	40.1	9.000	L1	19.7	18.9	59.0	Compliance
0.436318	36.8	9.000	L1	19.7	20.3	57.1	Compliance
0.709407	39.2	9.000	L1	19.7	16.8	56.0	Compliance
0.812315	37.2	9.000	L1	19.7	18.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.177322	37.3	9.000	L1	19.7	17.3	54.6	Compliance
0.266226	43.8	9.000	L1	19.7	7.4	51.2	Compliance
0.354674	34.2	9.000	L1	19.7	14.7	48.9	Compliance
0.532496	31.5	9.000	L1	19.7	14.5	46.0	Compliance
0.709407	30.0	9.000	L1	19.7	16.0	46.0	Compliance
1.239175	29.2	9.000	L1	19.7	16.8	46.0	Compliance

AC120V, 60Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.180171	54.1	9.000	N	19.7	10.4	64.5	Compliance
0.266226	45.1	9.000	N	19.6	16.1	61.2	Compliance
0.709407	36.2	9.000	N	19.6	19.8	56.0	Compliance
4.434225	37.3	9.000	N	19.7	18.7	56.0	Compliance
4.614454	37.8	9.000	N	19.7	18.2	56.0	Compliance
9.681660	41.5	9.000	N	19.8	18.5	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.266226	42.7	9.000	N	19.6	8.5	51.2	Compliance
0.351859	33.7	9.000	N	19.6	15.2	48.9	Compliance
0.528270	30.0	9.000	N	19.6	16.0	46.0	Compliance
0.709407	29.1	9.000	N	19.6	16.9	46.0	Compliance
9.528593	40.8	9.000	N	19.8	9.2	50.0	Compliance
9.681660	32.4	9.000	N	19.8	17.6	50.0	Compliance

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ± 4.7 dB;

200M~1GHz: ± 6.0 dB;

1G~6GHz: ± 5.13 dB;


6G~25GHz: ± 5.47 dB;

Table 2 – Values of U_{cisp}


Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed at the 3 meters distance in chamber, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13.5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	10 Hz	/	AVG

Test Procedure

During the radiated emissions, the adapter of EUT was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions

Temperature:	20.5~23.1 °C
Relative Humidity:	41~50 %
ATM Pressure:	95.2~95.7 kPa


* The testing was performed by Kevin Hu from 2017-02-10 to 2017-03-07.

Test Result: Compliance

Test Mode: Operating


1) Below 1GHz:

Low Resolution



Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
151.492500	42.2	400.0	H	1.0	-7.8	1.3	43.5
241.823750	43.1	400.0	V	0.0	-7.5	2.9	46.0
423.577500	44.9	400.0	V	359.0	-3.5	1.1	46.0
483.960000	44.8	400.0	V	32.0	-2.2	1.2	46.0
605.088750	44.8	400.0	H	42.0	-0.5	1.2	46.0
726.096250	42.8	400.0	H	112.0	1.7	3.2	46.0


Middle Resolution



Frequency (MHz)	QuasiPeak (dBµV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
151.371250	42.0	400.0	H	10.0	-7.8	1.5	43.5
423.577500	44.9	400.0	V	4.0	-3.5	1.1	46.0
484.081250	44.6	400.0	V	33.0	-2.2	1.4	46.0
605.088750	44.5	400.0	H	81.0	-0.5	1.5	46.0
726.096250	42.8	400.0	H	281.0	1.7	3.2	46.0
847.103750	42.0	400.0	H	273.0	3.3	4.0	46.0

High Resolution

Electric Field Strength with Scans



Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
152.705000	42.6	200.0	H	185.0	-7.8	0.9	43.5
241.945000	44.9	200.0	V	218.0	-7.5	1.1	46.0
423.577500	44.7	100.0	V	143.0	-3.5	1.3	46.0
484.081250	45.0	200.0	V	199.0	-2.2	1.0	46.0
605.088750	45.3	100.0	V	235.0	-0.5	0.7	46.0
726.096250	44.5	100.0	V	152.0	1.7	1.5	46.0

2) 1GHz-13.5GHz:

Low Resolution

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
1037.5	57.04	PK	H	22.90	2.03	26.77	55.20	74.00	18.80
1037.5	48.42	AV	H	22.90	2.03	26.77	46.58	54.00	7.42
1631.25	54.78	PK	H	24.31	2.77	26.46	55.40	74.00	18.60
1631.25	45.77	AV	H	24.31	2.77	26.46	46.39	54.00	7.61
1931.25	53.97	PK	H	24.79	3.00	26.75	55.01	74.00	18.99
1931.25	45.33	AV	H	24.79	3.00	26.75	46.37	54.00	7.63
2081.25	54.87	PK	H	24.62	3.04	26.83	55.70	74.00	18.30
2081.25	45.55	AV	H	24.62	3.04	26.83	46.38	54.00	7.62
2225	55.05	PK	H	24.14	3.02	26.85	55.36	74.00	18.64
2225	46.44	AV	H	24.14	3.02	26.85	46.75	54.00	7.25
2375	55.25	PK	H	23.63	3.01	26.87	55.02	74.00	18.98
2375	45.87	AV	H	23.63	3.01	26.87	45.64	54.00	8.36
1037.5	58.63	PK	V	22.90	2.03	26.77	56.79	74.00	17.21
1037.5	49.37	AV	V	22.90	2.03	26.77	47.53	54.00	6.47
1212.5	57.47	PK	V	23.35	2.27	26.61	56.48	74.00	17.52
1212.5	48.41	AV	V	23.35	2.27	26.61	47.42	54.00	6.58
1631.25	52.97	PK	V	24.31	2.77	26.46	53.59	74.00	20.41
1631.25	44.1	AV	V	24.31	2.77	26.46	44.72	54.00	9.28
2081.25	53.47	PK	V	24.62	3.04	26.83	54.30	74.00	19.70
2081.25	44.79	AV	V	24.62	3.04	26.83	45.62	54.00	8.38
2225	54.7	PK	V	24.14	3.02	26.85	55.01	74.00	18.99
2225	46.04	AV	V	24.14	3.02	26.85	46.35	54.00	7.65
2375	55.61	PK	V	23.63	3.01	26.87	55.38	74.00	18.62
2375	47.15	AV	V	23.63	3.01	26.87	46.92	54.00	7.08

Middle Resolution

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)					
1037.5	58.04	PK	H	22.90	2.03	26.77	56.20	74.00	17.80
1037.5	48.71	AV	H	22.90	2.03	26.77	46.87	54.00	7.13
1337.5	57.31	PK	H	23.68	2.45	26.49	56.95	74.00	17.05
1337.5	46.84	AV	H	23.68	2.45	26.49	46.48	54.00	7.52
1631.25	53.78	PK	H	24.31	2.77	26.46	54.40	74.00	19.60
1631.25	44.75	AV	H	24.31	2.77	26.46	45.37	54.00	8.63
1931.25	54.47	PK	H	24.79	3.00	26.75	55.51	74.00	18.49
1931.25	45.35	AV	H	24.79	3.00	26.75	46.39	54.00	7.61
2081.25	54.87	PK	H	24.62	3.04	26.83	55.70	74.00	18.30
2081.25	44.69	AV	H	24.62	3.04	26.83	45.52	54.00	8.48
2225	56.05	PK	H	24.14	3.02	26.85	56.36	74.00	17.64
2225	47.18	AV	H	24.14	3.02	26.85	47.49	54.00	6.51
1212.5	56.47	PK	V	23.35	2.27	26.61	55.48	74.00	18.52
1212.5	47.64	AV	V	23.35	2.27	26.61	46.65	54.00	7.35
1631.25	54.47	PK	V	24.31	2.77	26.46	55.09	74.00	18.91
1631.25	45.69	AV	V	24.31	2.77	26.46	46.31	54.00	7.69
1781.25	57.48	PK	V	24.55	2.88	26.61	58.30	74.00	15.70
1781.25	47.55	AV	V	24.55	2.88	26.61	48.37	54.00	5.63
2081.25	54.47	PK	V	24.62	3.04	26.83	55.30	74.00	18.70
2081.25	45.41	AV	V	24.62	3.04	26.83	46.24	54.00	7.76
2137.5	57.17	PK	V	24.43	3.03	26.84	57.79	74.00	16.21
2137.5	46.9	AV	V	24.43	3.03	26.84	47.52	54.00	6.48
2225	54.2	PK	V	24.14	3.02	26.85	54.51	74.00	19.49
2225	45.04	AV	V	24.14	3.02	26.85	45.35	54.00	8.65

High Resolution

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
1037.5	57.04	PK	H	22.90	2.03	26.77	55.20	74.00	18.80
1037.5	48.42	AV	H	22.90	2.03	26.77	46.58	54.00	7.42
1631.25	54.78	PK	H	24.31	2.77	26.46	55.40	74.00	18.60
1631.25	45.77	AV	H	24.31	2.77	26.46	46.39	54.00	7.61
1931.25	53.97	PK	H	24.79	3.00	26.75	55.01	74.00	18.99
1931.25	45.33	AV	H	24.79	3.00	26.75	46.37	54.00	7.63
2081.25	54.87	PK	H	24.62	3.04	26.83	55.70	74.00	18.30
2081.25	45.55	AV	H	24.62	3.04	26.83	46.38	54.00	7.62
2225	55.05	PK	H	24.14	3.02	26.85	55.36	74.00	18.64
2225	46.44	AV	H	24.14	3.02	26.85	46.75	54.00	7.25
2375	55.25	PK	H	23.63	3.01	26.87	55.02	74.00	18.98
2375	45.87	AV	H	23.63	3.01	26.87	45.64	54.00	8.36
1037.5	59.13	PK	V	22.90	2.03	26.77	57.29	74.00	16.71
1037.5	49.02	AV	V	22.90	2.03	26.77	47.18	54.00	6.82
1212.5	58.97	PK	V	23.35	2.27	26.61	57.98	74.00	16.02
1212.5	48.51	AV	V	23.35	2.27	26.61	47.52	54.00	6.48
1631.25	58.97	PK	V	24.31	2.77	26.46	59.59	74.00	14.41
1631.25	49.03	AV	V	24.31	2.77	26.46	49.65	54.00	4.35
1931.25	59.09	PK	V	24.79	3.00	26.75	60.13	74.00	13.87
1931.25	49.19	AV	V	24.79	3.00	26.75	50.23	54.00	3.77
2225	56.7	PK	V	24.14	3.02	26.85	57.01	74.00	16.99
2225	46.78	AV	V	24.14	3.02	26.85	47.09	54.00	6.91
2375	57.61	PK	V	23.63	3.01	26.87	57.38	74.00	16.62
2375	47.44	AV	V	23.63	3.01	26.87	47.21	54.00	6.79

***** **END OF REPORT** *****